TECHNISCHE UNIVERSITÄT
CHEMNITZ

Preference versus Performance in Automated Driving: A Challenge for Method Development

Dissertation

zur Erlangung des akademischen Grades
doctor rerum naturalium (Dr. rer. nat.)

vorgelegt der Human- und Sozialwissenschaftlichen Fakultät
der Technischen Universität Chemnitz

vorgelegt von:	Yannick Forster, geboren am 23.03.1992 in Lauingen (Donau)
eingereicht am:	03.11.2019
Disputation am:	22.06.2020
Erstgutachter:	Prof. Dr. Josef F. Krems, Technische Universität Chemnitz
Zweitgutachter:	Prof. Dr. Martin Baumann, Universität Ulm
Drittgutachter:	Prof. Dr. Georg Jahn, Technische Universität Chemnitz

[HTTPS://NBN-RESOLVING.ORG/URN:NBN:DE:BSZ:CH1-QUCOSA2-713685](https://nbn-resolving.org/urn:nbn:de:bsz:ch1-qucosa2-713685)

Danksagung

Die vorliegende Arbeit wäre ohne die Unterstützung einiger Personen in dieser Form nicht möglich gewesen. Deshalb möchte ich diesen zunächst meinen Dank aussprechen. Zu aller erst bedanke ich mich bei Dr. Sebastian Hergeth für die Betreuung auf Seiten von BMW. Besonders zielführend waren inhaltliche Hinweise und Anregungen im Laufe der Dissertation aber auch der Freiraum und die Offenheit gegenüber meinen Ideen sowie letztlich der strategische Weitblick bei der Betreuung. Des Weiteren bedanke ich mich bei Professor Dr. Josef Krems für die Betreuung der Promotion an der TU Chemnitz sowie bei Professor Dr. Martin Baumann für das Zweitgutachten. Für die Erstellung des Drittgutachtens möchte ich mich bei Professor Dr. Georg Jahn bedanken. Bei Dr. Frederik Naujoks möchte ich mich bedanken für die mittlerweile mehrjährige fachliche Zusammenarbeit, Unterstützung und Co-Autorschaft in diversen Publikationen. Zudem soll an dieser Stelle mein Dank an alle Kollegen/-innen der BMW Abteilung für Usability ausgesprochen werden. Allen voran sei dabei Dr. Andreas Keinath genannt, der diese Arbeit überhaupt möglich machte. Ein weiterer Dank geht an die (ehemaligen) BMW-Doktoranden/-innen Stefan Heijboer, Jeremy Dillmann, Stefan Breitschaft, Manuela Witt, Dr. Nina Kauffmann, Tobias Schmid und Wolfgang Wöhrle für den Austausch während der Doktorandenzeit. Neben BMW-internen Diskussionen waren für mich besonders die regelmäßigen Präsentationen und Abstimmungen an den betreuenden Lehrstühlen wichtig. Deshalb möchte ich mich bei allen Mitarbeitern/-innen des Lehrstuhls für Allgemeine und Arbeitspsychologie der TU Chemnitz sowie des Lehrstuhls für Human Factors an der Universität Ulm für ihre Anmerkungen und Hinweise bedanken. Danke an dieser Stelle besonders an Dr. Matthias Beggiato, der sich bei meinen Besuchen in Chemnitz immer Zeit für einen Austausch nahm. Im Laufe der Promotion entstand eine Reihe an Publikationen, von denen jedoch nicht alle vollumfänglich oder thematisch in die vorliegende Arbeit eingeflossen sind. Daher möchte ich Johannes Kraus, Dr. Anna-Katharina Frison und Dr. Philipp Wintersberger an dieser Stelle danken. Im Rahmen der Vorbereitung, Durchführung und Nachbereitung der hier berichteten Versuchsreihe konnte ich auf die Unterstützung meiner Praktikanten/-innen bauen und möchte ebenfalls Sophie Feinauer, Johanna Artmann, Katja Mayr, Viktoria Geisel, Sarah Fürstberger und Felix Rappenegger danken. Zudem sei den 225 anonymen Probanden/-innen gedankt, die an den drei Studien teilnahmen. Abschließend gebührt der wohl größte Dank meinen Eltern und meinem Bruder.

Zusammenfassung

Das automatisierte Fahren hat bereits den Weg auf den kommerziellen Markt geschafft und weiterer Fortschritt kann in naher Zukunft erwartet werden. Das Level 3 des automatisierten Fahrens verspricht steigende Sicherheit, Komfort und Verkehrseffizienz. Für den menschlichen Fahrer sind diese Funktionen und damit einhergehende Nutzerschnittstellen eine neuartige Technologie. Im Bereich Human Factors stehen Forschung und Entwicklung vor zwei Herausforderungen, welche (1) der Entwurf von intuitiven und einfach bedienbaren Nutzerschnittstellen und (2) die Entwicklung von Methoden zur Bewertung ebendieser sind. Bei der Bewertung von Technologie wurde bereits häufig auf die sogenannte Preference-Performance Dissoziation aufmerksam gemacht. Diese beschreibt das Ergebnis von Nutzerstudien, in denen die Präferenz (Selbstbericht) der Nutzer nicht mit deren Leistung (beobachtbares Verhalten) übereinstimmt. Dieses Phänomen stellt eine Gefährdung für die Bewertung von Nutzerschnittstellen beim automatisierten Fahren dar. Aufgrund dessen berichtet die vorliegende Dissertation zunächst Untersuchungen zur Messbarmachung von Präferenz und Leistung. Zudem wurde das Verständnis von automatisierten Systemen (mentales Modell) als ein wichtiger Einflussfaktor zur Entstehung des beobachtbaren Verhaltens angenommen und mit in die Arbeiten eingeschlossen. Mithilfe der gewonnenen Erkenntnisse der Messbarmachung widmete sich der zweite Teil der Dissertation den Faktoren, die einen Einfluss auf das Entstehen von Präferenz und/oder Leistung ausüben. Untersuchte Faktoren waren die Anzahl an Wiederholungen von Anwendungsfällen, Rückmeldung zur Bedienleistung, Nutzerschulung und eine statistische post-hoc Analyse. Um die Ziele der Messbarmachung und Einflussnahme zu erreichen wurden drei Fahrsimulatorstudien mit insgesamt $N=225$ Probanden durchgeführt. Die Hauptideen waren (1) die Entwicklung einer differenzierten Empfehlung von Fragebögen zur Erfassung der Nutzerpräferenz. Außerdem (2) wurden Erkenntnisse der Entwicklung von Verhaltensmaßen über die Zeit sowie deren Zusammenhang zu Präferenzmaßen gewonnen. Betreffend der mentalen Modelle (3) zeigte die vorliegende Arbeit, dass es wiederholter Interaktion bedarf, damit diese sich korrekt entwickeln. Außerdem kann das Verständnis durch Blickverhaltensmaße erfasst werden. Zusätzlich (4) zeigte sich, dass Leistungsrückmeldung Präferenz, nicht aber Leistung selbst beeinflussen kann. Im Gegensatz dazu (5) wirkt sich Nutzerschulung positiv auf die Korrektheit mentaler Modelle und nachfolgend der Nutzerleistung selbst aus, lässt aber Präferenzmaße unbeeinflusst. Abschließend zeigte

sich, dass (6) Nutzer verschiedener Leistungsstufen ähnliche Präferenzurteile fällen. Der theoretische Beitrag der vorliegenden Arbeit liegt in den Einblicken in die Entstehung der beiden Datenquellen der Preference-Performance Dissoziation wodurch diese erklärt und vorhergesagt werden kann. Der praktische Beitrag liegt in der Anwendung der Arbeit zur Messbarmachung von Variablen und Empfehlung zum Studiendesign hinsichtlich Anzahl an Messwiederholungen und Nutzerschulung. Abschließend betreffen die hier gewonnenen Erkenntnisse nicht nur die Bewertung von Nutzerschnittstellen beim automatisierten Fahren, sondern können auch auf andere Automationsbereiche der Mensch-Maschine Interaktion wie beispielsweise Luftfahrt, Robotik oder Medizintechnik übertragen werden.

Abstract

Driving automation systems have already entered the commercial market and further advancements will be introduced in the near future. Level 3 automated driving systems are expected to increase safety, comfort and traffic efficiency. For the human driver, these functions and according human-machine interfaces are a novel technology. In the human factors domain, research and development faces two challenges which are (1) the conceptualization of intuitive and easy to use interfaces and (2) the development of a methodological framework to evaluate these interfaces. In technology evaluation, a methodological phenomenon has frequently been reported which is called the preference-performance dissociation. It describes the outcome of studies where users' preference (i.e., self-report) does not match their performance (i.e., interaction behavior). This phenomenon poses a threat to the evaluation of automated vehicle HMIs. Therefore, the present thesis first reports investigations on how to operationalize both performance and preference. Moreover, the understanding (i.e., mental model) of automated vehicle HMIs was hypothesized as an influential precursor of performance and included in the present work. Using the insights of the operationalization part, the second part of the thesis aimed at finding out about factors that exert influence on preference and/or performance. Investigated factors were the number of use case repetitions, feedback on operator performance, user education and a post-hoc statistical analysis. To reach the operationalization and variation aims, three driving simulator studies with a total of $N=225$ participants were conducted. The main outcomes were that (1) a sophisticated recommendation regarding preference questionnaire application could be given. Furthermore, (2) insights into the development of behavioral measures over time and their relation to a satisfaction measure could be given. Concerning mental models, (3) the present work showed that it takes repeated interaction to evolve accurately and gaze measures could also be used for capturing these processes. In addition, (4) feedback on operator performance was found to influence preference but not performance while (5) user education increased understanding and subsequent performance but did not affect preference. Eventually it showed that (6) users of different performance levels report similar preference. The theoretical contribution of this work lies in insights into the formation of the two sources of data and its potential to both explain and predict the preference-performance dissociation. The practical contribution lies in the recommendation for research methodology regarding how to operationalize measures and how to

design user studies concerning the number of use cases and user education approaches. Finally, the results gained herein do not only apply to automated vehicle HMIs but might also be generalized to related domains such as aviation, robotics or health care.

Contents

1	Introduction	1
1.1	Challenges for Automated Driving Research	3
1.2	Manuscript Overview	4
1.3	Taxonomies of Automation	6
1.4	Human-Machine Interfaces for Automated Driving	9
2	Human Factors in Automated Driving: Status Quo of Research	15
2.1	Introduction	15
2.2	Pilot Study	19
2.3	Methods	21
2.4	Results	25
2.5	Discussion	28
2.6	Conclusion	31
3	How Usability can save the Day: Methodological Considerations for making Automated Driving a Success Story	32
3.1	Aim of this Chapter	32
3.2	Overview of Measures	33
3.3	Influential Factors and Dynamic Interplay	38
3.4	Conclusions	46
4	Aims and Objectives	47
4.1	Main Aim of the Thesis	47
4.2	Practical and theoretical Contribution	49
4.3	Allocation of the Aim into three Studies	50
5	Self-Report Measures for the Assessment of Human-Machine Interfaces in Automated Driving	53
5.1	Introduction	53
5.2	Method	59

5.3	Results	67
5.4	Discussion	75
6	Behavioral Measures, Mental Models and the Role of Feedback: Theory and General Method	83
6.1	Background on Learning and Behavioral Measures	84
6.2	Background on Mental Models	89
6.3	Background on Feedback	90
6.4	General Method	94
7	Learning to Use Automation: Behavioral Changes in Interaction with Automated Driving Systems	104
7.1	Results	105
7.2	Discussion	113
8	Learning and Development of Mental Models during Interactions with Driving Automation: A Simulator Study	121
8.1	Results	122
8.2	Discussion	125
9	Tell them how they did: Feedback on Operator Performance helps calibrate perceived Ease of Use in Automated Driving	128
9.1	Results	129
9.2	Discussion	132
10	User Education in Automated Driving: Owner's Manual and Interactive Tutorial support Mental Model Formation and Human-Automation Interaction	139
10.1	Introduction	140
10.2	Method	145
10.3	Results	154
10.4	Discussion	158
11	What and how to tell beforehand: The Effect of User Education on Understanding, Interaction and Satisfaction with Driving Automation	166
11.1	Introduction	167
11.2	Method	172

11.3 Results	176
11.4 Discussion	185
12 Unskilled and unaware: Subpar Users of Automated Driving Systems make spurious Decisions	196
12.1 Introduction	196
12.2 Method	197
12.3 Results	198
12.4 Discussion	200
13 General Discussion and Conclusions	202
13.1 Overall Findings	203
13.2 Theoretical Implications	204
13.3 Practical Application	207
13.4 Methodological Considerations	215
13.5 Future Research	216
Bibliography	219

List of Figures

1.1	SAE levels of driving automation. Retrieved from https://www.sae.org/news/press-room/2018/12/sae-international-releases-updated-visual-chart-for-its-%E2%80%9Clevels-of-driving-automation%E2%80%9D-standard-for-self-driving-vehicles	8
1.2	HMIs for active L3 automation taken from Naujoks et al. (2017a), Hergeth (2016) and HAVEit (2011) from left to right	11
1.3	HMIs for Take-Over Requests taken from Jarosch et al. (2019), Louw (2017) and Forster et al. (2017) from left to right	12
2.1	Decision Tree for paper selection.	20
2.2	Entity relationship diagram of the database structure showing the relations between papers, constructs, data collection methods and parameters.	24
2.3	Frequencies of publications regarding the investigated SAE levels of automation, presented over the time since 2010 (SAE L0 and L1 are excluded as they are not part of this literature review).	26
2.4	Frequencies [n] of age groups in the automated driving studies.	27
3.1	Randomly generated data sets for performance-preference correlations of the meta-analysis with $r=.46$ (left) and an idealized dataset with $r=.95$ (right).	41
5.1	Static driving simulator mockup used in the present study.	60
5.2	Flowchart of experimental procedure.	61
5.3	Visual HMI for an active L3 ADS, conditional TOR, immediate TOR and L3 ADS not available (rows from top to bottom). Numbers indicate HMI variations described in table 5.1 column 2.	63
6.1	Dynamic driving simulator from the outside (top) and inside mockup used in the current study (bottom).	96
6.2	Schematic outline of experimental procedure	97

6.3	AOIs (i.e., 1=operating element, 2=instrument cluster, 3=driving scene, 4=NDRT) from vehicle interior.	102
7.1	Means and standard errors for experimenter rating (top), reaction times (middle) and button presses (bottom) from block 1 to block 5. The power law of practice was fitted for UC1, UC3, UC4 and UC5 whereas a linear function was fitted for UC2 and UC6.	106
7.2	Scatterplots of preference-performance relationships for experimenter ratings, reaction times and button presses (from left to right) by the five experimental blocks.	111
8.1	Self-reported learning (M , SE) and according power-law fit	123
8.2	Number of gaze switches (M , SE) and according power-law fit	123
8.3	Monitoring frequency results (i.e., M , SE) in the four UCs by block and AOI.	124
8.4	Mental model questionnaire results (i.e., M , SE) by automation level and expertise	125
9.1	Means and standard errors for time on task in the 6 use cases by time of measurement (x-axis) and feedback condition	131
9.2	Means and standard errors for difficulty ratings in the 6 use cases by time of measurement (x-axis) and feedback condition.	132
10.1	Static driving simulator mockup used in the present study.	147
10.2	Schematic outline of experimental procedure	148
10.3	Excerpt from owner's manual. Note that icons had been disguised due to confidentiality and are represented as black squares. Specific function names have been replaced by " <i>L3 ADS</i> " and " <i>L2 automation</i> ".	151
10.4	Layout of interactive tutorial with operating element (upper left), instrument cluster (upper middle), driver's view (upper right), user task, and four alternative answers.	152
10.5	Matlab code for bootstrapping procedure.	154
10.6	Frequency [N] of L2 automation mental model ratings [1–7] for the four relevant items (columns) by experimental condition (rows 1–3: baseline grey, owner's manual blue, tutorial green).	156

10.7	Frequency [N] of L3 ADS mental model ratings [1–7] for the four relevant items (columns) by experimental condition (rows 1–3: baseline grey, owner’s manual blue, tutorial green).	157
10.8	Frequency [N] of experimenter ratings [1–5] in each use case (columns) by experimental condition (rows 1–3: baseline grey, manual blue, tutorial green).	158
11.1	Schematic outline of experimental procedure	174
11.2	Means and SE for L2 (top) and L3 automation (bottom) of the four items of interest by experimental condition (BL: white; ML: light grey; TL: dark grey; ML+TL: black).	177
11.3	Means and standard errors of the experimenter rating, time on task and error rate (columns left to right) for UCs 1-4 (rows). Each plot shows the four experimental conditions as separate lines for the first and second block on the x-axis.	181
11.4	Scatterplots of preference-performance relationships for experimenter rating, time on task and error rate (from left to right) by the four educational procedures.	184
12.1	Means and standard errors for preference-performance comparisons of SUS, VDL usefulness and VDL satisfaction (from left to right).	199

List of Tables

3.1	Overview of usability components according to ISO (2011), measures and possible operationalizations.	34
3.2	Overview of relevant constructs, scales, sources and google scholar citations (as of August 15th, 2019)	36
5.1	Variations for low compliance HMI for the two components with respective criterion and reference	63
5.2	Sequential order of use-cases in for each experimental drive	64
5.3	Constructs, questionnaires, scale and original sources) for self-report measures	65
5.4	Manipulation check item numbers, wording and respective guideline number in Naujoks, Wiedemann et al. (2019)	66
5.5	Reliability coefficients (Cronbach's alpha) for each subscale by HMI (i.e., high compliance, low compliance) and the original source (if reported). .	69
5.6	Items and respective scales with low face validity as indicated by the frequency of participants labelling an item as " <i>problematic to answer</i> ". .	71
5.7	Matrix with factor loadings after Varimax rotation. Factor loadings are sorted by size and small values (i.e., $<.5$) are colored in grey.	73
5.8	Descriptive (i.e., M , SD) and inferential (i.e., main effect for HMI and Interaction HMI x Subscale) statistics for each scale.	75
5.9	Result overview of construct validity analysis.	79
6.1	Overview of use cases for one experimental block.	99
6.2	Experimenter rating with label and description.	101
7.1	Mean and SD (λ) of NDRT inputs by UC and experimental block.	105
7.2	Descriptive statistics (i.e., M , SD) for experimenter rating and reaction time and lambda for error rate by time of measurement (columns) and use-case (rows).	107

7.3	Model fit equations and goodness of fit indices (i.e., R^2 , RMSE) for the three behavioral measures.	109
7.4	Descriptive results (i.e., M , SD , <i>Cronbach's</i> α) for System Usability Scale	110
7.5	Inferential statistics (i.e., F -, $df1$, $df2$, p -, η_p^2 -values) for the multivariate ANOVA and the univariate ANOVAs.	110
7.6	Linear regression coefficients (i.e., R^2 , p) and equations with criterion (C) and respective predictor (p) for experimenter rating, reaction times and button presses at five times of measurement.	112
8.1	Model fit equations and goodness-of-fit indices (R^2 , $RMSE$) for self-reported learning	122
8.2	Model fit equations and goodness-of-fit indices (R^2 , $RMSE$) for gaze switches by UC	123
9.1	Mauchly's test statistics of sphericity assumption for time on task.	129
9.2	Inferential statistics (i.e., F , $df1$, $df2$, p , η_p^2) of time on task.	130
9.3	Mauchly's test statistics of sphericity assumption for perceived ease of use.	131
9.4	Inferential statistics (i.e., F , $df1$, $df2$, p , η_p^2) of perceived ease of use.	132
10.1	Summary of characteristics of manual and tutorial based user education approaches.	144
10.2	Overview of use cases for one experimental block.	150
10.3	Overview of tutorial questions with corresponding UC, transition, and type of restriction for the transition.	153
10.4	Mental Model questionnaire with item number and item wording.	153
10.5	Means and 95% CI upper and lower bounds of bootstrapped mental model distributions for the four relevant items on L2 automation by the three experimental conditions.	156
10.6	Means and 95% CI upper and lower bounds of bootstrapped mental model distributions for the four relevant items on L3 ADS by the three experimental conditions.	156
10.7	Means and 95% CI upper and lower bounds of bootstrapped mental model distributions for the four relevant items on L3 ADS by the three experimental conditions.	158
11.1	Inferential statistics (i.e., F , $df1$, $df2$, p , η_p^2) of planned contrasts for the three performance parameters by UC, contrast type and contrast name .	180

11.2	Inferential statistics (i.e., F , $df1$, $df2$, p , η_p^2) for 2x4x4 mixed within-between ANOVA for each of the three parameters.	183
11.3	Linear regression coefficients (i.e., R^2 , p), equations with criterion (C) and respective predictor (p) and correlation coefficients (i.e., r , p) for experimenter rating, reaction times and error rate by four educational procedures.	185
12.1	Experimenter rating with domain, observed behavior and category. . . .	198
12.2	Descriptive statistics (i.e., N , M , SD , range) for performance parameter .	199
12.3	Descriptive Statistics (i.e., M , SD) for preference parameters (i.e., SUS, VDL usefulness, VDL satisfaction)	199
12.4	Inferential statistics (i.e., F , $df1$, $df2$, p , η_p^2 value) for performance and preference comparison by quartiles.	200

1 Introduction

Future modes of transportation in general and automated driving in particular are among of the most prominent challenges in the 21st century. Not a day passes by where news about technological advancements, new collaborations, ethical or liability issues concerning driving automation are reported in the media. People are both curious and skeptical about this trend. Before outlining theoretical considerations, the following scenario about a user with the arbitrary name David shall be considered:

As a customer, David buys a vehicle that is equipped with the latest technological features, among others driving automation. At the dealer site, he receives a brief introduction about multimedia, connected services and, of course automated driving features. When finally driving the car home and entering the highway, he decides to try the automated driving features. But: He notices that there are multiple control elements and also remembers that the vehicle is equipped with different levels of driving automation. By trying these features on the highway, David becomes more and more skilled in operating and understanding about the automation's capabilities, limitations and displays. Having arrived at home, his reporting to relatives and friends about the driving automation turns out to be enthusiastic due to the automated driving function itself and the unprecedented interface features.

This quite possible future scenario shows how users need a certain degree of initial understanding to appropriately use driving automation and operate the human-machine interface (HMI). Nevertheless, interface novelty and the new technological capability does not let some operating issues in the beginning show through in what he reports eventually. How do these seemingly contradictory examples align and what consequences does this pose to the development of research methodology for automated vehicle HMIs? The present thesis will encircle this initial thought experiment and investigate how users understand, interact and evaluate HMIs for automated driving.

According to Parasuraman and Riley (1997), automation can be defined as *"the execution by a machine agent of a function previously carried out by a human"* (p.231). Research on automation technology has a long tradition in many areas such as supervisory systems in refineries, naval and air transportation. For an extensive coverage of history of automation one might consider Bissell (2009). In the particular context of driving a vehicle, considerable efforts have been, are and will be undertaken to develop functions that partly or fully replace the human driver. At the present time, there is extremely fast growth in the race for commercial availability of driving automation. Assuming that Moore's law about exponential technology trends (Moore et al., 1965) holds true, an even more accelerated development can be expected for the future. With rapidly increasing system functionalities, there is an urgent need to consider appropriate HMIs to communicate system states especially via visual and auditory elements and also to let the user interact with these systems through haptic elements. The HMI is particularly important for a vehicle where a human driver is still an integral part and rules should ensure a high level of commonality (European Commission, 2017). This proliferation of functionality and interaction possibilities raises the necessity for developing robust methods to evaluate such interfaces (Kun, 2017; European Commission, 2017; Naujoks, Hergeth, et al., 2019). The Society of Automotive Engineers (SAE) norm J3016R states that level 3 (L3) automated driving systems (ADS) are characterized by temporarily taking over longitudinal and lateral vehicle control (SAE, 2018). It is not the driver's responsibility anymore to monitor correct system functioning (SAE, 2018) as compared to level 2 (L2) driving automation. The SAE levels of driving automation are more comprehensively outlined in chapter 1.3. Through this transfer of driving task responsibility, the opportunity to engage in non-driving related tasks (NDRT) arises. From a research methodological perspective, this change of responsibility requires the development of new methods for an evaluation of automated vehicle HMIs. Existing research methodologies (e.g., AAM, 2006; NHTSA, 2012) for HMIs cannot be simply transferred to higher levels of automation. The most obvious example is the case of lane keeping measures. In manual and L1 automation, lane keeping served as a measure of distraction potential and thus marked an important criterion for HMI evaluation. However, since driving automation of L2 and higher include additional lane keeping by the system, one cannot infer human performance from this measure anymore. In the next step from L2 to L3 automated driving, the driver's role shifts from monitoring correct system functioning in L2 to performing fallback performance in L3 in case the ADS leaves its Operational

Design Domain (ODD). The ODD is defined in SAE (2018) as “[...] *the specific conditions under which a given driving automation system or feature thereof is designed to function, including, but not limited to, driving modes*“ (p 12).

The potential benefits of automating the driving task such as increased comfort, safety and traffic efficiency (Nunes, Reimer, & Coughlin, 2018) can only arise if market introduction is successful. However, there might be resistance of people to actually use such systems (König & Neumayr, 2017). Eventually, it will be the soft, human factors such as safety and usability, not the hard technological factors, that determine success of technology introduction (Neale & Dingus, 1998). To overcome resistance and for the potential benefits to become reality, robust methods for the evaluation of both the system functions and especially the HMI are of utmost importance. Research on automated driving so far has largely investigated transfer of control events (so-called “*take-over situations*”) from the automated vehicle to the human operator. This revealed a variety of human factors issues such as fatigue (Jarosch, Kuhnt, Paradies, & Bengler, 2017; Woerle, Metz, Thiele, & Weller, 2019), trust (Forster, Naujoks, & Neukum, 2017; Hergeth, Lorenz, & Krems, 2017), mode awareness (Feldhütter, Segler, & Bengler, 2017) or controllability (Naujoks, Mai, & Neukum, 2014). In the present series of studies flawless functionality of driving automation is assumed at all times. Theoretically it is possible that sensors fail, digital maps are not available or other problems. However, to date there is no valid statement on the frequency of such incidents possible. An indication might be available from the California disengagement report (State of California, 2017), where developers of ADS have to report the number of safety driver interventions. As the systems are still under development and have not reached a maturity level for the commercial market, it is questionable whether these numbers resemble future series products. Instead of take-over scenarios, the assuredly much more frequent use case of a driver initiated transition between levels of automation (see e.g., Naujoks, Hergeth, Wiedemann, Schömig, & Keinath, 2018) under differing ODD restrictions shall receive attention in the present work.

Detailed background information on automated driving and human factors is outlined first. This chapter continues with the description of two important challenges for automated vehicle development, an overview of the SAE taxonomy (SAE International, 2018) and outline of prototypical HMI concepts. The subsequent chapter 2 reports a literature analysis and provides frequency indications on current trends in this particular field of study. The central issue for this thesis is then covered in chapter 3 leading to the main aim and objectives as described in chapter 4.

1.1 Challenges for Automated Driving Research

In the area of automated driving, two major challenges need to be considered in particular: Inexperienced users and increasing system complexity (C. A. Hart, 2019). Automating the driving task by implementing algorithms that take care of various vehicle guidance functions increases the distance between the driver and the vehicle (Billings, 2018). By rapidly adding more and more systems and functionalities (e.g., lane keeping assistant, adaptive cruise control, combined system function etc.), the driver is more and more detached from the direct, inner loop of vehicle control (Parasuraman & Byrne, 2003). Wickens, Hollands, Banbury, and Parasuraman (2015) describe the issue of *observability* that comes with automation. Here, due to complex algorithms that are embedded within the automation, the human operator is likely to not fully comprehend why and much less how an automated system does what it does. This rising complexity of driving automation marks the first challenge for human factors research.

The second challenge are inexperienced users in first contacts with driving automation technology. These first encounters with such an emerging and novel technology are characterized by inaccurate initial mental models (Beggiato, Pereira, Petzoldt, & Krems, 2015) and consequently poor operator performance (Rudin-Brown, 2010). Especially, when users initiate a transition between automation levels themselves (Naujoks, Hergeth, et al., 2018), they have to meet a certain number of conditions, depending on the desired level of automation (SAE, 2018). As during active L2 automation, the operator’s responsibility is to supervise correct system functioning, the number of restrictions concerning the ODD when initiating a transition to this particular level are comparably small. For L3 automation, however, the number of boundary conditions (i.e., speed, lateral position, automation availability) may rise due to the transition of driving task responsibility from the human driver to the ADS. These conditions for transitions between levels of driving automation and the increasing complexity pose a challenge to the human operator when interacting with this technology. The transitions, however, should not be difficult or time consuming for the driver to complete successfully (Parasuraman & Riley, 1997). If drivers face considerable task demands here in terms of understanding the HMI and executing the correct input action, it makes the system less attractive on the one hand and more prone to interaction errors on the other hand.

1.2 Manuscript Overview

The two challenges described above require the development of new methods. This work reports considerations and efforts of method development for automated vehicle HMIs. With a novel technology for inexperienced users, one phenomenon that can occur is the so-called *"preference-performance dissociation"* (Nielsen & Levy, 1994). As already described in the initial hypothetical scenario, users might hold favorable attitudes towards a technology but are poor at operating it. Conversely it can also occur that users succeed in interaction but still do not hold a favorable attitude towards the technology. These two instances where attitude and observed behavior do not agree are potential forms of the preference-performance dissociation. This relationship between preference (i.e., self-report) and performance (i.e., interaction performance) measures when conducting user studies marks the central issue on which the thesis is based upon. It shall be noted at this point that the aim is not to resolve the preference-performance relationship. Rather, this thesis aims to explain the underlying reasons. Hence, it can help to deal with influencing factors prior to planning user studies as well as explain dissociations post-hoc. An extensive outline of this phenomenon is provided in chapter 3. The first part of the thesis covers the question how to measure these two sources of data. The second part then investigates factors that influence either performance or preference and thus affect the relationship. For these purposes, three driving simulator studies were conducted. From this series of studies and theoretical considerations, nine publications have emerged of which eight are accepted and published and one is submitted and under review at present. As following, the publications are listed in the order of appearance herein. These nine manuscripts are the foundation for the following dissertation.

Manuscript 1 – Frison, A.-K., Forster, Y., Wintersberger, P., Geisel, V., & Riener, A. (2019). Where we Come from and Where we are Going: A systematic Review of Automated Driving Studies. *Manuscript submitted and under review.*

Manuscript 2 – Forster, Y., Hergeth, S., Naujoks, F., & Krems, J.F. (2018) How Usability can Save the Day: Methodological Considerations for making Automated Driving a Success Story. *Proceedings of the 10th International Conference on Automotive*

User Interfaces and Interactive Vehicular Applications. Toronto, ON, CN. ACM: New York. doi.org/10.1145/3239060.3239076

Manuscript 3 – Forster, Y., Hergeth, S., Naujoks, F., Krems, J. F., Keinath, A. (2019) Self-Report Measures for the Assessment of Human-Machine Interfaces in Automated Driving. *Cognition, Technology and Work*, 1-18. doi.org/10.1007/s10111-019-00599-8

Manuscript 4 – Forster, Y., Hergeth, S., Naujoks F., Beggiato, M., Krems, J. F. & Keinath, A. (2019). Learning to Use Automation: Behavioral Changes in Interaction with Automated driving Systems. *Transportation Research Part F: Traffic Psychology and Behaviour*, 62, 599–614. doi.org/10.1016/j.trf.2019.02.013

Manuscript 5 – Forster, Y., Hergeth, S., Naujoks, F., Beggiato, M., Krems, J. F., & Keinath, A. (2018). Learning and the Development of Mental Models in Automated Driving: A Simulator Study. *Proceedings of the 10th International Driving Symposium on Human Factors in Driver Assessment, Training and Vehicle Design*, Santa Fe, NM, USA, p. 398 – 404. doi.org/10.1145/3239092.3265960

Manuscript 6 – Forster, Y., Hergeth, S., Naujoks F., Krems, J. F. & Keinath, A. (2019). Tell Them How They Did: Feedback on Operator Performance Helps Calibrate Perceived Ease of Use in Automated Driving. *Multimodal Technologies and Interaction*, 3(2), 29. doi.org/10.3390/mti3020029

Manuscript 7 – Forster, Y., Hergeth, S., Naujoks F., Krems, J. F. & Keinath, A. (2019). User Education in Automated Driving: Owner’s Manual and Interactive Tutorial support Mental Model Formation and Human-Automation Interaction *Information (Switzerland)*, 10(4), 143. doi.org/10.3390/info10040143

Manuscript 8 – Forster, Y., Hergeth, S., Naujoks F., Krems, J. F. & Keinath, A. (2019). What and how to tell beforehand: The Effect of User Education on Understanding, Interaction and Satisfaction with Driving Automation. *Transportation Research Part F: Traffic Psychology and Behaviour*, 68, 316–335. doi.org/10.1016/j.trf.2019.11.017

Manuscript 9 – Forster, Y., Hergeth, S., Naujoks F., Krems, J. F. & Keinath, A. (2018). Unskilled and Unaware: Subpar Users of Automated Driving Systems Make

Spurious Decisions. *Adjunct Proceedings of the 10th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* Toronto, ON, CN. ACM: New York. doi.org/10.1145/3239092.3265960

1.3 Taxonomies of Automation

Automated driving is not binary yes versus no but characterized through a more gradual transition from manual operation without automated support up to full automation where human intervention is not necessary or not even possible at all. A generic taxonomy for automation has been suggested by Sheridan and Verplank (1978). The authors proposed a ten point scale from 1 (low) to 10 (high) automation based on different levels of human versus automation involvement and control. Here, the higher the level, the more involvement and control is transferred from the human to the automation. Actual system intervention in the task starts at level 5. Systems up to level 4 provide feedback but do not actively intervene or support in the task itself. Parasuraman, Sheridan, and Wickens (2000) extended this model to the stages of human information processing which are (1) information acquisition, (2) information analysis, (3) decision selection and (4) action implementation. Thus, automated systems might vary in the degree to which they support tasks on each of these four levels. With the rise of driving automation, domain specific frameworks have been developed. Three taxonomies are cited most frequently which are the German Federal Highway Research Institute (BAST) published by Gasser et al. (2012), the National Highway Traffic Safety Administration (NHTSA, 2013) and the SAE taxonomy that had been first published in 2014 and since revised twice in 2016 and 2018 (SAE, 2018). While the BAST and NHTSA align closely with their four levels of automation plus no automation at level 0, the SAE J3016R describes five levels of driving automation plus no automation at level 0. In 2018, the NHTSA officially adopted the SAE taxonomy with six levels of driving automation. As already objected by Hergeth (2016), the SAE taxonomy was eventually adopted by the research community as a common ground for communication. The six levels of SAE are shown in figure 1.1.

SAE J3016™ LEVELS OF DRIVING AUTOMATION

	SAE LEVEL 0	SAE LEVEL 1	SAE LEVEL 2	SAE LEVEL 3	SAE LEVEL 4	SAE LEVEL 5
What does the human in the driver's seat have to do?	<p>You <u>are</u> driving whenever these driver support features are engaged – even if your feet are off the pedals and you are not steering</p> <p>You must constantly supervise these support features; you must steer, brake or accelerate as needed to maintain safety</p>			<p>You <u>are not</u> driving when these automated driving features are engaged – even if you are seated in "the driver's seat"</p> <p>When the feature requests, you must drive</p> <p>These automated driving features will not require you to take over driving</p>		
What do these features do?	<p>These are driver support features</p> <p>These features are limited to providing warnings and momentary assistance</p> <p>These features provide steering OR brake/acceleration support to the driver</p> <p>These features provide steering AND brake/acceleration support to the driver</p>			<p>These are automated driving features</p> <p>These features can drive the vehicle under limited conditions and will not operate unless all required conditions are met</p> <p>This feature can drive the vehicle under all conditions</p>		
Example Features	<ul style="list-style-type: none"> • automatic emergency braking • blind spot warning • lane departure warning 	<ul style="list-style-type: none"> • lane centering OR • adaptive cruise control 	<ul style="list-style-type: none"> • lane centering AND • adaptive cruise control at the same time 	<ul style="list-style-type: none"> • traffic jam chauffeur 	<ul style="list-style-type: none"> • local driverless taxi • pedals/steering wheel may or may not be installed 	<ul style="list-style-type: none"> • same as level 4, but feature can drive everywhere in all conditions

Figure 1.1. SAE levels of driving automation. Retrieved from <https://www.sae.org/news/press-room/2018/12/sae-international-releases-updated-visual-chart-for-its-%E2%80%9Clevels-of-driving-automation%E2%80%9D-standard-for-self-driving-vehicles>

The step from one level to the next higher level of automation is characterized by an incremental transfer of responsibility for certain task components in the following order:

1. Steering OR accelerating
2. Steering AND accelerating
3. Monitoring correct system functioning
4. Performing fallback performance
5. Operation under unlimited conditions

The SAE J3016R considers systems up to L2 as "*driver support features*" and starting at L3, systems are considered as "*automated driving features*". Furthermore, it clearly describes what the human's and the system's responsibilities are at each level. Additionally, it provides examples for features at each level. The present work especially considers L3 automated driving being expected for market introduction soon. It also includes lower levels of automation (in particular L2) since vehicles will most certainly be equipped with combined automation functions. With the step from system monitor to the fallback ready user, conditions for human intervention with the system's HMI change. In the following chapter, an overview is presented about possible solutions for the design of automated vehicle HMIs.

1.4 Human-Machine Interfaces for Automated Driving

Some basic insights into design of HMIs are necessary to understand (1) conceptual approaches for automated vehicles in general and (2) understand about the methodology for evaluating these interfaces. This section will also show that the interfaces in the chapters describing the empirical work of this thesis (i.e., chapters 5–11) have used prototypical solutions for automated driving. Hence, the insights and method development generalize to a broad range of automated vehicle interfaces.

The HMI of an automated system has to show information about the to-be-automated driving task. Michon (1985) breaks this task down into operational (longitudinal and lateral vehicle guidance), tactical (maneuvering) and strategical (navigating) subtasks. The HMI especially needs to convey information about the operational aspect of accelerating/braking and steering as well as about maneuvers it is undertaking. By applying the SAE levels of automation (see chapter 1.3), certain requirements for the HMI can be derived from this taxonomy. Three straightforward requirements are outlined below.

1.4.1 HMI Requirements and Guidelines

First, due to the supervisory role of the driver in L2, silent automation failures (Louw et al., 2019) and transitions to manual without indications by the HMI are possible. In contrast, the take-over request (TOR) by the automated system for control transfers to the driver are a central aspect of L3 ADS and have been intensively investigated (see chapter 2). The fallback ready user in L3 automation can additionally be supported

with current information about system functioning during active automation. Such information, however, are not as mandatory for L2 automation since the driver’s role is supervising the driving automation(SAE, 2018).

Second, a difference between L2 and L3 automation is the extent of the ODD. While such an ODD is practically non-existent for L2 according to SAE J3016R, the L3 ADS *”permits engagement only within its ODD”* (p.20). Thus, only when specific conditions such as geographic, traffic or speed limitations are met, a transfer to L3 is possible. As a consequence, the HMI must not permit transitions as long as any of the required conditions is violated and also provide appropriate feedback (D. A. Norman, 1990) on the causes for potential failure to transfer control to L3 automation via its HMI.

Third, for the human driver to clearly distinguish between the levels of driving automation, active system states must be designed in a clearly distinguishable way so that issues such as mode awareness (Sarter & Woods, 1995) do not occur. These could lead to severe consequences in case a driver erroneously assumes a L2 as a L3 function, disengages from the driving task and is non-responsive to indications such as hands-on or attention requests (for abuse see e.g., Parasuraman & Riley, 1997). On the other hand, a confusion of L3 as L2 automation is not as dangerous but limits comfort since the user would most likely engage in the strenuous vigilance task of system monitoring instead of being relieved of this task.

These three examples as derived from the SAE (2018) have shown that HMI design has important challenges to face. Research and development has already come up with many suggestions for automated vehicle HMIs and representative examples shall be outlined in this section. In addition to a multitude of developed concepts, design frameworks and guidelines specifically aiming at standardization of automated vehicle HMIs have emerged recently. For example, consortia reports such as AdaptIVE Consortium (2017) of HAVEit Consortium (2011) describe HMI requirements. Building on these and earlier work in related domains such as warnings (Wogalter, 2006) and driver information systems (Green, Levison, Paelke, & Serafin, 1994), recent efforts are integrating automated vehicle research into these guidelines (Young, Koppel, & Charlton, 2017; Naujoks, Wiedemann, Schömig, Hergeth, & Keinath, 2019; Carsten & Martens, 2018). The work by Naujoks, Wiedemann, et al. (2019) developed a heuristic expert procedure with 20 items that evaluate the HMI regarding guideline compliance. Carsten and Martens (2018) discuss more generic goals of automated vehicles (e.g., engendering correct calibration of trust), discuss requirements and implications for design. The following outline is structured by describing different modalities, where the focus are visual and auditory

HMI components. Subsequently, the issue of automated vehicle operating elements for completing transitions and intervening in the automated driving task are discussed.

1.4.2 Examples for Automated Vehicle HMIs

Visual HMI Components

Besides components that are unique to automated driving, visual HMIs carry information that are also present during manual driving such as current speed and navigation information. For this reason, the strategic vehicle guidance (Michon, 1985) is not considered as important as operational and tactical information for HMI design. On an operational level, the HMI first has to support lateral and longitudinal vehicle guidance indications. Longitudinal guidance is frequently displayed through the absence or presence of a vehicle in front, time headway information in form of an adjustable distance bar and current set speed information (Naujoks, Forster, Wiedemann, & Neukum, 2017a; Manca, de Winter, & Happee, 2015; Carsten & Martens, 2018). Lateral guidance is usually displayed as the lane markings in the bird's eye view of the vehicle (see e.g., Kunze, Summerskill, Marshall, & Filtner, 2018). In general, these components resemble existing approaches for ACC with additional steering assistance (Purucker, Naujoks, Prill, & Neukum, 2016). In HAVEit Consortium (2011), they are considered essential information for automated vehicle HMIs. While this holds true for L3 ADS, it is not necessarily essential in L2 automation as mentioned above. Here, HMIs that are currently offered in the commercial market often only support single icons for these functions without showing the vehicle and its surroundings from a bird's eye view (see e.g., Carsten & Martens, 2018). Figure 1.2 shows possible design solutions for visual displays of L3 ADS systems. These all share the common features of (1) surrounding or at least a vehicle in front, (2) time headway and (3) lateral guidance indicators.

Figure 1.2. HMIs for active L3 automation taken from Naujoks et al. (2017a), Hergeth (2016) and HAVEit (2011) from left to right

A popular and important area of research is the transfer from automated to manual mode. Here, system-initiated messages have to be displayed that the fallback-ready user takes back control in a safe and efficient manner. HMI design for these scenarios has used the steering wheel as an indicator for manual vehicle control. Building on this, different HMIs show hands that grab the steering wheel (Jarosch, Bellem, & Bengler, 2019; HAVEit Consortium, 2011), elements indicating importance of the steering wheel (Louw, 2017) or further additional information about the upcoming control transfer such as situation specifics (Wiedemann, Schömig, Mai, Naujoks, & Neukum, 2015) or a countdown (Forster, Naujoks, Neukum, & Huestegge, 2017). Figure 1.3 shows potential design solutions for Take-Over Requests.

Figure 1.3. HMIs for Take-Over Requests taken from Jarosch et al. (2019), Louw (2017) and Forster et al. (2017) from left to right

HMI design issues of TOR such as the out-of-the-loop problem (Merat et al., 2019), NDRT engagement (Wandtner, 2018), timing and information issues (Wiedemann et al., 2015) have been addressed in prior research. System-initiated transitions from automated to manual control are not a focus here and this brief overview shall suffice.

Auditory HMI Components

Auditory displays do not require visual attention (Alvarez et al., 2011) and are therefore a useful and powerful channel especially under high workload conditions such as TOR scenarios (Politis, Brewster, & Pollick, 2015). On the downside of auditory display elements stands their nuisance potential (Beattie, Baillie, & Halvey, 2015) and therefore designers need to carefully consider the amount of implementation of auditory elements in HMIs for automated driving. Furthermore, due to the generic nature of earcons (Beattie et al., 2015), they first require learning. Results by Patterson (1990) have shown that such learning trials are rather short and earcons are learned quickly. Going further than the implementation of generic tones and earcons, there is also the

possibility to deliver semantic information via text-to-speech to the driver. Recently, this HMI channel has received attention in conceptual development and testing in driving simulation experiments (see e.g., Naujoks, Forster, Wiedemann, & Neukum, 2017b; Du et al., 2019; Koo et al., 2015).

Other HMI Components

Vibrotactile and olfactory HMI elements are also possible, but of inferior usefulness compared to visual and auditory messages. These elements might rather serve as additional HMI components but do not carry essential information. For overviews of olfactory interfaces see for example Dmitrenko, Vi, and Obrist (2016) and for vibrotactile interfaces see Petermeijer, De Winter, and Bengler (2015). Another possibility that can be applied in HMI design in addition to visual and auditory elements are motion cues such as roll and pitch vehicle motions (see e.g., Cramer & Kloth, 2019). The present work strongly puts its focus on the visual HMI with additional auditory elements.

HMI Input Components

Research on HMI input modalities in comparison to HMI output modalities is rather scarce. There is only a small number of studies that investigated different input components for interacting with the automated vehicle (e.g., D. R. Large, Banks, Burnett, & Margaritis, 2017; Frison, Wintersberger, Riener, & Schartmüller, 2017). At the present, commercial vehicles equipped with L2 automation provide the best insights into HMI development for operating components. Generally, two different approaches for operating automated driving are available. These are button-based and lever-based approaches. On the one hand, BMW, Audi and General Motors among others deploy button-based operating elements for activating and adjusting driving automation system. These buttons usually show icons or words indicating their respective effect or purpose. On the other hand, lever-based approaches are or have been pursued by Daimler, Tesla and Volvo. While Tesla uses the gear switch to activate the L2 automation, Volvo introduced two separate pedals behind the steering wheel that have to be pulled simultaneously. Up to now, these two approaches work quite well, but with approaching L3 automation and additional features, the approaches as they exist at the moment reach their limitations. Most likely, multiple buttons or level functions have to be merged and menu-based systems for selecting automation levels and adjusting single features need to be introduced. For example, ACC, lateral control and speed limiter are support systems and might be combined within a menu for selecting from driver support features in

button-based approaches. Lever-based interfaces also face similar challenges. The rising number of levels and functions on the one hand and the design principles of simplicity and appropriateness for automation (D. A. Norman, 1990) thus put a challenge to HMI designers and developers.

This section has briefly described requirements derived from SAE J3016R, design guidelines and shown prototypical examples of L3 automated vehicle HMIs. For output approaches, it especially described visual and auditory elements that characterize automated vehicle interfaces. The two most important input elements are buttons or levers at the present time. Taken together, these HMI elements will lie the foundation for the design of the HMIs in the empirical studies undertaken for the present thesis. By sticking close to these design approaches, the methodological insights gained in the present work can well be generalized to a wider spectrum of automated vehicle HMIs. Having outlined the conceptual basis of automated vehicle HMIs, the upcoming chapter focuses on the methodological aspects of automated driving research.

2 Human Factors in Automated Driving: Status Quo of Research ¹

Abstract: During the last decade, research has brought forth a large amount of studies that investigated driving automation from a human factors oriented perspective. Due to the many methodological possibilities for study design concerning investigated constructs, data collection and parameters, at present, the pool of findings is heterogeneous and nontransparent. This literature review applied a structured approach in reviewing $N=161$ scientific papers of relevant journals and conferences that investigated driving automation. It thus allows a statement on the status quo of existing methodological approaches. Results revealed that most studies focused on safety aspects followed by trust and acceptance. These were mainly collected through self-report measures. Driving/TOR performance also marked a significant portion of the data, however a wide range of different parameters are investigated. The findings identify gaps to be addressed in future studies, and allow researchers to investigate known constructs with established methods.

2.1 Introduction

This chapter takes a closer look into research trends and methods in the automated driving domain. It will describe a literature analysis that aimed at finding out about what topics have received considerable interest so far and simultaneously which topics still need closer investigation. Furthermore, it provides an in-depth assessment of methodological procedures and parameters found in 161 publications. Thus, a sophisticated decision concerning the area of research in the present work can be drawn.

The advent of automated driving functions and according HMIs marks one of the biggest

¹This chapter is based on a previous publication: Frison, A.-K., Forster, Y., Wintersberger, P., Geisel, V., Riener, A. (2019) Where we Come from and Where we are Going: A Systematic Review of Automated Driving Studies. *Manuscript submitted and under review*

game changers in transportation research and development of our time. In 2013, the SAE (2018) published the first version of their definition describing different levels of automation, which addresses challenges, sets foundation for future standardization, and establishes a common language. With SAE L2 driving automation already on the road, it is only a matter of time until SAE L3 ADS, or even higher levels, are commercially available. Due to the enormous potential of technological progress, enthusiasm among researchers has sparked to develop functions and interfaces. Investigations of these features through user studies are conducted to first determine feasibility and in a next step to fine tune conceptual approaches. Here, basic research findings from engineering psychology and human factors on the one side, as well as computer science on the other have been applied by automotive industry and academia. Furthermore, some lessons learned from prior automation development in the aviation sector (Gawron, 2019; Trösterer et al., 2017) could be transferred, despite different conditions for driving automation such as the user population or dynamic of traffic conditions. As a result, there is a wide range of challenges that need to be overcome and a multitude of publications addressing these timely issues have been published over the last years. However, it is often hard to integrate and/or compare the obtained findings as topics are often investigated differently. Furthermore, due to the sheer amount of findings it is hard for researchers to identify gaps on which they could build upon.

Thus, we² claim that the time has come to systematically review, which topics in driving automation received the most attention and which methods have been applied to investigate these.

2.1.1 Research Status on Automated Vehicle HMIs

User studies on automated vehicle HMIs have focused on different constructs, applied different collection methods, and also evaluated different parameters. In addition, different study design approaches are possible, which in turn depend on the respective construct and collection measure. Since there is no common agreed-upon methodological framework for evaluating automated vehicle HMIs, the only sources researchers could consult are several different consortia reports (e.g., AdaptIVe Consortium, 2017; RESPONSE Consortium, 2006; HAVEit Consortium, 2011). There have been first ef-

²Since this and following chapters are based on prior published or submitted manuscripts, first person pronouns appear in these chapters. To stick close to the original version and maintain readability, these formulations are kept throughout the thesis. The pronoun therefore refers to the respective authors of the original publication.

forts to give an overview of methodological approaches in automated driving (Forster, Hergeth, Naujoks, & Krems, 2018a) without reviewing a broader set of categories, or human-computer-interaction research on user experience in general (Pettersson, Lachner, Frison, Riener, & Butz, 2018). Therefore, the present work aims at combining these approaches, and provide researchers and practitioners with an overview of current and past topics of automated driving. It also points towards improvements in the future, and unveils directions that have yet to be investigated. The main contribution of this chapter is twofold concerning the status quo and derivation of future research directions:

- First, the present work provides an overview of different possibilities for study design in driving automation research
- Second, it outlines which constructs have been investigated, which data collection methods have been applied, and which specific parameters have been calculated and reported

To reach this aim, we developed and followed a well-structured approach for reviewing literature. First, we summarize important topics in driving automation that have been addressed in the last years, followed by a precise description of inclusion/exclusion criteria for publications used in this literature review. We then outline a procedure creating a database in which relevant contributions can be stored. Eventually, descriptive results of queries on the database are presented. The results of this literature review are expected to add to a better understanding of current trends and research directions of automated driving. Hence, it holds a mirror to this research community on what has been accomplished and which future aspects need more attention. We have to acknowledge the fact that, rather than taking a look outside of this community and bringing knowledge into the community, we can only provide a statement on the status quo of research within this community itself. However, this is a necessary first step before going beyond reviewing further conferences and journals.

2.1.2 Constructs and Dependent Measures

Early research efforts in automated driving have often focused on TOR scenarios, where the system exceeds its operational design domain, and prompts the driver to pause/stop their NDRT and regain manual vehicle control. These transitions are either due to sensor failures/malfunctions or because the system issues a planned indication to take over. In both cases it is the user’s responsibility to ensure a safe transition to manual. Other studies frequently applied survey approaches to investigate public acceptance and readiness

for the introduction of this technology to the consumer market (Nordhoff et al., 2018; Oswald, Wurhofer, Trösterer, Beck, & Tscheligi, 2012; Rödel, Stadler, Meschtscherjakov, & Tscheligi, 2014). The downside of these acceptance-related studies is that mostly, no realistic automated driving system is provided to the users. At best, a description of such a system is given that requires a lot of imaginative power. A closely linked construct to acceptance is trust in automation. Here, there have been driving simulator studies that supported realistic ADS representations and HMIs (Wintersberger, Riener, & Frison, 2016; Forster, Naujoks, Neukum, & Huestegge, 2017; Hergeth, 2016; Payre, Cestac, Dang, Vienne, & Delhomme, 2017). Other topics more recently emerged that go beyond safety-related issues, such as usability (Forster, Hergeth, et al., 2018a), and user experience (Rödel et al., 2014; Frison et al., 2017) of ADS and HMIs. In the usability domain, research questions mainly focus on the measures and appropriate conditions under which users effectively and efficiently interact with driving automation and in turn are satisfied with the interface (DIN-EN ISO, 2011). For a more comprehensive outline of usability and automated driving forming the central aspect of the present work see chapter 3.2. This also marks an additional factor in common acceptance frameworks (Davis, 1989; Venkatesh, Morris, Davis, & Davis, 2003).

User Experience (Hassenzahl, 2001) expands usability going beyond mere pragmatic aspects of using driving automation by adding hedonic qualities. With drivers being relieved of driving themselves, there might be a lack of fulfillment of needs (Sheldon, Elliot, Kim, & Kasser, 2001; Frison et al., 2017). Consequently, despite effectiveness and efficiency in interaction, positive emotions and attitudes towards driving automation are not guaranteed. For a more comprehensive outline of the attitude constructs (i.e., usability, UX, acceptance, trust) see chapter 3.2. Besides different constructs, collection methods, and parameters, which are all closely tied to dependent measures, there is also a variety of study design possibilities when conducting user studies on automated driving.

2.1.3 Possibilities for Study Design

One important aspect is the study environment which is a driving simulator in many instances. Here, the degree of immersion varies from low fidelity simulation with only a desk and attached steering wheel plus a simple desktop monitor (e.g., Forster, Naujoks, & Neukum, 2016; Seppelt, Lees, & Lee, 2005) to high fidelity driving simulation with (Wintersberger, Frison, Riener, & von Sawitzky, 2019; Forster et al., 2019b; Louw, 2017) or without a moving-base platform (Donmez, Boyle, Lee, & McGehee, 2006; Gold,

Damböck, Lorenz, & Bengler, 2013). Moreover, depending on the availability of an automation function, studies on test tracks and real roads are possible (van Veen, Karjanto, & Terken, 2016; Yusof et al., 2016). Other types of studies use an interview or survey setting to gain insights into automated driving because the users have used such a system before (e.g., Trösterer et al., 2017; Dikmen & Burns, 2016), or they rather target the readiness of the consumer population (e.g., Kyriakidis, Happee, & de Winter, 2015; Rödel et al., 2014).

Another aspect providing researchers with possibilities for study design is the representation of the automation. At the moment, most user studies in the automated driving context are set up in a simulation environment, since maturity of this technology is not yet given. A vast majority of studies has been conducted in driving simulators, where automated vehicle functions and HMIs can be implemented without much effort and tests in a risk-free and standardized environment are possible. However, first on-road tests have been conducted in Wizard-of-Oz (Omozik, Yang, Kuntermann, Hergeth, & Bengler, 2019; Naujoks, Purucker, Wiedemann, & Marberger, 2019) or real vehicles (Wintersberger, Riener, Schartmüller, Frison, & Weigl, 2018). As mentioned before, there are studies that take a survey approach and represent the driving automation by means of static descriptions (Kyriakidis et al., 2015) or sketches (Rödel et al., 2014).

Studies also differ in the type of research or main focus and contribution they bear. Some studies target conceptual development with a subsequent proof-of-concept user study (Kunze et al., 2018; Hock, Kraus, Walch, Lang, & Baumann, 2016; Chang, Toda, Sakamoto, & Igarashi, 2017). Other approaches more generically cover basic research topics, and focus on fundamentals of human perception and action in the automated driving context. Such research is rather independent from specific HMI concepts but implications hold true for the variety of conceptual approaches (van der Meulen, Kun, & Janssen, 2016; Sikkenk & Terken, 2015). A similar independence from certain HMI concepts is a characteristic of methodological work. Such studies aim at providing instruments and tools for proper study conduction when evaluating HMIs (Naujoks, Wiedemann, et al., 2019; Balters, Sibi, Johns, Steinert, & Ju, 2017).

The heterogeneity of constructs, use cases and ADS operationalization has recently led to first efforts in methodological standardization. For example, various taxonomies (McCall, McGee, Meschtscherjakov, Louveton, & Engel, 2016; Naujoks, Hergeth, et al., 2018) have been proposed to describe TOR scenarios and related use cases (Gold, Naujoks, Radlmayr, Bellem, & Jarosch, 2017). Also regarding TOR, many research groups follow their own measurement procedures and evaluation methods, which highlights the

need for standards. With these considerations and the authors' experience in automated driving research in mind, we defined the reviewing process for this literature review.

2.2 Pilot Study

2.2.1 Purpose and Method

To first identify relevant journals and conferences in the Human Factors community, we conducted a pilot study. An online survey was distributed via social media (e.g., Twitter, LinkedIn etc.) and to peers of the authors. In the survey, participants could indicate (1) both the top 3 journals and conferences where they have already published as well as (2) both the top 3 journals and conferences where they consider submitting an article (favored). Moreover, the survey included questions on whether the authors have already published original research on automated driving (yes vs. no) and the year of the author's first publication. Eventually, demographic data (i.e., age, gender, academic degree and academic background) were collected.

2.2.2 Results

Demographics showed that mean age of the $N=21$ participants ($n=5$ female) was 32.81 years ($SD=5.65$, $MIN=24$, $MAX=49$). $N=10$ participants held a Master's degree, $n=9$ a PhD and $n=2$ were professors. The Academic Background showed that the majority were psychologists ($n=8$), followed by engineers ($n=5$), computer scientists ($n=5$). $N=2$ participants had a Human Factors or Media Informatics background. For Academic background there was more than one indication possible. Out of the $N=21$ participants, $n=19$ have already published whereas $n=2$ have not yet published their research. The earliest publication dates back to 1999 and the latest to 2016.

For the identification of relevant venues, we counted the overall number of instances independently from its position (i.e., 1st vs. 2nd vs. 3rd rank). The results regarding journals showed that Transportation Research Part F ($n=7$ publications, $n=11$ favored), the Journal of Human Factors ($n=7$ publications, $n=11$ favored) and Accident Analysis and Prevention ($n=7$ publications, $n=6$ favored) were the most frequently indicated venues. Regarding conferences, the AutomotiveUI ($n=6$ publications, $n=13$ favored), the Human Factors and Ergonomics Society Annual Meeting ($n=2$ publications, $n=11$ favored) and the CHI conference ($n=2$ publications, $n=6$ favored) were mentioned most

Figure 2.1. Decision Tree for paper selection.

frequently. Based on this expert survey we reviewed these three journals or conferences regarding automated driving evaluation.

2.3 Methods

2.3.1 Selection Process

The basis for the selection of papers for the present literature analysis were all publications in the respective venues (see section 2.2) in the years up to and including 2018. We developed a decision tree to decide in a standardized and stepwise manner, whether or not to include each publication. This decision tree is depicted in figure 2.1. It features four steps represented through binary decisions, where each has to be answered with "yes" for a respective publication to be included into our analysis. To pass the first step of the decision tree, the publications had to contain at least one of a set of keywords related to driving automation in the full text (see below). These keywords were selected to initially reduce the amount of publications in a reasonable way, and at the same time to ensure that no potentially relevant publication would be excluded in this step. The first step of the decision tree was implemented by searching all data bases using the following search terms:

"automated driving" OR "autonomous driving" OR "self-driving" OR "self driving" OR "autonomous vehicle" OR "automated vehicle"

Publications that did not feature automated driving represented by at least one of the keywords, as well as short papers, posters, and adjunct proceedings (e.g., Forster, Hergeth, Naujoks, & Krems, 2018b), were excluded in this step. For the remaining publications, the next step in the selection process consisted in examining if its objective was an empirical study to discard other literature reviews, as well as juridical, theoretical, or ethical publications (e.g., Millonig & Fröhlich, 2018; Inners & Kun, 2017). The subsequent step of the decision tree aimed at the primary focus of the empirical works. If this was not research and development of automated driving, the respective publication was excluded from further analysis. This step was incorporated to discard works on a concept that, in principle, could be used for the development of automated driving, but were not originally investigated with that purpose (e.g., Roider, Rümelin, Pfleging, & Gross, 2017). In the last step of the selection process,

we took a closer look at the levels of automation (SAE, 2018) that were investigated. The level of mere driver assistance (Level 1) as well as concepts which do not fall under the driving automation definition according to SAE (e.g., Merenda et al., 2017; R. Liu, Kwak, Devarakonda, Bekris, & Iftode, 2017) were out of scope for this literature analysis. Thus, only publications examining L2 and/or higher levels of automation (i.e., simultaneous lateral and longitudinal vehicle guidance) were included. Overall, 161 publications passed all steps of the decision tree and were included in the literature analysis.

2.3.2 Reviewing Strategy - Workshops

After selection of the papers, we developed a reviewing strategy for literature analysis in two expert workshops. The first workshop lasted six hours and aimed at developing a standardized reviewing procedure to ensure high inter-rater reliability. In order to verify inter-rater reliability, the five reviewers classified ten randomly selected papers according to the decision tree. The outcome is presented in the following result section (see section 2.4). After the workshop, the resulting categories/dimensions as well as their emerging relations were translated into a database. For a detailed description of the categories and the database see chapter 2.3.3. Subsequently, five reviewers classified the selected 161 publications by sorting them into the categories of the database. In case a new category occurred that had not been considered before, it was added to the database. Despite setting up a large number of constructs during the expert workshop and adding further options during the review process, there still remained a considerable number of parameters that could not be assigned free of doubt. This resulted in the two constructs *General Attitude* and *Interaction Behavior*. In these instances, information was scarce and only high level indications about interface evaluation were provided by the authors. After reviewing, we conducted another expert workshop which lasted approximately four hours. During this workshop, lessons learned from the reviewing process were derived and each reviewer could put unclear classification up for discussion. Thus we ensured high reviewer agreement in classification of the selected papers.

2.3.3 Database Structure

We set up an Microsoft Access data base to capture the relevant information for the investigation (see figure 2.2). The schema consisted of the five main tables *Paper*, *Con-*

ference, *Construct*, *CollectionMethod*, and *Parameter*. In the following, we introduce the most relevant properties:

- **Paper:** For each paper, we collected descriptive information (title, abstract, year, authors, conference), as well as the levels of automation addressed in the study. The following additional information was collected: The type of user (driver, passenger, external), road type (urban, highway, rural, not relevant), study type (lab, test track, real road, survey), the representation of the AV (static text description, sketch, driving simulator, Wizard-of-Oz, real vehicle), study period (single session, short-term, long-term), type of research (basic research, concept evaluation, method development, model development), as well as participant information, such as the number of subjects, their mean age, as well as if they were internally (students, employees, etc.) or externally recruited.
- **Construct:** Represents the topics of investigation. To avoid subjective interpretation by the reviewers, we only collected constructs which were explicitly mentioned by authors in the publications (such as *Safety*, *Trust*, *Acceptance*, etc.). All constructs which were only investigated by one single paper are summarized within an *other* construct. Generic investigations on participants' opinion and general perception without explicitly mentioning specific constructs are summarized as a *General Attitude* construct.
- **Collection Method:** Relevant data collection methods, such as *driving performance*, *TOR performance*, *secondary task performance*, *standardized questionnaire*, *interview*, etc.. Again, we came up with initial suggestions that were expanded in case a new item emerged during the reviewing process.
- **Parameter:** Parameters that were used in the different data collection methods, for example standard deviation of lateral position (SDLP, Knappe, Keinath, & Meinecke, 2006), reaction time, gaze-off-road time, technology acceptance model (Davis, 1989), NASA-TLX (S. Hart & Staveland, 1988) (examples for standardized questionnaires).
- **Relationships:** To structure our data, we created a relationship table to represent (n:m) relations of papers, collection methods, parameters and constructs. Thus, each paper can investigate different constructs, each construct can be assessed by one or multiple data collection methods and each data collection method by one or multiple parameters. For each relation, we observed whether the set was

Figure 2.2. Entity relationship diagram of the database structure showing the relations between papers, constructs, data collection methods and parameters.

measured through behavioral, self-reported or physiological data. Furthermore, we assessed if the parameter was measured before, during or after a trial in the experiment. This data model allowed us to store all information without duplicates (each construct/parameter/collection method was stored only once), while the relations allow to perform powerful queries on the data (in comparison to pure list/sheet based representations).

2.4 Results

In the following, we report the results from our literature study on the final 161 publications, which were identified as relevant for further investigation. All results were obtained using the built-in structured query language (SQL) of MS-Access.

2.4.1 Inter-rater Reliability

To ensure inter-rater reliability, the five raters were compared by means of intra-class correlations (ICC). ICC estimates were calculated based on a single-rating, consistency, 2-way random-effects model. Results revealed a high inter-rater reliability with a correlation of $r=.809$ ($F(9,36)=22.170$, $p<.001$). Due to this result, high inter-rater reliability of the following classifications can be assumed.

Figure 2.3. Frequencies of publications regarding the investigated SAE levels of automation, presented over the time since 2010 (SAE L0 and L1 are excluded as they are not part of this literature review).

2.4.2 General Study Details

Regarding levels of automation, we found that SAE L3 is the most frequently studied level of automation with 58.39% ($n=94$) followed by Level 2 (36.65%, $n=59$) and Level 4 (22.36%, $n=36$). Level 5 was investigated in 19.88% ($n=32$) of the studies. The number of publications gradually increased up to 2018 regardless of a specific level of automation. Outstanding is L3, which attracted earlier attention than the other levels (see figure 2.3).

Overall, 73.29% ($n=118$) of all studies were conducted in a lab environment, 13.66% ($n=22$) as a survey, and 11.80% ($n=19$) on real road. 2.48% ($n=4$) reported results from a test track study. This is in accordance with the automated vehicle representation. 71.43% ($n=115$) of the papers reported to have used a driving simulator, 12.42% ($n=20$) a real vehicle, 7.45% ($n=12$) a Wizard-of-Oz setup, 11.18% ($n=18$) a textual description and 3.11% ($n=5$) a visualization. There was a clear tendency towards single session evaluation (94.41%, $n=152$). 3.11% ($n=5$) of the studies were conducted over a short time period (up to six days; e.g., J. Lee et al., 2016). $N=3$ studies (1.86%) investigated long-term effects (e.g., Dikmen & Burns, 2016).

While 60.25% ($n=97$) of the publications focused on basic research such as observing

Figure 2.4. Frequencies [n] of age groups in the automated driving studies.

pedestrians' interaction behavior with AVs on real roads (Currano et al., 2018), 34.78% ($n=56$) evaluated a specific concept in their study such as a haptic seat to prepare driver for TORs (Telpaz, Rhindress, Zelman, & Tsimhoni, 2015). Smaller numbers of studies report empirical research about AD with the aim to create a method (8.07%, $n=13$) or a model (1.86%, $n=3$).

The center of empirical research on AD is clearly the driver, who was investigated in 78.26% ($n=126$) of all studies. Passengers (9.32%, $n=15$) and other road users (e.g., pedestrians, 6.83%, $n=11$) are still a side topic. The ADS context is varying, while 47.83% ($n=77$) investigated a highway scenario, 19.88% ($n=32$) urban and 19.25% ($n=31$) rural road conditions. For the remaining studies (13.04%, $n=21$), the road type was not relevant or not reported.

Study participants' mean age in the most papers is below 40 years ($n=98$). A smaller number of publications report high mean ages such as Frison et al. (2017), who invited participants older than 65 to compare their acceptance of automated vehicles with participants of younger age (see figure 2.4). In 12.42% ($n=20$), participants' age is not reported.

2.4.3 Methodological Approaches

Regarding methodological approaches we observed that 74.91% ($n=119$) of all papers involve self-reported data collection, 64.60% ($n=104$) behavioral and 10.56% ($n=17$) psycho-physiological data.

More than 50% of the publications collected different types of data (55.28%, $n=89$). Here, 44.72% ($n=72$) of the papers collected behavioral and self-report data. Less common is the combined collection of self-report, behavioral and psycho-physiological data (6.21%, $n=10$). The combinations of behavioral and psycho-physiological data ($n=5$) and self-reported and psycho-physiological data ($n=2$) occur seldom. A large portion of the publications (44.72%, $n=72$) is working with only one type of data. These papers use mainly self-report measures (27.95%, $n=45$), while 16.77% ($n=27$) of the papers report exclusively behavioral data.

Overall, we identified $n=22$ different collection methods. The self-defined questionnaire is the most frequently used method (54.94%, $n=89$) in automated driving publications. This is in accordance with the large number of self-report data. Standardized questionnaires (43.83%, $n=71$) and TOR performance measures (37.65%, $n=61$) are frequently used as well. Driving performance measures (24.07%, $n=39$), eye tracking/gaze behavior (24.07%, $n=39$), Interviews (15.43%, $n=25$) and secondary task performance (9.26%, $n=15$) are used more seldom.

2.4.4 Constructs and Parameters

To describe empirical research on automated driving in more detail, we took a closer look at the constructs, which were investigated in the individual studies. We observed that there was a broad range of 36 distinct constructs in all analyzed studies. Constructs, which are used frequently are safety (50.93%, $n=82$), trust (22.98%, $n=37$), acceptance (21.12%, $n=34$) and workload (19.88%, $n=32$). General attitude (12.42%, $n=20$), situation awareness (11.18%, $n=18$), stress (9.32%, $n=15$), interaction behavior (6.83%, $n=11$), drowsiness/fatigue (6.83%, $n=11$) and user experience (6.21%, $n=10$) are also frequently investigated. A small number of publications regards automated driving issues such as comfort and productivity (5.59%, $n=9$ each), emotions (4.97%, $n=8$) or usability (4.35%, $n=7$). The present thesis will not go into more detail concerning frequencies of parameters for all the constructs and collection methods as they can mostly be derived from the figure. What is worth a mention, however, is the usability construct: To assess *usability* of automated driving, authors mainly developed an own questionnaire ($n=4$) or used the System Usability Scale (SUS, $n=3$) (Brooke, 1996). A single paper used the Think Aloud technique and two publications report results of semi-structured interviews.

2.5 Discussion

The present literature review showed that self-report measures mark the most prominent measure in automated driving research. In comparison to that, there is further need to report accompanying behavioral measures, such as driving/TOR performance, or gaze behavior. Moreover, concerning areas of research, safety aspects received the most attention to date, followed by acceptance and trust. From these results, recommendations and future research directions were derived. The following paragraphs discuss findings of (1) study setups, (2) data collection methods, (3) reported parameters, and (4) investigated constructs.

2.5.1 Study Setups

Concerning representation and study type we found that most studies were conducted using driving simulators. Hence, present research supports high internal validity making effects of differing conditions on dependent measures interpretable. On the downside, the obtained results might lack external validity, and there is no guarantee that they generalize to real world settings, since driving simulators may lack realism due to insufficient field of view or motion feedback. Thus, by lacking a feeling of presence (Slater, 2003), transfer of behavior found in the laboratory to real world settings might be limited (Will, 2017). Conditions in realistic driving studies are not as controlled as in a laboratory but might differ in terms of surrounding traffic, weather conditions or vehicle speeds. Despite the restriction of high internal but limited external validity, we can assume that strong and consistent effects such as the dependency of TOR response time on driver state (e.g., Jarosch et al., 2017; Naujoks, Befelein, Wiedemann, & Neukum, 2017; Gold et al., 2013; Wandtner, 2018; Wintersberger et al., 2018) also pertain in real world driving. Despite this criticism, we acknowledge that driving simulators are still immersive research tools providing a certain and in many cases sufficient degree of external validity (Kemeny & Panerai, 2003; Hock et al., 2018). In that vein, the experiments that are conducted for the present thesis align to state of the art settings using high fidelity driving simulation.

Results showed that research interest especially for SAE L3 automated driving has sparked in the last decade (see figure 2.3). This supports the aim of the present work for intensifying research effort in this domain. Especially since method development and standardization have largely been neglected as compared to conceptual development and technological feasibility.

The age distribution showed similarities a bell shape curve (see figure 2.4). This indicates that across all identified studies, participants' age was balanced and overall, findings can be well generalized to the population. Both young and therefore novice, as well as elderly drivers, are considered in these studies.

2.5.2 Constructs

The majority of parameters were well classifiable within the database. The safety construct constituted the largest part of all measures. This shows the importance of safety concerns when it comes to investigate driving automation technology. Investigations on TOR performance during system failures have been the first scenarios in human-automation interaction research (Gold et al., 2013; Merat, Jamson, Lai, Daly, & Carsten, 2014; Naujoks et al., 2014). Right now, it seems like a re-orientation of recent research is taking place which is also reflected in the remaining constructs of the database. Trust (Ghazizadeh, Lee, & Boyle, 2012) and intention to use (Davis, 1989) constitute precursors of actual system use, and therefore research has more closely investigated these constructs. Besides the outlined well-investigated constructs, there remain other constructs that have rather been neglected until now. The reason why research has paid less attention on usability or UX until now might be that these are rather precursors of the higher priority constructs (i.e., safety, acceptance). Another reason might be that the scenario where automation fails and humans need to step into action was an important issue to determine feasibility of driving automation in general. We argue, that more emphasis should be paid to other types of interaction such as ongoing automation, user-initiated or planned transfers of control, as most likely, these use cases will occur more frequently than automation failures (Eriksson & Stanton, 2017). From that, the need to investigate efficient and effective interaction arises (see chapter 3).

2.5.3 Data Collection Methods

Concerning collection methods, the results showed that a vast majority of studies collected self-report data. In comparison to that, behavioral data was reported in about two out of three publications. From there, the question arises, what the reasons for this observation are. One obvious reason is that survey approaches (Rödel et al., 2014; Löcken, Heuten, & Boll, 2016) might focus more on technology readiness and deliberately collect attitudinal measures only. For these approaches, to date, there is no available behavioral criterion, such as buy/usage rates. As soon as the functions are available,

however, research needs to investigate whether predictions made by these studies hold true. With commercial availability of L2 automation, such a study could have already been conducted, but to our knowledge this is still missing.

Research on acceptance of driving automation is not a focus of the present thesis since behavioral measures for these attitudes stretch over longer periods of time that a driving simulator study could afford. Furthermore, acceptance research requires the user to freely choose behavioral interaction with the driving automation which he/she decides based on specific attitudes towards the system and the HMI. Since research on human-automation interaction focusing on HMI issues rather forces participants to solve certain use cases (see e.g., Naujoks, Hergeth, et al., 2018), the behavior is not independently chosen by the user and thus acceptance assessments are restricted (see also chapter 3.2.1).

Another factor for the imbalance might be that self-report measures are seemingly easier to collect. It does not take comparably much effort to hand out a questionnaire or interviewing participants. However, researchers need to be careful when it comes to collect reliable and valid self-report data. This concern is further elaborated on in chapter 5.1. In contrast, the collection of behavioral data is much more complex. For example, dynamic vehicle data requires extensive pre-processing before descriptive and inferential analyses can be run. The collection of eye-tracking data requires even more resources due to the need for manual calibration to ensure data quality, although such data provides the possibility to make direct inferences about cognitive processes (Just & Carpenter, 1976). For example, prior research has shown that the number of gaze switches can serve as an indicator for reliance behavior (Hergeth, Lorenz, Vilimek, & Krems, 2016). Its role for interface understanding is still unclear and empirically investigated in chapter 8. One solution to the difficulty and extensive effort of collecting behavioral data might be experimenters' single-item ratings of interaction performance (e.g., Kenntner-Mabiala, Kaussner, Hoffmann, & Volk, 2016; Jarosch & Bengler, 2018). However, this approach requires well-trained raters and, ideally, ratings are given single-blind, so that the rater is not aware of assigned experimental conditions for the participant. Also, there should be more than one rater to ensure inter-rater reliability. Despite requiring additional time and cost efforts, the analysis of behavioral data should be an inherent part of a user study, since it can provide additional valuable insights about the tested interface or feature. It is not for nothing that the usability ISO-9241 (DIN-EN ISO, 2011) includes effectiveness and efficiency as behavioral components and satisfaction as an attitudinal component.

The present review has shown that many behavioral and self-report measures for the evaluation of automated vehicle HMIs are available. Yet, the suitability of these measures remains to be investigated. Chapters 5 and 7 provide empirical results on reliability and validity of self-report and behavioral measures in driving automation research.

2.6 Conclusion

This chapter provided a review of the status quo of methods for automated driving research and pointed towards future research directions. We followed a structured approach to give an overview of the research domain by selecting relevant papers and reviewing them in a standardized manner using a relational database. There is a good portion of research in different aspects of driving automation indicating that researchers in the community work with a broad focus in the timely issue of developing and improving automated vehicle HMIs.

This chapter showed that the construct of usability has so far been largely neglected in research on automated driving. While imperfect automation and TOR scenarios have already received much attention, it is time to assume flawless functioning and investigate automated vehicle HMIs accordingly (see also chapter 1.1). Additionally, this chapter gave an overview of methodology for automated driving research and supports the approach of the empirical work reported herein (e.g., driving simulator, sample age distribution, single session). The following chapter will turn towards the central research issue of agreeableness between preference and performance data in human factors research in general and automated driving in particular.

3 How Usability can save the Day: Methodological Considerations for making Automated Driving a Success Story ³

Abstract: It will not be long until Level 3 Automated Driving Systems (L3 ADS) enter the consumer market. An important role corresponds to methodology development. The present paper gives impetus to the process of developing robust methods for evaluating Human-Machine Interfaces (HMI) for L3 ADS. First, a literature review on automotive interfaces concerning methodology application is outlined showing that studies often lack to provide both self-report and observational data. To derive a comprehensive image of HMI quality, we recommend multi-method approach in user research. Subsequently, we provide an overview of state-of-the-art self-report and observational measures. From the availability of measures and the necessity to include both in user studies, the issue of the performance-preference dissociation arises. It threatens study designs and interpretation of results. Following methodological recommendations from the present work supports researchers and practitioners in the area of automated driving for proper study design and interpretation of study results.

3.1 Aim of this Chapter

The previous chapter gave an overview of current trends and future research directions in automated driving. It showed that usability research for L3 ADS needs closer investi-

³This chapter is based on a previous publication: Forster, Y., Hergeth, S., Naujoks, F., Krems, J.F. (2018) How Usability can save the Day: Methodological Considerations for making Automated Driving a Success Story. *Proceedings of the 10th International Conference on Automotive User Interfaces and Interactive Vehicular Applications*. Toronto, ON, CN. ACM: New York. doi.org/10.1145/3239060.3239076

gation especially from a methodological perspective. There are some issues at this point. Intention to buy an automated driving system is largely determined by attitudes towards automated driving. In user studies, self-report measures are applied to assess attitudes. In case someone holds a positive attitude towards this technology and buys the system functions, this does not mean that he/she can and will use the function appropriately. On the other hand, observational measures of interaction behavior between the user and the automated driving function also play an important role. If users successfully interact with the system as intended by the HMI designers, this does not necessarily mean that they hold a positive attitude towards the system and end up buying or using the function. These two examples emphasize the importance of appropriate selection of research methodology for automated vehicle HMIs. Therefore, it is the role of usability evaluation of HMIs to support market introduction success. Human factors research needs to ensure the quality of self-report and behavioral observation measures at the same time.

By reviewing and analyzing ten years of research on automated driving, the preceding chapter has shown that there are instances where self-report measures are not accompanied by behavioral measures. This chapter outlines state of the art methods for the evaluation of automated driving HMIs. From that, the issue of preference-performance dissociation arises. Potential underlying reasons for this phenomenon are described and research directions that are targeted in the following chapters are derived.

3.2 Overview of Measures

The duality of measures in user studies is also reflected in the usability definition in DIN-EN ISO (2011). Table 3.1 gives an overview of usability components according to DIN-EN ISO (2011), measures and possible operationalizations. This framework combines effectiveness and efficiency as observational data and satisfaction as self-report data. The following section outlines the heterogeneity of evaluation methods in user studies on automated vehicle HMI evaluation.

Table 3.1

Overview of usability components according to ISO (2011), measures and possible operationalizations.

Usability Component	Measure	Operationalization
Effectiveness	Success	Error Frequency
Efficiency	Effort	Time on Task
Satisfaction	Attitude	Self-Report

3.2.1 Preference as an Attitude: Self-Report Measures

When users report the degree to which they favor or disfavor an object, they report their attitude. By definition, attitudes are *"a mental representation that summarizes an individual's evaluation of a particular person, group, thing, action or idea"* (Smith, Mackie, & Claypool, 2015). According to Wege, Pereira, Victor, and Krems (2014), attitudes are part of motivational internal processes in human-automation interaction. The most straightforward way to measure attitudes is to simply ask people about their evaluation of an object by means of an attitude scale. In the formation and reporting of attitudes, there are different factors influencing these processes. For example, while Petty and Cacioppo (1986) proposed two routes to attitude formation, Ostrom (1969) proposes three informational sources that influence attitude formation. These influences can lead to different manifestations when users report their attitude toward an object. The most important constructs for an attitude assessment regarding preference in automated driving are acceptance, trust, user experience and usability. The previous chapter 2 showed that trust and acceptance are already established and well-investigated constructs regarding driving automation. UX and usability, however, have only received first attention and are emerging topics. The present thesis uses *"preference"* as an umbrella term for these attitude measures. For each of the four preference constructs, there exists an ample range of questionnaires. The following paragraphs outline the state of the art methods of self-report measures to assess user preference. Table 3.2 outlines relevant constructs with according scales, their original source and number of google scholar citations. Taking into account the date of first publication, this chapter used frequently applied questionnaires.

Sauer (1993) stated that the evaluation of acceptance of in-vehicle HMIs is critical being *"the single, most important factor in determining success or failure of information systems and technologies"* (p.4). Based on the theory of reasoned action (Ajzen, 1985),

Davis (1989) developed the Technology Acceptance Model (TAM), which assumes that intention to use a certain technology is derived from a combination of perceived usefulness and ease of use. The Unified Theory of Acceptance and Use of Technology (UTAUT, Venkatesh et al., 2003) combines eight different models of user acceptance within one framework. In the automotive context, researchers have built upon this work to develop models and according questionnaires that predict usage of car technology in general (Osswald et al., 2012), warning systems (D. Large et al., 2018), SAE Level 1 (Adell, Nilsson, & Varhelyi, 2014), SAE Level 2 (Rahman, Lesch, Horrey, & Strawderman, 2017), SAE Level 3 (Bazilinskyy, Eriksson, Petermeijer, & de Winter, 2017), SAE Level 4 (Nordhoff, van Arem, & Happee, 2016) and SAE Level 5 systems (Nees, 2016). According to the framework by van der Laan, Heino, and de Waard (1997), usefulness and satisfaction as two independent dimensions compose acceptance. This definition, however, does not align as much with the TAM and UTAUT but the satisfaction component is also linked to the usability definition (DIN-EN ISO, 2011).

Trust is a precursor for acceptance of technology (Ghazizadeh et al., 2012; Mirnig, Wintersberger, Sutter, & Ziegler, 2016). Generally, low levels of trust lead to low acceptance and to rejection of a system (Eichinger, 2011; J. D. Lee & See, 2004). J. D. Lee and See (2004) define trust as "*the attitude that an agent will help achieve an individual's goals in a situation characterized by uncertainty and vulnerability*" (p.2). Trust is an important construct in the driving automation domain since the attitude trust is closely tied to the resulting reliance behavior (J. D. Lee & See, 2004). Jian, Bisantz, and Drury (2000) developed a psychometric questionnaire that is widely used in the assessment of trust in automation operationalized as an attitude. In the context of driving automation, this questionnaire or adaptations from it have been frequently used (Beggiato et al., 2015; Forster, Naujoks, Neukum, & Huestegge, 2017; Gold, Körber, Hohenberger, Lechner, & Bengler, 2015; Hergeth et al., 2017; Naujoks, Kiesel, & Neukum, 2016; Verberne, Ham, & Midden, 2012; Waytz, Heafner, & Epley, 2014).

Furthermore, the human-centered design approach (D. A. Norman, 2005) becomes important to prevent unintended consequences such as misuse or disuse (Parasuraman & Riley, 1997). The most commonly accepted definition for usability stems from the ISO norm 9241-210 which states that usability is "*[...] the extent to which a product can be used by specified users to achieve specified goals with effectiveness, efficiency and satisfaction in a specified context of use*" (DIN-EN ISO, 2011). One of the most frequently applied scales to quantify usability is the System Usability Scale (SUS, Brooke, 1996). The Post-Study System Usability Questionnaire (PSSUQ, Lewis, 2002) is another question-

naire that is frequently applied in user studies (e.g., Gugenheimer, Schaub, Neiswander, Guneratne, & Weber, 2014; Walch, Baumann, Jaschke, Weber, & Hock, 2017). Usability measures cover satisfaction with pragmatic aspects of product use. However, they largely neglect non-instrumental aspects such as joy (Hassenzahl, Burmester, & Koller, 2003) or need fulfillment (Sheldon et al., 2001). The lack of including such qualities into the evaluation of product perception led to the rise of User Experience in the 1990s and early 2000s (D. Norman, Miller, & Henderson, 1995). By definition, UX goes beyond the mere pragmatic aspect of usability as it covers aspects before and long after product use and includes non-pragmatic aspects such as joy and comfort. ISO 9241-210 defines UX as *”a person’s perceptions and responses that result from the use or anticipated use of a product, system or service”* (DIN-EN ISO, 2011). To quantify UX, Hassenzahl et al. (2003) developed and validated the AttrakDiff questionnaire. From there more questionnaires for UX were developed such as the User Experience Questionnaire (UEQ, Laugwitz, Held, & Schrepp, 2008) or the modular evaluation of key Components of User Experience (meCUE, Minge, Thüring, Wagner, & Kuhr, 2016).

Table 3.2

Overview of relevant constructs, scales, sources and google scholar citations (as of August 15th, 2019)

Construct	Scale	Source	Citations
Usability	SUS	Brooke (1996)	7459
	PSSUQ	Lewis (2002)	360
Acceptance	UTAUT	Venkatesh et al. (2003)	24458
	TAM	Davis (1989)	44833
	van-der-Laan Scale	van-der-Laan et al. (1997)	526
UX	AttrakDiff	Hassenzahl et al. (2003)	809
	UEQ	Laugwitz et al. (2008)	629
	meCUE	Minge et al. (2016)	53
Trust	ATS	Jian et al. (2000)	639

3.2.2 Performance as Behavior: Observational Measures

The present thesis regards behavior as a precursor of attitudes. It does thus not regard influences from attitude to behavior as they are described in expectancy-value models (e.g., Davis, 1989). Reasons for this approach is given in the subsequent section.

The *”Joint Conceptual Framework (JCTF) of Behavioural Adaptation in Response*

to *Advanced Driver Assistance Systems*” (Wege et al., 2014) identifies several factors influencing the adaptation of behavior. Among these are external factors such as *time of usage* which can manifest in short medium and long-term or the *system* itself which is defined by its level of automation and properties. Driver characteristics such as demographics, personality, driver state and prior attitude together with the external factors influence driver processes. These are cognitive (e.g., mental model, situation awareness), motivational (e.g., attitudes, trust) and energetic (e.g., workload, attention). From a complex interplay, behavior and performance in the respective task with the ADAS results. With motivational processes excluded and energetic processes assumed as constant within single session experiments, the present work takes a cognitive perspective on factors that determine human-automation interaction performance. But what are behavioral measures for assessing interaction performance with automated vehicle HMIs? This section outlines measures for the constructs that had been outlined in the previous section.

With the driving task being executed by the driving automation system, lane keeping (Knappe et al., 2006) and acceleration or braking behavior (Neukum, Lübbecke, Krüger, Mayser, & Steinle, 2008) are not applicable for HMI evaluation during active system functioning. For use cases of L3 ADS availability, where the operator executes a transition from manual to automated mode (see Naujoks, Hergeth, et al., 2018), however, these metrics still apply. First human factors research efforts on L3 ADS focused on transitions from automated to manual mode (for an overview see Eriksson & Stanton, 2017). In the transition process from automated to manual mode, several reaction time (Gold et al., 2013) and driving intervention (Radlmayr, Gold, Lorenz, Farid, & Bengler, 2014) metrics can be calculated (see also chapter 2.4). From a theoretical perspective, these measures are rather safety than usability related and it is not clear, how well they relate empirically to user preference. Driver-initiated transitions from manual to automated mode and transitions between automated modes, however, have not been investigated in a comparably extensive manner. Measures such as time to activate the system, time to release controls and time to resume a non-driving related task could be promising for usability studies. If users can easily activate and adjust a L3 ADS, this indicates high efficiency (DIN-EN ISO, 2011).

Usability and User Experience

Research on driving automation usability needs to develop and bring together measures about interaction with these systems and interfaces and the usability aspects effectiveness and efficiency. A meta-analysis by Hornbæk (2006) identified measures for effectiveness and efficiency. Effectiveness is operationalized through binary task completion, accuracy (i.e., error rates), recall, completeness, quality of outcome or an expert assessment. Transferring this to the automated driving usability context, it is possible to examine whether users successfully activate/deactivate the correct automation level (i.e., SAE L1, L2, L3) or make setting modifications (e.g., time headway/lateral offset adjustments). Similar to the instrument proposed by Naujoks, Wiedemann, Schömig, Jarosch, and Gold (2018), completion rates can be confirmed through expert assessments. Time on task, input rate, effort/workload, usage patterns and learning serve as efficiency measures (Hornbæk, 2006). These metrics can be transferred to usability in driving automation as the time to complete a successful transition of control from one level to another and the number of erroneous operating inputs.

According to Jacob and Karn (2003), gaze behavior is a promising measure for usability studies. However, the authors criticize that usage of these metrics need to be more widespread. Recent research on display complexity has found gaze behavior as a sensitive tool (S. C. Lee, Hwangbo, & Ji, 2016; S. C. Lee & Ji, 2018). Hence, future research effort is necessary to examine the relationship between gaze behavior and preference measures.

Trust

There is already strong evidence of behavioral correlates for trust in automation. Trust as an attitude results in reliance behavior. For L3 ADS, Hergeth et al. (2016) found evidence of gaze behavior operationalized through the monitoring frequency (i.e., number of monitoring glances scaled to the duration of a non-driving related task) as a behavioral correlate of trust in automation. Participants reported higher automation trust under less frequent system monitoring. However, monitoring behavior relates to changes between a non-driving related task and observation of appropriate system functioning. The observation of HMI components is not reflected in this measure. A closer investigation of monitoring behavior of different HMI components and the relation to knowledge about the system is described in chapter 8.

Acceptance

Acceptance models define intention to use as a direct precursor of actual use (Venkatesh et al., 2003; Davis, 1989). Resulting behavior is reflected in actual usage. In the area of L3 ADS, this behavior is difficult to measure since the functions do not exist commercially, yet. Until now, user studies are limited to driving simulation or studies on test tracks. Large-scale field operational tests (FOT) or naturalistic driving studies (NDS) can bring insights into actual usage of advanced driver assistance systems or in-vehicle infotainment systems (Dingus et al., 2006). As already outlined in chapter 2, behavioral measures of acceptance are not investigated further in this work.

3.3 Influential Factors and Dynamic Interplay

As outlined in chapter 2, there is a heterogeneity of measures for the assessment of automated vehicle HMIs. Since there are two types of data (i.e., self-report and behavior), researchers need to include both in user studies to derive a holistic picture of the system and HMI (Pettersson, Frison, Lachner, Riener, & Nollhage, 2018; Pettersson, Lachner, et al., 2018). Thus, one can make robust statements about both whether people can successfully operate a system (observational data) and hold a favorable attitude towards the system (self-report data). The application of a variety of measures provides superior insights into the quality of an HMI. Researchers and practitioners use these measures to decide whether and how to develop a certain concept or to decide between different concepts during the development process. Ideally, users' preference and performance produce a consistent picture where superior interaction behavior in form of shorter total task times and fewer errors are associated with favorable attitudes towards a certain HMI concept.

3.3.1 Attitude-Behavior Relationship

The relationship between attitudes and behavior, however, is not always congruent. Before going into more detail, it shall be noted here that the present work investigates the relationship for attitudes that are derived from behavior, but excludes the vice versa path. There are attitude functions to guide behavior, such as trust leading to reliance behavior (J. D. Lee & See, 2004) or expectancy-value models in general (Ajzen, 1985; Davis, 1989). However, this work focuses on attitudes that are built on the basis of a prior experience and do not directly relate back to the behavior. For example, the degree

of satisfaction with an interface does not directly lead to shorter time on task or fewer errors while operating an HMI. Here, study design characteristics force users to complete certain tasks and subsequently report their attitude. Behavior is not chosen voluntarily by the user and as a consequence the present work does not investigate any further a direct link from attitude to behavior. This thesis targets the preference-performance relationship under the assumption that users observe their behavior in terms of interaction performance and derive their attitude towards the object from self-observation (see e.g., Bem, 1972).

In the 1970s, Ajzen and Fishbein (1977) already reported that attitude and behavior only correlate to a low degree. The authors grouped empirical studies into three categories, namely *"lack of correspondence"*, *"partial correspondence"* and *"high correspondence"*. Glasman and Albarracin (2006) have engaged in an extensive literature review on the attitude-behavior relation to find out more about factors that moderate the correlation in these instances. Overall, they report a correlation of $r=.52$. The most important contribution of this work lies in the finding that people form more valid and pertaining attitudes when they are motivated and the behavior is accessible. While in social psychology the relation mostly focuses on the predictive validity of attitudes (and thus the path that was explicitly excluded for the thesis), the opposite direction has not received considerable research interest, yet. To fill this gap, the thesis at hand investigates the factors influencing the formation of attitudes and relation to behavior in the applied setting of usability research with a focus on driving automation.

3.3.2 Overview of Dissociations

In a more applied setting such as workload research, the dissociation between self-report and behavioral measures appears. A recent overview by Hancock and Matthews (2018) reports that self-reported, physiological and behavioral measures often do not agree. Here, a dissociation is characterized by high workload on one measure but low workload on another measure. Additionally, there might be cases where the relation is *"insensitive"*. This means that while one measure provides for example high workload, another measure provides neither high nor low results. Similarly, Endsley (2019) reports a divergence of objective and subjective measures for situation awareness. In a review of $n=37$ empirical studies a wide range of measurements with divergence between the two sources of data emerged. According to the author, possible reasons for such diverging results are lack of meta-awareness, poor calibration and confounds with related measures. These two overviews on workload and situation awareness support the argument

that dissociations between attitude and behavioral measures for a given construct is a timely issue and needs additional research efforts.

A meta-analysis of 57 usability studies by Nielsen and Levy (1994), found a positive association between users' task performance and system preference. The correlation of $r=.46$ indicates that performance accounts for 21% of the observed variance in self-reported preference scores. The correlation is still not as large as one would expect. This indicates that there are users, who perform poorly at using a system but show high system preference. On the other hand, there are also users, who perform fairly well with a system but do not ascribe comparably high preference scores. To better visualize this issue, figure 3.1 depicts a randomly generated data set with a correlation of $r=.46$ that was found in the meta-analysis (Nielsen & Levy, 1994). Here, it becomes obvious that there are systems that exhibit comparable performance, but very different preference. Conversely, there are also systems that are evaluated similarly in terms of preference but interaction behavior differed largely. On the right it shows an idealized data set (randomly generated) with a correlation of $r=.95$. Here, users assign preference scores that are closely related to their performance with the system. From that, behavioral measures can strongly predict user preference and vice versa. These examples show, that dissociations between two sources of data are a timely issue in human factors and transportation requiring further investigation.

Figure 3.1. Randomly generated data sets for performance-preference correlations of the meta-analysis with $r=.46$ (left) and an idealized dataset with $r=.95$ (right).

3.3.3 Examples of Preference-Performance Dissociations

In usability and automotive studies, the dissociation between preference and performance also appears frequently. For example, Roberts, Gray, and Lesnik (2017) investigated the usability of metro maps. The authors found that reaction times and error rates were not in accordance with self-reported satisfaction. Investigating interfaces for virtual citizen science platforms, Sprinks, Wardlaw, Houghton, Bamford, and Morley (2017) report user preference for interfaces providing greater autonomy and variety, which did not translate in improved performance. Investigating driving behavior and self-reported attitudes about these, Kaye, Lewis, and Freeman (2018) searched several data bases and systematically reviewed empirical evidence. The meta-analysis showed that there are both disparities and similarities between self-reported and observed driver behavior. The authors suggest that valid conclusions about the reasons for disparities cannot be drawn and future research is necessary. Kruger and Dunning (1999) asked participants to take a test on humor, grammar and logic. Additionally participants rated their own performance in the test. Results showed that especially participants scoring in the bottom quartile grossly overestimated their performance. In the automotive HMI

context, Mehler, Reimer, Lee, Kidd, and Reagan (2017) compared two different voice recognition interfaces. The authors found that participants did not favor the system that led to the best observed interaction performance. A dissociation between acceptance of warning systems and observed efficiency and effectiveness of use is reported in Navarro, Mars, Forzy, El-Jaafari, and Hoc (2010). Evaluating motor priming for lane departure warnings, the study found that participants preferred auditory warnings over motor priming even though motor cues were more beneficial for recovery maneuvers compared to auditory signals. In the driving automation context, Naujoks, Forster, et al. (2017b) report improved usefulness through additional HMI speech output which was reflected in behavioral measures (i.e., glance behavior) but counteracted by familiarity effects. One might object at this point that preference and performance might simply be two separate dimensions when it comes to evaluate human-technology interaction and as a consequence it is necessary to simply measure both. This is also reflected in the three-stage usability taxonomy of DIN-EN ISO (2011). On the contrary, the problem remains, where the dissociation stems from and under which circumstances it is likely to appear. Furthermore, if one obtains such a result in a user study, it is not clear what efforts regarding a system or HMI need to be undertaken to resolve the issue and how this might affect the outcome of a subsequent study. For researchers and practitioners it is important to be aware of study design factors that might influence the relationship. This work's aim is explicitly not to bring the pattern on the left as close as possible to the pattern on the right. It shall rather serve as a guideline that suggests methodological approaches and considerations when collecting both self-report and behavioral measures in human-automation interaction research. The following section outlines possible roots of the performance-preference dissociation and leads towards the research questions of the following chapters.

3.3.4 Roots and Countermeasures for the Dissociation

Preference Measures

The first possible reason for the performance-preference dissociation is the operationalization of the respective preference measure. As described earlier, HMI researchers and practitioners can operationalize preference (in the automation context) through usability, UX, acceptance or trust. The heterogeneity of measures for HMI evaluation shows, that user preference is made of different aspects such as pragmatic or hedonic criteria (Hassenzahl et al., 2003). In the emerging field of automated vehicle HMIs there have

been plenty of studies conducted and a multitude of questionnaires have been applied. However, the suitability of these has not been investigated within one comparative study. Therefore, the only reason to apply a certain questionnaire in one's study is an expert's best guess and positive assessment of the scale's face validity. However, there are more aspects to consider when making a sophisticated decision about scale application. When dealing with self-report data in form of standardized measures, it is important to consider psychometrics of the measures. Psychometric quality of a questionnaire is determined by objectivity, reliability and validity (Bühner, 2011; Nunnally, 1978). A test is objective, if the results are independent from the observer. Reliability refers to the degree of accuracy that a test measures a certain trait with, independent whether the test claims to measure this construct or not. A test has sufficient validity if its items are representative of the construct (content validity), if a test measures the construct that it intends to measure (construct validity) and if they are reflected in an external criterion (criterion validity). Ajzen and Fishbein (1977) note that the relationship between attitude and behavior can be attenuated when inappropriate measures are obtained. Furthermore, they suggest to undertake precautions in form of applying standard scaling procedures with respect to measures of attitudes. Only if the applied measure is suitable for the context and research purpose, attitude and behavior can show correspondence in a reliable and valid manner.

Performance Measure

Another possible root for the dissociation lies in the respective observational measure. Here, the same reasoning as above holds true: There are many different measures available but choosing an inappropriate one might lead results and resulting interpretations astray. In addition, Ajzen and Fishbein (1977) suggest to collect multiple measures for behavior. Reaction time and error rates by themselves allow describing interaction behavior on an operational level. This bears the potential to disregard effects on a tactical level. Here, observations by the experimenter can be helpful tools to assess interaction performance (e.g., Kenntner-Mabiala et al., 2016; Naujoks, Wiedemann, et al., 2018). Furthermore, gaze behavior is an additional measure for workload (de Waard, 1996) and cognitive processes (Duchowski, 2007). Gaze metrics can provide insights into cognitive functions as they are preceding motor actions (Hayhoe, Shrivastava, Mruczek, & Pelz, 2003). At first, an evaluation of behavioral measures and metrics regarding suitability for human-automation interaction is necessary. The suitability of behavioral measures

should also meet quality standards that can well be described by psychometrics as outlined in the paragraph above.

Mental Model

One influential factor for interaction performance is the mental model that users hold about the automated system. A mental model (Durso & Gronlund, 1999) describes the integrated understanding about the functionality of the system. It thus differs from mere factual knowledge in a sense that a user has to actively imagine interaction and anticipate the effects of his/her behavior on the output of the automated system. These mental representations directly influence the interaction between the driver and the system since they reflect the understanding about functioning principles and usage conditions (Wege et al., 2014). Thus, higher level cognitive processes such as the formation of mental models and learning to operate an ADS influence observable behavior (Rudin-Brown, 2010). Support for this comes from Parasuraman and Riley (1997) noting that *"better operator knowledge [...] should results in more appropriate use of automation"* (p.248). Thus, we assume that the better a user understands system functioning, the better the manifestation of their interaction behavior should be eventually. On the contrary, if a user holds inaccurate mental models about a system, human-automation interaction might turn out to be inefficient at best and dangerous at worst (Wege et al., 2014). Especially when it comes to system limitations such as the ODD to and from an L3 ADS, the mental model is especially important taking into account this very aspect. Therefore, the mental model as a precursor of interaction performance needs closer attention. Similar to self-report and behavioral measures, the issue of how to assess mental models arises. There is prior evidence that questionnaires provide valid insights into such understanding (Blömacher, Nöcker, & Huff, 2018; Beggiato et al., 2015; Richardson, Sprung, & Michel, 2019). As gaze behavior is closely linked to cognitive processes and actions (Duchowski, 2007; Hayhoe et al., 2003), additional insights can be expected from these. Moreover, mental models are repeatedly updated during interaction with ADAS (Beggiato, 2013). During a single interaction, users form a certain *situation model*, that is matched with the existing long-term memory structure (i.e., the mental model) and updates this if necessary. By repeatedly comparing the specific situation model and the more generic mental model, the latter gets more accurate over time.

Repeated Interaction and User Education

The experimental design affects the performance-preference relationship. One example is the user's respective skill that might be affected by repeated interaction or user education. Concerning the relationship between preference and performance, Nielsen and Levy (1994) report a difference between the correlations of experienced ($r=.62$) and novice users ($r=.36$). The reasons for this observations, however, still remain unknown. There is still large variance in self-reports and interaction behavior in learning and familiarization trials. The variance in subsequent trials decreases due to increasing operator understanding and behavioral adaptation (Rudin-Brown, 2010; Wege et al., 2014). Therefore, familiarization trials or repeated interaction prior to evaluating the automated vehicle HMI might be necessary. The time course that is considered in the present work covers only immediate (directly after experience) and short term (at maximum hours) adaptation (Manser, Creaser, & Boyle, 2013). This is due to the context of the present research which primarily addresses driving simulator studies and usability evaluations. For appropriate automation use, Parasuraman and Byrne (2003) even explicitly demand to train operators of automated systems. Since the predecessor of observable behavior in form of mental models is expected to update over time (Beggiato, 2013), this process should also be reflected in behavioral measures. For example, Hergeth et al. (2017) found evidence of the effects of prior familiarization with take-over requests in L3 ADS. Effects of repeated interaction are also reported for the evaluation of usefulness of an HMI for L3 ADS during independent system maneuver execution by Naujoks, Forster, et al. (2017b) or reactions to warnings (Winkler, Kazazi, & Vollrath, 2018). While standardized manuals exist for the evaluation of an HMI's distraction potential in manual driving (AAM, 2006), there is no common ground on how to treat participants in studies on automated driving. Therefore, the role of user education and repeated interaction with driving automation needs closer attention.

Feedback

One issue, as outlined initially is that ADS are a novel technology for novice users. Thus, they might not have accurate understanding of this technology. Without sufficient understanding, the validity of self-reported preference might be threatened as users assume correct interaction despite observed problems from a designer's point of view. A potential supporting factor for accurately classifying their interaction performance could be performance feedback. However, at the same time it confounds self-report measures

in a way that the researcher primes participants with their performance indicator. If one decides not to report whether a participant succeeded in the use case or not, it might be that participants always assume they had succeeded the trial. This effect has been reported by Kruger and Dunning (1999). Especially users in the bottom quartile of performance overestimate their performance. As a consequence self-reports are biased towards the positive end. In this regard, Glasman and Albarracin (2006) outline the hedonic-instrumental correspondence. They argue that strengthening the cognitive focus towards instrumental qualities supports correspondence between attitude and behavior. More than two decades ago, Andre and Wickens (1995) mentioned that “*users often want what is not best for them*”. To solve this issue, the authors argue to implement the systems resulting in best performance and to explain to users the favorable aspects of performance to possibly change their attitudes (if needed).

3.4 Conclusions

The present chapter provided an overview of existing methods for measuring performance and preference of automated vehicle HMIs. It showed that there is a heterogeneity in available research methods concerning dependent variables and opportunities for study design. In the interpretation of user study results, the performance-preference dissociation can occur. The chapter discussed potential roots of this phenomenon which are targeted in the empirical chapters of this thesis. Subsequent to these potential influencing factors, the following chapter derives research aims and direction from the existing evidence and considerations.

4 Aims and Objectives

4.1 Main Aim of the Thesis

The aim of the present thesis is to find out about the issue of preference versus performance in the applied setting of automated vehicle HMI research. The previous chapter showed that these two sources of data frequently do not match and there must be reasons for this. The purpose of this work is explicitly not to resolve the issue. It shall rather shed light into factors that lead to stronger or weaker alignment of the two sources of data. To reach this aim, the thesis has two major aims and intends to find out

1. how to measure each component (Operationalization) and find out
2. about influential factors (Variation) from a methodological point of view.

In order to meet these two global aims, they are broken down into more local ones that shall be answered in a series of driving simulator studies.

4.1.1 Aim and Research Direction 1: Operationalization

When choosing from the heterogeneous pool of measures, researchers have to consider including an appropriate self-report measure. By means of psychometric quality criteria, a comparative evaluation of the goodness of standardized scales for human-technology interaction shall be conducted. Chapter 5 reports the results of a psychometric analysis of self-report measures for automated vehicle HMIs.

In the same manner, an evaluation of available behavioral metrics of human-automation interaction will be undertaken. Effectiveness metrics (i.e., error rates) are only the tip of the iceberg since they only provide a binary result without explaining the root of the outcome. Efficiency metrics of reaction times are often misleading and only describe performance without providing information about the underlying process. These metrics and additional experimenter observations are examined regarding reliability and

validity in chapter 7. Duchowski (2007) acknowledges the contribution of process metrics since eye movements could help corroborating performance metrics of efficiency and effectiveness (p. 174). Glance behavior should therefore be considered as an additional dimension in research on automated vehicle HMIs. As mental models are a precursor for interaction success or failure, their operationalization through questionnaires as well as behavioral measures in form of gaze behavior shall be investigated. Chapter 7 outlines the development of gaze metrics and mental models over repeated interaction with automated driving.

If possible, one should decide for a measure that is suitable in the respective field of application. Before engaging in excessive conceptual evaluation, it is necessary to examine measures concerning psychometrics. If the a measure does not meet the criteria of objectivity, reliability and validity, a dissociation between preference and performance is more likely to occur.

4.1.2 Aim and Research Direction 2: Variation

It remains an open question, if and how repeated interaction and prior experience of driving automation affects both preference and performance measures of such HMIs. It seems logical that rising competence increases performance in form of decreases in total task times and error rates. While theoretical considerations have led to the assumption that familiarization and repeated interaction support the formation of accurate mental models and consequently better interaction performance, their impact on preference measures remains to be answered. Therefore, these factors might lead to different relationships between preference and performance. The following studies aim at finding out about the effects and importance of experience with automation and familiarization trials for usability evaluation in automated driving. The role of repeated interaction on the development of the preference-performance relationship is described in chapter 7. The influence of user education on interaction performance, mental models and self-reported satisfaction is covered in chapters 10 and 11.

The role of performance feedback on validity of self-report measures shall also be investigated herein. If there actually is an effect, this begs the question on potential advantages and disadvantages of such a calibrating effect. Chapter 9 provides insights into this research question. Furthermore, referring to Kruger and Dunning (1999), differences in performance for certain sub-samples might not be evident in self-report measures. The occurrence of this effect in human-automation interaction is of additional interest in the present work. The Kruger-Dunning effect is therefore covered in chapter 12.

4.2 Practical and theoretical Contribution

This thesis was carried out in the applied context of driving automation and HMI evaluation to target the research question how attitude and behavior relate to each other and which factors might influence this relationship. Hence, it holds both practical and theoretical implications.

4.2.1 Practical Contribution

First, its practical contribution lies in the insights into study planning and conduction when evaluating automated vehicle HMIs. The previous two chapters already outlined factors that practitioners should consider not only for driving automation HMIs but for automated systems or technology in general. The following chapters show how these factors (e.g., respective measure, feedback, education) affect study results when conducting a user study in one way or another. For example, when one sets up a study where high agreeableness between performance and preference can be expected, one might even consider cutting down the amount of dependent variables for the sake of parsimony. Instead of collecting potentially redundant and mutually approving measures, one might disregard cost and time expensive manual video annotation or questionnaires and rather engage in further usability engineering of the evaluated HMI. It shall be noted here that eventually, empirical evidence for both measures is critical to determine HMI quality and decide about market introduction. However, during the usability engineering circle (DIN-EN ISO, 2011) and in agile development, findings reported herein can well be applied to make development more time and cost effective. In addition, this work can serve as a guideline when interpreting existing study outcomes and critically scrutinizing experimental design.

4.2.2 Theoretical Contribution

The theoretical contribution of this thesis are its insights into the relationship between attitudes and behavior. As outlined in chapter 3, research on the attitude behavior relationship has a long tradition (e.g., Ajzen & Fishbein, 1977). Ideally, people should act according to their attitude on the one hand and also form attitudes based on their own behavior and observation of themselves on the other hand. Contrary to the expectation and rational reasoning, these two instances often do not occur. While the predictive validity of attitudes for the manifestation of behavior has been an important focus of

psychology (e.g., Ajzen, 1991) and information technology research (e.g., Davis, 1989; Venkatesh et al., 2003), the present work targets the vice versa path, namely the formation of behavioral observations and inference of attitudes from these. The second main aim (i.e., variation) sheds light into how several influential factors (e.g., user education, feedback) impact one component but leave the other one unaffected. Eventually, relating to figure 3.1, a better understanding of methodological reasons for the frequent observation of *"users, that want what's not best for them"* (Andre & Wickens, 1995) can be derived from this work.

4.3 Allocation of the Aim into three Studies

To meet the two main aims, three driving simulator studies were conducted. From these, seven publications (see manuscripts 3-9 in chapter 1) emerged that lie this thesis' foundation. It is obvious that some manuscripts are based on the same data and methodology. For this reason, the chapters do not repeatedly outline the same methodological approaches but refer to an earlier chapter if use cases, measures, driving simulation or the like had been described before. The need for method development and the issue of the preference performance dissociation as main motivations for each of the studies had been removed since chapters 1, 2 and 3 provided extensive outlines of these. This section briefly summarizes considerations behind each of the studies in terms of the addressed aims and in which chapters the respective analysis can be found.

4.3.1 First Study: Quality Criteria

The first study was conducted to find out about the operationalization of preference measures. Literature provided a multitude of potentially applicable scales but it seemed like a sophisticated and robust recommendation could only be derived from an expert's gut feeling. Assessing psychometric criteria of reliability and validity for self-report measures (i.e., summative questionnaires) gave insights into operationalization of self report measures. Chapter 5 reports the outcome of a driving simulator study with $N=57$ participants concerning psychometric properties of the scales in automated driving.

Since data on interaction performance were also assessed from the specific use cases, a first evaluation regarding influential factors for the preference-performance relationship was undertaken. The specific research question in this case was whether the relationship is dependent on operator skill. Assuming that poor performance is accompanied by spu-

rious overestimation of performance, preference and performance were compared based on a quartile split in the performance measure. Chapter 12 reports the outcome of the quartile split comparison. This chapter is located at the end of the manuscript-based chapters because it targets the second main aim (i.e., variation) and rounds up the discussion of user skill and expertise from an ex-post perspective (rather than ex-ante as in chapters 10 and 11).

4.3.2 Second Study: Prediction Power

The second driving simulator study's aim was to investigate the operationalization of behavioral measures. Just like in the first study, psychometrics were used as a criterion for the suitability of the measures. The study was termed "Prediction Power" since reliability was examined by fitting a *power* law to the data. Furthermore, study one raised the issue of an external criterion for preference apart from guideline conformity. Study two took up this open question and investigated validity of the measures in form of linear regression fits to find out whether one measure can *predict* the respective other. This analysis at the same time targeted both the main aim of operationalization and variation. These outcomes of a driving simulator with $N=59$ participants are reported in chapter 7.

In addition to classical behavioral measures, data on gaze behavior was also recorded. Since these can provide insights into cognitive processes, the time course of gaze behavior was investigated here. In addition, the study targeted the operationalization of the mental model by means of questionnaires for specific HMI functions. The results for gaze behavior and relation to mental models are reported in chapter 8.

While in the first study summative self-report measures were in the focus, an additional analysis from the second study targeted the suitability of diagnostic self-report measures in terms of development over time and use case specificity. These two factors relate to the first main aim of operationalization. An exploratory approach was followed in reporting interaction success to one half of the participants in order to find out whether participants' self-reported perception of the interaction differs depending on feedback. This factor is related to the main aim of variation since it was expected to influence self-reports but not interaction performance. The outcomes of this analysis are reported in chapter 9.

The results of this study are reported in three consecutive chapters. To not redundantly report theoretical considerations and methodology, chapter 6 reports theoretical considerations and derives hypotheses for each of the study aims. In addition, it com-

prehensively outlines the methods for the study so that the subsequent chapters only report results and discussions.

4.3.3 Third Study: Automation Intro

The third study with a total of $N=109$ participants concerned the varying factor of user education. It was split into two parts which were the manipulation check and the main study. These studies included the outcomes and recommendations of the prior two studies concerning operationalization of preference, performance and mental models. At first, conceptual development and considerations for prior treatments of driving automation users are outlined. The first part regarding concept evaluation and manipulation check for the following large-scale user study is reported in chapter 10. The larger part (i.e., main study) was methodology-oriented. It outlines the effect of different combinations of user education approaches on mental model formation, subsequent transfer to interaction performance and the development from first to second contacts with the HMI as well as on satisfaction. The outcome of this second part is described in chapter 11.

So far, the background of this thesis was outlined. It now turns towards the empirical chapters where the findings of the driving simulator studies are described. The following chapter covers the evaluation of nine different preference measures using psychometric quality criteria. The subsequent chapters follow in the order as shown in the manuscript overview (see chapter 1.2).

5 Self-Report Measures for the Assessment of Human-Machine Interfaces in Automated Driving ⁴

Abstract: For a successful market introduction of Level 3 Automated Driving Systems (L3 ADS), a careful evaluation of Human-Machine Interfaces (HMI) is necessary. User preference has often focused on Usability, User Experience, Acceptance and Trust. However, a thorough evaluation of measures when applied to ADS HMIs is missing. We investigated the appropriateness of nine self-report measures in terms of reliability and validity. A sample of $N=57$ participants completed two 15-minute simulator drives with a L3 ADS. They experienced two variations of an HMI that differed in the degree of complying with common guidelines. Consistency analysis identified scales that showed insufficient reliability. Validity examination revealed a three-factorial structure of self-reports for construct validity. These factors are design-orientation, usability-orientation and acceptance-orientation. All measures were sensitive to the HMI manipulation and therefore exhibited criterion-related validity. The present study provides researchers and practitioners in the area of ADS with a recommendation for self-report measure application.

5.1 Introduction

In principle, both self-report (e.g., questionnaires) and behavioral measures (e.g., interaction performance) can be used for HMI evaluation (Hornbæk & Law, 2007; Nielsen & Levy, 1994). In that sense, it is necessary to investigate the suitability of the ample range of available self-report measures. Since the driver becomes the mere fallback

⁴This chapter is based on a previous publication: Forster, Y., Hergeth, S., Naujoks, F., Krems, J. F., Keinath, A. (2018) Self-Report Measures for the Assessment of Human-Machine Interfaces in Automated Driving *Cognition, Technology and Work*, 1-18.

performer, circumstances of HMI evaluation have fundamentally changed at this level of automation compared to manual driving or partial automation (Naujoks, Hergeth, et al., 2019). Testing scenarios for automated vehicle HMIs include not only voluntary transitions of control initiated by the driver but also system initiated transitions from the ADS to the driver (so called Take-Over Requests, TOR). There is dearth of research concerning appropriateness of self-report application for L3 ADS evaluation despite the ample range of self-report measures. Scales that are applied without intensive investigation of its suitability for a particular context can lead researchers and practitioners astray in their decision of the quality of an HMI. Another problem arises when trying to compare results across studies. Without a consensus about methodological application, studies differ substantially in terms of user education, testing scenarios and dependent measures. There have been first efforts into standardization of testing scenarios (Gold et al., 2017; Naujoks, Hergeth, et al., 2018). Concerning self-report measures, a recent study by Zoellick, Kuhlmei, Schenk, Schindel, and Blüher (2019) outlined concerns about attitude measures for automated vehicles and brought forth empirical evidence that data structure and validity of attitude measures lack suitability for this context. Similarly, chapter 3 has pointed towards the examination of self-report measure suitability. Therefore, the aim of the present methodological work is to thoroughly examine self-report measures for the evaluation of L3 ADS HMIs. The following paragraphs will give an overview of preliminary findings and constructs for the evaluation of HMIs and driving automation. Furthermore, psychometric measures as an evaluation criterion are outlined. From there, research questions are derived resulting in a study that eventually presents a comparative evaluation of different self-report measures.

5.1.1 Background

According to François, Osiurak, Fort, Crave, and Navarro (2016), usability and acceptance are important evaluation criteria for HMIs. Additionally, the construct of trust has gained considerable research interest in the evaluation of automated driving lately (J. D. Lee & See, 2004). Moreover, the construct User Experience (UX) became popular since the 1990s (D. Norman et al., 1995). The following paragraphs briefly outline those four constructs and relate them to automated driving research.

Usability

When it comes to design for automation, the human-centered design approach gains importance (DIN-EN ISO, 2011). According to the ISO 9241, effectiveness, efficiency and satisfaction compose usability. The satisfaction component as a self-report measure refers to the user's attitude towards product use. A frequently applied scale to quantify self-reported usability is the System Usability Scale (Brooke, 1996). It consists of ten items in total on the two subscales usability and learnability (Lewis & Sauro, 2009). It was initially developed to serve as a usability measure that is applicable across a wide range of contexts. The SUS has previously been applied in research on automated driving (Forster et al., 2016; Hergeth, 2016). The Post Study System Usability Questionnaire (Lewis, 2002) was initially developed for the evaluation of speech dictation systems. Its structure with a total of 19 items can be described with the three subscales system usefulness, information quality and interface quality. Thus, it already bridges the gap to acceptance through its usefulness subscale and to design related interface features of user experience (e.g., attractiveness) through its interface quality subscale. It has also been used by Walch et al. (2017) to evaluate a L3 ADS HMI. The present study thus examined the applicability of these questionnaires for the evaluation of L3 ADS HMIs.

Acceptance

In the automotive context, researchers have built upon acceptance theory (Davis, 1989; Venkatesh et al., 2003) to develop models that predict usage of car technology. The Unified Theory of Acceptance and Use of Technology (Venkatesh et al., 2003) comprises the four subscales Performance Expectancy, Effort Expectancy, Social Influence and Intention to Use with a total of 13 items. The UTAUT combines eight different acceptance models within one generic framework and is a popular tool to evaluate acceptance. Questionnaires on its basis have been adapted to automotive technology in general (Osswald et al., 2012), L1 driving automation (Adell et al., 2014), Level 2 (Rahman et al., 2017), Level 3 (Bazilinskyy et al., 2017), Level 4 (Nordhoff et al., 2016) and Level 5 systems (Nees, 2016). According to the acceptance framework by van der Laan et al. (1997), usefulness and satisfaction as two independent dimensions compose acceptance. The van-der-Laan scale consists of 9 items on a 7-point semantic differential scale. Since its acceptance definition includes satisfaction as an integral component, it might also be linked with the definition of usability in DIN-EN ISO (2011). This framework has been applied for the evaluation of auditory HMI components for an L3 ADS by Bazilinskyy et

al. (2017). Many studies on acceptance focus on acceptability of system functions without providing an experience of the respective technology (Forster, Kraus, Feinauer, & Baumann, 2018; Kyriakidis et al., 2015; Nees, 2016; Payre, Cestac, & Delhomme, 2014). The present work fills this gap by examining and comparing acceptance measures for L3 ADS after an experience of the technology in a driving simulator.

User Experience

Usability measures cover satisfaction with pragmatic aspects of interaction with a product (i.e., perception of interaction performance). However, they largely neglect non-pragmatic aspects such as interface attractiveness or joy during interaction. The lack of including such qualities into the evaluation of product perception led to the rise of User Experience (UX) in the 1990s (D. Norman et al., 1995). To quantify UX, Hassenzahl et al. (2003) developed and validated the AttrakDiff questionnaire. The 28 item questionnaire covers pragmatic aspects (pragmatic quality) and hedonic aspects (stimulation, identification). It was originally developed in a website and MP3-player context. Subsequently the authors report positive results of the UEQ in two validation studies using software products. The 26 semantic differentials describe six subscales (i.e., Attractiveness, Perspicuity, Efficiency, Dependability, Stimulation, Novelty). Stating that the AttrakDiff puts too much emphasis on non-instrumental product aspects, Laugwitz et al. (2008) developed the User Experience Questionnaire (UEQ) over six different contexts such as cell-phones, statistical packages (SYSTAT) or SAP-tools (customer relationship management; CRM). Minge et al. (2016) developed the modular evaluation of key Components of User Experience (meCUE) as a tool to measure UX. In their self-report measure, 33 items are allocated to nine subscales representing hedonic and pragmatic product qualities, emotions towards a product and usage intention. Hence, the meCUE includes aspects of acceptance through its intention subscale and usability through its UX definition of pragmatic product qualities. There have been applications of the AttrakDiff (Frison et al., 2017), meCUE (Auricht, Stark, & Blume, 2014) and UEQ (Haeuslschmid, Pfleging, & Alt, 2016) in the driving automation context. However, empirical support for the appropriateness of scale application is still missing.

Trust

Trust is an influential factor on acceptance of technology (Ghazizadeh et al., 2012). Consequently, low levels of trust lead to low acceptance and to rejection of a system (Eichinger, 2011; J. D. Lee & See, 2004). Among others, Jian et al. (2000) and (Chien,

Semnani-Azad, Lewis, & Sycara, 2014) have developed psychometric scales to measure the attitude trust in automation. The 12-item Automation Trust Scale (ATS; Jian et al., 2000) was explicitly developed for the automation context in computerized systems. From a three-phased experiment (i.e., word elicitation study, questionnaire study, paired comparison study) the authors report the development of a scale to assess human-machine trust. The Universal Trust in Automation scale (UTA; Chien et al., 2014) consists of two components which are “*general automation*” and “*specific automation*”. Each dimension includes the three subscales of Performance, Process and Purpose. To evaluate a product or HMI in particular, the “*specific automation*” component is sufficient. It combines 18 items in total. One important aspect that the authors considered during the development process were inter-cultural differences in trust evolution. In the context of driving automation, these questionnaires or selected items have been frequently used in HMI evaluation (Beggiato et al., 2015; Forster, Naujoks, & Neukum, 2017; Gold et al., 2015; Hergeth et al., 2017; Naujoks et al., 2016; Waytz et al., 2014; Verberne et al., 2012). Up to now, it is not clear which scale fits best for evaluating HMIs for L3 ADS. In their work on the development of the Automation Trust Scale (ATS), Jian et al. (2000) recommend to examine the questionnaire in terms of validity and reliability. The current study follows this recommendation and thoroughly examines self-report measures for trust in automation.

The previous outline of constructs and measures has shown that there is a heterogeneity of constructs and measures that can theoretically be applied in HMI evaluation for L3 ADS. The constructs are not completely distinct, but overlap in certain parts. Hassenzahl (2001) describes usability in the sense of pragmatic product quality as one dimension of UX. Satisfaction can be found in both acceptance (van der Laan et al., 1997) and usability (DIN-EN ISO, 2011) definitions. There are also links between usability and trust based on theoretical considerations (Hoff & Bashir, 2015; J. D. Lee & See, 2004) as well as on empirical research on ADS (Hergeth, 2016). A recent study by Frison et al. (2019) found a link between interface aesthetics and trust in the ADS. Finally, Ghazizadeh et al. (2012) included trust as a precursor for technology acceptance in the framework of (Davis, 1989). Thus, the issue arises which constructs are necessary and suitable for L3 ADS HMI evaluation.

Psychometrics

The present study aims to examine and compare the psychometric properties of self-report measures for HMI evaluation in the context of L3 ADS. The quality of questionnaires is determined through psychometrics (Bühner, 2011; Nunnally, 1978). There are main quality criteria and side quality criteria. A high-quality measure adheres to the main quality criteria of objectivity, reliability, validity. The following paragraphs briefly outline these criteria.

Objectivity. Objectivity of a test refers to the degree to which test results are independent from the experimenter. If a test does not vary between experimenters, evaluators and interpreters, it conforms to this criterion. The present work focused on self-report measures that provide standardized instructions for participants when giving their ratings. They also provide instructions for researchers when scoring the questionnaire. Objectivity of conductors, evaluators and interpreters of these methods can thus be assumed and is not in the focus of this study.

Reliability. Reliability refers to the degree of accuracy that a test measures a certain trait with, independent whether the test claims to measure this construct or not. There are several different measures for reliability (e.g., Bühner, 2011). Sijtsma (2009) describes Cronbach's alpha as the most frequently used measure. considered as an independent test. Accordingly, its accuracy is reflected in the average relationship between all single tests in consideration of the test length. Reliability is a necessary but Reliability is a necessary but not sufficient prerequisite for validity.

Validity. There are three types of validity, which are content validity, construct validity, and criterion validity (Bühner, 2011). A test has sufficient content validity if its items are representative of the construct. A quantification of content validity is not possible. A closely related concept is face validity. A test has face validity if one can immediately form a connection between an item and a to-be-assessed behavior. Construct validity indicates whether an instrument measures the construct it intends to measure. Convergent (i.e., strong relationships between similar constructs) and divergent validity (i.e., weak relationships between dissimilar constructs) together determine construct validity (Campbell & Fiske, 1959; Cronbach & Meehl, 1955). A possible numerical method to evaluate construct validity is a factor analytical approach (Bühner, 2011). Finally, criterion validity describes the relationship between the test and an external criterion. In HMI research, there is a wide range of guidelines for HMI design (Bubb, Bengler, Grünen, & Vollrath, 2015; Green et al., 1994; Naujoks, Wiedemann, et al., 2019). The degree of compliance of an interface to these guidelines can be an external criterion to

self-report measures. Thus, the questionnaire should provide statistically significant results for different compliant and non-compliant HMIs.

Side quality criteria. Side quality criteria also add to the overall quality. These criteria are standardization (i.e., availability of norms), comparability (i.e., availability of parallel test forms), economy (i.e., brief and effortless administration) and usefulness (i.e., practical relevance of assessed criterion). These criteria are beyond the scope of the present study but should be considered individually when designing a study and using these questionnaires.

5.1.2 Research Questions and Study Aim

In a review on usability measures, Hornbæk (2006) recommends the validation of self-report measures. For the constructs usability, acceptance, UX and trust there are several scales that have been applied in HMI research settings. To date, there exists no general recommendation and no study on the appropriateness of self-report measures for the evaluation of HMIs for driving automation. The scales that are frequently used such as the SUS, AttrakDiff or van-der-Laan certainly bear the advantage of flexibility and adaptability to many different contexts. However, once circumstances of human-technology interaction have changed with the step to L3 automated driving, it is no proper procedure to simply assume method suitability since it had been applied in other automotive contexts such as in-vehicle information systems (IVIS). The current study aims to fill this gap and provide researchers and practitioners with a recommendation for choosing an appropriate self-report measure. Hence, the primary aim is the investigation of the suitability of different self-report measures when evaluating automated vehicle HMIs. A possible criterion to evaluate such self-report measures are psychometrics (Bühner, 2011; Nunnally, 1978). Therefore, the questionnaires in this study were evaluated in regard to reliability and validity. We do explicitly not claim to conduct a rigorous psychometric evaluation of measures but rather use psychometrics as evaluative criteria to guide the quantification of self-report measure performance. The contribution of this work lies in methodological development for automated vehicle HMI testing. Since high-fidelity driving simulation experiments are time and cost consuming, particular circumstances of such setups (e.g., sample size, experimental duration, external validity of safety critical vehicle behavior) apply. Eventually, the goals of this study are (1) to find out whether the self-report measures would exhibit sufficient reliability and (2) meet the validity in terms of content-, construct and criterion-related validity.

5.2 Method

5.2.1 Participants

In total, $N=57$ (9 female, 48 male) participants took part in the driving simulation experiment. Mean age was 40.56 years ($SD=9.32$, $MAX=60$, $MIN=25$). All participants were BMW Group employees, held a German driver's license, had normal or corrected to normal vision and had not previously partaken in a driving simulator study on L3 ADS. Thus, we ensured that there was no familiarity of any of the participants with HMIs for automated driving.

5.2.2 Driving Simulation and Automated Driving Function

The study was conducted in a high-fidelity static driving simulator (see figure 5.1). The integrated vehicle's console contained all necessary instrumentation and was identical to a BMW 5 series with automatic transmission. The front channels were displayed through three LED screens (each 1920x1080 pixels, 50" size) providing a combined field of view of 120°. Three LED screens behind the vehicle displayed the rear-view for the mirrors. Driving simulation was rendered with a frequency of 60 Hz. Once activated, the L3 ADS executed both longitudinal and lateral vehicle control. When the L3 ADS encountered a scenario that exceeded its operational design domain (see 2.6 Use cases), a 20-second take-over cascade was initiated and displayed to the driver (see chapter 5.2.4).

Figure 5.1. Static driving simulator mockup used in the present study.

5.2.3 Study Design and Procedure

There were two different HMIs in the present study. The study employed a one-factor within subject design with two levels of HMI guideline compliance. Participants were randomly assigned to either the (1) high compliance HMI or the (2) low compliance HMI condition in the first drive and experienced the respective other condition in the second drive. The two HMIs and respective differences are outlined in the section 2.5 Human-Machine Interface.

Upon arrival, participants were welcomed and gave informed consent. The experimenter explained that the study purpose was to examine two HMIs for automated driving and to evaluate different measures. To accustom themselves with the driving simulation, participants completed a five-minute familiarization drive. Prior to each experimental drive, the experimenter explained that, once activated, the L3 ADS would execute lateral and longitudinal vehicle guidance. Furthermore, the experimenter pointed out, that in case of exceedance of the system's limits, it would inform them with sufficient notice to take over manual control. Participants completed the first drive with all use cases (see table 5.2) and subsequently evaluated the HMI in the first inquiry on all nine questionnaires. After this inquiry participants again completed the experimental drive with the respective other HMI. In the second inquiry, they evaluated the HMI again with the same scales as in inquiry 1. Participants received the questionnaires in a randomized order to counteract sequential effects. The experimental procedure is depicted in figure 5.2.

Figure 5.2. Flowchart of experimental procedure.

5.2.4 Human-Machine Interface

An HMI for automated driving, that had previously been used in studies by Jarosch et al. (2017) and (Hergeth et al., 2017) served as the high compliance HMI. It was depicted in the instrument cluster. When activated, the blue colour of the lane symbols, the text and the steering wheel indicated that the system function carried out longitudinal and lateral vehicle guidance. This HMI (see figure 5.3) resembles that of

existing HMI solutions for adaptive cruise control (i.e., longitudinal vehicle guidance, ACC) with additional steering assistance (Naujoks, Purucker, & Neukum, 2015). Information was redundantly communicated by means of pictograms and a textbox above (Stevens, Quimby, Board, Kersloot, & Burns, 2002). Textual information was displayed in German language. During the approach of the system limits, the HMI announced system limitations through a take-over cascade in form of an announcement, a conditional Take-Over request (*soft TOR*) and an immediate take-over request (*hard TOR*) (Forster, Naujoks, Neukum, & Huestegge, 2017). The stages lasted for 7 seconds (announcement and soft TOR) and 6 seconds (hard TOR), respectively. 20 seconds before reaching the limitation, a generic warning tone announced the upcoming limit. Additionally, the textbox displayed messages. The low compliance HMI did not provide textual feedback. The soft TOR followed this notification after six seconds and the HMI color switches from blue to yellow. The HMI shows hands that grab the steering wheel and additional information in the text. After seven more seconds, the hard TOR appeared with the HMI colored in red and hands grabbing the steering wheel. A more critical warning tone accompanies the visual information. Drivers could activate the L3 ADS by pressing a button on the left side of the steering wheel with the label *AUTO*. Deactivation was possible through either braking/accelerating, active steering input or pressing the *AUTO*-button with subsequently putting hands on the steering wheel. During the hard TOR, a hands-on signal immediately deactivated the L3 ADS. The development of a non-guideline compliant HMI and comparison with a compliant HMI is a mean for the purpose of investigating criterion-related validity. To create a difference between two HMIs, compliance with common HMI guidelines was systematically impaired in the low compliance condition. A checklist for ADS HMI design by (Naujoks, Wiedemann, et al., 2019) served as the criterion for HMI compliance. From the high compliance HMI, both the display component and the operation component (i.e., *AUTO*-button) changed by intentionally violating five items of the checklist. Table 5.1 provides an overview of variations in the HMI, the accordingly varied guideline and reference. The guideline items from (Naujoks, Wiedemann, et al., 2019) were the following:

- Item 3: System state changes should be effectively communicated.
- Item 7: The visual interface should have a sufficient contrast in luminance and/or color between foreground and background.
- Item 8: Texts (e.g., font types and size of characters) and symbols should be easily readable from the permitted seating position.

- Item 9: Commonly accepted or standardized symbols should be used to communicate the automation mode. Use of non-standard symbols should be supplemented by additional text explanations or vocal phrases.
- Item 14: The colors used to communicate system states should be in accordance with common conventions and stereotypes.

Figure 5.3 depicts the high compliance HMI (left) and the low compliance HMI (right) when the L3 ADS is activated (1st row), the soft TOR (2nd row), hard TOR (3rd row) and when the ADS was not available (bottom row).

Figure 5.3. Visual HMI for an active L3 ADS, conditional TOR, immediate TOR and L3 ADS not available (rows from top to bottom). Numbers indicate HMI variations described in table 5.1 column 2.

Table 5.1

Variations for low compliance HMI for the two components with respective criterion and reference

Component	Variation	Guideline number	Reference in guideline of Naujoks, Wiedemann et al. (2019)
Operation component	Activation and deactivation through long-press (i.e., 0.8 seconds)	Item 3	AdaptIVe Consortium (2017)
Display	(1) Pictograms are 60% of the original size	Item 8	Tullis, Boynton, and Hersh (1995)
	(2) No text information except for L3 ADS availability	Items 2, 3, 9	AdaptIVe Consortium (2017), CAMP (2016), Stevens et al. (2002)
	(3) no color coding for cautionary and imminent TOR	Items 3, 7, 14	AdaptIVe Consortium (2017), ISO 15008 (2012), Stevens et al. (2002)
	(4) no blue colour coding for active L3 ADS	Items 3, 7, 14	AdaptIVe Consortium (2017), ISO 15008 (2012), Stevens et al. (2002)

5.2.5 Use cases

Use-cases of the present study were chosen based on the HMI testing scenario catalogue for L3 ADS proposed by (Naujoks, Hergeth, et al., 2018). Use-cases included driver initiated activations and deactivations, two TORs due to road works and the end of L3 ADS availability as well as independently executed system maneuvers (Naujoks, Forster, et al., 2017b). The eight use cases were arranged in a fixed order. This is necessary in studies on automated driving since for example a TOR always requires a user-initiated transition to an automated mode as the subsequent UC. The TOR scenario itself lasted 30 seconds in total if the driver does not intervene. The driver initiated UCs took until the UC was completed successfully. At a maximum, the experimenter waited for two minutes. If the participant could not complete the respective transition, he/she was instructed by the experimenter. An analysis of the duration of the activation scenarios is reported in chapter 7. One drive lasted approximately 15 minutes. Table 5.2 shows the eight UCs with information about the initiator (i.e., driver vs. system)..

Table 5.2

Sequential order of use-cases in for each experimental drive

Number	Use case	Initiator
UC1	Initial activation	Driver
UC2	Independent lane change	System
UC3	Driver-initiated deactivation	Driver
UC4	Re-activation	Driver
UC5	TOR (road works)	System
UC6	Re-activation	Driver
UC7	Independent speed adaptation	System
UC8	TOR (end of L3 ADS)	System

5.2.6 Dependent Variables

Table 5.3 summarizes the dependent measures used in the present study. Section 5.1.1 already provided information about the development of the respective scales. Questionnaires that did not exist in German language (i.e., UTAUT, PSSUQ) were translated and backtranslated by a German and an English native speaker (Jones, Lee, Phillips, Zhang, & Jaceldo, 2001). To investigate face validity, participants were asked to additionally indicate when they struggled in answering a specific item due to unclear formulation of the item or inappropriateness in the automated driving context.

Table 5.3

<i>Constructs, questionnaires, scale and original sources) for self-report measures</i>			
Construct	Questionnaire (subscales)	Scale	Source
Usability	SUS (2)	Likert [1-5]	Brooke (1996)
	PSSUQ (3)	Likert [1-7]	Lewis (2002)
Acceptance	UTAUT (4)	Likert [1-7]	Rahman et al. (2017) adapted from Venkatesh et al. (2003) and Adell (2010)
	van-der-Laan Scale (2)	Semantic Differential [1-5]	van-der-Laan et al. (1997)
	AttrakDiff (3)	Semantic Differential [1-7]	Hassenzahl et al. (2003)
User Experience	UEQ (6)	Semantic Differential [1-7]	Laugwitz et al. (2008)
	meCUE (9)	Likert [1-7]	Minge et al. (2016)
Trust	ATS (2)	Likert [1-7]	Jian et al (2000)
	UTA (3)	Likert [1-5]	Chien et al. (2014)
Manipulation check	HMI design guidelines	Likert [1-7]	Naujoks et al. (2019)

5.2.7 Manipulation Check

An expert evaluation served as manipulation check to ensure a successful variation of HMI compliance. It consisted of eight items on a 7-point Likert scale from 1 ("not at all") to 7 ("very much") concerning the guidelines for HMI design (Naujoks, Wiedemann, et al., 2019). Participants answered each item for both the high and low compliance HMI. The manipulation check for HMI guideline criteria was averaged into a composite. The items number with the wording are shown in Table 5.4.

Table 5.4

Manipulation check item numbers, wording and respective guideline number in Naujoks, Wiedemann et al. (2019)

Item Number	Item Wording	Guideline number in Naujoks, Wiedemann et al. (2019)
1	The driver is supported by the HMI in his/her perception of system state changes.	3
2	There is a sufficient contrast between foreground and background.	7
3	The visual display and the background differ sufficiently by color.	7
4	Color coding is according to urgency.	14
5	The displayed symbols are easily readable from the permitted seating position.	8
6	The displayed text is easily readable from the permitted seating position.	8
7	The operating elements of the HMI is intuitive.	3, 9
8	There is immediate feedback about user input on the HMI.	3, 9

5.2.8 Statistical Procedure and Data Analysis

To ensure that no confounding factor (i.e., HMI guideline compliance) is present which could lead to an interaction between dependent measures and stages of the independent variable, reliability and validity are examined separately for both HMI conditions. Subscales were averaged into a composite as described in the original source. Mean ATS scores were calculated separately for trust and distrust as suggested by (Spain, Bustamante, & Bliss, 2008). Hence, there are two separate mean scores (i.e., trust, distrust) with a value between 1 and 7 each. Cronbach's alpha was calculated as a measure of scale reliability (Cronbach, 1951). To evaluate reliability coefficients in an absolute sense, the present values were compared to a minimum value of $\alpha=0.7$ (Kline, 1999; Nunnally, 1978) as well as the coefficients in the original source (if reported).

We evaluated content validity by means of participants' evaluation about whether they struggled giving their rating on the respective item (i.e., face validity). Here, we counted the total number of indications for each item.

To determine construct validity, the correlations of the entire set of subscales in the present study were evaluated by means of an exploratory factor analysis (EFA) approach (Bühner, 2011). This approach allows combining subscales to a certain number of factors that assess a similar construct and distinguish them from other subscales that assess a different facet of user preference.

Criterion-related validity was evaluated by means of inferential statistical analysis of the within-subject factor HMI compliance. A repeated measures-ANOVA was calculated for all self-report measures. Thus, criterion-related validity represents sensitivity of the questionnaires to the experimental HMI variation. If a questionnaire is valid in

this sense, it must be sensitive to the manipulation and reveal a statistically significant main effect of HMI condition.

5.3 Results

5.3.1 Manipulation Check

$N=8$ experts in the field of Human Factors (at a minimum Master's degree in psychology, human-computer interaction or related field) completed the manipulation check. The experts completed the manipulation check questionnaires (see chapter 5.2.6) after experiencing both the high and low compliance HMI. Descriptive data for the fulfillment of HMI guidelines showed that the high compliance HMI was considered superior ($M=5.30$, $SD=0.57$) compared to the low compliance HMI ($M=2.31$, $SD=0.42$).

5.3.2 Missing Data

Across all participants, only $n=4$ missed to answer single items. This led to a total of $N=13$ missing items. One participant did not complete the van-der-Laen scale. With every participant answering 334 items in total, the percentage of missing data is very low and equals 0.1%. Reliability analysis used listwise deletion. For validity and sensitivity, however, an exclusion of $n=4$ participants would be necessary. According to Tabachnick and Fidell (2007) '*Expectation-Maximization-methods sometimes offer the simplest and most reasonable approach to imputation of missing data, as long as your preliminary analysis provides evidence that scores are missing randomly*' (p.71). Since the loss of information looms larger than the overestimation of effects through the Expectation-Maximization (EM) approach, missing raw values as well as the van-der-laen scale scores were estimated by an EM Algorithm (Lüdtke, Robitzsch, Trautwein, & Köller, 2007).

5.3.3 Reliability

The following section outlines reliability results for the subscales of self-report measures. Table 5.5 summarizes coefficients of the present study for both the high and the low compliance HMI overall. In addition, the reliability coefficient alpha of the original source is reported. Concerning the ATS, Jian et al. (2000) did not provide Cronbach's alpha for a two factorial solution, so no comparison is possible.

Reliability analysis found that $n=7$ subscales did not meet the minimum value of $\alpha=0.7$

in at least one of the two experimental conditions. If a low internal consistency was observed in the present data, the original source also reported comparably low alpha values such SUS Learnability, UATUT Social Influence and UEQ Dependability. Conversely, there are also subscales (i.e., UTA Process, Purpose; meCUE Intention, Usefulness) that exhibited low internal consistency while the original source reports sufficient reliability.

Table 5.5

Reliability coefficients (Cronbach's alpha) for each subscale by HMI (i.e., high compliance, low compliance) and the original source (if reported).

Scale	Subscale	high compliance HMI	low compliance HMI	Original
SUS	Learnability	.571	.544	.70
	Usability	.824	.863	.90
PSSUQ	System Usefulness	.940	.940	.96
	Information Quality	.898	.903	.96
	Interface Quality	.783	.880	.92
UTAUT	Perf.-Expectancy	.774	.823	.87
	Effort Expectancy	.907	.902	.86
	Social Influence	.194	-.133	.48
	Intention to Use	.900	.879	.91
VDL	Usefulness	.795	.811	.73-.87
	Satisfaction	.887	.879	.81.90
AttrakDiff	Hed-Stim	.829	.868	.76-.87
	Hed-Ident	.872	.927	.73-.83
	Pragmatic	.832	.872	.83-.85
meCUE	Usefulness	.588	.718	.83
	Usability	.890	.898	.89
	Status	.789	.793	.83
	Aesthetics	.799	.857	.89
	Commitment	.806	.768	.86
	positive Affect	.892	.886	.94
	negative Affect	.851	.814	.93
	Intention	.716	.571	.86
	Loyalty	.749	.838	.76
UEQ	Attractiveness	.896	.954	.89
	Perspicuity	.786	.863	.82
	Efficiency	.769	.729	.73
	Dependability	.669	.866	.765
	Stimulation	.791	.799	.76
	Novelty	.906	.922	.83
ATS	Distrust	.732	.826	N/A
	Trust	.940	.946	N/A
UTA	Performance	.820	.828	.889
	Process	.560	.751	.870
	Purpose	.560	.752	.870

5.3.4 Validity

Content Validity

We approached content validity via participants' face validity ratings. Table 5.6 shows items with a minimum of $n=11$ participants that considered an item as problematic to answer which equals close to every fifth participant (19.3%). This threshold was not chosen out of convenience but because from an expert's perspective, 20% or more of a sample indicating issues in answering a respective item is problematic. Analogous to the procedure to determine the number of factors for the EFA in the following section, a Scree-plot of the number of indications across all 168 items led to the threshold of $n=11$ that are worth mentioning here. When a smaller percentage (e.g., 3 out of 57 participants) indicated that they struggled in understanding, no consistent picture across the entire sample could be drawn. If a participant marked the same item at both times of measurement, he/she was counted as one. Results revealed $n=15$ items with low face validity. PSSUQ ratings depend on whether the experiment included use cases with error messages and participants who had made a mistake and needed to recover from these. Both items of the UTAUT Social Influence subscale were considered problematic. The AttrakDiff included the highest number of items with low face validity ($n=5$). A large number of participants also considered meCUE items related to status as problematic. This is in accordance with the UTAUT Social Influence result. Another reason for face validity concerns were unclear content of expressions as observed for 'integrity' (ATS) and 'performance' (UTA).

Table 5.6

Items and respective scales with low face validity as indicated by the frequency of participants labelling an item as "problematic to answer".

Scale	Item	Face validity concerns [n]
PSSUQ	The system gave error messages that clearly told me how to fix problem.	12
	Whenever I made a mistake using the system, I could recover easily and quickly.	17
UTAUT	People who influence my behavior would think that I should use the system	19
	People who are important to me would not think that I should use the system	12
AttrakDiff	isolating-connective	15
	alienating - integrating	17
	brings me closer to people-separates me from people	26
	cautious - bold	11
	harmless-challenging	11
meCUE	The product would enhance my standing among peers	11
	By using the product, I would be perceived differently	12
	Compared to other products, this product seems incomplete	12
ATS	The system has integrity.	17
UTA	The system uses appropriate methods to reach decisions	20
	I can always rely on the system to ensure my performance	14

5.3.5 Construct Validity

Construct validity was investigated for the high compliance HMI condition by means of a factor analysis. The Kaiser-Meyer-Olkin (KMO) as a test for the appropriateness of the entire correlation table (relationship between all subscales) for factor analysis revealed a score of .878. This that indicates appropriateness of data for a subsequent factor analysis. Bartlett's test for sphericity became highly significant ($\chi^2(496)=1955.340$, $p<.001$). To determine the factor structure of the preference ratings, an EFA with principal-component factor extraction and Varimax orthogonal rotation was carried out. The Scree-criterion and Velicer's minimum average partial test (O'Connor, 2000; Velicer, 1976) suggested a three-factor solution. The factors can explain 28.33%, 25.70% and 16.30% of total variance, respectively, adding up to a total variance explained of 70.33%. Table 5.7 shows factor loadings for a three-factor Varimax orthogonal rotated solution sorted by size. Loadings smaller than 0.5 are colored in grey. Self-report measures that use semantic differentials such as all subscales of the AttrakDiff, four subscales of the UEQ and the van-der-Laan scale show high loadings on factor 1. This factor combines

measures that evaluate the graphical interface design. Self-report measures that focus on interaction and pragmatic qualities of the interface such as the SUS, UTAUT Effort Expectancy and PSSUQ System Usefulness exhibit large factor loadings on factor 2. Finally, subscales that assess future intentions regarding the use of the system function accumulate on factor 3. Both ATS subscales load only weakly on factor two. This indicates that trust as measured by ATS rather forms a fourth component of user preference or is not suitable for interface evaluation.

According to the Fornell-Larker criterion, factor loadings of a component on its factor needs to be at least 0.7 for sufficient convergent validity. To meet requirements of divergent validity, the item's factor loading on other factors must not exceed 0.3. The present results show that eight subscales on factor 1 show high convergent validity. This factor combines subscales that primarily assess an interfaces' design features and graphical appearance. Seven subscales show high convergent validity on factor 2. Scales that assess a user's interaction and ease of it load high on this factor. These subscales are all closely tied to the usability construct. One subscale of factor 3 showed sufficient convergent validity (i.e., UTAUT Intention). Subscales that assess usage intention accumulate on this factor. Scales that did not exhibit convergent validity (e.g., meCUE Usefulness) neither met the divergent validity goal. These subscales are represented by a combination of two or more factors rather than by one factor alone. Results of the EFA procedure for ratings of the low compliance HMI conditions also revealed a three factor solution for user preference with similar factor loadings. Due to pagination constraints, these results are not reported here.

Table 5.7

Matrix with factor loadings after Varimax rotation. Factor loadings are sorted by size and small values (i.e., $<.5$) are colored in grey.

Subscale	Factor 1	Factor 2	Factor 3
UEQ Novelty	0.883	0.083	0.090
UEQ Stimulation	0.841	0.226	0.315
meCUE Aesthetics	0.811	0.176	0.175
AttrakDiff Pragmatic Quality	0.793	0.339	0.223
UEQ Attractiveness	0.773	0.378	0.330
AttrakDiff Stimulation	0.771	0.454	0.236
AttrakDiff Identification	0.747	0.510	0.119
PSSUQ Interface Quality	0.721	0.360	0.076
UEQ Efficiency	0.671	0.416	0.270
VDL Usefulness	0.644	0.396	0.416
meCUE Usefulness	0.589	0.304	0.444
PSSUQ Information Quality	0.581	0.553	0.109
UTAUT Effort Expectancy	0.226	0.889	0.112
UEQ Perspicuity	0.269	0.849	0.053
meCUE Usability	0.283	0.841	0.082
SUS Usability	0.101	0.804	0.211
SUS Learnability	0.101	0.804	0.004
PSSUQ System Usefulness	0.291	0.803	0.207
UTA Process	0.411	0.714	0.159
meCUE Negative Affect	0.378	0.692	0.170
VDL Satisfaction	0.591	0.606	0.322
UEQ Dependability	0.524	0.605	0.112
ATS Distrust	0.461	0.497	0.306
ATS Trust	0.038	0.267	0.116
meCUE positive Affect	0.514	0.102	0.700
UTA Performance	0.500	0.138	0.767
meCUE Intention	0.510	0.138	0.664
meCUE Commitment	-0.030	0.029	0.655
meCUE Status	0.506	-0.092	0.610
UTAUT Intention	0.498	0.325	0.598
UTAUT Performance Expectancy	0.463	0.096	0.594
UTA Purpose	0.069	0.305	0.547
meCUE Loyalty	0.402	0.377	0.491
UTAUT Social Influence	-0.098	0.373	0.378

5.3.6 Criterion Validity

To determine each scale's criterion validity regarding guidelines for HMI design, 2-factorial repeated measures ANOVAs were calculated for all nine questionnaires. The within-subject factors were HMI compliance (high vs. low) and number of subscales. Table 5.8 shows descriptive (i.e., M , SD) and inferential results for the main effect of the HMI and the interaction between HMI and order of presentation (i.e., Wilk's λ). Results of inferential tests revealed that all scales could discriminate between the high and the low compliance HMI (significant main effects). Thus, the external criterion of HMI compliance is reflected in all self-report measures. Significant interaction effects (i.e., PSSUQ, UTAUT, meCUE Module 1, UEQ, ATS, UTA) indicate that the difference between the high and the low compliance HMI is not equally present at all subscales of the respective questionnaire. These questionnaires contain subscales that are highly sensitive to the experimental variation and subscales that are not as sensitive to the HMI criterion.

Table 5.8

Descriptive (i.e., M , SD) and inferential (i.e., main effect for HMI and Interaction HMI x Subscale) statistics for each scale.

Scale	Subscale	high compliance M , SD	low compliance M , SD	Main effect HMI	Interaction HMI x Subscale
SUS	N/A	82.45 (14.01)	67.11 (19.14)	$t(56)=5.959$, $p<.001$, $d=.778$	N/A
PSSUQ	SysUse	6.20 (0.89)	5.36 (1.13)	$F(1,56)=63.439$, $p<.001$, $\eta_p^2=.531$	$F(2,55)=8.463$, $p<.05$, $\eta_p^2=.235$
	InfoQual	5.48 (1.14)	4.08 (1.28)		
	IntQual	5.64 (1.09)	4.29 (1.57)		
UTAUT	Perf.-Expectancy	5.28 (0.94)	4.79 (1.17)	$F(1,56)=38.583$, $p<.001$, $\eta_p^2=.408$	$F(3,54)=4.561$, $p<.05$, $\eta_p^2=.202$
	Effort Expectancy	6.10 (0.88)	5.23 (1.20)		
	Social Influence	4.71 (1.03)	4.41 (0.93)		
	Intention to Use	6.22 (0.87)	5.73 (1.11)		
VDL	Usefulness	4.24 (0.52)	3.73 (0.66)	$F(1,56)=40.736$, $p<.001$, $\eta_p^2=.421$	$F(1,56)=3.726$, $p=.059$, $\eta_p^2=.062$
	Satisfaction	4.24 (0.59)	3.57 (0.80)		
AttrakDiff	Hed-Stim	5.32 (0.85)	4.47 (1.10)	$F(1,56)=38.951$, $p<.001$, $\eta_p^2=.410$	$F(2,55)=3.103$, $p=.053$, $\eta_p^2=.101$
	Hed-Ident	5.07 (0.81)	4.28 (0.98)		
	Pragmatic	5.13 (0.86)	4.89 (1.08)		
meCUE	Usefulness	5.64 (0.83)	4.95 (1.02)	$F(1,65)=41.276$, $p<.001$, $\eta_p^2=.424$	$F(3,54)=8.652$, $p<.001$, $\eta_p^2=.395$
	Usability	6.06 (0.95)	5.05 (1.33)		
	Status	4.16 (1.26)	3.84 (1.35)		
	Aesthetics	4.74 (1.12)	3.61 (1.51)	$F(1,56)=22.793$, $p<.001$, $\eta_p^2=.289$	$F(1,56)=.035$, $p=.852$, $\eta_p^2=.001$
	Commitment	2.52 (1.11)	2.26 (1.15)		
	positive Affect	4.65 (1.03)	4.07 (1.12)		
	negative Affect	5.37 (1.00)	4.82 (1.06)	$F(1,56)=40.383$, $p<.001$, $\eta_p^2=.419$	$F(1,56)=3.678$, $p=.060$, $\eta_p^2=.062$
	Intention	5.40 (1.04)	4.67 (1.07)		
	Loyalty	4.44 (1.13)	3.49 (1.31)		
UEQ	Attractiveness	5.72 (0.86)	4.73 (1.34)	$F(1,56)=48.355$, $p<.001$, $\eta_p^2=.463$	$F(5,52)=3.402$, $p<.05$, $\eta_p^2=.274$
	Perspicuity	6.02 (0.89)	5.00 (1.25)		
	Efficiency	5.77 (0.86)	5.23 (0.97)		
	Dependability	5.79 (0.79)	4.85 (1.23)		
	Stimulation	5.25 (0.92)	4.50 (1.25)		
	Novelty	4.88 (1.37)	3.99 (1.61)		
ATS	Distrust	5.59 (0.67)	4.70 (1.18)	$F(1,56)=34.551$, $p<.001$, $\eta_p^2=.382$	$F(1,56)=3.550$, $p=.065$, $\eta_p^2=.036$
	Trust	5.63 (1.07)	5.03 (1.23)		
UTA	Performance	3.78 (0.76)	3.46 (0.80)	$F(1,56)=58.848$, $p<.001$, $\eta_p^2=.512$	$F(2,55)=12.442$, $p<.001$, $\eta_p^2=.311$
	Process	4.11 (0.56)	3.31 (0.80)		
	Purpose	3.88 (0.59)	3.41 (0.76)		

5.4 Discussion

The current study examined self-report measures that are frequently applied to evaluate L3 ADS HMIs regarding psychometrics. $N=57$ participants completed nine questionnaires for the constructs usability, acceptance, user experience and trust

once for a high compliance and once for a low compliance L3 ADS HMI. Cronbach's alpha served as an estimate of scale reliability. We applied an EFA approach for the investigation of construct validity. We furthermore followed an inferential analysis of the high compliance and low compliance HMI for the examination criterion validity. This section discusses the outcomes and methodological aspects for each requirement.

5.4.1 Reliability

Measures of reliability were mostly sufficient in an absolute sense (Kline, 1999) and comparable to the values reported in the original source (see table 5.5). The PSSUQ, van-der-Laan scale, AttrakDiff, UEQ and ATS showed positive results (i.e., high α -values) of the reliability analysis. Reliability of the two-factorial structure of the SUS (Bangor, Kortum, & Miller, 2009) turned out to be sufficient for the usability subscale but insufficient for the learnability subscale. Reliability results for the SUS suggest following the SUS score calculation instructions in Brooke (1996) and rather rely on a one-factorial solution. Subscales that revealed unreliable results were the UTAUT Social Influence subscale and UTA subscales Process and Purpose. These results discourage future administration of these scales in the ADS context because the UTAUT Social Influence subscale was highly unreliable and the UTA showed two out of three subscales that could not reach the criterion of 0.7. Furthermore, there were also instances in the meCUE (usefulness, intention) and UEQ (Dependability) with insufficient Cronbach's alpha values. These are also considered as problematic to use. However, the UEQ subscale was just close to the threshold value. Regarding the meCUE, this does not mean that the entire scale might not be used since the modules can be applied separately. Still, one might consider the van-der-Laan scale for usefulness and UTAUT for intention as superior when it comes to reliability.

5.4.2 Validity

Content Validity

Content validity as indicated by face validity was high for the SUS, van-der-laan scale and UEQ (see table 5.6). Furthermore, participants considered only one item each of the PSSUQ and ATS as problematic to answer. Thus, we consider content validity for these two measures as given. Face validity investigation revealed that people struggled with scales and items that relate to the opinion to other people such as the UTAUT

Social Influence and the meCUE Status subscale. A possible explanation for this finding might be that L3 ADS are not yet commercially available. Thus, peer-related questions require a lot of imagination and do not lead to valid results. Items that cover the HMIs suitability for communication such as three AttrakDiff items were considered as problematic to answer, as communication with other people was not a design purpose of the present HMIs for automated driving. The present results suggest omitting questions on other peoples' opinions as long as there is no commercial availability or distribution on the consumer market. There are two different reasons for low validity of UTA items. First, complexity of an L3 ADS is high and people can hardly judge, how the system makes decisions and comes to conclusions. Furthermore, the term performance within the L3 ADS context remains unclear. Generally, the interaction success with a certain technology is considered as performance (e.g., driving a vehicle), while in the L3 ADS context, the performance per se (i.e., driving) is executed by the system function and the driver's performance is rather reflected in NDRT engagement or reaction to a TOR. Therefore, the performance term remains obscure for many participants and should be applied with caution in this context.

Construct Validity

Construct validity examination led to a three-factor solution for self-report measures (see table 5.7). The first factor includes mostly graphical design-related measures. The second factor is composed of the usability and instrumental scales and is therefore interaction-oriented. The third factor combines scales that assess usage intention and therefore we consider the factor acceptance-oriented. Two separate factors for instrumental and non-instrumental qualities as suggested by Hassenzahl et al. (2003) were apparent in the present solution. Acceptance-related scales are separated from instrumental and non-instrumental qualities. Minge et al. (2016) have suggested this additional dimension but point towards the fact that there are correlations between measures of acceptance and usability. Support for this assumption comes from the results of discriminant validity. Subscales from the intention factor also revealed remarkable loadings on both the design and usability factor. The present analysis found that the SUS and meCUE showed best results of construct validity due to high discriminant and convergent validity on the respective factors. SUS subscales loaded on the interaction-oriented factor and meCUE subscales loaded across all factors in the way that was expected according to Minge et al. (2016). It is unclear whether the construct of trust relates to these measures. The ATS subscales did not align with the present solution while

the UTA subscales aligned with the interaction and intention factor. Considering that reliability and face validity results were more positive for the ATS, we argue against the application of trust measures when investigating HMI preference. The PSSUQ as a proposed usability measure was located not only on the expected interaction factor but also on the unexpected design factor. Therefore, validity is on a medium level. UTAUT's intention and effort subscales loaded as expected. The performance subscale was expected to also align with the interaction factor but eventually showed more alignment with the intention factor leading to a medium validity. Validity on the van-der-Laan scale was low due to the observation of loadings on multiple factors (e.g., usefulness on design and interaction). Factor loadings of the AttrakDiff revealed that they all assess design-oriented criteria in this context. This is not in accordance to the originally proposed structure of pragmatic and hedonic product qualities (Hassenzahl et al., 2003). Hence, low validity was assigned. With efficiency as a clearly interaction oriented factor loading on design, validity of the UEQ was impaired. The other subscales accumulated on the factor that could be expected from their original proposition (Laugwitz et al., 2008). Table 5.9 summarizes the results of construct validity examination.

Criterion-related Validity

Examining criterion validity, main effects of the inferential tests showed that all scales could discriminate between the two experimental conditions (see table 5.9). Even though there are scales with reliability and validity concerns they can detect a difference if HMI design guidelines are violated (Naujoks, Wiedemann, et al., 2019). Significant interaction effects indicate that differences between the high compliance HMI and low compliance HMI are not reflected in the same way across all subscales. These questionnaires incorporate subscales with a varying degree of sensitivity to the experimental HMI compliance manipulation. The SUS due to the single percent measure for sensitivity, van-der-Laan, AttrakDiff and ATS showed continuously strong differences between the two HMI variations. When evaluating L3 ADS HMIs with any of the other scales, one has to be aware of differences in sensitivity of the subscales within the questionnaire. The evidence from the present study indicates that all the present self-report measures adhere to the external criterion of adherence to HMI design guidelines.

Table 5.9

Result overview of construct validity analysis.

Construct	Questionnaire	Result	Interpretation
Usability	SUS	- Both subscales located on interaction factor	high validity
	PSSUQ	- Located on both design and interaction factor	medium validity
Acceptance	UTAUT	- Effort and intention loading on respective factors	medium validity
		- Performance on acceptance dimension	
	van-der-Laan Scale	- Usefulness loading on design and acceptance factor - Satisfaction loading on design and interaction factor	low validity
User Experience	AttrakDiff	- All subscales on design-factor	low validity
	UEQ	- High loadings on design and interaction factor - Efficiency loading on design factor	medium validity
	meCUE	- Loadings on all three factors	high validity
		- Module 1 and Module 3 factors loading as expected	
Trust	ATS	- Poor alignment with present factor solution - Suitability for HMI evaluation questionable	low validity
	UTA	- Congruency with acceptance and usability measures - Reflection of trust component in relation to ATS unclear	medium validity

Limitations and Future Research

Analysis of reliability through the calculation of internal consistency by means of Cronbach’s alpha is considered problematic. Sijtsma (2009) outlines that there are better measures for reliability such as the lower bounds (Guttman, 1945) or omega (Revelle & Zinbarg, 2009). For the sake of comparability with the originally reported values, we chose the alpha approach to reliability.

One drive in the present experiment lasted 15 minutes. This short amount of time restricts the possible amount of interactions with the HMI. Especially for attitudes that require long-term experience (i.e., trust, acceptance) this might represent a limitation. However, the use cases (see Table 5.2) chosen for the present experiment already represent a good portion of interactions that are possible with an HMI for L3 ADS (Naujoks, Hergeth, et al., 2018). Hence, participants could derive a good impression of HMI functionality and interaction possibilities from the 15-minute driver. Still, for evaluation of the ADS itself regarding lane or distance keeping and maneuvering, a longer experience might be required to provide information about a user’s acceptance and trust. Since the study thus only allows short-term evaluation of the automated vehicle HMI, only initial knowledge and interactions are the basis for user preference ratings. However, there is evidence that interaction performance (see chapter 7 and mental models that discriminate between L2 and L3 automation (see chapter 8) change with rising

experience. Therefore, additional knowledge gained through experience might generate the occurrence of dissonances (Vanderhaegen & Carsten, 2017). Such dissonances are characterized by an inconsistency between initial and additional knowledge and brings the potential of influencing long-term perception of the automated vehicle HMI. In this sense, future research should also consider conflicting information for different levels of automation over prolonged time periods.

As outlined in chapter 5.1.2, particular circumstances apply to experimental settings in driving simulation research. The present study included $N=57$ participants. Concerning the reliability analysis, the lowest subject-to-item ratio for the entire scale is observed for the meCUE equaling 1.73 and this approach can be considered uncritical. To carry out factor analyses in psychometric evaluation, Anthoine, Moret, Regnault, Sébille, and Hardouin (2014) found that a large number of studies reported minimum subject-to-item ratios of close to two. Due to the present sample size, an EFA on item level was not possible here. Therefore, the EFA approach was conducted using the subscales instead of single items. The sample size of $N=57$ cases for the $n=34$ subscales refers to a subject-to-case ratio of 1.68 and thus we conclude that this approach is reasonable. Still, the sample size in relation to conducting an EFA with proposed requirements of up to 300 cases (Tabachnick & Fidell, 2007) is a drawback of this study. Conclusions of the factor structure are drawn from an aggregated level. The possibility that a different factor structure for self-report measures might have emerged on item level might have emerged cannot be categorically ruled out.

The examination of criterion validity used a criterion on system level (i.e., HMI guideline compliance). Future research also needs to bring forth evidence of criterion validity on subject level. Especially for the usability-related factor of user preference, it remains to be seen whether and how well self-reports are reflected in interaction measures such as accuracy, speed or attentional demand (Wickens et al., 2015). In that vein, chapter 3 outlined the importance of a multi-method approach (Hornbæk, 2006; Nielsen & Levy, 1994) when evaluating ADS. The present work contributes to this call for methodological development as it provides empirical evidence of the suitability of different self-report measures for L3 ADS. However, future research efforts are necessary to find out about the suitability of different observational measures and their relationship with self-report measures.

The present sample was drawn from BMW employees and supplier companies. This might be a critique for the study outcome concerning self-report measures. Although BMW employees might differ from the general population in some aspects, this does not

necessarily limit the external validity of the current findings. The main focus of the current study was not participants' general attitude towards automated driving and cars, but specific aspects of the HMI as targeted by the scale items. The sample consisted of people with diverse backgrounds such as participants working for suppliers, business partners and interns, who differed in demographic variables (see for example age) as well as educational background (e.g., economists, psychologists, computer scientists). In this regard, it might be argued that the sample could have been even more representative of the population in question than, for example a sample drawn from college students, who have been shown to differ substantially from the population at large and "are among the least representative populations one could find for generalizing about humans" (Henrich, Heine, & Norenzayan, 2010). Taken together, inferences drawn from the sample investigated in the current study should also generalize to the population of drivers evaluating an ADS in the future (see also sample considerations in trust research in Hergeth, 2016).

The open question of how to proceed with scales that revealed limited psychometric properties remains. For example, one might still apply a scale but discard certain items that were problematic in this context (see table 5.6). This could also improve reliability of the respective subscale but at the same time one could debate whether the scale still covers the initially proposed construct comprehensively. If a scale, however, brings specific instructions on how to calculate overall scores such as the SUS, deleting items is not an option. The adaptation of wording of single items is also a possible approach. Especially in acceptance research using items of the UTAUT framework, subtle differences were apparent in the works on different levels of automation (Adell, 2010; Rahman et al., 2017). When adapting existing items or even adding new items due to certain peculiarities of HMI functionality, one has to consider that this influences reliability of the scale. Moreover, adding items to an already reduced item pool can affect construct validity by adding to the correlational matrix between items and potentially leading to new dimensions in factor analyses. Also it can change content validity through shifting the focus of the subscale. Some tools such as the meCUE bear the advantage of their modular nature. This means that not all subscales need to be applied but can be administered independently from each other. Therefore, if the present work for example found limited reliability of one pragmatic subscale, the other scales can still be used regardless in terms of reliability. Concluding, there are several possibilities on how to improve certain questionnaires in new contexts but one has to keep in mind that interventions might affect psychometrics not only to the better.

5.4.3 Conclusions

To conclude, SUS, UTAUT, UEQ and meCUE revealed the most positive results concerning psychometrics in L3 ADS evaluation. For an overall L3 ADS HMI evaluation, results from this study suggest to apply the meCUE when all dimensions of preference are of interest. Depending on the specific aspect of a particular study (i.e., design, interaction or acceptance evaluation), we recommend to apply scales or subscales that suit the respective purpose. The present work points towards the importance of psychometric scale evaluation in a new context. Since the L3 ADS circumstances are fundamentally different from conventional Human-Computer Interaction, self-report measures do not necessarily work as proposed in their original context. When setting up an experiment for automated driving and HMI research, one has to face challenge of choosing between available self-report measures. The present study provides researchers and practitioners with a recommendation of self-report measures and their suitability for evaluating L3 ADS.

6 Behavioral Measures, Mental Models and the Role of Feedback: Theory and General Method ⁵

This chapter provides a combination of theoretical considerations for the second study conducted herein. From that, it derives hypotheses for each of the three subsequent chapters. The first part concerns behavioral measure application and the effect of practice. It additionally takes on the development of the relationship between preference and performance over time. Part two includes the operationalization of mental models in regard to the ODD and development over time. It does not only rely on user's self-reported understanding but also introduces gaze behavior as a behavioral marker of system understanding. The third aspect of this study focused on calibrating effects of performance feedback for attitude measures. In contrast to summative measures (see chapter 5), it examined diagnostic and use case specific measures. Since the publications emerged from the same driving simulator experiment, the methodology is also described in this chapter before proceeding to the results and discussions separately. Each respective chapter still contains the original publication abstract to provide a brief introduction.

⁵This chapter is based on three previous publications:

- Forster, Y., Hergeth, S., Naujoks F., Beggiato, M., Krems, J. F. & Keinath, A. (2019). Learning to Use Automation: Behavioral Changes in Interaction with Automated Driving Systems. *Transportation Research Part F: Traffic Psychology and Behaviour*, 62, 599–614. doi.org/10.1016/j.trf.2019.02.013
- Forster, Y., Hergeth, S., Naujoks F., Beggiato, M., Krems, J. F. & Keinath, A. (2019). Learning and Development of Mental Models during Interactions with Driving Automation: A Simulator Study *The 10th International Driving Symposium on Human Factors in Driver Assessment, Training, and Vehicle Design*. Santa Fe, NM, USA
- Forster, Y., Hergeth, S., Naujoks F., Krems, J. F. & Keinath, A. (2019). Tell Them How They Did: Feedback on Operator Performance Helps Calibrate Perceived Ease of Use in Automated Driving. *Multimodal Technologies and Interaction*, 3(2), 29.

6.1 Background on Learning and Behavioral Measures

Measures in HMI Evaluation

The following theoretical consideration has two objectives. First, it focuses on the evaluation of different behavioral measures in the context of HMIs for automated driving with regard to effects of practice. Secondly, as behavioral measures are expected to improve with practice, the development of the agreeableness between behavioral measures and self-report measures over time is investigated (see chapter 7.1.3). The following sections outline the two objectives.

When evaluating HMIs for automated driving, a multi-method approach is recommended including both self-report and observational measures (Forster, Hergeth, et al., 2018a; Pettersson, Frison, et al., 2018). The present work aims at a thorough investigation to determine the suitability of behavioral measures. Psychometric quality criteria (Amelang & Schmidt-Atzert, 2006; Bühner, 2011; Nunnally, 1978) constitute a criterion for evaluating these measures. Reliability can be operationalized as the test-retest reliability. Thus, the stability of a measure over two or more times of measurement is evaluated. A possible operationalization for validity is criterion validity. Criterion validity describes the relationship between the test and an external criterion such as self-reported usability and observable interaction behavior. The previous chapter pointed towards the examination of criterion validity. The present study follows this open question by examining the relationship between different observational measures to a usability self-report measure.

The multi-method approach is not only present for self-report vs. observational measures but also within observational measures. Researches can apply the “*big three*” measures which are accuracy, speed and attentional demand (Wickens et al., 2015). Accuracy is operationalized as the number of errors, while speed is operationalized via the time on task or reaction time. These two variables have also entered the usability ISO norm as effectiveness and efficiency (DIN-EN ISO, 2011). As attentional demand is operationalized through gaze behavior, collecting data is far more time and cost consuming. There is a wide range of gaze metrics such as dwell times (Hayhoe & Ballard, 2005), monitoring frequency (Hergeth et al., 2016) or the dispersion index (Louw, Madigan, Carsten, & Merat, 2016). Due to the many possible operationalizations and difficulty of analyzing, the present work focuses on the first two measures of the “*big three*”. Chapter 8 describes the development of gaze behavior during interactions with driving automation.

Naujoks, Wiedemann, et al. (2018) highlighted the role of additional observations by the experimenter to support speed and accuracy measures. A comprehensive assessment of human performance should not only include data on operational level (such as speed and accuracy measures), but also observed impairments on tactical and strategic level (Michon, 1985). Experimenter ratings have been successfully introduced as tools to extend the assessment of take over performance (Jarosch & Bengler, 2018) and fitness-to-drive (Kenntner-Mabiala et al., 2016). Thus, in the present work we used experimenter ratings of interaction performance in addition to speed and accuracy.

The Effect of Learning

Learning processes of many activities such as perceptual-motor skills, decision-making or problem-solving follow a learning curve (Newell & Rosenbloom, 1981). Neves and Anderson (1981) observed a steep initial increase with subsequent stabilization of performance in skill acquisition of mathematical problem solving. Newell and Rosenbloom (1981) described the “*power law of practice*” as a function with the general form of:

$$P(N|a, b, c) = a + b * N^{-c}$$

The performance P is a function of the number of trials N given the three parameters a , b and c . The parameter a is the asymptote of P with N increasing indefinitely. The parameter b describes the amplitude of learning between initial performance and asymptotical performance. Parameter c is the learning rate.

Jahn, Krems, and Gelau (2009) investigated skill acquisition processes in navigational entry and could show that mean total glance and mean total task times followed a learning pattern that corresponds to the power law. Similarly, Totzke (2012) investigated the power law for the interaction with menu-controlled in-vehicle-information systems (IVIS). Concerning safety aspects, Winkler et al. (2018) investigated the effect of four repetitive trials on behavior (e.g., brake reaction times, collision frequency) and self-report measures (e.g., criticality, understandability) when using an advanced driving assistance system. They found evidence of an effect of practice but they did not fit to their data to a learning model. In the automation context, Beggiato et al. (2015) report evidence of the power law function in the development of trust, acceptance and self-reported learning in L1 driving automation (i.e., adaptive cruise control). The application of the power law for interaction behavior of higher levels of automated driving has still not been comprehensively investigated. An analysis by means of the power law is chosen instead of simple ANOVA or contrast approach for the first compared to

subsequent trials, because an ANOVA would assume a linear model for data analysis. As described in Newell and Rosenbloom (1981), learning does not follow a linear trend but is rather characterized by a steep increase in performance with subsequent stabilization which can best be described by the formula shown above. Therefore, the present study investigates the application of the power law of learning in the context of driving automation focusing on L2 and L3 automated driving. In regard to learning, the present work does explicitly not assume, that increases in interaction performance are due to the development of a certain perceptual-motor skill but rather an increased understanding of what correct behavioral actions are that lead to the desired system actions or states. Here, increasing performance is viewed as the result of a ubiquity of learning that includes not only perceptual-motor skills but also higher-level processes such as decision-making and problem-solving (Newell & Rosenbloom, 1981). The perceptual-motor skill of human operators to successfully complete a transition from manual to L3 automated mode which requires for example adaptation of speed, lateral position and ensuring availability of the ADS (SAE, 2018) can well be assumed. Drivers holding a valid license should be skilled enough to operatively navigate their vehicle in highway traffic and pushing certain buttons on an input element on the steering wheel as in the present study or pull a lever to activate driving automation systems. Therefore, we assume that with repeated interaction, users of driving automation will show increased performance due to enhanced understanding of the way how to execute the control transitions including messages from the HMI and understanding of operating conditions (e.g., speed). A better understanding of different operator inputs and resulting system consequences as shown by HMI and system behavior is expected to consequently lead to the adaptation of observable user behavior. This reasoning is supported in chapter 8 where increased self-reported learning and more accurate mental models with rising system experience was observed. At that point, automated driving development is facing a crucial challenge. With all users being novices in interacting with automation technology, the amount of automation levels, assistance systems and warning systems puts them into a situation, where they need to figure out correct ways of operation for desired systems states. To operate these functions accordingly, users have to bring graphical HMI elements, input-modalities and operating conditions in line. As a consequence they do not have to learn a respective motor skill, but how and under which conditions to execute simple behavioral actions so that they lead to the desired consequences.

From a methodological perspective, the application of the power law gives a deeper insight into familiarization trials. Carsten, Kircher, and Jamson (2013) recommend sep-

arating out the phase of learning how to use a new system. However, it is not possible to give a categorical recommendation of how long these familiarizations should last. Since to date there is no commercial availability of a combination of L3 and lower automation yet, all users must be considered as novices in this context. It is likely that first time users of driving automation might not have read the owner’s manual (Mehlenbacher, Wogalter, & Laughery, 2002) when they encounter these functions. Therefore, they might be unfamiliar with the concept of automation levels (SAE, 2018) and the terminology of the respective function. Additionally, the name of L2 and L3 functions differs between automobile manufacturers (Abraham, Reimer, & Mehler, 2017). The present work therefore examines behavioral adaptation processes of first time users of driving automation. As there is first evidence of applicability of the power law with L1 driving automation (Beggiato et al., 2015) and behavioral adaptation in menu-controlled IVIS (Totzke, 2012), it is of interest how interaction with combined automation functions (i.e., L2 and L3) changes over time. In addition, as outlined below, a change over time in either performance or preference measures might affect the relationship between these two measures (see chapter 6.1.1).

The different levels of driving automation pose different demands to the operator. Especially, when users initiate a transition between automation levels themselves (Naujoks, Hergeth, et al., 2018), they have to meet a certain number of system conditions, depending on the desired level of automation (SAE, 2018). As the operator’s responsibility is supervising the correct functioning during L2 automation, the number of necessary conditions from self-driving to active L2 driving is rather small. For L3 automation, however, the number of conditions (i.e., speed, lateral position, automation availability) rises due to the transition of driving task responsibility from the human operator to the ADS. Consequently, the present work compares the practice effects between different user-initiated transitions of automation levels. According to Wickens et al. (2015), error-free trials are achieved easily, while it takes longer for task completion times and attentional demand to stabilize and reach a comparably constant level.

When examining human-technology interaction and the effects of learning in different use cases, researchers apply permutation to counteract order effects. In the area of automated driving, however, a full permutation of interaction scenarios is not possible. This is an issue especially for transitions to manual from any level of automated driving. These interactions can never be first contacts with a HMI as there must be a preceding activation. Without fully automated driving functions available, we must assume that even if the ODD for any given level of automation is already met at the beginning of a

trip, there must be an input by the human operator to initiate a transition from manual to the automated mode. Thus, whenever a human operator deactivates a driving automation system and completes a transition to manual, he/she must have activated the function beforehand. It is likely that learning for transitions to manual driving already occurred during the activation and it is questionable whether the power law of practice applies here. To prevent overfitting and following Okham’s principle of parsimony (e.g., Vandekerckhove, Matzke, & Wagenmakers, 2015), transitions to manual might be better explained with a linear regression approach. Hence, the present work aims at a comparison of the learning process between the different observational measures in driver-initiated transitions between manual driving, L2 and L3 automation.

6.1.1 Preference-Performance Relationship

Users do not always report behavior-consistent attitudes after using certain products or systems (Andre & Wickens, 1995; Nielsen & Levy, 1994). The so-called “*preference-performance dissociation*” poses a challenge for the evaluation of HMIs for automated driving. As the agreeableness between self-reported satisfaction and behavioral interaction measures is limited in many user studies (see chapter 3.3), the present study aims at providing a deeper insight into the development over time. The need of an evaluation of the preference-performance relationship is outlined in a recent literature review regarding driving behavior and road safety by Kaye et al. (2018). Chapter 3 described this phenomenon in relation to automated vehicle HMI research and development. It suggested a thorough examination of both the suitability of self-report and behavioral measures. The relationship might be influenced by the time course as (1) performance measures show learning curves with ongoing practice (Neves & Anderson, 1981; Newell & Rosenbloom, 1981; Wickens et al., 2015) and (2) learning is also observed for self-report measures such as acceptance and trust in the system (Beggiato et al., 2015). However, the attitude towards usability and design of an automated vehicle HMI should remain constant since this attitude relates to fixed features of the HMI. Even as users improve their competence and mental model of the system (Beggiato & Krems, 2013), the system’s properties and features remain constant. This leads to the assumption, that “*the die is cast*” after the first interaction trials. Subsequent self-reports therefore always consider the first interaction rather than going along with rising interaction success. Even if initial errors and long times on task have been eradicated, initial attitudes persist and hardly change (Ross, Lepper, & Hubbard, 1975). In this case, HMI intuitiveness and first contact success or failure would be critical for self-report measures.

6.1.2 Research Question and Hypotheses related to Chapter 7

From theoretical considerations outlined above, this work examined two research questions. The first research question is how behavioral measures for HMI evaluation change over time. Two hypotheses emerge:

- H1a: There is a learning curve for interaction behavior following the power law of learning.
- H1b: The learning curves differ between the observational measures and the different transitions between levels of automation.

The second research question is how self-report measures relate to behavioral measures with rising user practice. Three hypotheses are derived in for this research question:

- H2a: Self-reported usability remains stable over time despite rising practice.
- H2b: The preference-performance relationship changes over time.
- H2c: An exploratory approach shall investigate the strength of the preference-performance relationship at each given point of interaction.

According Results and discussions for the investigation of these two research questions are reported in chapter 7.

6.2 Background on Mental Models

Another objective of this study was to gain insight into the development of higher level cognitive processes when interacting with driving automation. This is crucial in the successful development of automated driving as the evaluation of interfaces frequently only applies initial contacts (e.g., Forster et al., 2016; Frison et al., 2017). However, if users have not yet fully understood the system, their self-reported evaluation of the system in question might be unreliable and therefore invalid (Beggiato et al., 2015). The present work contributes to the refinement of research methods by (1) examining the behavioral measures describing the learning process and (2) investigating the development of the mental model for L2 and L3 automated driving.

There remains a dearth of research on the development of higher level cognitive processes when interacting with L2 and L3 driving automation. A study by Beggiato et al. (2015) for L1 driving automation illustrated that learning, trust and acceptance can

be applied in accordance with the power law of learning (Newell & Rosenbloom, 1981) that is described in section 6.1. Beggiato et al. (2015) investigated higher level cognitive processes by means of the mental model; they found that it takes up to ten repeated encounters with the system for an accurate mental model to evolve.

Besides self-reported measures on learning and the mental model, eye-tracking metrics allow researchers an insight into higher level cognitive processes at the behavioral level (Just & Carpenter, 1984). The present experiment therefore examined gaze behavior in addition to the behavioral measures described above to discover whether it could be used to capture the evolution of self-reported learning and mental models in automated driving. Empirical support for this consideration comes from Sarter, Mumaw, and Wickens (2007) who revealed a connection between the mental model and gaze behavior in pilots interacting with flight automation. Similarly, Underwood (2007) observed a lack of both adequacy of mental models and efficiency of visual scanning with inexperienced users. Besides differences in scanning behavior with repeated exposure, there is evidence that gaze behavior is task-dependent (Hayhoe & Ballard, 2005). Due to differences in activation conditions between levels of automation (SAE, 2018), the present study aims to investigate gaze behavior in different transitions of control (Naujoks, Hergeth, et al., 2018). Bridging the gap between self-reported higher level cognitive processes (Beggiato et al., 2015) and behavioral measures (Sarter et al., 2007) the current research aims at a comprehensive examination in the area of L2 and L3 automated driving.

6.2.1 Research Questions and Hypotheses related to Chapter 8

Based on the aforementioned considerations and prior research, we derived two research questions: First, how do self-reported measures of higher level cognitive processes evolve over time while interacting with driving automation? To answer this question, we assume that self-reported learning of the interaction follows the power law of learning (Hypothesis 1a). Furthermore, repeated interaction should lead to more accurate mental models (Hypothesis 1b). Second, how do behavioral measures of higher level cognitive processes evolve after repeated interactions with driving automation? Concerning this question, we expect the number of gaze changes between different areas of interest (AOI) to follow the power law (Hypothesis 2a). The development of gaze behavior should additionally proceed in a task-dependent manner (Hypothesis 2b).

According Results and discussions for the investigation of these two research questions are reported in chapter 8.

6.3 Background on Feedback

This work contributes to method validation and development for automated driving by investigating the role of experience formation and use case specificity on diagnostic measures in HMI evaluation. Furthermore, the study examines the effect of feedback on operator success or failure when interacting with driving automation.

6.3.1 Validation and Development of Methodology

The evaluation of HMIs has a long tradition in the automotive context. In manual driving (SAE L0), the evaluation focused on the distraction potential of IVIS. Thus, the central goal here was and still is the assessment of visual workload associated with the IVIS (AAM, 2006; NHTSA, 2012). While standardized test protocols and best practice approaches have been established for driver distraction, the change of the driver's role from manual driver to supervisor in L2 and fallback performer in L3 automation makes the application of these methods impossible. One further step towards ADS method validation concerns the investigation of dependent measures for a usability assessment as described in chapter 3. In principle, both self-report data and behavioral observations can be used to assess the quality of an HMI for automated driving. First research efforts on the quality criteria of summative evaluations (Sweeney, Maguire, & Shackel, 1993) brought forth empirical evidence for applying questionnaires when it comes to assessing satisfaction (see chapter 5). Chapter 7 provides evidence that summative evaluations of automated vehicle HMIs remain on a constant level over time. It also showed that summative evaluations are closely tied to interaction performance in first system encounters. However, research on the suitability of diagnostic tools (Sweeney et al., 1993) for usability evaluation in this context is scarce. Diagnostic instruments seek to identify shortcomings and provide interface developers with recommendations for redesign. They capture the user's state at a given time of measurement in a specific use case. Additionally, they indicate whether specific system functions work as intended or whether these are overly demanding for users.

One such measure is perceived ease of use (PEOU, Davis, 1989), which can be operationalized as a single item measure. PEOU has indeed been frequently used in automated vehicle research (Forster et al., 2016; Frison et al., 2017; Guo, Sentouh, Popieul, & Haué, 2019; D. Large, Burnett, Crundall, Lawson, & Skrypchuk, 2016; Nordhoff et al., 2018; Payre et al., 2014; Rahman et al., 2017; Rödel et al., 2014; Wintersberger et al., 2018). The technology acceptance model (Davis, 1989) incorporates external factors

(e.g., training), which directly influence PEOU. Consequently, ease of use should increase with more system experience. A study by Karahanna and Straub (1999) on acceptance of e-mail systems, however, contradicts the assumption that training affects PEOU. Due to contradictory evidence, the present study investigates the effect of repeated exposure to an automated driving HMI on PEOU. Transitions from L0 to automated driving mode (e.g., L2, L3) are expected to show a strong effect over time. In contrast, user-initiated transitions to L0 should not show a comparable effect, since learning about the interaction has already occurred during the activation (see also the discussion in chapter 7.2.1). Therefore, one aim of the present work is to investigate diagnostic measures (i.e., PEOU) regarding the influence of (1) repeated interaction and (2) use case specificity.

6.3.2 Judgment Calibration

Moreover, the present study examined the role of feedback about interaction performance on diagnostic self-report measures. The coupling of ADAS and driving automation increases the complexity of these systems as outlined in chapter 1. As a consequence, users face high demands when operating these for the first time. Simultaneously, all users of ADS must be considered as novices when facing such an emerging technology (C. A. Hart, 2019). Support for this assumption comes from studies on system understanding and mental models of driving automation (Beggiato et al., 2015). The understanding of system and HMI functionality tends to be quite inaccurate before and after only one brief system exposure (see chapter 8). These two conditions – high system complexity and an inaccurate mental model as a novice user – pose a threat to the validity of diagnostic measures in automated driving development. If users of driving automation systems are not aware that their interaction did not follow the designer’s intent, they might consider it as easy to use. In contrast, from a designer’s perspective they had not shown error-free interaction. One example might be that users who try to activate an L3 ADS erroneously activate L2 driving automation. Without sufficient understanding of the HMI, they might still assume a successful interaction and report high ease of use. Users’ judgments thus might not align with what happened in reality and calibration of these judgments might be necessary.

Calibration research assumes that varying conditions under which judgments are made lead to different fits of these with the operator’s actual performance (Bol & Hacker, 2012). Such calibration effects are closely linked to self-regulatory mechanisms (Zimmerman, 2000). Self-reported judgments depend on feedback loops that provide necessary information about the status of one’s knowledge and strategies. The present work draws on

the question and the effects of anchoring mechanisms from which judgments are made. More than four decades ago, Tversky and Kahneman (1974) have investigated humans' judgments under uncertainty. They showed that people tend to estimate their performance in accordance to an initial value. However, driving automation users cannot have a realistic initial value of interaction performance besides their self-observation of time on task. Hence, their reported ease of use might be biased. Interacting with a system where only button presses while driving are necessary could seem comparably effortless. Even major problems from a designer's perspective might not be obvious to the users thus biasing their initial estimation towards a positive value. From that, we assume that novice users do not exactly know whether and/or how well their interaction proceeded in accordance with the HMI designer's intent. Calibrating effects for ease of use judgments should therefore be present when users are provided with information about their performance.

Calibrating users' judgments in the automation domain up to now has mainly been investigated for trust in automation (Helldin, Falkman, Riveiro, & Davidsson, 2013; Seong & Bisantz, 2008). By investigating calibration for ease of use judgments, this work expands existing evidence of calibration in automated driving. It is important to mention that there is a close link between trust in automation and ease of use as suggested by J. D. Lee and See (2004). This also points towards investigations of calibrating ease of use judgments. With the present study, we aim to find out about different manifestations of PEOU judgments under different conditions regarding feedback loops (i.e., additional feedback vs. no feedback). If presented with feedback, users should be able to recognize whether and to what degree a trial was error-free or not and consequently adapt their PEOU ratings.

6.3.3 Objective and Hypotheses related to Chapter 9

From prior research and the considerations outlined above, the present work aims at an examination of ease of use judgments in automated driving. It shall be noted here that the present work focuses on the circumstances that might influence ease of use judgment. It shall provide researchers and practitioners with methodological insights into how such diagnostic measurements might manifest depending on study design. This work does explicitly not try to establish a method that researchers have to apply in future research settings. On the contrary, its goal is to provide a set of methodological possibilities (e.g., repetition, use cases, feedback) for research settings that lead to different outcomes of this dependent measure. Depending on each specific study purpose, researchers can

draw from the present work for study design when it comes to ease of use judgments. The following hypotheses are derived:

- H1: Perceived ease of use increases over time.
- H2: Perceived ease of use shows use case specific patterns.
- H3: There is a calibrating effect of feedback on perceived ease of use. By providing feedback, perceived ease of use decreases.

According results and discussions for the investigation of these two research questions are reported in chapter 9.

6.4 General Method

6.4.1 Sample

A total of $N=59$ participants took part in the driving simulation experiment. All participants were BMW Group employees, held a German driver's license and had normal or corrected to normal vision. $N=2$ drop-outs occurred due to simulator sickness. The analyzed sample sizes for the three subsequent chapters differ due to different data sources.

Sample Characteristics for Chapters 7 and 9

$N=2$ data sets had to be excluded due to data collection issues. This left $N=55$ (14 female, 41 male) participants for data analysis. Mean age of the final sample was 31.64 years ($SD=9.97$, $MAX=62$, $MIN=20$).

Sample Characteristics for Chapter 8

Five incomplete data sets for eye-tracking were excluded. This left $N=52$ (14 female, 38 male) participants for data analysis. The mean age of the final sample was 31.88 years ($SD=10.09$, $MAX=62$, $MIN=20$).

6.4.2 Driving Simulation

The study was conducted in a moving-base driving simulator (see figure 6.1, top). The integrated vehicle's console contained all necessary instrumentation and was identical

to a BMW 5 series with automatic transmission (see figure 6.1, bottom). Seven 1080p projectors provided a 240° horizontal $\times$ 45° vertical frontal field of view. One LCD screen positioned behind the back inside the vehicle mockup seats and two outside projections with the same specifications served as rear view. The motion system consisted of a hydraulic Hexapod with six degrees of freedom, capable of up to 7 m/s^2 transitional acceleration and 4.9 m/s^2 continuous acceleration. Driving simulation was rendered with a frequency of 50 Hz. To provide the opportunity of engaging in a non-driving related task during automated mode, there was a 12.3" tablet mounted on the center stack console displaying the Surrogate Reference Task (SuRT; ISO, 2012). NDRT data input was logged with a frequency of 25 Hz.

6.4.3 Driving Automation System

As soon as the driver activated the respective function, it carried out longitudinal and lateral vehicle guidance. The guidance of the L2 and L3 automation was identical. The L2 driving automation displayed a hands-on request (HOR) after 15 seconds of hands-free driving. The L3 ADS was capable of executing independent lane change maneuvers (e.g., slower vehicles ahead, pulling back to right lane). The L2 driving automation set speed was the current velocity and could be adjusted without restrictions. The L3 ADS set speed was 130 km/h and could be adjusted to slower speeds. If adjusted to a higher speed than 130 km/h, it deactivated the L3 ADS and activated the L2 driving automation. Vehicle following distance (time headway) to a lead vehicle was 2 seconds.

6.4.4 Study Design and Procedure

The study employed a 2×5 mixed within-between subjects design. The within subject factor "*time of measurement*" had five levels from the first to the fifth block of use cases. The between-subjects factor "*feedback*" had two levels where participants either received the experimenter's rating of interaction quality after each use case (condition "*additional feedback*", $n=27$) or not (condition "*no feedback*", $n=28$). Participants were randomly assigned to the between-subjects factor. The between-subjects factor did not reveal statistically significant differences for the variables reported in chapters 7 and 8. Therefore, the these two chapters report results of the within-subject factor "*time of measurement*". Chapter 9 reports an investigation of the effect of feedback on diagnostic measures controlling for the effect of actual performance.

Upon arrival, participants were welcomed and gave informed consent. After a brief

(a) Outside Simulator

(b) Inside Mockup

Figure 6.1. Dynamic driving simulator from the outside (top) and inside mockup used in the current study (bottom).

explanation of the study purpose, the experimenter led them to the vehicle mockup. To accustom themselves with the simulator setup, participants had to complete at least two correct trials with the SuRT and then completed a five-minute manual familiarization drive. Prior to the experimental drive, the experimenter outlined the procedure and explained that participants would encounter two driving automation systems that are the L3 ADS and the L2 automation. They also received information that they do not have to constantly monitor correct functioning of the L3 ADS. They did not receive prior information on how to activate or deactivate the driving automation nor were there any practiced control transitions before the experiment. No specific additional information about the six items of the mental model questionnaire was given. Prior to each block, participants were instructed that they could decide for themselves whether to engage in a non-driving related task (NDRT) when the automation was active. The experimenter explained that use case specific instructions would be given through recorded samples. To familiarize themselves with the recorded samples, the familiarization drive included an instruction to change lanes. The experimenter explained that participants could freely choose to engage in the NDRT when automation was active. The subsequent experimental drive included five blocks of six interactions between the driver and the driving automation systems each. After each interaction, there was a brief inquiry during the drive which is reported in chapter 9. In order to avoid anticipation of use case instructions by the participants, the experimenter waited a minimum of 30 seconds after the use case specific inquiry to trigger the next use case. There were no external factors (e.g., slow car ahead, intersection) that could have indicated an upcoming transition. After each block, the driver was told to pull over to the right shoulder, stop there and complete the block inquiry. Participants completed the drive on a three-lane highway with low to medium traffic density. The experimental drive lasted approximately 60 minutes. Figure 6.2 schematically depicts the experimental procedure.

Figure 6.2. Schematic outline of experimental procedure

6.4.5 Human-Machine Interface

The visual HMI was shown on the instrument cluster. It showed the vehicle and its surroundings in both L2 and L3 automated driving. The HMI for automated driving resembled a combination of adaptive cruise control and additional steering assistance (Naujoks, Purucker, Neukum, Wolter, & Steiger, 2015). The present HMI constitutes a representative solution for an automated system due to the conceptual similarity to solutions in prior research (Forster et al., 2016; Manca et al., 2015) and the expertise of the manufacturer (see also chapter 1.4.2). The L2 vehicle surroundings and L3 vehicle surroundings differed in (1) their informational content (i.e., higher level of detail in L3: visibility of adjacent lanes and vehicles) and (2) their perspective (i.e., larger field of view in L3). An activated L2 automation was colored in green while an activated L3 ADS was colored in blue. The system functions could be activated with a button on the left side of the steering wheel for both levels of automation each. The input device included three more buttons, which did not produce an effect. A rocker switch served for the adjustment of cruising speed in both automated driving modes. Participants could reach the buttons easily with the left thumb. Activation of the L2 driving automation was possible without any restrictions. For the L3 ADS, however, there were several activation barriers (SAE, 2018). These were (1) availability of the ADS, (2) velocity below 130 km/h and (3) lane keeping within a certain lateral margin. The L3 ADS could be deactivated through braking, accelerating, steering wheel input or pressing the L3 ADS button with additional hands on the steering wheel. The L2 driving automation could be deactivated by braking or pushing the L2 automation button. In case of accelerating or steering wheel input, the system would initiate a temporary downward-transition into L1 driving automation of either longitudinal or lateral vehicle guidance until the driver would let go of the respective input.

6.4.6 Use Cases

The present experiment included driver initiated transitions between manual, L2 and L3 automated driving (Naujoks, Hergeth, et al., 2018). Considering both upward and downward transitions, one experimental block consisted of six use cases. These use cases with transition type, automation level at use case initiation, target automation level and use case numbering are shown in table 6.1. To counteract sequential effects, participants were randomly assigned to one of six possible block sequences that were created using a Latin square. Each block consisted of six trials. In total, each participant completed 30

Table 6.1

Overview of use cases for one experimental block.

Transition type	Scenario	Automation level at UC initiation	Automation target level	Use case number
Upward transition	Activation L3	L0	L3	1
	Activation L3	L2	L3	4
	Activation L2	L0	L2	3
Downward transition	Deactivation L3	L3	L0	2
	Deactivation L3	L3	L2	5
	Deactivation L2	L2	L0	6

use cases. Motivations for such transitions by users are (1) activating higher automation levels to get relieved of parts of the driving or supervising task (UCs 1, 4, 3), (2) driving themselves for the pleasure of driving (UCs 2, 6) and (3) choosing a higher speed or deactivate certain functionalities (Naujoks, Hergeth, et al., 2018).

To standardize instructions, we recorded samples for each use case that were triggered by the experimenter. Use cases with L3 ADS activation (UC1 and UC4) additionally included a 10-second delay between the experimenter’s instruction and the availability of the ADS. Within this 10-second window, the L3 ADS could not be activated. Therefore, participants were instructed to “*activate the L3 ADS as soon as it is available*”.

6.4.7 Dependent Variables

Self-Report Measures

Participants completed the System Usability Scale (SUS) as a self-report measure of usability (Brooke, 1996). The SUS is a 10-item questionnaire with a two-factorial underlying structure of learnability and usability (Lewis, 2002). The SUS has been applied in prior research on automated driving (Forster et al., 2016; Hergeth, 2016). The applicability of the SUS for automated vehicle HMI evaluation was shown in chapter 5. Participants completed the SUS after each experimental block.

The dependent variable for diagnostic evaluation was PEOU. Having completed the respective UC and having received feedback on the interaction (or not), participants reported difficulty on a 7-point Likert scale from 1 (“*very easy*”) via 4 (“*neither nor*”) to 7 (“*very difficult*”). The item read “*How easy or difficult was the last use case?*”.

Regarding this measure, time on task was used as a manipulation check (see chapter 9) since it represents an indicator of the “*big three*” interaction measures (Wickens et al., 2015). Wickens et al. (2015) describe the role of feedback as a form of training. Thus, ease of use might rather be facilitated by differences in interaction performance than by feedback itself. To control for potential influences of differences in interaction behavior that impact PEOU, we additionally investigated the main and interaction effects of feedback on time on task.

Observational Measures

Prior to UC specific performance analysis, the NDRT behavior in form of inputs on the SuRT was assessed. Thus we ensure appropriate interpretation of performance results which might differ due to higher engagement in the SuRT during active L3 automation. Therefore, a time window of 20 seconds before the onset of the UC specific instruction was chosen where the number of inputs on the surface was counted. As the variable of interest reflects disengagement from the driving/supervising task in general rather than additional performance parameters in the NDRT, we report this variable independent from correct or incorrect input.

Accuracy is reflected in the error rate. In the present study, we counted the number of button presses on the input device as an operationalization of the error rate. With five buttons labeled differently and a rocker switch on the operator component, there was a considerable number of possible erroneous input actions. Furthermore, intended button presses on the correct element that did not lead to function activation (e.g., L3 ADS not available yet) were also counted as errors. Consequently, the minimum error rate corresponds to 1 for all use cases besides the L3 ADS deactivation (UC2), which is also possible without input on the button (see chapter 6.4.5).

Speed is reflected in time on task or reaction time. Reaction time was assessed as the time from the onset of the experimenter instruction until the use case was solved. A use case was counted as successfully solved if the target system state (i.e., L3, L2, manual) was active for at least five seconds without unintended deactivations or interruptions.

The present approach employed a five-point rating scale for user interaction success. Table 6.2 outlines the experimenter rating applied in the present study. The experimenter rated participants’ behavior right after each use case during the experiment. Prior to the experimental procedure, the five categories had been adapted specifically to each use case. The generic categories led to specific descriptions of behavior for each category and use case. Thus, the present approach made sure to counteract potential bias in

experimenter ratings as the sequential order was known to the rater. For simplification purposes, table 6.2 only provides the generic descriptions.

Table 6.2

<i>Experimenter rating with label and description.</i>		
Category	Value	Description
No Problem	1	<ul style="list-style-type: none"> • No problem
Hesitation	2	<ul style="list-style-type: none"> • Independent solution without errors • But: Hesitation, very conscious operating and full concentration
Minor errors	3	<ul style="list-style-type: none"> • Independent solution without or with minor errors which were corrected confidently • But: longer pauses for reflection • Evaluation of potential operating steps
Massive errors	4	<ul style="list-style-type: none"> • One or multiple errors • Clearly impaired operation flow • Excessive correction of errors • No help of experimenter necessary
Help of experimenter	5	<ul style="list-style-type: none"> • Multiple errors • Massive errors require to restart task • Help of experimenter necessary

Mental Model and Gaze Behavior

The mental model questionnaire and items for self-reported learning developed by Beggiato et al. (2015) were adapted for L2 and L3 driving automation. Participants completed the questionnaire after receiving instructions (and prior to the first drive), and then again after each experimental block. The mental model questionnaire included 11 items on a 7-point Likert scale ranging from 1 (“*strongly disagree*”) to 7 (“*strongly agree*”) for both the L2 and L3 automation. Six items covered participants’ understanding of the system, while five items served as distractors. Thus, for each item of interest, the opposite end of the scale was correct for the two levels of automation. If “*strongly disagree*” was the correct answer for L2, “*strongly agree*” was correct for L3

and vice versa. Items were specifically derived to detect differences between L2 and L3. Self-reported learning for the combined automated driving HMI (i.e., L2 and L3) was measured with four items on a visual analogue scale ranging from 0-100.

Gaze data were collected with Dikablis 2.5. Prior to analysis, data quality was ensured by manually recoding all relevant sections. AOIs (i.e., driving scene, instrument cluster, operating element, NDRT) were defined in D-Lab 2.5 (see figure 6.3). Gaze behavior was analyzed from the onset of the standardized experimenter instructions until a UC was solved; a UC was solved successfully if a desired system state was constant for at least five seconds without unintended deactivations or interruptions. For each UC, the number of gaze switches between AOIs was calculated. Two or more glances at the same AOI that were separated by less than 150ms were combined. Glances shorter than 150ms on an AOI were eliminated from the analysis (Irwin, 1992). Besides the number of switches between AOIs, Jacob and Karn (2003) describe the monitoring frequency as a usability gaze measure. In comparison to the total number of gaze switches between AOIs, the monitoring frequency scales these to the total task duration. The monitoring frequency represents the relative importance of a certain AOI. As time on task becomes shorter with repeated interactions (see chapter 7), the monitoring frequency makes for a more valid comparison of subsequent trials:

$$\text{Monitoring frequency} = \frac{n_{\text{monitoring glances}}}{t_{\text{non-driving-related task}}}$$

Figure 6.3. AOIs (i.e., 1=operating element, 2=instrument cluster, 3=driving scene, 4=NDRT) from vehicle interior.

6.4.8 Statistical Procedure and Data Analysis

Driving simulation data was pre-processed and visualized using Matlab Version 2015b. Statistical test were calculated using IBM SPSS Statistics Version 23. Given that the error rate and NDRT input frequency are count data, we computed the parameter lambda (λ) to describe the Poisson distributed data. Here, λ equals both the arithmetic mean and SD of the distribution (Plan, 2014). Means and standard deviations (SD) were calculated for reaction times, experimenter ratings and mean number of glance switches. The power law of learning was fitted on the respective behavioral data and subjective learning by means of the MatLab fit-function. To prevent overfitting and following Okham's principle of parsimony (Vandekerckhove et al., 2015), transitions to manual were fitted with a linear regression model. For multivariate analysis of the preference-performance relationship, the SUS score served as the preference measure. To compare the behavioral measure with the SUS score after each block, use case specific behavioral measures were averaged into a composite resulting in five mean experimenter ratings, mean reaction times and mean number of errors. Thus, the preference-performance relationship was examined on an aggregated level for the behavioral measures. To better visualize and compare the data, all performance measures and the SUS were z-standardized. In addition, z-scored performance measures were reversed so that higher values reflect better performance. Besides the count data nature of error rate, the ANOVA approach was followed for inferential analysis since the discrete number of button presses represent a quantitative attribute in increasing number (Tabachnick & Fidell, 2007). The evaluation of diagnostic measures followed a repeated measures ANOVA approach. The evolution of mental models and monitoring frequency was analyzed descriptively. A significance level of $\alpha=.05$ was applied unless stated otherwise. To control for alpha inflation due to multiple testing, correction after Bonferroni-Holm was applied if necessary.

7 Learning to Use Automation: Behavioral Changes in Interaction with Automated Driving Systems

6

Abstract: To evaluate human-machine interfaces for automated driving systems, a robust methodology is indispensable. The present driving simulator study investigated the effect of practice on behavioral measures (i.e., experimenter rating, reaction times, error rate) and the development of the preference-performance relationship for automated driving human-machine interfaces. In a within-subject design, $N=55$ participants completed several transitions between manual, Level 2 and Level 3 automated driving. Behavioral measures followed the power law of practice with exception of transitions to manual and error rates for Level 3 automation. After the first block of interactions, preference no longer predicted performance. The preference-performance relationship remained stable after the second block of interactions, which is mainly due to a stabilization in behavioral parameters. To get a deeper insight into the evaluation of human-machine interfaces for automated driving, the results suggest the application of multi-method approaches. Furthermore, we found evidence for the influence of initial interactions for self-reported usability.

This chapter reports the results and discussion of these in relation to the hypotheses stated in chapter 6.1.2.

⁶This chapter is based on a previous publication: Forster, Y., Hergeth, S., Naujoks F., Beggiato, M., Krems, J. F. & Keinath, A. (2019). Learning to Use Automation: Behavioral Changes in Interaction with Automated Driving Systems. *Transportation Research Part F: Traffic Psychology and Behaviour*, 62, 599–614. doi.org/10.1016/j.trf.2019.02.013

7.1 Results

7.1.1 Screening for NDRT Engagement Prior to Use Cases

Table 7.1 shows mean and SD of input frequency (λ) on the surface within the 20 seconds before onset of the UC specific instructions. The data revealed that overall there is a small number of NDRT engagement with the highest mean not exceeding two inputs within the 20 seconds. Over time, there is a trend towards higher engagement with rising system experience in UCs from L2 (UC4, UC6) and L3 (UC2, UC5) automation. UCs whose onset was preceded by manual driving (UC1, UC3) showed closely to no NDRT engagement at all independent from the block. The highest NDRT engagement was observed for UCs with preceding L3 automation where participants were either prompted to complete a transition to manual (UC2) or L2 automation (UC5). This engagement was more than twice as high compared to engagement in UCs with preceding L2 automation (UC4, UC6).

Table 7.1

Mean and SD (λ) of NDRT inputs by UC and experimental block.

UC	Block 1	Block 2	Block 3	Block 4	Block 5
UC1	0.000	0.064	0.043	0.043	0.043
UC2	0.447	0.957	1.125	1.532	1.596
UC3	0.000	0.000	0.021	0.043	0.043
UC4	0.043	0.255	0.319	0.596	0.511
UC5	0.340	0.830	1.298	1.596	1.468
UC6	0.000	0.298	0.340	0.617	0.596

7.1.2 Behavioral Measures: Effect of Learning

Figure 7.1 shows means and standard errors of experimenter ratings and reaction times as well as lambda for error rates in all six interactions by the five experimental blocks. Additionally, the power law of practice was fitted to the data. Descriptive statistics (i.e., M , SD) are shown in table 7.2.

Behavioral measures in use cases that involved a transition to L2 or L3 followed a power law function. Transitions to manual followed a constant flat line without learning effects. Fitted model functions with according goodness of fit indices R^2 and root mean square error (RMSE) are shown in table 7.3. The determination coefficient R^2 is

Figure 7.1. Means and standard errors for experimenter rating (top), reaction times (middle) and button presses (bottom) from block 1 to block 5. The power law of practice was fitted for UC1, UC3, UC4 and UC5 whereas a linear function was fitted for UC2 and UC6.

Table 7.2

Descriptive statistics (i.e., M , SD) for experimenter rating and reaction time and lambda for error rate by time of measurement (columns) and use-case (rows).

Variable	UC	Block 1	Block 2	Block 3	Block 4	Block 5
Exp.- Rating (M, SD)	UC1	2.87(1.19)	2.56(0.94)	2.16(1.08)	2.40(1.06)	2.11(1.08)
	UC2	1.51(0.92)	1.35(0.64)	1.38(0.71)	1.33(0.72)	1.22(0.57)
	UC3	2.95(1.42)	1.49(0.63)	1.40(0.60)	1.31(0.50)	1.22(0.42)
	UC4	2.85(1.16)	2.35(1.09)	2.22(1.12)	2.38(1.08)	2.07(1.05)
	UC5	2.62(1.38)	1.60(0.83)	1.78(0.81)	1.56(0.69)	1.45(0.63)
	UC6	1.20(0.62)	1.09(0.35)	1.11(0.42)	1.20(0.56)	1.24(0.64)
RT (M, SD)	UC1	28.26(18.40)	19.61(7.35)	16.95(9.17)	18.26(7.03)	17.39(7.05)
	UC2	6.78(2.44)	6.34(1.55)	6.85(2.60)	6.36(2.16)	5.90(2.10)
	UC3	28.93(25.26)	8.22(4.32)	7.69(3.40)	7.45(4.19)	7.53(5.08)
	UC4	23.17(15.31)	17.59(9.36)	16.24(7.38)	16.80(8.80)	16.46(9.14)
	UC5	22.20(22.34)	12.04(9.36)	9.44(7.38)	8.40(2.83)	8.32(2.61)
	UC6	6.44(4.99)	5.67(1.52)	5.53(1.80)	5.84(1.90)	6.24(5.68)
Button presses (λ)	UC1	2.83	2.69	2.11	2.95	2.29
	UC2	0.76	0.78	0.87	0.65	0.69
	UC3	3.64	1.07	1.09	1.05	1.02
	UC4	2.84	2.53	2.44	2.76	2.40
	UC5	2.20	1.16	1.13	1.09	1.02
	UC6	1.31	1.02	0.98	1.18	1.07

a normed measure for the deviation of observed values from predicted values in relation to the mean model. R^2 ranges from zero indicating poor model fit to one indicating perfect model fit. RMSE is an absolute measure for the deviation of observed values from predicted values. In this case, lower values indicate better fit.

Experimenter ratings of transitions to L3 stabilized at a higher level compared to deactivations and transitions to L2. Except for the L2 ADS deactivation ($R^2=0.2049$), all models fitted the observed data well explaining more than 80% of the variance (see table 7.3). Reaction times for transitions to L2 showed strong learning effects with the upward transition from L0 reaching the constant level considerably earlier than the downward transition from L3. Both transitions to L2 and transitions to manual converged between 6 and 7 seconds. This corresponds to the duration of the experimenter instruction samples. For both transitions to L2 and L3, amplitude of learning (reflected in the b-parameter) was considerably larger for transitions from manual compared to transitions from the respective other level of driving automation. The amplitude of learning from manual to L2 driving automation equals 21.42 while the amplitude from L3 ADS to L2 driving automation equals 15.22. The amplitude of learning from manual to L3 ADS equals 11.11 while the amplitude from L2 driving automation to L3 ADS equals 6.84. The power law model fits explain the observed mean reaction time data very well with more than 98% of explained variance. The linear model fit for deactivation of the L3 function showed an acceptable fit while the fit for the L2 deactivation was poor.

The fitted power law for transitions to L3 regarding button presses showed a poor model fit explaining only 18.8% (transition from manual) or 8.0% (transition from L2) of explained variance. The error rate for transitions to L2 showed a good fit of the power law of learning. The linear model fits for the transitions to manual showed medium (L3 deactivation) to poor (L2 deactivation) model fits. The present results of the power law fit showed that if the power law applies to the use case and the behavioral measure, the model closely approaches the asymptotic value at the second block. A constant level is reached after at least three repetition trials.

7.1.3 Preference-Performance Relationship

Two participants missed one single SUS item each. Missing values were estimated using an Expectation-Maximization Algorithm (Howell, 2007; Lüdtke et al., 2007). Evaluation of the SUS showed high ratings after the first block, which slightly increased for consecutive blocks (see table 7.4). Reliability for the SUS was on a high level in all experimental blocks. Figure 7.2 shows scatterplots for the preference-performance rela-

Table 7.3

Model fit equations and goodness of fit indices (i.e., R^2 , $RMSE$) for the three behavioral measures.

Variable	UC	Power Law/Model	R^2	$RMSE$
Exp.- Rating (M, SD)	UC1	$P = 1.622 + 1.257 * t^{-0.521}$	.836	0.1784
	UC2	$P = 1.536 - 0.06 * t$	.8176	0.0517
	UC3	$P = 1.247 + 1.697 * t^{-2.64}$	.9964	0.0613
	UC4	$P = 2.144 + 0.7074 * t^{-1.693}$	.8720	0.1490
	UC5	$P = 1.571 + 1.046 * t^{-3.590}$	.9378	0.1646
	UC6	$P = 1.113 + 0.018 * t$	.2049	0.0654
RT (M, SD)	UC1	$P = 17.17 + 11.11 * t^{-2.408}$	.9815	0.8997
	UC2	$P = 6.973 - 0.176 * t$	.5172	0.3105
	UC3	$P = 7.51 + 21.42 * t^{-4.89}$	1.000	0.0825
	UC4	$P = 16.33 + 6.843 * t^{-2.643}$	.9901	0.4090
	UC5	$P = 6.985 + 15.22 * t^{-1.62}$	.9992	0.2324
	UC6	$P = 6.014 - 0.023 * t$	.0092	0.4413
Button presses (λ)	UC1	$P = 2.436 + 0.407 * t^{-1.588}$	.1879	0.4581
	UC2	$P = 0.8345 - 0.0272 * t$	.2580	0.0844
	UC3	$P = 1.053 + 2.584 * t^{-6.775}$	.9995	0.0358
	UC4	$P = 2.532 + 0.305 * t^{-31.14}$	.0802	0.2003
	UC5	$P = 1.056 + 1.143 * t^{-3.215}$	.9958	0.0453
	UC6	$P = 1.205 - 0.031 * t$	.1539	0.1413

Table 7.4

Descriptive results (i.e., M , SD , Cronbach's α) for System Usability Scale

	Block 1	Block 2	Block 3	Block 4	Block 5
M	75.32	76.50	79.55	79.49	80.09
SD	15.89	16.87	15.83	16.65	18.29
Cronbach's α	.849	.875	.872	.883	.886

Table 7.5

Inferential statistics (i.e., F -, $df1$, $df2$, p -, η_p^2 -values) for the multivariate ANOVA and the univariate ANOVAs.

Statistical Method	Variable	F	$df1$	$df2$	p	η_p^2
Multivariate ANOVA (M, SD)	Exp.-Rating	15.897	8	47	<.001	.730
	Reaction Times	15.398	8	47	<.001	.724
	Button Presses	6.663	8	47	<.001	.531
Univariate ANOVA	Exp.-Rating	45.379	4	216	<.001	.457
	Reaction Times	75.283	2.213	119.480	<.001	.579
	Button Presses	18.366	2.600	140.389	<.001	.254
	SUS	5.757	2.929	158.164	<.001	.096

tionship between the SUS and the experimenter rating (left), reaction times (middle) and error rate (right). The plots depict z-standardized values for reverse scored performance measures and z-standardized SUS scores. Thus, higher values indicate better performance.

The centroid of the performance-preference relationship at each block is highlighted as a large dot. The lines represent linear regression fits (see also table 7.6). A single factor within-subject multivariate analysis of variance (MANOVA) was performed on each preference-performance relationship (i.e., experimenter rating – SUS, reaction times – SUS, button presses – SUS). The independent variable consisted of the time of measurement with five levels (block 1 to 5). Mauchly's test for sphericity revealed significant effects for reaction times ($\chi^2(9)=79.143$, $p<.001$), error rates ($\chi^2(9)=54.763$, $p<.001$) and the SUS ($\chi^2(9)=54.615$, $p<.001$). Therefore, degrees of freedom were adjusted after Greenhouse-Geiser. Multivariate tests showed significant effects of the time of measurement for all three observational measures (see table 7.5).

Figure 7.2. Scatterplots of preference-performance relationships for experimenter ratings, reaction times and button presses (from left to right) by the five experimental blocks.

Thus, the mean preference-performance relationship changes over time. To determine the impact of each dependent variable, univariate ANOVAs with alpha correction after Bonferroni-Holm were calculated for the behavioral measures and the SUS. Results revealed significant effects for all four tests (see table 7.5). However, strong effect sizes were only observed for the behavioral measures whereas the effect size for the SUS was small accounting for only 9.6% of explained variance in the data. Consequently, the multivariate effect of time of measurement is more strongly driven by the change in behavioral observations than the change in self-report data. This result and preceding power law results suggest that the preference-performance relationship reaches a constant level at the second or third trial, respectively.

To examine the preference-performance relationship at each time of measurement more closely, linear regressions were calculated for the z-standardized values of the SUS with each behavioral measure. The resulting goodness of fit, significance and equation results are shown in table 7.6.

The results of regression analysis show that there is a statistically significant relationship between preference and performance at the first block. Reaction times and error rates did not show statistically significant equations at subsequent blocks. The experimenter rating revealed two significant predictions after block 3 and 5 as well as two non-significant predictions after blocks 2 and 4. Non-significant predictions are reflected in flat lines in the scatterplots above (see figure 7.2). These results indicate that while behavioral measures are developing, the agreeableness between the two measures

Table 7.6

Linear regression coefficients (i.e., R^2 , p) and equations with criterion (C) and respective predictor (p) for experimenter rating, reaction times and button presses at five times of measurement.

Variable	Block	Linear Model Equation	R^2	p
Exp.- Rating	Block 1	$C = 0.171 + 0.333 * p$	.126	.004
	Block 2	$C = -0.114 + 0.083 * p$	.004	.329
	Block 3	$C = -0.005 + 0.346 * p$	.095	.011
	Block 4	$C = 0.051 + 0.216 * p$	.032	.095
	Block 5	$C = -0.114 + 0.460 * p$	.115	.005
RT	Block 1	$C = 0.131 + 0.221 * p$	.070	.026
	Block 2	$C = -0.136 + 0.183 * p$	.012	.209
	Block 3	$C = 0.049 + 0.074 * p$	.002	.362
	Block 4	$C = 0.011 + 0.215 * p$	.010	.232
	Block 5	$C = 0.036 + 0.166 * p$	.007	.276
Button presses	Block 1	$C = 0.047 + 0.259 * p$	.135	.003
	Block 2	$C = -0.125 + 0.131 * p$	.007	.274
	Block 3	$C = 0.020 + 0.189 * p$	.002	.150
	Block 4	$C = 0.093 + 0.003 * p$	.000	.491
	Block 5	$C = -0.012 + 0.354 * p$	.043	.065

vanishes. Participants that showed poor performance evaluated the HMI less favorable. With rising system experience, the mean performance increased until it reached an asymptotic level (see figure 7.1). Descriptively, not only mean performance increased but also variance in performance measures (see table 7.2). On the other hand, variation in the self-report measure remained at a constant level across the five blocks. Consequently, with increasing practice preference and performance become independent from each other.

7.2 Discussion

The present driving simulator study investigated the effect of practice on behavioral measures and the development of the performance preference relationship for automated vehicle HMIs. In a within subject design, $N=55$ participants completed five blocks of six transitions between manual, L2 and L3 automated driving. Results showed that experimenter ratings and reaction times in transitions to an automated driving mode followed the power law of learning. Due to sequential effects, learning was not observed for transitions to manual driving. Error rates showed a learning curve for L2 driving automation, but not for transitions to L3. Further examination of the preference-performance relationship showed a stabilization after the second block of interactions, which is driven mainly by a change in behavioral parameters. The predictive value of preference for performance was only observed for the first block of interactions. The results suggest that a multi-method approach for the evaluation of ADS is indispensable since the trend curves differ both between use cases and dependent measures.

7.2.1 Effect of Practice on Behavioral Measures

Before interpreting results of behavioral adaptation in interaction with driving automation systems, NDRT engagement results will be briefly discussed to put results into perspective. Engagement showed that there was close to no NDRT engagement before transitions from manual to both L2 and L3 automation. Therefore, the performance parameters for UC1 and UC3 can be interpreted independently from disengagement from the driving task. Similarly, the transitions from L2 to manual and L3 automation, respectively showed a very low frequency of engagement in the SuRT. The transitions from L3 to manual and L2 automation, respectively, showed up to 1.5 inputs on average. However, considering the window of 20 seconds, these numbers are still small. Furthermore,

the results showed that in block 1 there is almost no engagement in the SuRT across all UCs (see table 7.1), which rises with more system experience. At the same time, results of the performance parameters (i.e., RT, error frequency, experimenter ratings) showed learning curves with considerable increases especially from the first to the second time of measurement and subsequent stabilization. Here, poor operator performance is more strongly tied to limited NDRT engagement. Thus, potentially detrimental effects of high NDRT engagement on interaction performance can be ruled out. Data of UC2 especially support this reasoning since the observed NDRT activities are high compared to the other UCs in the present study and increase over time. Simultaneously, operator performance was on a stable and good level from the first to the last block.

The present study found evidence that behavioral measures for human-automation interaction follow the power law of practice. When switching between different levels of automation such as L2 and L3 automated driving in the present study, measures for tactical (i.e., experimenter rating) as well as operational (i.e., reaction times, error rate) performance showed a strong increase in performance at the beginning and a stabilization after about three trials. The fitting results of the power law of practice support hypothesis 1a. The results show, that first contact interactions with driving automation pose challenges to human operators. In the present experiment, this effect can be explained through a combination of increased understanding of the experimenter instructions (i.e., name of respective function and level of driving automation) and increased understanding in relation to the HMI itself over time. Subsequent improvements (i.e., from the second block on) in operator performance as observed in experimenter ratings (e.g., UC1), reaction times (e.g., UC5) and errors (e.g., UC1) are thus due to HMI usability alone.

Specific circumstances of the levels in terms of number of requirements for the activation play an important role. Thus, the power law curves for the L2 and L3 automation differ in the amplitude of learning, which was larger for L2 than for L3 automation (see table 7.3 and figure 7.1). In addition, the asymptotic value differed for transitions to L2 compared to transitions to L3. In the present study, this difference can be explained through the 10-second delay in L3 ADS availability after the experimenter instruction and the required speed threshold of 130 km/h.

Furthermore, a linear regression fit showed good results for modelling behavior in transitions to manual. This result corroborates prior considerations about the nature of sequential effects in ADS evaluation and therefore support hypothesis 1b. Following design guidelines for HMIs (e.g., Naujoks, Wiedemann, et al., 2019), deactivation of a

function should be possible the same way as activation (e.g., pressing the same button again). The linear regression model fits for driver-initiated transitions to manual showed that prior considerations about parsimony held true. As the fits for these UCs in figure 7.1 show close to horizontal lines, there is no learning between the first and subsequent blocks apparent. Interaction performance for the behavioral interaction measures were already on an asymptotic level. Therefore, learning on how to deactivate driving automation systems happens at the activation of these functions and are transferred by users to transitions to manual. The process behind this pattern of data might lie in the learning curves for transitions to the respective level of automation that had been executed before. While users have to learn about ensuring the conditions and correct user input for a transition from manual to L3 automated driving, transitions backward only require the identical input. Therefore, the learning in transitions to L2 and L3 is transferred to the transitions to manual. Furthermore, the particular HMI state when driving manually can be anticipated by the users as they had already been in manual mode before any transition to automation. Consequently, the probability of switching back and forth between levels of automation due to uncertainty of current system states is low. In automated mode, however, this probability is higher since users might not be as certain about the correct system state. Another explanation is that participants unwillingly deactivated the function or switched to the other level of automation by quickly pressing multiple buttons when in automated mode compared to manual mode. Data preparation considered these effects by counting a UC as successfully solved as soon as the respective target mode had been activated for at least five seconds (see chapter 6.4.7).

Taking a closer look at sequential effects, the results of transitions to L2 or L3 automation, respectively, revealed that transitions from manual led to worse performance than the transition from the respective other automated mode. Table 7.3 and figure 7.1 show that the learning amplitude for transitions to L2 and L3 from the respective other automated mode is smaller than the transition from manual. This result can also be explained with sequential effects. Whenever there is a transition from one automated mode into another (e.g., transition from L2 to L3), there has been a preceding transition to an automated mode (e.g., L2). Thus, the user makes first progress in learning. Nevertheless, the results show the importance of these “*second-order*” use-cases as they also showed good model fits for the power law function (see table 7.3). Consequently, researchers must not only consider transitions from manual to an automated mode (“*activations*”) but also take transitions between automated modes into account.

These empirical results support the considerations of Naujoks, Hergeth, et al. (2018) who theoretically derived use cases for the evaluation of HMIs for automated driving. Comparing the three observational measures showed that the power law fit for button presses in transitions to L3 ADS was poor (see table 7.3). This result suggests that users increased the speed of their interaction (reflected in reaction time decrease), but kept on making erroneous operational actions. The comparably higher asymptotical value of experimenter ratings in L3 compared to L2 supports this observation. This result contradicts Wickens et al. (2015), who stated that users accomplish error-free trials first. One possible explanation is that users were not aware of making an error by pressing the activation button while the L3 ADS was not yet available. The learning rates of errors and reaction times in transitions to L2 driving automation (see table 7.3) supports the argument that users first accomplish error-free interactions followed by further improvement in reaction times. In most parts, these results support hypothesis 1b.

Referring to considerations on underlying mechanisms for learning to use driving automation, the present study results support the assumptions that at first, an understanding of behavioral causes and system effects might be at play. At the same time, there is no specific behavioral skill that is learned during the interaction. This is reflected in the asymptotic level which is reached not later than the third trial. Compared to complex skill acquisition processes such as playing piano (Palmer & Meyer, 2000) or juggling (Huys, Daffertshofer, & Beek, 2004), operating automated driving systems requires comparably simple skills. However, large gains in performance are reached through making the correct input action to complete the respective task. Furthermore, in a realistic setting, one has to assume that users are not well trained and informed about the correct utilization of automation technology (Beggiato & Krems, 2013; Mehlenbacher et al., 2002). Therefore, it is likely that in first contacts with driving automation, users will not know exactly, how to operate such a system through its HMI. Consequently, the present study design stuck as close to a presumably realistic setting as possible. It could thus show that uninformed users will need to try operating the driving automation system on a trial and error basis until they had figured out the correct way of operating. Following from that, suppliers of driving automation systems have to consider carefully how to mitigate the detrimental effects observed in first contact human-automation interactions. Potential solutions and effects of these are in the focus of chapters 10 and 11. The close coupling of performance-enhancements through more accurate system understanding is further elaborated on in the following chapter. To identify the processes at work that are

responsible for the changes from the first to subsequent human-automation interactions, there is still potential for future basic research.

7.2.2 Development of the Preference-Performance Relationship

Within the examination of the preference-performance relationship, the present study first examined the effect of practice on self-report ratings. We found evidence that self-reports increase slightly over time. However, the practical relevance of this result is questionable due to the small effect size (Sullivan & Feinn, 2012). This supports hypothesis 2a. Compared to attitude ratings such as trust and acceptance, which change over time, self-reported usability remains at a constant level. This result corroborates prior considerations that usability ratings can be considered as a fixed property of an object rather than a calibrating attitude of the human operator. It implies for researchers and practitioners that self-reported usability can be assessed at one time of measurement without repeated application of the scale. In the interpretation of the results it is important to consider, that self-reported usability measures such as the SUS incorporate specific questions on initial interaction success.

The preference-performance relationship changed over time (see table 7.5). This change is rather ascribed to the observed change in behavioral measures than self-report measures. Therefore, hypothesis 2b is supported by the multivariate ANOVA.

Furthermore, results of the regression analysis (see table 7.6) for all behavioral measures revealed strong preference-performance relationships only at the first time of measurement. A significant relationship at later times of measurement was only present for the experimenter rating. This result also supports the consideration of applying not only operational but also measures of tactical performance. The predictive validity of self-reports for behavioral measures is only given for initial contact with the automated vehicle HMI. This effect is due to the performance increase and stabilization for behavioral measures as outlined above. Thus, we conclude that the initial success of interaction is crucial to establish self-reported satisfaction. This result is in accordance with attitude formation theory, which proclaims that attitudes are hard to change once they are formed (Ross et al., 1975). It can explain why the phenomenon of the preference-performance dissociation might occur in studies of human-computer interaction. Whenever there is learning involved, users improve their performance. Researcher frequently apply familiarization trials with an interface or system before the experimental trials begin (AAM, 2006). When examining preference and performance later on, both measures might not

be in accordance as preference measures take performance from familiarization trials into account.

7.2.3 Practical Implications

The present work holds several implications for researchers and practitioners conducting studies on automated driving. First, the results revealed that human operators must learn interacting with automation technology. Depending on the respective study aim that can be either intuitiveness or experienced use of an interface, study designs need to include a certain number of interactions between the operator and the system. When setting up an experiment, only testing initial interactions represents a conservative strategy. Repeated measurements of the interactions in contrast represents a more liberal approach as one can expect more positive results from interaction performance.

Second, it is not enough for researchers to collect single observational measures but rather include a wider range such as error rates, reaction times and tactical measures (e.g., experimenter rating).

Third, when evaluating automated vehicle HMIs in user initiated scenarios, transitions between different levels of driving automation should be prioritized over transitions to manual. It is sufficient to test transitions to manual for one single time as no behavioral change over time can be assumed.

Concerning the relationship between preference and performance, researchers can rely on self-report data independent from the time of measurement, given they apply a reliable and valid instrument. Self-reported satisfaction with an interface remains considerably constant over time. Special attention should be paid when it comes to the interpretation of self-report data since this measure also reflects initial interactions with the interface that might have been observed in familiarization trials. If a dissociation between self-report data and behavioral measures appears, this might be attributable to the fact behavioral measures have reached a constant level and variation within this measure is scarce.

7.2.4 Limitations and future Research

It is important to consider that the present results are specific to the HMI and setup of the present study. The transitions to L3 automation posed three requirements at the same time (i.e., availability, speed limitation, lateral position) to the drivers. Future research shall also consider investigation when the ADS is already available at the onset

of the experimenter instruction. Furthermore, the asymptotical values for reaction time measures range on a higher level compared to the transitions to L2 and manual since the drivers had to wait for at least 10 seconds until the function was available.

The post-hoc analysis of the MANOVA usually requires a Roy-Bargman Stepdown Analysis (Tabachnick & Fidell, 2007). Due to the present within-subject design, this approach was not possible and instead univariate ANOVAs were calculated for the SUS instead of an analysis of covariance that takes the respective behavioral measure into account. Even though we followed a standardized approach by assigning specific observable behavior in the different use cases to each category of the experimenter rating, there is still room for interpretation for the experimenter. Moreover, the experimenter was aware of the sequential order and a certain bias in ratings cannot be categorically ruled out. Thus, the experimenter rating as an instrument for assessing behavior on a tactical level eventually also depends on the subjective evaluation of the rater. Future research on experimenter ratings in automated driving HMI evaluation shall consider ratings of video recordings to ensure independence of the rater from order information.

Despite the ordinal nature of the experimenter rating, the present analysis used the mean instead of the median for further analysis. G. Norman (2010) dissects arguments against the use of parametric statistical methods on ordinal data. According to the author, (1) there is an ample range of studies showing robustness, (2) for statistical tests. Furthermore (2), *“the numbers don’t know where they come from”* (Lord, 1953) and thus, statistical treatment is applicable as long as the interpretation of results accounts initial scaling. Finally (3), G. Norman (2010) describes an example of parametric and non-parametric correlation approaches showing that both deliver the same result on ordinal data. In the area of automotive controllability, Cooper-Harper scale items have frequently been treated with parametric approaches (i.e., calculating means, applying t-tests and ANOVAs) (Kauffmann, Winkler, & Vollrath, 2018; Naujoks, Purucker, Neukum, Wolter, & Steiger, 2015; Neukum et al., 2008). The present research used an aggregated level of behavior in multivariate analysis. Future research needs to inspect the relationship on a more granular use-case level with a single item for usability (Konradt & Christophersen, 2013). One solution might be the overall satisfaction item of the Post-Study System Usability Scale (Lewis, 2002). As the experiment reported here lasted approximately 60 minutes, the non-change of SUS ratings over time might be due to the experimental setting as participants might easily remember prior ratings. When conducting longitudinal research, the present results need further support of satisfaction ratings with automated vehicle HMIs over longer period of time. However, as

the present work also aimed at contributing to methodological development for automated vehicle HMI evaluation, the reported stability over time holds the methodological implications mentioned above.

Additionally, the study procedure assumed non-informed users when first encountering driving automation. OEMs providing automation technology, however, will need to consider user education approaches to ensure safe and appropriate use of the functions (NHTSA, 2016). Therefore, prior treatments for user training should be developed such as owner's manuals, interactive tutorials or video footage (Hergeth et al., 2017; Payre et al., 2017). The present thesis outlines the conceptual development and a pilot study in chapter 10 and a large-scale driving simulator study on combined user education approaches in chapter 11. The present results describe what happens when learning occurs, but not how this process evolves. As noted above, Wickens et al. (2015) name attentional demand as a third important behavioral measure in human-computer interaction. Eye-tracking metrics also give insight into tactical and strategical behavior while they incorporate operational (i.e., reaction time) components at the same time. Chapter 6 already provided theoretically derived hypotheses for gaze behavior and understanding of HMI functionality. The following chapter 8 takes a closer look to not only describe but also explain the behavior and the process of learning. It additionally reports the analysis of eye-tracking data recorded in this experiment.

8 Learning and Development of Mental Models during Interactions with Driving Automation: A Simulator Study ⁷

Abstract: Higher level cognitive processes such as learning and mental models play a fundamental role in the success of automated driving, as technology can only be as good as our understanding and expectations of it. The present study investigated the development of these processes during interactions with driving automation. In a driving simulator study, $N=52$ participants completed several transitions between manual and Society of Automotive Engineers (SAE) levels 2 and 3 automated driving. Self-reported learning progress and mental model development were assessed via questionnaires. In parallel, eye-tracking data were collected as a behavioral measure of higher level cognitive functions. The results demonstrated that self-reported learning and gaze behavior followed a power-law function; the power-law functions showed task specific parameter manifestations. The evolution of the mental models of the level 2 and level 3 human-machine interface continued up to the fifth contact, indicating a long lasting process. For researchers and practitioners, the present study implies that accurate mental models require up to 5 repeated interactions. Furthermore, learning progress with driving automation can be captured through gaze behavior.

This chapter reports the results and discussion of these in relation to the hypotheses stated in chapter 6.2.1.

⁷This chapter is based on a previous publication: Forster, Y., Hergeth, S., Naujoks F., Beggiato, M., Krems, J. F. & Keinath, A. (2019). Learning and Development of Mental Models during Interactions with Driving Automation: A Simulator Study *The 10th International Driving Symposium on Human Factors in Driver Assessment, Training, and Vehicle Design*. Santa Fe, NM, USA, p. 398 – 404.

8.1 Results

Model fits of the power law for self-reported learning (see figure 8.1 and table 8.1) demonstrated a steep increase from the prior assessment to the first block and a subsequent slight increase up to the fifth block. Self-reported learning stabilized at a considerably high level, indicating that participants were subjectively familiar with the system. The change in total gaze switches between AOIs (figure 8.2 and table 8.2) over time showed that participants' gaze behavior adhered to the power law of learning. Each UC showed a specific learning pattern: There were lower asymptotes for the transitions to L2 automation (UC2, UC4) than for transitions to L3 (UC1, UC3). The highest learning rate and amplitude was observed in the transition from manual to L2 automation (UC2), while the lowest amplitude was observed in the transition from L2 to L3 automation (UC3). The transition from L3 to L2 automation (UC4) took the longest to stabilize in terms of gaze behavior, which is reflected in its considerably low learning rate of 1.217. The monitoring frequency results (see figure 8.3) revealed that in all four UCs, the driving scene and the instrument cluster were the most important AOIs. There was no considerable change across the blocks except for UC4, where initial frequencies of about 0.35 dropped towards a frequency of about 0.2. In comparison, the NDRT and the operating element were less important. However, in the first block the operating element was of considerable importance in all four UCs whereas the monitoring frequency dropped from the first to the second block.

Table 8.1

Model fit equations and goodness-of-fit indices (R^2 , $RMSE$) for self-reported learning

	Power Law	R^2	$RMSE$
Learning 1	$N = 86.58 - 55.36 * t^{-1.825}$	.9983	1.0924
Learning 2	$N = 87.93 - 45.58 * t^{-1.447}$	.9965	1.4659
Learning 3	$N = 85.18 - 42.27 * t^{-1.278}$	.9954	1.2903
Learning 4	$N = 84.23 - 51.94 * t^{-1.324}$	.9920	2.0737

Figure 8.1. Self-reported learning (M , SE) and according power-law fit

Table 8.2

Model fit equations and goodness-of-fit indices (R^2 , $RMSE$) for gaze switches by UC

	Power Law	R^2	$RMSE$
Use Case 1	$P = 24.16 + 18.53 * t^{-2.818}$	.9765	1.7311
Use Case 2	$P = 10.41 + 33.71 * t^{-4.805}$	.9997	0.3519
Use Case 3	$P = 21.72 + 9.54 * t^{-3.000}$	.9921	0.5146
Use Case 4	$P = 6.13 + 25.42 * t^{-1.217}$	.9975	0.6307

Figure 8.2. Number of gaze switches (M , SE) and according power-law fit

Figure 8.3. Monitoring frequency results (i.e., M , SE) in the four UCs by block and AOI.

The results for the mental model questionnaire revealed that development occurs up to the fifth block (see figure 8.4). With increasing experience, participants could better discriminate between L2 and L3, as indicated by rising mean differences between the two automation levels. The rising accuracy of the mental models is reflected in the differences between both systems, as well as in smaller mean distances towards their respective ends of the scale. System monitoring related items (i.e., Items 3, 5) already showed large differences between L2 and L3 before the first block. Three variables showed a steadily increasing difference (i.e., Items 1, 4, 6). A difference in the relevance of lane keeping (Item 2) emerged after the fourth block of interactions. After five blocks, there was still room for improving the mental model, as indicated by distances between the mental model mean and the correct answer (1 or 7, respectively).

Figure 8.4. Mental model questionnaire results (i.e., M , SE) by automation level and expertise

8.2 Discussion

The objective of this study was to examine the effect of increasing practice on higher level cognitive processes at both the self-reported and behavioral levels. The results for the development of both measures over time confirmed Hypotheses 1a and 2a. Both the self-reported learning and the number of gaze switches between AOIs followed the power-law of learning and demonstrated sufficient goodness-of-fit (see Tables 8.1 and 8.2). The decrease and subsequent stabilization of the number of transitions between the AOIs across all UCs indicates that scanning efficiency increased. Driving automation users thus seem to improve their visual scanning behavior over time (Underwood, 2007). Results of the monitoring frequency development over time, however, show that the increase of efficiency is due to shorter time on task (see also chapter 7.2.1). This implies that drivers did not alter their scanning behavior per se in a sense that they adapted a novel strategy but they rather needed a smaller number of switches between AOIs within the time they took until successful completion of the respective use case. In addition, the different model fits for the four transitions and importance of AOIs support the task-dependency of gaze behavior (Hayhoe & Ballard, 2005). These results support Hypothesis 2b, as each transition poses different demands to the human operator: Transitions with ongoing manual vehicle guidance (UC1, UC2) exhibited more

learning compared to transitions between two levels of automation (UC3, UC4). This result emphasizes that the design process should focus on the task-specific requirements of control transitions. Future research should therefore examine the dispersion of visual attention allocation in transitions between automation levels more closely.

The mental model results support Hypothesis 1b. While participants could not effectively discriminate between L2 and L3 automation before using automated driving, subsequent interactions improved the accuracy of their mental model (see figure 8.4). Accordingly, researchers and practitioners in the field of automated driving need to consider that accurate mental models require repeated interactions, even after operational behavior has reached a constant level. Even after five repetitions, there were still participants that did not have an accurate mental model. The difference between L2 and L3 automation was not evident to many participants during their first interactions; for example, the relevance of lane keeping for transitions in L3 took up to four repetitions to become even slightly apparent (see figure 8.4, Item 2). Despite the apparent simplicity of interacting with the system (e.g., pressing a button to activate it), these results emphasize the difficulty and long-lasting process of building accurate mental models. As the present experiment only included L2 and L3 automated driving, this effect is proposed to be even stronger with additional automation functions (e.g., L1, L4). The present work supports prior evidence that mental models for driving automation are slow to evolve (Beggiato et al., 2015). In automated driving research, the interpretation of self-reported satisfaction with driving automation must consider that these evaluations were provided during a phase in which the participants' understanding of the system was still evolving (e.g., Forster et al., 2016; Frison et al., 2017).

Future research efforts are necessary to identify the impact of rising experience with and accuracy of mental models on the development of self-reported satisfaction with HMIs for automated driving. This work supports the operationalization of learning through gaze behavior and provides the literature with an insight into the long-lasting process of mental model evolution in automated driving.

Up to this point, the thesis described the operationalization of self-reported satisfaction, understanding and interaction behavior. In addition, the first varying factor of UC repetition for the preference-performance relationship was investigated. As described in the general method section in chapter 6, the second experiment also included a between-subjects factor, namely feedback, that has not been considered in

the previous two chapters. It shall receive closer attention in the upcoming chapter. Additionally, it remains an open question how diagnostic self-report measures in comparison to summative self-report measures (see SUS development in chapter 7) evolve over time. The following chapter takes on these two research questions (see also chapter 6 for more background information).

9 Tell them how they did: Feedback on Operator Performance helps calibrate perceived Ease of Use in Automated Driving ⁸

Abstract: The development of automated driving will profit from an agreed-upon methodology to evaluate human-machine interfaces. The present study examines the role of feedback on interaction performance provided directly to participants when interacting with driving automation (i.e., perceived ease of use). In addition, the development of ratings itself over time and use case specificity were examined. In a driving simulator study, $N=55$ participants completed several transitions between Society of Automotive Engineers (SAE) level 0, level 2, and level 3 automated driving. One half of the participants received feedback on their interaction performance immediately after each use case, while the other half did not. As expected, the results revealed that participants judged the interactions to become easier over time. However, a use case specificity was present, as transitions to L0 did not show effects over time. The role of feedback also depended on the respective use case. We observed more conservative evaluations when feedback was provided than when it was not. The present study supports the application of perceived ease of use as a diagnostic measure in interaction with automated driving. Evaluations of interfaces can benefit from supporting feedback to obtain more conservative results.

This chapter reports the results and discussion of these in relation to the hypotheses stated in chapter 6.3.3.

⁸This chapter is based on a previous publication: Forster, Y., Hergeth, S., Naujoks F., Krems, J. F. & Keinath, A. (2019). Tell Them How They Did: Feedback on Operator Performance Helps Calibrate Perceived Ease of Use in Automated Driving. *Multimodal Technologies and Interaction*, 3(2), 29.

9.1 Results

9.1.1 Manipulation Check: Time on Task

Mauchly's test of sphericity revealed statistically significant effects for all factors (see table 9.1). Therefore, degrees of freedom were adjusted after Greenhouse–Geisser. The manipulation check applied a 2x5x6 (feedback x time of measurement x use case) mixed within-between ANOVA. Inferential results for time on task (see table 9.2) showed significant main effects for time of measurement and use case. These results indicate that participants' performance improved over time and differed between use cases. The UC difference lies in the nature of the UC design. While the transition from L0 to L2 could be completed within 5-10 seconds after repeated exposure (see UC3 and UC5 in figure 9.1), transitions to L3 lasted between 15 and 20 seconds. There is a 10-second window where the ADS was not available and therefore shorter time on task was not possible (see chapter 6.4.6). The significant interaction between use case and time of measurement points towards different demands in the use cases. While there were no performance improvements in transitions to L0 (i.e., UC2, UC6), interaction performance improved for transitions between levels of automation. There was no significant main or interaction effect of feedback present. The manipulation check thus supports the assumption that the experimental manipulation did not directly affect interaction performance. Figure 9.1 shows the results of time on task for the use cases by time of measurement and feedback condition. The plots show that in single interactions such as UC1 block 1 and UC 3 block 1 there was a tendency towards differences in interaction performance between the two feedback conditions.

Table 9.1

Mauchly's test statistics of sphericity assumption for time on task.

Effect	Approx. χ^2	<i>df</i>	<i>p</i>
Time of measurement	82.002	9	<.001
Use case	100.439	12	<.001
Time of measurement * Use case	1235.381	209	<.001

9.1.2 Perceived Ease of Use

Figure 9.2 shows descriptive statistics (i.e., *M*, *SE*) of perceived ease of use in the six use cases by time of measurement and experimental feedback condition. Prior to inferential

Table 9.2

Inferential statistics (i.e., F , $df1$, $df2$, p , η_p^2) of time on task.

Effect	F	$df1$	$df2$	p	η_p^2
Time of measurement	73.630	2.177	123.278	<.001	.581
Use case	103.203	3.580	189.754	<.001	.661
Feedback	0.832	1	53	.366	.015
Time of measurement * Feedback	0.588	2.177	123.278	.571	.011
Use case * Feedback	0.342	3.580	189.754	.829	.006
Time of measurement * Use case	8.305	4.501	238.556	<.001	.135
Time of measurement * Use case * Feedback	2.250	4.501	238.556	.057	.041

statistics, factors with repeated measures (i.e., time of measurement, use case) were tested for sphericity. The results showed statistically significant effects for both main factors and their interaction (see table 9.3). Therefore, degrees of freedom were adjusted after Greenhouse–Geisser. A 2x5x6 (feedback x time of measurement x use case) mixed within-between ANOVA was conducted for perceived ease of use. Inferential statistics revealed two significant main effects for time of measurement and use case. There was no main effect of feedback. The main effects indicate that perceived ease of use depends on specific transitions of control as well as on the number of times that participants had completed the use case. In addition, there were two significant two-way interactions between use case and feedback as well as between time of measurement and use case. The test statistics are reported in table 9.4. With two significant two-way interactions, the significant main effects cannot be interpreted. The significant interaction between use case and feedback indicates that there is an effect of feedback on perceived ease of use ratings which depends on the respective use case. The transitions to L0 showed ratings on a very high level overall, with only small variation and no difference between the two experimental conditions. These use cases are perceived as effortless from the first time of measurement. Furthermore, UCs 1, 4 and 5 exhibited a tendency towards decreased ease of use ratings in the feedback condition. This result means that when participants received feedback on their interaction performance, their ratings became more conservative in terms of lower ease of use. In contrast, UC3 led to higher self-reported ease of use in the feedback condition. Thus, participants who received feedback about their interaction quality tended to rate the interaction as more effortless compared to the group with no feedback. The interaction between time of measurement and use case indicates that perceived ease of use depends on the time of measurement, which

Figure 9.1. Means and standard errors for time on task in the 6 use cases by time of measurement (x-axis) and feedback condition

is in turn different between the use cases. While ease of use ratings increased towards higher ratings with rising experience in UCs 1, 3, 4 and 5, this trend over time was not apparent in transitions to L0 (UC2, UC6). The transitions to L2 automation (i.e., UC3, UC5) showed a steep increase in ease of use ratings from the first to the second time of measurement. In contrast, a more gradual increase was observed for transitions to L3 automation (i.e., UC1, UC4).

Table 9.3

Mauchly's test statistics of sphericity assumption for perceived ease of use.

Effect	Approx. χ^2	df	p
Time of measurement	49.001	9	<.001
Use case	48.367	14	<.001
Time of measurement * Use case	567.343	209	<.001

Table 9.4

Inferential statistics (i.e., F , $df1$, $df2$, p , η_p^2) of perceived ease of use.

Effect	F	$df1$	$df2$	p	η_p^2
Time of measurement	49.231	2.685	142.281	<.001	.482
Use case	23.717	3.869	205.076	<.001	.309
Feedback	0.725	1	53	.398	.013
Time of measurement * Feedback	1.601	2.685	142.281	.372	.019
Use case * Feedback	4.529	3.869	205.076	<.01	.079
Time of measurement * Use case	8.660	8.200	434.589	<.001	.140
Time of measurement * Use case * Feedback	0.961	8.200	434.589	.467	.018

Figure 9.2. Means and standard errors for difficulty ratings in the 6 use cases by time of measurement (x-axis) and feedback condition.

9.2 Discussion

The present study examined the effect of operator performance feedback on PEOU in the context of automated driving. In a driving simulator study, $N=55$ participants completed several transitions between levels of driving automation. One part of the participants received standardized feedback on their performance while the other part

did not. To find out about the effects of time of measurement, use case and feedback, participants answered a single-item question on PEOU after having successfully completed each use case. The results revealed that feedback facilitates PEOU in a use case specific manner. Transitions to L0 were considered as very easy independently from the experimental conditions. In contrast, transitions between automation levels were affected by the feedback condition. This indicates that there is a calibrating effect of feedback for diagnostic measures. The following section discusses and explains the results found above and derives implications regarding time of measurement, use case and the provision of feedback.

9.2.1 Effect of Feedback on Interaction Performance

The results did not show an effect of feedback on actual interaction performance operationalized through the time on task. This result is not in line with considerations about training effects through feedback by Wickens et al. (2015). One possible explanation is that the feedback in this study was provided after the interaction and not concurrently. The temporal course of interaction and subsequent feedback makes it impossible for participants to be able to connect the feedback with actual operating behavior. Furthermore, the experimenter only provided generic category names and did not specifically report why the respective rating was assigned. Therefore, participants could not directly infer which issues in interaction were still present and adapt their behavior accordingly. Only if a participant could not solve a use case and the experimenter had to explain the correct operating path (i.e., category 5, see table 6.2) did participants receive specific instructions. From the independence of the interaction performance from feedback, we conclude that there is a direct link between feedback and diagnostic measures. Thus, valid conclusions for the analysis of the main and interaction effects of feedback on perceived ease of use can be drawn.

9.2.2 Change over Time and UC Specificity

The significant main and interaction effects of time of measurement (see table 9.4 and figure 9.2) corroborates considerations of the technology acceptance model that repeated interaction increases ease of use (Davis, 1989). Thus, hypothesis 1 is confirmed. The present results do not support observations by Karahanna and Straub (1999), who did not find an effect of training on PEOU. Especially first contacts (i.e., Block 1) showed a trend towards the “*difficult*” end of the scale, while subsequent ratings aligned to-

wards the upper end (i.e., “*easy*”). User studies on novel technologies in general and on automated driving in particular often investigate short term usage only. In an applied setting on automated vehicle HMIs, Frison et al. (2017) report close to average ease of use ratings. However, with experimental drives lasting only 10 minutes, subsequent improvements in ease of use might be possible. In contrast, a study by D. Large et al. (2016) deliberately trained participants until they assumed competence in operating the interface. Thus, the authors ensured that differences between conceptual approaches are not only present at initial operations but also hold true for more skilled users.

In general, a trend towards the “*very easy*” end of the 7-point Likert scale could be observed and it seems that a ceiling effect was present here. This was especially evident for transitions to L0 (i.e., UC2, UC6), where no change over time was evident (see figure 9.2). This result supports the considerations on use case specificity of learning effects (Gagne, 1984) and confirms hypothesis 2. As a consequence, only a small diagnostic benefit can be drawn from use cases with driver-initiated transitions to L0. This suggests that future studies investigating human–automation interaction for do not need to consider these use cases closely but should rather focus on transitions towards levels of automation. When researchers aim at finding issues in operating an ADS, driver-initiated transitions to different levels of driving automation can bring diagnostic benefit.

9.2.3 Calibrating Effects of Feedback

The present study’s aim was to show that different judgments arise when the performance feedback loop is closed. The present results did not show a main effect of feedback on PEOU. However, in interaction with use case, there was a significant effect on PEOU (see table 9.4). These results highlight the use case specificity (Gagne, 1984) that was also apparent for the time of measurement factor. It means that there is an effect of feedback on the calibration of PEOU in a sense that participants provided more conservative ratings when they received feedback compared to when they did not receive any feedback. This effect, however, depended on the specific transition and is not apparent in transitions to L0, where a ceiling effect was present in both groups. To be more specific, UC1, UC4 and UC5 tended to lead to more conservative PEOU ratings in the feedback condition. In the light of the manipulation check of actual interaction performance, differences in PEOU between feedback conditions are limited to certain interactions (see e.g., UC3 block 1, figure 9.2). Thus, the result of higher PEOU judgments observed in UC3 with additional feedback cannot be interpreted insofar as the feedback

itself led to this observation, but it is rather due to the interaction performance. Besides these restrictions, the significant interaction effect between performance feedback and use case highlights the calibrating role of feedback for self-reported diagnostic measures. Hypothesis 3 is thus partly confirmed. Feedback influenced PEOU such that participants gave more conservative judgments tending towards the “*difficult*” end of the scale and the ceiling effect was mitigated. These results support prior considerations on the calibrating role of feedback. However, in comparison to calibrating effects of feedback on trust in automation (e.g., Helldin et al., 2013; Seong & Bisantz, 2008) the influence is not as pervasive in the present analysis. The observation of feedback influencing ease of use is also in accordance with the trust model by J. D. Lee and See (2004) which proclaims a link between the attitudes of trust and ease of use.

In an applied context of HMI testing in user studies, there are many examples reporting high ease of use (e.g., Forster et al., 2016; Guo et al., 2019; Wintersberger et al., 2018) even in first contacts. These results certainly give an important insight into participants’ subjective evaluation, namely that they perceive interaction as considerably effortless. However, the interpretation of these observations needs to carefully incorporate the notion that potentially more conservative estimates might have been present if users had known about potential errors.

To novice users, the interface design might seem comparably simple including buttons on a steering wheel and a display in the instrument cluster. However, automated vehicle HMIs are considerably complex and it is likely that users cannot recognize this at the first glance. Therefore, only scratching the surface with their interaction might seem simple if one is not aware of system limitations and ODD restrictions. Errors in interaction with the automated vehicle HMI might thus not be integrated into a larger picture of system states, HMI displays and traffic conditions. This might consequentially lead to judgments that are on the one hand subjectively true for the user but on the other hand seem unreasonable to the HMI designer. By providing feedback that there actually was an error (e.g., category 3, see table 6.2), users are more likely to recognize the degree of deviation from error-free interaction. The degree of uncertainty about interaction performance decreases due to feedback (Tversky & Kahneman, 1974) and an anchor for realistic judgments is provided.

Overall, absolute judgments in the feedback conditions were still recorded with a considerable alignment towards the upper end of the PEOU scale. The present HMI solution in essence contained two buttons and a graphical interface in the instrument cluster. Therefore, with more available levels of driving automation and ADAS (e.g., Adaptive

Cruise Control, Speed Limiter), PEOU ratings are expected to shift towards the lower end of the PEOU continuum. The obtained results indicate that study designs of automated vehicle HMIs can benefit from feedback on operator performance if researchers aim at a more conservative and/or realistic evaluation of HMIs.

In regards to method development and standardization in the driving automation domain, this work contributes insofar as it outlines an additional possible procedure. Despite following the human-centered design approach for HMI design, system functionality might still lead to considerably complex interfaces. Especially in these instances, such a procedure could be applied. As outlined before, users struggle with giving confident estimates as long as they are uncertain about their actions and the HMI's conceptualization. It might also be possible operationalize feedback differently than the present experimenter rating on a scale from one to five. If users could not solve the use case by themselves, the experimenter explained the correct operating path. Such explanations about users' actions including information about one or multiple errors during operational inputs could as well be provided independent from the rating category.

9.2.4 Limitations and Future Research

This study comes with limitations and opportunities for future research. The experiment only included a restricted number of use cases from the catalogue by Naujoks, Hergeth, et al. (2018) as well as automation levels. Future HMI concepts for automated driving may also incorporate L1 (both lateral and longitudinal) functionality as well as customizable solutions for specifying automation functionality (e.g., setting speed, lateral offset).

Future conceptual approaches might consider to provide feedback via different modalities. Conceivable approaches are displaying performance through a visual display or auditory tones. Thus, feedback on operator performance could be embedded within the existing HMI concept. Furthermore, the use cases were restricted to driver-initiated control transitions and left out system-initiated transitions such as take-over requests (e.g., Eriksson & Stanton, 2017).

Concerning feedback, future research is necessary to find out about these effects under circumstances where PEOU ratings are more distributed across the applied scale. Since a ceiling effect occurred in the present study, the effect of feedback on more scale-centered ratings is yet to be investigated. In addition, a wider range of dependent variables such as usefulness (Davis, 1989) or single-items on perceived usability (Lewis, 2002) might be influenced by feedback and should be investigated for this effect.

The present research specifically examined the effect of operator feedback for the calibration of ease of use judgments. This marks a first step going beyond calibrating effects in automation trust. However, there remain important research areas such as mode awareness (Feldhütter et al., 2017) or mental models (Beggiato et al., 2015) where the role of feedback remains unknown.

9.2.5 Conclusions

The present study provides three core findings. First, the observation that PEOU changes over time implies that initial measurements give the most conservative estimate of an HMI’s ease of use. Concerning repeated exposure, we conclude that only limited diagnostic insights can be drawn from trained users (e.g., after 5th repetition of UC). However, the subsequent tendency towards the upper end shows that repeated measurements are necessary to also make statements about an HMI’s ease of use when more experienced users are regarded. The repeated measure approach also bears the advantage to make estimations about the magnitude of learning from the first to the second contact.

Second, the use case specificity indicates that transitions to an automated mode are of higher importance than transitions to manual. These use cases seem to put higher demands on the users in terms of HMI operation and understanding thereof. To derive a more comprehensive image of an automated vehicle HMI, transitions to automated mode should be completed twice within an HMI evaluation. Concerning use case specificity, we conclude that simple interaction scenarios (e.g., UC2, UC6) do not provide substantial insights into issues of HMI design. In contrast, activation of driving automation systems and changes between levels of driving automation provide more valuable directions for future development.

Eventually, researchers and practitioners should acknowledge that users’ perception can differ from what the experimenter actually observes during the interaction. In the present case, we observed this as a dependency of PEOU on the information about performance (i.e., feedback vs. no feedback). The present study does not raise the claim that one approach is superior compared to the other. It rather points out that researcher will obtain different results when applying one or the other method. If one does not provide feedback, he/she leaves users with judgments under uncertainty (Tversky & Kahneman, 1974) thus potentially leading to stronger ceiling effects. Furthermore, the discrepancy between actual performance and self-reported ease of use might be larger giving a more heterogeneous picture of the automated vehicle’s HMI. In comparison, calibrated judg-

ments provide a more homogeneous picture when it comes to relating behavioral and self-report measures (Nielsen & Levy, 1994). While on the one hand, this bears the possibility to better infer behavior from self-report data and vice versa, on the other hand a metric that is influenced by feedback might be diluted and does not reflect future users' unswayed attitude towards the system and its HMI. Here, it is important to mention that the present work does not suggest that by providing feedback, the necessity to collect behavioral measures (e.g., time on task, error rate, gaze metrics) becomes obsolete. On the contrary, we explicitly demand researchers to investigate human-automation interaction by means of both sources of data to derive a holistic conclusion (see also chapters 2 and 3). This work, however, points out that the link between behavior and attitude might be moderated by self-regulatory processes. If one observes such ceiling effects in self-reports when evaluating emerging technologies, these might be counteracted through closing the feedback gap.

User studies usually do not include additional provision of feedback as this procedure requires a highly-trained and fast rater that is well-informed about the HMI. It is therefore debatable whether to include such a procedure into user studies. Another possibility to make participants more sensitive to HMI operation is user education. Here, information on correct and incorrect operational actions is provided before rather than after interaction as in the present study. Therefore, the present study supports the existence of calibrating effects on PEOU when closing attitude-behavior feedback loops *ex post*. This feedback loop might also be closed *ex ante* by means of educating users of driving automation technology so that they could classify their operational behavior within a larger set of interaction behavior possibilities. There are already first efforts towards developing and testing user education approaches for automated driving (Hergeth et al., 2017; Payre, Cestac, & Delhomme, 2016; Sportillo, Paljic, & Ojeda, 2018). Such procedures are investigated in more depth in the following two chapters.

10 User Education in Automated Driving: Owner's Manual and Interactive Tutorial support Mental Model Formation and Human-Automation Interaction

9

Abstract: Automated driving systems (ADS) and a combination of these with advanced driver assistance systems (ADAS) will soon be available to a large consumer population. Apart from testing automated driving features and human-machine interfaces (HMI), the development and evaluation of training for interacting with driving automation has been largely neglected. The present work outlines the conceptual development of two possible approaches of user education which are the owner's manual and an interactive tutorial. These approaches are investigated by comparing them to a baseline consisting of generic information about the system function. Using a between-subjects design, $N=24$ participants complete one training prior to interacting with the ADS HMI in a driving simulator. Results show that both the owner's manual and an interactive tutorial led to an increased understanding of driving automation systems as well as an increased interaction performance. This work contributes to method development for the evaluation of ADS by proposing two alternative approaches of user education and their implications for both application in realistic settings and HMI testing.

⁹This chapter is based on a previous publication: Forster, Y., Hergeth, S., Naujoks F., Krems, J. F. & Keinath, A. (2019). User Education in Automated Driving: Owner's Manual and Interactive Tutorial support Mental Model Formation and Human-Automation Interaction *Information (Switzerland)*, 10(4), 143. doi:10.3390/info10040143

10.1 Introduction

Human factors research strives to accomplish the task of safer and more efficient human-automation interaction, where the first and most important aspect that must be regarded is appropriate HMI design with a user-centered perspective. Following guidelines for proper interface design in automated driving (e.g., Naujoks, Wiedemann, et al., 2019), developers can design HMIs that are simple, intuitive, and user-friendly. As well, one additional challenge for a successful market introduction is the development and deployment of user education with driving automation. Educating users is needed to support safe and efficient interaction when using driving automation (NHTSA, 2016). It shall be noted that through good interface design the demand for user education might be reduced to a certain degree, but most likely it cannot be eradicated. In the area of manual driving, there has been considerable interest in research for educating novice drivers in order to enhance road safety (Crundall, Andrews, van Loon, & Chapman, 2010; Mehlenbacher et al., 2002). The body of knowledge in the automated driving domain, however, is rather scarce even though the National Highway Traffic Safety Administration's (NHTSA) automated vehicles policy (NHTSA, 2016) explicitly points towards the development of user education approaches. The importance of automation user education and the retrieval of manual operation skills in control transfer events, however, had been raised by (Bainbridge, 1983) more than two decades ago. More recently, Endsley (2017) described an impression of user education when first encountering a Tesla Model S equipped with autopilot. According to the author, there were brief verbal descriptions and after repeated questioning a rather unstructured familiarization drive was offered. Similarly, a report by Pradhan, Sullivan, Schwarz, Feng, and Bao (2019) of a round table discussion on driver training showed that there is a pressing need to develop and evaluate user education for driving automation. The present work contributes to the challenge of conceptual development of user education procedures by outlining possible approaches for user education (i.e., owner's manual, interactive tutorial). The aim of the present study is to investigate the effects of different user education approaches on system understanding and interaction performance.

10.1.1 Background

The previous chapters have shown that strong learning effects are at play when novice users interact with driving automation systems for the first time. When it comes to using L3 ADS, users face complex system architectures that are communicated via graphical

and auditory HMI elements. One difference between L3 ADS and lower levels of driving automation (i.e., L2 and lower) is that there is a different number of ODD-related restrictions for system activation as described in chapter 1.

One considerable aspect that arises between different transitions of control is the interference between driving and ADS operation. Users that are driving manually have to perform the entire dynamic driving task (DDT). At the same time, they have to successfully operate the automated vehicle's HMI to complete control transitions which require sensory processing, perception, response selection, and response execution (Wickens, 2002). These two tasks (i.e., DDT, operating HMI) are likely to interfere with each other. Thus, performance is impeded in both driving and human-automation interaction performance. Both activation performance (e.g., errors, time on task) and driving performance (e.g., standard deviation of lateral position, Knappe et al., 2006) should be worse for untrained users as compared with more skilled users due to distraction effects (e.g., AAM, 2006; NHTSA, 2012).

Until now, familiarization and user education in studies on automated driving evaluation have been rather unstructured and there is no commonly accepted standardization or best practice recommendation. On the one hand, there are some studies that only included a brief description of the automated driving function (Forster, Naujoks, Neukum, & Huestegge, 2017), while on the other hand, some studies included comprehensive familiarization drives with additional descriptions by the experimenters (Beller, Heesen, & Vollrath, 2013; Louw & Merat, 2017).

Comparing the automotive domain with research on automation in the aviation domain (e.g., Trösterer et al., 2017) clearly shows that user education will be one of the inevitable challenges to face for successful introduction of this technology. Thus, there is a pressing need to develop user education approaches in order to enable novice users of driving automation to appropriately use this emerging technology.

The following paragraphs outline considerations of two conceptual user education approaches and existing empirical evidence on an owner's manual (textual information) and an interactive tutorial. One important aspect that both approaches share is that they focus on building declarative knowledge rather than procedural knowledge (Anderson & Lebiere, 2014). Results from chapters 8 and 7 have shown that it takes considerably longer to build up declarative knowledge in the form of accurate mental models as compared with procedural knowledge in the form of adequate interaction performance. The two approaches explicitly target user education approaches supporting the formation of declarative knowledge.

10.1.2 Owner's Manual Based User Education

One traditional approach to educate users is the owner's manual (Mehlenbacher et al., 2002), which, in principle, is available to all later users of driving automation systems. The owner's manual based approach can be characterized as passive and unguided learning according on Wickens et al. (2015). Users of this technique only consume information without relating it to an applied context. In addition, the degree of guidance is low since learners decide for themselves how much they would read and even decide on the order of information they would process. Owner's manuals, if designed appropriately, do not convey erroneous operating paths but rather focus on correct ways of operating a certain technology. Therefore, it does not provide users with conflicting information and instead focuses on appropriate interaction. Owner's manuals are often designed such that they do not support users by providing procedural information on how to solve a task or problem when using a technology, but rather support users by providing knowledge and skills that they have to transfer to the task later on (van Loggem, 2013). It follows that in an owner's manual, HMI elements are presented separately without relating different operating components to graphical elements or auditory elements. Therefore, learners need to transfer knowledge gained from abstract descriptions of HMI elements to the applied context in the vehicle interior. Additionally, due to the dominance of textual information, users might get lost in the complexity of the information (Wickens et al., 2015). A potential drawback of owner's manuals is that the information on automated driving composes only a small portion of an enormous amount of text that can be comprised of up to 500 pages. Therefore, it might be challenging for users of driving automation to ensure that the information is not lost within other components of an owner's manual such as technical data, maintenance and repair information.

Before encountering driving automation, the research on owner's manuals or textual information showed that they largely affect the behavior and attitude of users. When users of driving automation are provided with varying descriptions of degrees of completeness, correctness or reliability, these largely influence the evolution of mental models, trust, and acceptance (Beggiato et al., 2015; Forster, Kraus, et al., 2018; Körber, Baseler, & Bengler, 2018). While most prior approaches of providing information have focused on trust and acceptance-related issues, the aim of the present study is to investigate building declarative knowledge as assessed through mental models and its association with the impact on interaction behavior (e.g., accuracy, speed) with driving automation.

10.1.3 Tutorial Based User Education

There are many different possible designs of interactive tutorials for user education. One design, the click dummy or minimum viable product version, is intentionally not considered here for two reasons. Using this version users freely try interacting with the system before actually proceeding to the respective application in the simulator or on the real road. The first reason for not considering this is that such an approach would rather build procedural knowledge through trial and error without the users being provided with appropriate descriptions of system functionality. Secondly, results from chapter 7 have already shown how interactions with driving automation without prior declarative knowledge evolve over time. Another imaginable approach is the education during interaction approach. Such procedures would lead the user step by step through the operating process by giving explanations and providing feedback. While such a procedure bears the advantage, for example, in rental car scenarios where users want to start driving and use the function right away, there are also problems with this approach. The reason the user uses automated driving is to be relieved of the driving task and engage in different NDRT. Comprehensive explanations by a system avatar (Hock et al., 2016) might take a long time and users want the function to execute the task right away. Therefore, we focus on an approach to educate users prior to first interaction. It might also be possible in car rental scenarios that by booking a tablet or computer, a brief tutorial could be completed. This procedure of educating users prior to first system encounters is also supported by inferences from aviation where only trained individuals operate automated systems and they are not trained during use. Therefore, the present work considers an interactive tutorial approach that is characterized by active and guided learning (Wickens et al., 2015). Such a user quiz consists of questions on how to operate the driving automation system in several use cases (Naujoks, Hergeth, et al., 2018). This tutorial is completed prior to the first interaction with driving automation. With the possibility of giving wrong answers, the tutorial supports learning from erroneous trials. If users take erroneous choices in a tutorial-based approach, these errors should not occur in subsequent interactions in the vehicle. Tutorials are characterized by a high degree of experimental control since users can only proceed to using the ADS in the vehicle after they have successfully completed the assigned questions. Thus, after an interactive tutorial, all users should have the same degree of system understanding before their first encounter with the driving automation system (Pradhan, Pollatsek, Knodler, & Fisher, 2009). Another characteristic of an interactive tutorial is that it is somewhat focused on specific tasks that users can subsequently face as compared with

abstract system descriptions in an owner's manuals (van Loggem, 2013). Therefore, tutorials provide a meaningful context in which a driving automation system will be used and it is not necessary to transfer knowledge from abstract descriptions to specific use cases. Interactive tutorial approaches offer the possibility to provide the user a close-to-reality impression of the HMI, providing a higher degree of immersion (Slater, 2003) as compared to owner's manual-based approaches. Designers can implement the HMI components (i.e., operating elements, buttons, graphical interface) in a way that it resembles later interior integration. As an active learning approach, the design makes the availability of erroneous answers indispensable. This can be considered a downside of the approach since learners might get confused from the sheer amount of wrong answers in relation to correct answers (e.g., 1:3 ratio). This becomes even more crucial considering that in order to foster active learning the distractors should be designed in a way that they are not too obviously wrong. As users do not have any knowledge of the system beforehand, it is likely that they frequently select wrong answers and become frustrated from the trial and error approach. Therefore, designers of such tutorials should give careful attention to the communication of the outcome of erroneous answers so that they do not lead to reactance from the learner.

Research on interactive user education approaches has led to positive results in educating novice drivers (Pradhan, Fisher, & Pollatsek, 2005; Yamani, Samuel, Knodler, & Fisher, 2006). Considering that these systems are not yet commercially available and users are unfamiliar with driving automation in general, research on efforts towards educating users with ADS need to be undertaken. In the automated driving domain, research on trust and controllability regarding take-over situations provided the first evidence that the familiarization of users with the HMI by means of descriptions, HMI presentations or actual experience, can have beneficial effects (Hergeth et al., 2017; Payre et al., 2017). However, conceptual approaches for teaching users how to interact with driving automation technology are still scarce. Table 10.1 compares the owner's manual and tutorial approaches with respect to education design characteristics.

Table 10.1

Summary of characteristics of manual and tutorial based user education approaches.

Characteristic	Source	Owner's Manual	Interactive Tutorial
Type of learning	Wickens(2015)	Passive Learning	Active learning
	Pradhan et al.(2009) Wickens et al.(2015)	Unguided/uncontrolled learning	Guided learning/ experimental control
Focus of education	van Loggen(2013)	System focused	Use case focused
Type of information	N/A	Correct information only	Presence of distracting information
Degree of realism	Slater(2003)	Abstract representation of HMI	Immersive representation of HMI

10.1.4 Aims and Objectives

The present work has two objectives. The first objective is to determine if an experimental manipulation with respect to user education approaches consisting of an owner's manual or an interactive tutorial as compared with generic information about the system function, would result in more accurate mental models and superior operator performance in automated driving. Secondly, it focuses on a proof-of-concept for educating users in a risk-free environment on a desktop screen before they might be exposed to the task in a real vehicle on the road or in a driving simulator.

This study does not claim to explicitly investigate systematic differences between the two proposed user education approaches. Therefore, the analysis primarily focuses on evaluating each approach as compared to a baseline. Subsequently, it is the task of future research to discover more about the specific mechanisms of learning that underlie each of the two approaches.

On the basis of the considerations outlined above, we hypothesize that both the owner's manual and the tutorial would lead to more accurate mental models regarding the HMI for L2 and L3 automation as compared to mere generic information about the system's functionality. No hypothesis can be stated for a difference between the two treatments since the conceptual difference is based on a combination of education characteristics (see table 10.1). Thus, potential differences cannot be traced back to a single cause. Nevertheless, an exploratory approach has been undertaken by comparing mental model results for the two user education approaches.

Since we expect that the two treatments will support the evolution of accurate mental models of the HMI and the system, interaction performance in both treatment conditions should be enhanced compared to mere generic information. Similar to the experimen-

tal variations above, we follow an explorative approach when comparing the two user education procedures. In addition, due to the task-dependent characteristics of learning (Gagne, 1984), we investigate whether the two user education approaches work as expected in all use cases considered in the study or whether specific use case specific strengths and weaknesses are present.

10.2 Method

10.2.1 Sample

The sample consisted of $N=24$ participants (6 female, 18 male) with $n=8$ participants assigned randomly to each experimental condition. No dropouts were recorded. Mean age of the sample was 33.96 years ($SD=12.99$, $MAX=62$, $MIN=20$). All participants were BMW Group employees, held a German driver's license, and had normal or corrected to normal vision.

10.2.2 Driving Simulation and Driving Automation System

The study was conducted in a fix-base driving simulator (see figure 10.1). The vehicle mockup was identical to a BMW 5 series with automatic transmission and contained all necessary instrumentation. The front channels provided a field of view of 220° and were displayed through five front projectors. The rear view was displayed through three LED screens that were placed behind the vehicle.

The L2 and L3 driving automation carried out longitudinal and lateral vehicle guidance as soon as the driver activated the respective function. The L2 automation let the driver take his/her hands off the steering wheel for 15 seconds before displaying a hands-on request (HOR). The L3 ADS could execute independent lane change maneuvers such as decelerating due to slower vehicles ahead or pulling back to the right lane. There was no restriction in the adjustment of current velocity for L2 automation. At activation, the current velocity was the set speed of the system. For L3 automation, the speed could only be set to speeds slower than 130 km/h. If set to a higher speed, the system would suggest a transition to L2 driving automation. In all cases the set speed of the L3 automation was 130 km/h. The vehicle also included Adaptive Cruise Control which executed the longitudinal vehicle guidance as well as the speed limiter. In reference to SAE (2018), the L3 automation is considered an ADS while the L2 automation is considered a driver support system.

Figure 10.1. Static driving simulator mockup used in the present study.

10.2.3 Study Design and Procedure

The study employed a single-factorial between-subjects design. The between-subjects factor, “*education*”, had three levels which were baseline information (BL), owner’s manual (ML), and interactive tutorial (TL). Participants were randomly assigned to the between-subjects factor. This chapter reports the findings of the mental model formation after the different treatments had been provided and of the interaction performance in a subsequent block of different transitions of control.

Upon arrival, the experimenter welcomed participants and informed consent was obtained. First, the experimenter provided a brief explanation of the purpose of the study. Then, the experimenter outlined which education approach participants would receive and gave a standardized instruction for each condition. The maximum time to complete the educational procedure was 10 minutes in each condition. Having finished the educational procedure, participants completed a mental model questionnaire (see chapter 10.2.7) and were led to the vehicle mockup. Before proceeding to the experimental drive and operating the driving automation, participants completed a short manual familiarization drive to accustom themselves with handling the simulator. Since instructions for the use cases were given through recorded samples, participants were introduced to a sample telling them to change lanes in the familiarization trial. During the experimental drive, participants had to complete two blocks of six interactions each (see chapter 10.2.5). The use cases specific self-report data were collected after each interaction dur-

ing the drive. Participants could not anticipate the instruction of use cases since the experimenter deliberately waited at least 30 seconds from the end of the use case specific inquiry before triggering the instruction to follow. Additionally, upcoming transitions could not have been indicated by external cues such as highway intersections or slow cars ahead. Having finished one block, the participants filled out the block inquiry at standstill on the right shoulder. Traffic density on the three-lane highway was low to medium. The drive lasted approximately 20 minutes. Figure 10.2 schematically depicts the experimental procedure.

Figure 10.2. Schematic outline of experimental procedure

10.2.4 Human-Machine Interface

The visual HMI showed the vehicle and its surroundings in L3 automation and this was displayed on the instrument cluster. While the L2 automation was engaged, icons on the left side of the instrument cluster depicted lateral and longitudinal vehicle guidance. There was no display of the vehicle and its surroundings during active L2 automation. Active L2 and L3 automation were colored differently. Similar solutions for visual automated vehicle HMIs have been proposed by Forster et al. (2016) and outlined in Manca et al. (2015). Thus, the present conceptual approach constituted a representative solution for an automated vehicle HMI (see also chapter 1.4.2). Generally, the HMI is comprised of steering assistance and adaptive cruise control interface features (Naujoks, Purucker, Neukum, Wolter, & Steiger, 2015). Referring to design considerations by Naujoks, Forster, et al. (2017a), the present HMI also contained information about the main state such as lateral and longitudinal guidance, current velocity, and set speed information. It also followed the design principle of redundancy by showing vehicle and surroundings plus icons indicating an active L3 ADS. A countdown provided information about the duration of the automated driving availability during active functioning. The system states were also different if the system was not activated and not available versus not activated and available. This was indicated by the L3 ADS availability icon in the instrument cluster. There were buttons on the left side of the steering wheel

for both the ADS and the driver support functions for the participants to initiate the respective control transition and also to deactivate the function to return to manual driving. The buttons were not illuminated in any automated mode. Participants could switch between different driver support functions (i.e., L2 automation, adaptive cruise control, speed limiter) with one button. The input device included three more buttons (e.g., set speed). For adjusting cruising speed in both L2 and L3, there was a rocker switch among the buttons. The buttons were easily reachable for participants using their left thumb. No restrictions were present for the activation of the L2 automation. In contrast, participants had to meet certain conditions for completing a transition to L3 automation (SAE, 2018). These conditions were: (1) availability of the ADS, (2) velocity below 130 km/h, and (3) lane keeping within a certain lateral margin. Besides pressing the L3 automation button with both hands on the steering wheel, participants could deactivate the ADS and drive manually by accelerating, braking or applying a small force to the steering wheel. Participants could only deactivate the L2 automation by pressing the “*driver support*” button or braking. Accelerating temporarily led to a L1 automation state (i.e., lateral support only). Likewise, applying a force on the steering wheel only led to a temporary L1 automation state of longitudinal support. These temporary states were active until the drivers let go of the respective input.

10.2.5 Use Cases

The present experiment included driver initiated transitions between manual, L2, and L3 automated driving (Naujoks, Hergeth, et al., 2018). A total of six use cases per experimental block were possible from all combinations of upward and downward transitions. Transitions to manual were not regarded in this context since there is evidence that these UCs do not require any learning (see chapter 7). Table 10.2 outlines use cases with transition type, initiation automation level, target automation level, and number of the respective use case. There were six possible sequences of use cases for each block, to which participants were randomly assigned. Therefore, sequential effects could be ruled out. The upward transitions of automated driving were motivated by the driver wanting to be relieved of the driving task itself (UC1, UC2) or the supervising task (UC 3). The downward transition from L3 to L2 automation could be motivated by the user’s wish to deactivate certain functionalities or drive at a higher speed (Naujoks, Hergeth, et al., 2018).

Table 10.2

Overview of use cases for one experimental block.

Transition type	Scenario	Automation level at UC initiation	Automation target level	Use case number
Upward transition	Activation L3	L0	L3	1
	Activation L3	L2	L3	3
	Activation L2	L0	L2	2
Downward transition	Deactivation L3	L3	L2	4

The experimenter triggered standardized samples for the onset of each use case that were recorded prior to the experiment. There was a 10-second delay from the onset of the standardized sample instruction for UC1 and UC3 (transitions to L3) and the availability of the ADS. Therefore, it was not possible for participants to activate the L3 ADS within these 10 seconds. The instruction for transitions to L3 thus included an additional indication to activate the ADS (i.e., “(...) *as soon as it is available*).

10.2.6 User Education Approaches

Baseline Information

Baseline information conveyed merely generic information about the equipped driving automation as reflected in SAE J3016R (SAE, 2018). Participants received a description that the simulated vehicle incorporated a L2 and L3 driving automation. Depending on the situation, both functions would break or accelerate the vehicle and keep distance to the vehicle ahead. In addition, both functions would execute lateral vehicle guidance. The L3 ADS would execute lane changes if necessary. With the L3 ADS, certain NDRTs could be engaged in and the driver did not need to continuously monitor the traffic surroundings. However, the driver needed to resume vehicle guidance upon system notice. In contrast, with the L2 automation, the driver had to continuously monitor the traffic conditions. The baseline information preceded both the owner’s manual and the interactive tutorial.

Owner’s Manual

The owner’s manual was designed in accordance to existing BMW manuals which are characterized by short sentences and listings if possible. It also incorporated graphical

elements of buttons when these were referenced. The document was clearly structured by inserting headings and subheadings. If an information was especially important, it was shown in a separate text box. The owner’s manual was a four-page DIN-A4 text document that users had to read prior to system use. It contained all relevant icons in the instrument cluster and buttons on the operating element. The owner’s manual was structured covering the L2 and L3 relevant HMI elements in successive steps. It provided information about activations, deactivations, and the ODD of the respective functions. Figure 10.3 shows an excerpt of the owner’s manual (originally presented in German language). Note that icons had been disguised due to confidentiality and are represented as grey squares. Specific function names have been replaced by “*L3 ADS*” and “*L2 automation*” for the same reason.

Figure 10.3. Excerpt from owner’s manual. Note that icons had been disguised due to confidentiality and are represented as black squares. Specific function names have been replaced by “*L3 ADS*” and “*L2 automation*”.

Interactive Tutorial

The interactive tutorial was designed using Microsoft PowerPoint. The tutorial showed the operating element (i.e., buttons on the left of the steering wheel), the instrument cluster with the present system state and a driver’s view of the vehicle interior. Next, there was a description of the task including the current system state target system state, and target system name. The four answers included the respective buttons and/or icons

that could appear in the instrument cluster. Participants could select an answer by clicking on the respective box. If a wrong answer was given, a box appeared in the foreground explaining what would happen and that the answer was not correct and redirected the participant to the task. If the answer was correct, the same box appeared telling the test taker what HMI elements would appear and that the answer was correct. The tutorial was finished when all tasks were completed successfully. In the tutorial, each task had only one correct answer. Incorrect answers were derived from an inquiry of the second experiment in this thesis (see chapter 4). Table 10.3 provides an overview of the seven questions in regard to UCs, transition type and restriction as reported in SAE (2018). Figure 10.4 shows a screenshot of tutorial question 1. Note that buttons on the steering wheel and icons in the answer options were disguised due to confidentiality. The function name of the L2 automation has been replaced by “*L2 automation*” for the same reason.

Figure 10.4. Layout of interactive tutorial with operating element (upper left), instrument cluster (upper middle), driver’s view (upper right), user task, and four alternative answers.

10.2.7 Dependent Variables

The mental model questionnaire developed by Beggiato et al. (2015) was adapted for L2 and L3 driving after automation (see table 10.4 for item wording). Participants completed the questionnaire after they had received the treatment and then after the six interactions. However, the present work only reports results from the mental model

Table 10.3

Overview of tutorial questions with corresponding UC, transition, and type of restriction for the transition.

Tutorial question	Relevant UC	Relevant transition	Restriction as of SAE(2018)
1	2	L0→L2	None
2	1	L0→L3	Availability restriction
3	1	L0→L3	Speed restriction
4	1	L0→L3	Lateral guidance restriction
5	3	L2→L3	Availability restriction
6	3	L2→L3	Speed restriction
7	4	L3→L2	None

questionnaire before the drive. The mental model questionnaire included 11 items on a seven-point Likert scale from 1 (“*strongly disagree*”) to 7 (“*strongly agree*”) for both the L2 and L3 automation. Two items covered the participant’s understanding of HMI in general, four items covered the understanding of the HMI with a focus on transition restrictions (SAE, 2018) (SAE, 2018), and five items served as distractors. In the present study, the four items covering HMI and transition restrictions were analyzed (see table 10.4). Items were derived to specifically detect differences between the L2 and L3. Thus, for each item of interest, the opposite end of the scale was correct for the two levels of automation. If “*strongly disagree*” was the correct answer for L2, “*strongly agree*” was correct for L3 and vice versa. In the present experiment, the correct answer for all four items of relevance was 1 (“*strongly disagree*”) for L2 and 7 (“*strongly agree*”) for L3 automation.

Interaction performance was assessed by means of a five-point rating scale, which is described in chapter 6.4.7 and shown in table 6.2.

10.3 Results

No missing data were recorded for self-report or observational measures. The present study included a small number of participants per between-subjects factor, and therefore the use of estimation methods that require assumptions on sample distributions are

Table 10.4

Mental Model questionnaire with item number and item wording.

Item number	Wording
1	There is a speed limitation that must not be exceeded to activate the system
2	Lane keeping is relevant for the system activation
3	The system displays availability to the driver
4	There are road sections where the system is not available

problematic (Nevitt & Hancock, 2001). Therefore, we applied bootstrapping for analyzing the data since this procedure has been found to be robust in cases of heterogeneity and non-normality (Keselman, Wilcox, Othman, & Fradette, 2002). We calculated 95% confidence intervals (CI) for comparisons between the experimental conditions as a state-of-the-art inferential statistics technique (Cumming, 2013; Schäfer, 2018). We report means, upper, and lower bounds of 95% CIs in table 10.5 (mental model L2 automation), table 10.6 (mental model L3 automation) and table 10.7 (interaction performance). Inferential p-values are reported after the rule described in Cumming and Finch (2005). Bootstrap analysis was performed using Matlab R2015b. The code of the bootstrapping procedure to generate $n = 10,000$ data set replicates is shown in figure 10.5.

```

%Set number of bootstrap replicates
nrep=10000;
%Create space for bootstrap replicates
mean_BL=zeros(1, nrep);
mean_ML=zeros(1, nrep);
mean_TL=zeros(1, nrep);
%Start for loop
for i=1:nrep
    %draw a random sample with replacement from each condition
    sample_Baseline=randsample(MM_L3_BL, length(MM_HAF_BL), true);
    sample_Manual=randsample(MM_L3_ML, length(MM_HAF_ML), true);
    sample_Tutorial=randsample(MM_L3_TL, length(MM_HAF_TL), true);
    %calculate mean from each random sample and store in array
    mean_BL(i)=mean(sample_Baseline);
    mean_ML(i)=mean(sample_Manual);
    mean_TL(i)=mean(sample_Tutorial);
end

```

Figure 10.5. Matlab code for bootstrapping procedure.

10.3.1 Mental Model Questionnaire

Results for the mental model are provided separately for the L2 (see table 10.5 and figure 10.6) and L3 automation (see table 10.6 and figure 10.7). Mental models for the L2 automation showed that knowledge about the system in item 1 (speed limitation) and item 3 (availability display) was enhanced in both treatment conditions in a comparable manner. The results revealed bimodal distributions in many cases (e.g., BL item 1 and item 4, figure 10.7). However, the means of these distributions fell right in between the two distribution modes. Consequently, a mean value on the center of the scale as reported in the tables must regard the respective distribution in the according figure. While participants in the baseline condition strongly assumed a speed limitation and availability display for the L2 automation, participants in the treatment conditions were surer that there was no speed limitation ($p < .05$) and did not as strongly assume an availability display ($p < .01$). A large overlap between the conditions was present for item 2 (lane keeping) as indicated by the CIs (see table 10.5). On a descriptive level, participants in the baseline condition showed a trend towards the most correct answers. Thus, no statistically differences in regard to lane keeping relevance for L2 automation were present. Item 4 (road section availability) showed that participants in the baseline condition strongly assumed a restricted ODD, while the distribution for the tutorial condition was spread almost over the entire seven-point Likert scale, and participants in the owner's manual condition showed the best answers (i.e., no restriction of ODD). The difference between baseline and tutorial was not statistically significant. The owner's manual condition differed significantly from both the baseline ($p < .01$) and the tutorial ($p < .05$). Results for the mental model L3 automation showed that the participants in the baseline condition had to guess whether there was a speed limitation or not (item 1). In comparison, mental models for the owner's manual ($p < .05$) and tutorial ($p < .05$) differed significantly from the baseline condition with most participants indicating a strong approval for the statement. Participant understanding of lane keeping relevance, (item 2) in the tutorial condition, was more accurate as compared to the baseline ($p < .01$). On a descriptive level, the owner's manual condition was superior to the baseline, but inferior to the tutorial condition, however, due to a large margin of error, no statistical significance can be inferred. In regard to the availability display (item 3), participants in all three experimental conditions indicated strong approval for the existence of an availability display for the L3 automation. Thus, CIs overlapped to a large degree and no significant differences are present. Answers for item 4 (road section availability) revealed that participants in the baseline were indifferent whether a restricted ODD is present

on the highway or not, which is reflected in a mean of 3.87 (see table 10.6). Compared to the baseline, participants in the owner’s manual condition indicated existence of a restricted ODD ($p<.01$). Participants in the tutorial condition were more accurate on a descriptive level as compared with the baseline, without reaching statistical significance.

Table 10.5

Means and 95% CI upper and lower bounds of bootstrapped mental model distributions for the four relevant items on L2 automation by the three experimental conditions.

	Speed limitation		Lateral guidance		Availability display		Road section	
	Distr.	95% CI	Distr.	95% CI	Distr.	95% CI	Distr.	95% CI
	mean	bounds	mean	bounds	mean	bounds	mean	bounds
Baseline	5.00	[4.00-5.80]	3.75	[2.88-4.20]	6.75	[6.50-7.00]	5.63	[4.63-6.00]
Manual	2.61	[1.13-4.13]	3.88	[2.38-5.50]	4.40	[2.88-5.88]	2.37	[1.38-3.63]
Tutorial	2.62	[1.13-4.13]	5.01	[3.88-6.00]	4.76	[3.25-6.13]	4.37	[3.50-5.25]

Figure 10.6. Frequency [N] of L2 automation mental model ratings [1–7] for the four relevant items (columns) by experimental condition (rows 1–3: baseline grey, owner’s manual blue, tutorial green).

Table 10.6

Means and 95% CI upper and lower bounds of bootstrapped mental model distributions for the four relevant items on L3 ADS by the three experimental conditions.

	Speed limitation		Lateral guidance		Availability display		Road section	
	Distr. mean	95% CI bounds	Distr. mean	95% CI bounds	Distr. mean	95% CI bounds	Distr. mean	95% CI bounds
Baseline	4.00	[2.50-5.38]	3.50	[2.63-4.50]	6.01	[5.00-6.75]	3.87	[2.63-5.13]
Manual	6.27	[4.75-7.00]	5.01	[3.50-6.38]	5.99	[4.75-7.00]	6.38	[5.13-7.00]
Tutorial	6.12	[4.75-7.00]	6.00	[5.50-6.50]	6.50	[6.21-6.87]	5.37	[4.38-6.38]

Figure 10.7. Frequency [N] of L3 ADS mental model ratings [1–7] for the four relevant items (columns) by experimental condition (rows 1–3: baseline grey, owner’s manual blue, tutorial green).

10.3.2 Interaction Performance Ratings

Results for observational measures (see table 10.7 and figure 10.8) in UC1 revealed that both the owner’s manual and the tutorial led to superior performance in activation of the L3 ADS as compared with the baseline. In addition, the participants that had read the owner’s manual showed better performance than the participants that had received the tutorial. Activation of L2 (UC2) showed that both the owner’s manual and the tutorial significantly increased performance with no difference between the two conditions. Transitions from L2 to L3 (UC3) showed that best performance was achieved in the tutorial condition where participants performed significantly better than in the

baseline and in the owner’s manual condition. Baseline and manual conditions did not differ significantly. Eventually, no differences among all three conditions were observed for the transition from L3 to L2 automated driving (UC4).

Table 10.7

Means and 95% CI upper and lower bounds of bootstrapped mental model distributions for the four relevant items on L3 ADS by the three experimental conditions.

	UC1		UC2		UC3		UC4	
	Distr. mean	95% CI bounds	Distr. mean	95% CI bounds	Distr. mean	95% CI bounds	Distr. mean	95% CI bounds
Baseline	3.50	[3.00-3.88]	3.38	[2.63-4.00]	2.87	[2.13-3.50]	2.75	[2.13-3.50]
Manual	1.88	[1.25-3.63]	1.88	[1.25-2.63]	2.63	[1.87-3.38]	3.00	[2.50-3.50]
Tutorial	3.00	[2.50-3.50]	1.87	[1.38-2.38]	1.38	[1.00-2.13]	2.87	[2.13-3.63]

Figure 10.8. Frequency [N] of experimenter ratings [1–5] in each use case (columns) by experimental condition (rows 1–3: baseline grey, manual blue, tutorial green).

10.4 Discussion

The present driving simulator study investigated the effects of two different user education approaches which were (a) the owner’s manual, and (b) an interactive tutorial on mental model formation and human-automation interaction, in comparison to (c) a

generic functionality description (SAE, 2018). We hypothesized that participants in the owner’s manual and interactive tutorial conditions would have a better understanding and show superior operator behavior as compared with the group that had only received a generic description. In a between-subjects design, $N=24$ participants were randomly assigned to one of three treatment groups (i.e., baseline, owner’s manual, tutorial). Having finished the respective education, the mental model was assessed and subsequently, drivers completed several transitions between manual, L2, and L3 automated driving. The results showed that both owner’s manual and tutorial led to more accurate mental models and improved interaction performance as compared with the baseline. In addition, a use case specific trend was observed since only trained participants showed better performance than untrained participants in first-order use cases (i.e., transitions from manual to L2/L3) as compared with second-order use cases (i.e., transitions between two levels of automation). The results suggest that user education approaches, as conceptualized in the present study, significantly add to a better understanding of automated vehicle HMIs and this knowledge is also transferable to users’ interactions with the driving automation system. The following paragraphs discuss findings and limitations of the present results and derive practical implications.

10.4.1 Mental Model

Interpretation of the results of mental model formation must consider that the items focused on system restrictions that existed for L3 and not for L2. Both user education approaches communicated this difference by introducing the restrictions for the L3 function while not mentioning these for the L2 function. As a consequence, the only way to identify the non-existence of the restrictions for L2 automation was by inferring this from the fact that it was not mentioned in the respective treatment.

Results for L2 mental models (figure 10.6 and table 10.5) showed a trend towards more correct answers in the treatment conditions, especially for the speed (item 1) and availability restriction (item 3 and item 4). Both approaches were successful in conveying that the ODD restrictions do not exist for L2 automation. No difference was apparent for the lateral guidance item (item 2). This result might be due to the fact that understanding and terminology of lane keeping is difficult for users, and it also corroborates evidence on mental model formation for the aspect of lane keeping from chapter 8. A slightly different picture emerged for the formation of mental models of L3 automation where ODD restrictions for activating driving automation are present. While both user education approaches could deliver first evidence for conveying speed (item 1) and avail-

ability of road sections (item 4), there was no difference apparent for an availability display (figure 10.7 and table 10.6). However, this result is due to user expectations in the baseline. This group showed a strong trend towards assuming that an availability display existed. Consequently, there is no room for additional improvement here. Therefore, the diagnostic benefit of this item for L3 mental model assessment is rather small. What has not been assessed, however, is the degree of users' certainty when answering mental model items. It is speculated that although the present results did not show a difference between the conditions, participants in the two treatment groups should be more certain about their indication, while baseline participants might rather have indicated their expectation of the HMI. Concerning lateral position ODD restriction, the present study found a descriptive trend that users in the owner's manual condition gave more correct answers as compared with the baseline. A strong shift towards the correct answer was observed for the tutorial. This finding is explained through the use case focus of the tutorial, since one of seven questions specifically addressed this restriction. In comparison, the owner's manual only mentioned the importance of lane keeping within a larger set of paragraphs. This result supports considerations based on Wickens et al. (2015), who found that use case specific user education is more beneficial than system specific where users can get lost in the complexity of the information.

Mental model findings for L2 and L3 automation highlight the importance of user education for forming an accurate understanding of the automated vehicle HMIs. There was no clear superiority of either of the education approaches. It seems like when it comes to abstract questions (e.g., item 4, "*there are road sections where the system is not available*"), owner's manual approaches are more beneficial than tutorial approaches. On the other hand, if items are not abstract but rather align closely with a scenario that had been taught in the tutorial (e.g., item 2 and tutorial question 4), the results turned out to favor the latter.

The results of the mental model questionnaire might also hold important implications for mode awareness issues. Feldhütter et al. (2017) among others have shown that users frequently cannot discriminate between L2 and L3 automation based on HMI and functionality alone. Therefore, we assume that users also have a better understanding of current system states when being supported with knowledge on how to complete control transitions. From their own actions they should be able to infer the correct system state and not confuse L2 and L3 as frequently as without information on control transitions. However, to verify this assumption future research is necessary.

10.4.2 Interaction Performance

The present findings support the a priori stated hypothesis that user education improves interaction performance with driving automation. However, this finding does not apply to all use cases, but is limited to a specific pattern (see figure 10.8 and table 10.7). The owner’s manual provided the most support when completing the transition from manual to L3 automation. In contrast, the tutorial delivered the best interaction results when participants were driving with L2 automation before performing the transition to L3. Both education approaches showed the same superiority over the baseline information for the transition from manual to L2 automated mode. However, this superiority was not present for either condition when participants were driving in L3 automated mode before performing the transition to L2. Therefore, perhaps the target system state is not only important for interaction performance, but also the preceding system state. In the present study, the owner’s manual approach did not provide any better results as compared with the baseline for transitions between automation levels. UC3 and UC4 require preceding transitions to the respective level (i.e., L2 for UC3 and L3 for UC4). Therefore, learning mechanisms from the preceding interactions come into play. These might interfere with the information that users have gained from either the manual or the tutorial. Similarly, chapter 7 describes learning effects between different transitions of automation levels when evaluating HMIs for driving automation. Referring to results from the mental model, interaction measures support the reasoning that user education is especially beneficial in first-order use cases. However, the procedural knowledge about the automated driving HMI that is gained through interaction significantly influences subsequent trials. Once there was a successful interaction with the driving automation (which was always the case in the present study), this experience more strongly influenced subsequent behavior than declarative knowledge from the prior treatment. On the other hand, this reasoning is contradicted by the results of extremely good performance in UC3 in the tutorial group in comparison with the owner’s manual and the baseline groups. This data show barely any variation of the experimenter rating. It might be that this observation is an artifact of the ordinal nature of the experimenter rating itself. The step from the category at the top end of the scale (i.e., category “*no problem*”) to the middle of the scale (i.e., category “*minor problems*”) is considerably small. As a consequence, there is a need for future research that applies interval scale observational measures such as error rates and time on task (Wickens et al., 2015) in order to more closely determine the differences between first and second-order interactions. Even though experience with the system seemed to largely influence interaction behav-

ior, the present results emphasize the important role of user education for successful interaction with driving automation. It seems that an interplay of prior education and learning from these first-order interactions is present. Therefore, vehicle manufacturers and employers of driving automation might consider supporting users with information material prior to first use, as these are influential for subsequent interactions. At the same time, automated driving development needs to consider that interface design itself results in learning that adds to the content from tutorials and owner's manuals. Thus, even when users activate L3, they learn how to activate parts of the L2 automation, or at least can rule out other possible operating paths.

On the basis of prior considerations of the role of task interference between operating in-vehicle HMIs and performing the DDT, this study provides evidence that user education has beneficial effects for a safer and more efficient transition from manual to automated driving mode. User education in the area of driving automation is of utmost importance because first contacts with combined automation and ADAS are challenging for users. The mitigation of ineffective and inefficient human operator performance with driving automation plays an important role not only for proximal goals of safety and effectiveness, but also for the more distal adoption of this technology with ease of use being a precursor of intention to use (Davis, 1989). Valuable insights for technology adoption can be gained by considering research on automation in aviation (Sarter et al., 2007; Trösterer et al., 2017) where the training approaches for pilots have been successfully established. Trösterer et al. (2017) outlined how pilots practiced operating an airplane under fully functional and defective conditions in both simulation and real-world environments. Such educational approaches, however, are most likely not applicable for driving automation since the user population is much larger as compared with the small number of pilots and the enormous time and financial costs of such trainings. While automated driving users must be considered as novices when it comes to using automation (C. A. Hart, 2019), aircraft pilots are highly skilled and trained individuals when operating an automated system. We must conclude that the driving automation domain faces different conditions from that of the aviation sector. Nevertheless, there is the same need for user training and regulation thereof.

A combined view of results in the mental model questionnaire and interaction performance shows that at first, user education positively impacts the knowledge on how to interact with driving automation. This knowledge is then transferred to actual application when encountering a combined ADAS and automation function. However, one has to take into consideration that the declarative knowledge is rather transferred to

first-order use cases of transitions from manual as compared with second-order use cases of transitions between levels of automation.

Directly comparing the owner’s manual and the tutorial showed that no clear advantage of one approach over the other was present. There was no larger issue detected for the transfer of information from abstract system description in the owner’s manual to the application context in the automated vehicle. The use case focus of the tutorial did not show a clear advantage for the outcome of the experimenter rating and this finding does not support prior considerations based on Wickens et al. (2015). We explanation for this is the fact that the tutorial, as designed for this study, also conveyed information in a comparably complex way for the participants through the presence of erroneous answers. In addition, there was no clear advantage of active and guided learning as compared with passive and unguided learning. This result might also be due to the combined complexity of the questions and distractors. The users might also have gotten lost in the tutorial itself rather than only in the owner’s manual (Wickens et al., 2015).

10.4.3 Limitations and Future Research

The two user education approaches in this study were used as stand-alone procedures. Hence, both of them suffer from specific drawbacks (see table 10.1). For example, the owner’s manual does not support strict experimental control in terms of objectivity and is passive in its nature of learning. Major drawbacks of the tutorial are the degree of complexity which is mainly due to the high amount of incorrect answers and the necessary trial-and-error approach that users have to take without being provided with any information on the HMI beforehand. Thus, a combination of both approaches in the form of a system-focused information presentation by means of the owner’s manual and subsequent guided-learning objectives test might be more suitable. Such approaches are frequently used in web-based trainings by large companies to ensure that their employees have an understanding of their roles and responsibilities within the working context (McIlwraith, 2016).

The number of participants in the present study was rather small when considering the between-subjects design leading to a sample size of $n=8$ per condition. Cumming and Finch (2005) recommend a number of $n=10$ when applying CI approaches for determining statistical inference. The aim of the present research, however, was to find out about differences and trends of user education concepts and these can well be inferred from the present data and the applied statistical method. Subsequent investigations should consider collecting larger samples to ensure statistical robustness.

Furthermore, there was only one behavioral measure included in the present analysis. The question of how behavioral indicators on a more operational level (Michon, 1985) such as speed and accuracy (Wickens et al., 2015) benefit from user education remains to be answered. One also has to consider that the experimenter rating, as used in the present study, represents a rather conservative performance indicator compared to time-on-task and error rates, and in chapter 7 did not show strong performance increases in repeated interaction with driving automation. In this study, despite the standardized approach in applying the experimenter rating, there still remained room for interpretation for the experimenter. As far as possible we counteracted this by assigning specific errors (e.g., pressing a wrong button, unintendedly deactivating the function) to each category for all use cases. Nevertheless, we cannot categorically rule out a certain bias. Hence, further research efforts are necessary, including a blind rating process by multiple raters and subsequent comparison of these by means of inter-rater reliability measures. Additionally, the open question of how long performance gains from user education are apparent over repeated trials of interaction remains to be answered. Considering that first-order interactions (UC1, UC2) affect performance in second-order interactions (UC3, UC4), it is likely that benefits from user education are not only evident at the very first but also at the same time as most critical encounters with driving automation. The same holds true for mental models. With a superiority of user education present, it remains unclear, whether and how fast non-educated users catch up with informed users. In that vein, it is also the role of future research to learn the implications of training on mental models and operator performance over a longer course of time. The present study found effects of education on single trials within a short simulation drive. However, users of driving automation might also be trained for long-term effects, and retrained in case new functionalities are added to the automated vehicle via over-night updates. Moreover, automated vehicle HMIs will most likely differ between OEMs and thus the question arises as to how to train users so that when changing to another automated vehicle their understanding and appropriate performance are ensured.

This study showed that an approach based on the owner's manual contributes to formation of accurate mental models and increases interaction performance. However, for an application under real-world conditions, there is the issue that less than half of the users will read the owner's manuals (Mehlenbacher et al., 2002). From this group, there might still be a large estimated number who preferred to skim through the owner's manual and not fully understood the presented information. Therefore, it

is questionable whether the positive effects of stand-alone owner's manual-based user education procedures emerge for the introduction of combined automation and ADAS to the consumer market. In addition, as outlined in the prior considerations, information about automated vehicle HMIs is not presented separately but rather within a booklet that can be composed of up to 500 pages. Despite the positive effects of the owner's manual found here, it remains to be seen whether future users find this information and apply it accordingly after having read additional information on vehicle maintenance, warnings, and much more.

In the present analysis, we calculated mean instead of median values as the measure of central tendency even though the experimenter rating is ordinal in nature. This procedure is supported by Norman(2010) who describes the applicability of parametric statistical methods on ordinal data. Prior research on controllability have also used Cooper–Harper scale items and applied parametric approaches on them (Kauffmann et al., 2018; Naujoks, Purucker, Neukum, Wolter, & Steiger, 2015; Neukum et al., 2008). The present work followed an applied research purpose to investigate the applicability of two user education concepts. Thus, results of increased mental models and interaction performance cannot be traced back to a single variation between the two conditions but rather to a combination of several factors. There is a need for future basic research to determine how each approach individually might be improved or impeded by systematically varying conceptual characteristics.

This chapter comprehensively outlined the conceptual development of two educational procedures. Moreover, the study reported herein served as a first proof-of-concept for the manual and the tutorial. The following chapter builds on the insights gained here and additionally combines the two procedures. It will take a methodology oriented perspective on user education and examine the influence on satisfaction, understanding and interaction behavior with driving automation in a detailed manner. From that, advantages and disadvantages of educational procedures in user testing are discussed.

11 What and how to tell beforehand: The Effect of User Education on Understanding, Interaction and Satisfaction with Driving Automation ¹⁰

Abstract: The success of introducing automated driving systems to consumers will depend on an appropriate understanding and human-automation interaction with this technology. Educating users with driving automation technology bears the potential to attain these two requirements. In a driving simulator study, we investigated the effects of user education on mental models, human-automation interaction performance (i.e., time on task, error rate, experimenter rating) and satisfaction with a Human-Machine Interface (HMI) for automated driving. $N=80$ participants were randomly assigned to one of three different user education conditions or to a baseline. Subsequently, they completed several driver-initiated control transitions between manual, Level 2 (L2) and Level 3 (L3) automated driving. Results revealed that user education promoted accurate evolution of mental models of driving automation. These in turn facilitated interaction performance in transitions from manual to both L2 and L3 automated driving. There was no comparable influence of prior education on performance in transitions between the automation levels. Due to the performance enhancing effects of user education, no further improvements of interaction performance were observed for educated users in comparison to uneducated users. There was no effect of user education on satisfaction. The current findings emphasize the necessity to provide information about automated

¹⁰This chapter is based on a previous publication: Forster, Y., Hergeth, S., Naujoks F., Krems, J. F. & Keinath, A. (2019). What and how to tell beforehand: The Effect of User Education on Understanding, Interaction and Satisfaction with Driving Automation *Transportation Research Part F: Traffic Psychology and Behaviour*, 68, 316–335. doi.org/10.1016/j.trf.2019.11.017

vehicle HMIs to first-time users to support accurate understanding and behavior. Based on the current findings, we propose first conceptual approaches to teach users and derive implications for user studies on automated vehicle HMIs.

11.1 Introduction

The present chapter investigates the effects of user education approaches on behavioral measures, mental model evolution and satisfaction with an automated vehicle HMI. While in the preceding chapter, the focus was more conceptually oriented, this chapter's focus lies on methodological issues when educating users with driving automation.

The need to develop and test user education approaches is described from a methodological and theoretical perspective at first. Following this, first empirical evidence on educating and training users is reported and open research questions are derived eventually leading to specific hypotheses for the present study.

11.1.1 Directions and Challenges in Automated Driving Research

By providing a priori knowledge about HMI and system functioning, human factors research can directly target one of the two challenging factors mentioned in chapter 1 (i.e., novice users) while the other (i.e., system complexity and design) remains an engineering challenge. That being said, first and foremost research and development needs to consider appropriate HMI design with a user-centered perspective. The present work does explicitly not support the introduction of user education approaches as a countermeasure for poor interface design. Instead, the development and deployment of education approaches marks an additional challenge to HMI and function development for a successful market introduction. It must be noted here that through good interface design, the demand for user education might be reduced to a certain degree but most likely it cannot be eradicated.

11.1.2 Educating Users with Driving Automation

As a consequence of the preceding reasoning, there is need to investigate user education approaches from both a methodological and a theoretical point of view. Research methodology can greatly benefit from user education in driving automation studies since

to date, there is no common agreed-upon approach on whether and how to treat participants before engaging in HMI testing. Moreover, both legal authorities and the scientific community have called for development of user education approaches. Eventually, from a theoretical perspective it remains to be seen whether user education leads to a better understanding about HMI functionality and is directly transferred into adaptation of behavior (Rudin-Brown, 2010).

Methodological Backlog

First, from a methodological point of view, there is no agreed-upon approach when it comes to inform participants in user studies before valid empirical data can be collected. Familiarization and user education in such studies are often rather unstructured, and to date there is standardization or best practice recommendation. For example, on the one hand there are studies which only included a brief description of the automated driving function (Forster, Naujoks, Neukum, & Huestegge, 2017). On the other hand, there are studies that included comprehensive familiarization drives with additional experimenter descriptions (Louw & Merat, 2017; Beller et al., 2013). To contribute to method development for automated vehicle HMI evaluation, the current study investigated effects of user education approaches regarding observational and self-report measures. This provides researchers and developers of automated vehicle HMIs with insights into facilitating effects of a priori treatments when users interact with driving automation technology.

Calling for User Education

Regulatory entities such as the National Highway Traffic Safety Administration (NHTSA) have recently published the automated vehicles policy (NHTSA, 2016). This policy – among other issues such as the HMI design and functionality itself – explicitly calls for appropriate consumer education approaches. Hence, ADS providers should strive to “[...] *provide the target users the necessary level of understanding to use these technologies properly, efficiently and in the safest manner possible*” (p.24). Similarly, Pradhan et al. (2019) report the outcomes of a round table discussion on the need for user education in automated driving. Referring to this need to develop training approaches for L2 driving automation, Casner and Hutchins (2019) outline that three kinds of knowledge must be incorporated. These are (1) knowledge about the automation in form of mental models, (2) knowledge about the user and (3) knowledge about the changed task in terms of how to assess and comprehensively describe interaction performance under changed circumstances of automation. A recent survey by Abraham, Reimer, and

Mehler (2018) investigated user preferences for learning procedures of in-vehicle technology (especially ADAS). The authors found that learning success is determined by the fit between the users' preferred method and the actually applied method among others. Moreover, the study reports that users wish for assistance about in-vehicle technology from an expert or dealership plus additional information through websites, owner's manuals or computerized assistance. In fact, user education for automated systems has a longstanding precedent. Bainbridge (1983) emphasized the role of proper user education of users of any kind of automated system more than three decades ago. These examples make obvious that both regulatory entities and the scientific community regard user education for driving automation as an integral part of technology development.

Theoretical Considerations

From a theoretical point of view, the current research aims to facilitate understanding and interaction with driving automation by means of supporting a priori knowledge. There is empirical evidence on how procedural knowledge (Anderson & Lebiere, 2014) in form of repeatedly interacting with a certain technology updates mental models (Blömacher et al., 2018; Beggiato et al., 2015) and leads to behavioral adaptations (Naujoks & Totzke, 2014; Winkler et al., 2018). Mental model formation solely based on experience without or only with incomplete prior education involves the danger of inaccurate mental model formation. This can also translate into lower trust and acceptance (Beggiato & Krems, 2013). Similarly, Seppelt and Lee (2019) provide evidence that continuous dynamic feedback during experiential learning can support driver understanding. This, in turn exerts a positive influence on trust and reliance in vehicle automation. Since in-the-wild experiences of automation features do not guarantee a comprehensive encounter of potential system limitations, the mental models for frequent scenarios will most likely be more accurate. In contrast, user' mental models cover rather infrequent scenarios such as weather conditions (*"ACC works in the fog"*, Beggiato & Krems, 2013) or lateral vehicle guidance (*"Lane keeping is relevant for system activation"*, see chapter 7) less well. Moreover, there is recent work (Abraham et al., 2017; Homans, Radlmayr, & Bengler, 2019) that even the mere name of an automated vehicle function fosters certain expectations towards capabilities and limitations of these. Consequently, one has to assume that the mental model that users establish will also be influenced by external factors such as the manufacturer's reputation (Forster, Kraus, et al., 2018) or the function's name itself (Abraham et al., 2017). These examples show that both experiential learning and external factors influence the mental model forma-

tion. However, they bear the danger of leading understanding of this technology astray. Wege et al. (2014) point out that improperly formed mental representations can trigger misuses of the system leading to potentially dangerous situations. In contrast to this learning from actual experience approach, the present study aims at teaching users before interacting with driving automation. Therefore, the user education approaches rather support declarative knowledge about HMI and system functioning. However, since these two components of memory modules are not mutually exclusive and completely separate from each other (Anderson et al., 2004), the users are also expected to learn about productions (i.e., how to do things). The combination of declarative and procedural knowledge gained from prior information is transferred into larger parts of procedural knowledge through the experience gained during subsequent interaction. The mental model concept (Durso & Gronlund, 1999) is closely related to the representation of procedural knowledge. Mental models are not characterized by mere knowledge about facts but rather as a comprehensive understanding about driving automation technology. By forming mental models, the user has to incorporate knowledge about system capabilities, limitations, environmental circumstances and user actions among others. Hence, the mental model is not only knowledge about simple facts since the user has to transfer facts into a meaningful context (e.g., traffic surroundings) and anticipate the effect of certain courses of action (e.g., activating the ADS while driving at a certain speed). From that we expect that more accurate mental models are formed through prior user education, which, in turn is translated into superior human-automation interaction. Support for this theoretical approach can be found in Rudin-Brown (2010) stating that mental models are translated in task performance on a strategical, tactical and operational level (Boer & Hoedemaeker, 1998). By educating users of driving automation, the present research aims at supporting declarative knowledge prior to first encounters with automated vehicle HMIs. Furthermore, prior knowledge of automated driving should support users both in information selection (e.g., visual attention allocation) and encoding (e.g., adding incoming information to a coherent knowledge structure).

11.1.3 Existing Empirical Evidence

In automated driving research, there have been efforts to inform users prior to first time use and find out how it affects both behavior and attitudes. There are studies that used textual information to inform participants about automation capability. For example, Beggiato and Krems (2013) presented different descriptions of automation capability to users and found that it affects the evolution of mental models, trust and acceptance of

L1 automation. Similarly, Körber et al. (2018) found effects of initial information on trust evolution for L3 automation which is also reflected in reliance behavior. In a recent study on L4 automation, Price, Lee, Dinparastdjadid, Toyoda, and Domeyer (2019) provide evidence that variations in responsibility-instructions focusing on either the automation or the driver (i.e., L2 vs. L4) impact gaze behavior during active automation. Such approaches resemble owner’s manual descriptions for driving automation and mark one possibility to educate users of driving automation. Driving simulator studies on prior familiarization with L3 automation have been conducted focusing on facilitating take-over requests (Hergeth et al., 2017; Payre et al., 2017; Sportillo et al., 2018). These studies provide evidence for the efficiency of training programs. Results by Hergeth et al. (2017) support the assumption that more information and a higher degree of immersion with a take-over request during a training session leads to faster reaction times and lower self-reported criticality. Support comes from Payre et al. (2017) who showed that elaborated training in form of textual information, questions and a tutorial video decreased response times to an emergency take-over request in comparison to a simple training procedure. Sportillo et al. (2018) compared an immersive virtual reality (VR) familiarization with an owner’s manual and a driving simulator experience. The authors of this study found that both behavior (e.g., reaction time, lane deviation) and self-reports (e.g., appreciation, simulator sickness) were superior for the VR and driving simulation in comparison to the owner’s manual procedure. These studies have in common that they support users with different amounts of education. Here, highly elaborated procedures have been compared to simple education procedures or no education at all. Thus, we conceptualize user education from a top-down perspective. This means that from combined approaches such as description plus exposure (Hergeth et al., 2017) or description plus tutorial plus simulator training (Payre et al., 2017), the components are successively withdrawn until only a simple or no education at all remains for comparison. In a recent study Noble, Klauer, Doerzaph, and Manser (2019) exposed users of ADAS for either a conventional training protocol, self-learning through an owner’s manual or an experimental (multimedia) training protocol. The authors found that the training strategies only lead to small differences in knowledge, behavior and attitudes of the users. Due to the realistic driving study context, the level of automation is restricted to L2 automation. Hence, the resulting system and interface complexity cannot be compared to L3 automation.

The present study targets human-automation interaction with a usability focus (DIN-EN ISO, 2011) investigating effectiveness, efficiency and satisfaction. Satisfaction marks one

of three pillars for usability evaluation (DIN-EN ISO, 2011) and in the context of testing automated vehicle HMIs, an important methodological aspect lies in the agreeableness between preference and performance (Nielsen & Levy, 1994) when interacting with such interfaces (see chapter 3). There is first evidence that despite changes in behavior and mental models, satisfaction remains on a constant level (see chapters 7 and 8). Due to this observation, the present study also assumes that satisfaction with an interface for automated driving remains unaffected by user education.

11.1.4 Research Question and Hypotheses

Based on the considerations outlined above, the research question of the study at hand is to determine how users of driving automation can be educated to support HMI understanding and interaction. The present research follows a top-down approach when it comes to comparing effects of the amount of user education. This means that we originate from an existing two-step user education approach and systematically withdraw components. The following hypotheses are derived:

- H1: Users' initial understanding of driving automation and ODD-restrictions is more accurate if there is more user education available.
- H2: Users show more efficient and effective human-automation interaction performance if there is more user education available.
 - H2a: Users show superior performance in initial contacts with driving automation if there is more user education available.
 - H2b: Users show smaller learning effects from the first to the second contact with driving automation if there is more user education available.
- H3: There is no effect of the amount of user education on self-reported satisfaction.

11.2 Method

The present method includes the driving simulator, HMI, Driving Automation System, Use Cases and User Education approaches as described in chapter 10.2. This section separately describes the specifics concerning study design and procedure, dependent variables and the analyzed sample.

11.2.1 Sample

A total of $N=85$ participants took part in the driving simulation study. We recorded $n=5$ drop outs due to technical difficulties ($n=2$) and non-adherence to the experimenter's instructions ($n=3$). This left $n=80$ participants for data analysis (27 female, 53 male) with each of the four experimental groups including $n=20$ randomly assigned participants. Mean age of the final sample was 28.39 years ($SD=8.79$, $MAX=58$, $MIN=18$). All participants were BMW Group employees, held a German driver's license and had normal or corrected to normal vision. Participants that had taken part in user studies on automated driving (i.e., L2 or L3) were not considered for participation. The demographic questionnaire additionally screened for experience with Advanced Driver Assistance Systems (ADAS). Participants could indicate whether they had experience with a certain ADAS or not. 88.75% of the sample ($n=71$) had experience with cruise control and 43.75% ($n=35$) had experience with Adaptive Cruise Control (ACC). 49% of the sample ($n=49$) had experience with Lane Keeping Assistance.

11.2.2 User Education Conceptualization and Design

User Education (also referred to as "*treatments*") was designed as a two-step procedure, which included (1) textual information that the learner receives and (2) a subsequent interactive tutorial. This combination of textual information and a tutorial resembles the elaborated training as reported in Payre et al. (2017). Theoretically it is also possible to provide the users with one of the two approaches separately. The two concepts are described in detail in chapters 10.1.2 and 10.1.3. From here on, the two-step procedure will be referred to as "*Manual+Tutorial*", (ML+TL) while the stand-alone procedures are referred to as "*Manual*" (ML) and "*Tutorial*" (TL), respectively. In addition, the baseline (BL) consisted of a standardized description of the driving automation as reported in J3016 (SAE, 2018). The baseline information preceded the owner's manual, the interactive tutorial and the combination of these. It described that the simulated vehicle incorporated a L2 and L3 driving automation as follows: Depending on the situation both functions (i.e., L2 and L3) would break or accelerate the vehicle and keep distance to the vehicle ahead. In addition, both functions would execute lateral vehicle guidance. The L3 ADS would execute lane changes if necessary. With the L3 ADS, certain defined non-driving related tasks can be engaged in and the driver does not need to continuously monitor the traffic conditions. However, the driver needs to resume vehicle

guidance upon system notice. In contrast, the driver has to continuously monitor the traffic conditions with the L2 driving automation.

11.2.3 Study Design and Procedure

The study employed a 2 x 4 (block x education) mixed within-between design. The within-subject factor “*block*” had two levels and reflects the first and second contact for each UC. The between-subjects factor “*education*” had four levels which were baseline information, the two stand-alone procedures owner’s manual and interactive tutorial and the two step procedure owner’s manual plus interactive tutorial. In the tutorial-only condition, participants only received the BL before the actual treatment information but no information beyond such as information about the questions or UCs. Thus, they had to learn based on a trial-and-error approach. Participants were randomly assigned to the between-subjects factor.

Upon arrival, participants were welcomed and gave informed consent. After an explanation of the study purpose, the experimenter briefly outlined which education participants would receive and gave a standardized instruction for each condition. The participants could then complete the respective education procedure and were granted no more than ten minutes to do so. Having finished the education approach, participants completed the mental model questionnaire (see Dependent Variables) and were led to the vehicle mockup. To accustom themselves with the simulator setup, participants completed a five-minute manual familiarization drive. The experimenter explained that UC specific instructions would be given through recorded samples. To familiarize themselves with the recorded samples for experimenter instructions, the familiarization drive included an instruction to change lanes. The subsequent experimental drive included two blocks of interactions between the driver and the driving automation systems each (see section Use Cases). To avoid anticipation of UC instructions by the participants, the experimenter waited a minimum of 30 seconds after the UC specific inquiry to trigger the next UC. There were no external factors (e.g., slow car ahead, intersection) that could have indicated an upcoming transition. After each block, the driver was told to pull over to the right shoulder, stop there and complete the block inquiry. Participants completed the drive on a three-lane highway with low to medium traffic density. The experimental drive lasted approximately 20 minutes. Figure 11.1 schematically depicts the experimental procedure.

Figure 11.1. Schematic outline of experimental procedure

11.2.4 Dependent Variables

The present chapter applied the same mental model questionnaire as outlined in chapter 10.2.7. Moreover, behavioral measures of interaction performance (i.e., time on task, error rate, experimenter rating) are comprehensively described in chapter 6.4.7. Additionally, participants completed the SUS (see chapter 6.4.7).

11.2.5 Statistical Procedure and Data Analysis

Driving simulation data was pre-processed and visualized using Matlab Version R2015b. Statistical test were calculated using IBM SPSS Statistics Version 23. To determine whether initial user education affects mental models, relevant items for both L2 and L3 after the experimental variation were analyzed descriptively with additional standard errors as an indicator for inferential conclusions (Cumming, 2013; Schäfer, 2018). Satisfaction was analyzed through a one-factorial between-subjects ANOVA. Given that the error rate is count data in nature, we report the parameter lambda (λ) to describe the Poisson distributed data. Here, λ represents the mean and standard deviation of the distribution (Plan, 2014). Despite the count data nature of error rate, the ANOVA approach was followed for inferential analysis since the discrete number of button presses represents a quantitative attribute in increasing number (Tabachnick & Fidell, 2007). Testing for overall influence of experimental factors, data for the experimenter rating, time on task and error rate were analyzed by means of a 2x4x4 (block x education x use case) mixed within-between ANOVA. To more specifically test the a priori stated hypotheses, we applied a planned contrast analysis. To answer hypothesis 2a, three between-subjects contrast analyses were performed for each UC and performance measure in the first block resulting in a total of 36 F-statistics to test for the influence of user education at initial contacts. The two stand-alone procedure conditions (i.e., ML and TL) were combined and compared to the respective other conditions since no specific hypothesis concerning superiority of one over the other stand-alone approach could be stated. The three contrasts thus included the two-step procedure versus the combination

of the two stand-alone procedures, the combination of the two stand-alone procedures compared to the baseline and the two-step procedure compared to the baseline. To answer hypothesis 2b, three within-subject contrast analyses were performed for each UC and performance measure resulting in a total of 36 F-statistics to test for learning effects from the first to the second block. The three contrasts thus included the increases of the two-step procedure, combined stand-alone approaches and baseline. A first investigation with $N=24$ participants served as the manipulation check of first versions of the manual and the tutorial. The results of the manipulation check are reported in the previous chapter. Subsequently to this manipulation check, the two educational procedures were adapted according to semi-structured interviews with the participants leading to the final version applied in the present study.

The preference-performance relationship was analyzed as described in chapter 6.4.8. Due to the finding that the relationship was only present at the first block (see figure 7.2 and table 7.6), only the first block was analyzed here. Moreover, only the four transitions of interest as reported in the present chapter were used for aggregating the respective performance indicator. The SUS score also served as the preference measure. Performance measures (i.e., experimenter rating, time on task, error rate) were identically aggregated across use cases, inverted and z-scored.

11.3 Results

11.3.1 Mental Model

Results for the mental model are shown in figure 11.2. In L2 automation, the correct answer for all four items of interest was 1 („*strongly disagree*“). Descriptively, participants in the ML+TL condition showed best results being closest to 1 for all items. Both stand-alone procedures were on a comparable level besides for the availability display that revealed a slight advantage of the TL group over the ML Group. Results of the BL group were mostly close to guessing probability (i.e., “*neither agree nor disagree*”, category 4). Concerning the availability display (i.e., item 3), participants assumed the existence such a display while in fact, there was none. In L3 automation, the correct answer for all items was 7 (i.e., „*strongly agree*“). All user education groups showed the same pattern with almost exclusively correct answers. In contrast to that, results of participants in the BL condition revealed that participants did not understand whether the transition restrictions existed or not. This is reflected in values close to 4 (“*neither*

agree nor disagree”). The availability display item marks one exemption to that since participants expected such a display element as they just had for L2 automation as well. The results indicate that user education supports accurate formation of mental models for L2 and L3 automation. Additionally, there is more gradation between the approaches in L2 (see figure 11.2 top) compared to L3, where the three approaches all led to equally good results (see figure 11.2 bottom).

Figure 11.2. Means and SE for L2 (top) and L3 automation (bottom) of the four items of interest by experimental condition (BL: white; ML: light grey; TL: dark grey; ML+TL: black).

11.3.2 Interaction Performance

Descriptive statistics (i.e., M, SE, λ) for each interaction performance measure (i.e., experimenter rating, time on task, error rate) are shown in figure 11.3. Inferential results for mixed within-between ANOVA are presented in table 11.2. Table 11.1 shows all 72 planned contrast results. In general, significant effects for both differences in the first block and performance increases from the first to the second block were mostly observed for transitions from manual to L2 and L3, respectively. Transitions between automation levels (i.e., UC3 & UC4) only showed a small number of significant planned contrasts. These results indicate that the treatments rather affect first-order UCs. As a consequence, performance increases from the first to the second encounter are predominantly

present in first-order UCs for the BL condition. The following paragraphs provide a more detailed outline of results regarding contrast analysis.

In the first block, both the two-step and combined stand-alone education approaches revealed significantly superior performance in comparison to the baseline for all three performance measures. No performance parameter revealed significant differences between two-step and stand-alone procedures. Significant performance increases over time for the experimenter rating were observed in the ML+TL condition and in the baseline condition. The non-significant effect of the combined stand-alone approaches results from the descriptive decrease in performance as measured by the experimenter rating for the TL condition. The ML group showed similar increases as the other two groups. Inferential statistics did not show significant results for performance increases of either condition concerning time on task. However, there was a considerable effect size for the baseline condition present pointing towards performance increases over repeated interaction. Error rate results revealed significant performance increases only for the baseline, but not for the other conditions.

Concerning differences in block 1 between the user education approaches, the same pattern as observed for UC1 was present in UC2. All three performance measures revealed a superiority of two-step and stand-alone procedures over the baseline approach. There was no difference between the education approaches themselves. Strong and significant learning effects were present for all three measures in the stand-alone approaches and the baseline. For the ML+TL condition only mean experimenter rating performance significantly increased from the first to the second block. Examining effect sizes, results showed that improvements in all three performance measures were strongest for the baseline as compared to the education conditions being partly more than twice as high. These results show that the descriptively best performance in the ML+TL condition did not further improve, but for the slightly poorer stand-alone approaches and the significantly poorer baseline condition, there was still room for improvement left.

There was only one statistically significant planned contrast for the transition from L2 to L3 automated mode. Participants in the ML+TL condition received better experimenter ratings than participants in the baseline condition in the first block. These results indicate that user education is mostly ineffective for the first encounters in this second-order UC. The fact that there was no difference apparent for the combination of ML and TL in comparison to the baseline is due to the poor performance as measured by experimenter rating and time on task observed for the ML group. In addition, there was no improvements in performance from the first to the second block for neither of

the conditions and measures.

Significant planned contrasts supporting the effectiveness of user education in transitions from L3 to L2 automation were only present for the experimenter rating. Here, the combined stand-alone procedures led to significant improvements as compared to the baseline and the ML+TL approach when compared to the baseline just reached the threshold of statistical significance. There were no further significant differences recorded for time on task or error rates. However, concerning time on task, there were differences between the user education approaches and the baseline on a descriptive level not reaching statistical significance but considerable effect sizes.

Table 11.1

Inferential statistics (i.e., F , $df1$, $df2$, p , η_p^2) of planned contrasts for the three performance parameters by UC, contrast type and contrast name

UC	type	Contrast	Experimenter Rating						Time on Task						Error Rate					
			F	df1	df2	p	η_p^2	F	df1	df2	p	η_p^2	F	df1	df2	p	η_p^2			
UC1	between	Two-step vs. stand-alone	0.000	1	76	1.000	.000	0003	1	76	.960	.000	1.026	1	76	.314	.013			
		Two-step vs. baseline	8.871	1	76	.004	.105	4.191	1	76	.044	.052	11.217	1	76	.001	.129			
		Stand-alone vs. baseline	11.828	1	76	.001	.135	5.355	1	76	.023	.066	8.148	1	76	.006	.097			
	within	Two-step increase	4.607	1	19	.045	.195	1.318	1	19	.265	.065	1.197	1	19	.288	.059			
		Stand-alone increase	1.386	1	38	.246	.035	1.920	1	38	.174	.048	0.337	1	38	.565	.009			
		Baseline increase	8.598	1	19	.009	.312	3.194	1	19	.090	.144	4.406	1	19	.049	.188			
UC2	between	Two-step vs. stand-alone	2.166	1	76	.145	.028	2.483	1	76	.119	.032	1.003	1	76	.320	.013			
		Two-step vs. baseline	13.663	1	76	<.001	.152	13.599	1	76	<.001	.152	11.195	1	76	.001	.128			
		Stand-alone vs. baseline	7.820	1	76	.007	.093	7.195	1	76	.009	.086	8.190	1	76	.005	.097			
	within	Two-step increase	4.524	1	19	.047	.192	1.553	1	19	.228	.076	3.111	1	19	.094	.141			
		Stand-alone increase	21.757	1	38	<.001	.364	7.645	1	38	.009	.167	4.615	1	38	.038	.108			
		Baseline increase	15.545	1	19	.001	.450	14.311	1	19	.001	.430	11.930	1	19	.003	.386			
UC3	between	Two-step vs. stand-alone	2.681	1	76	.106	.034	1.012	1	76	.318	.013	0.929	1	76	.338	.012			
		Two-step vs. baseline	9.731	1	76	.003	.114	0.078	1	76	.718	.001	0.066	1	76	.798	.001			
		Stand-alone vs. baseline	3.860	1	76	.053	.048	0.467	1	76	.497	.006	1.589	1	76	.221	.020			
	within	Two-step increase	0.213	1	19	.649	.011	0.018	1	19	.894	.001	0.016	1	19	.902	.001			
		Stand-alone increase	0.649	1	38	.426	.017	0.091	1	38	.765	.002	0.211	1	38	.649	.006			
		Baseline increase	0.458	1	19	.507	.024	0.060	1	19	.809	.003	0.017	1	19	.898	.001			
UC4	between	Two-step vs. stand-alone	0.000	1	76	1.000	.000	0.116	1	76	.685	.002	0.045	1	76	.832	.001			
		Two-step vs. baseline	3.964	1	76	.050	.050	3.608	1	76	.061	.045	.0195	1	76	.660	.003			
		Stand-alone vs. baseline	5.285	1	76	.024	.065	3.192	1	76	.078	.040	0.088	1	76	.767	.001			
	within	Two-step increase	6.047	1	19	.024	.241	2.696	1	19	.117	.124	1.117	1	19	.304	.056			
		Stand-alone increase	7.887	1	38	.008	.172	4.803	1	38	.035	.112	3.275	1	38	.078	.079			
		Baseline increase	6.333	1	19	.021	.250	4.582	1	19	.046	.194	1.858	1	19	.189	.089

Figure 11.3. Means and standard errors of the experimenter rating, time on task and error rate (columns left to right) for UCs 1-4 (rows). Each plot shows the four experimental conditions as separate lines for the first and second block on the x-axis.

Inferential results for the experimenter rating revealed three significant main effects and two significant two-way interactions. Due to the disordinal nature of the two-way interactions, none of the main effects can be interpreted globally and therefore only two-way interactions are considered further. Each performance indicator revealed a statistically significant two-way interaction between UC and block. Thus, it depends on the respective UC, whether there is a difference between the two blocks in form of performance improvement. This result supports observations from planned contrast analyses that there was no difference between the blocks in the transition from L2 to L3 (i.e., UC3) for neither performance parameter. At the same time, strong increases were observed especially in UC1 and UC2. The significant two-way interactions between block and treatment for experimenter rating and time on task indicate that educating users had an effect on these performance parameters, which depended on whether one examines the first or the second block. In reference to planned contrast results reported above, this result indicates that treatment differences existed in the first block. These differences vanished in the second block due learning from the preceding successful interaction. No significant three-way interactions were recorded.

Table 11.2

Inferential statistics (i.e., F , $df1$, $df2$, p , η_p^2) for $2 \times 4 \times 4$ mixed within-between ANOVA for each of the three parameters.

Measure	Effect	F	$df1$	$df2$	p	η_p^2
Exp.- Rating	UC	5.301	3	74	.002	.177
	Block	47.068	1	76	<.001	.382
	Treatment	8.239	3	76	<.001	.245
	UC * Block	7.294	3	74	<.001	.112
	UC * Treatment	1.504	9	180.247	.149	.057
	Block * Treatment	3.202	3	76	.028	.112
	UC * Block * Treatment	1.062	9	180.247	.393	.041
Time on Task	UC	7.942	3	74	<.001	.244
	Block	41.681	1	76	<.001	.354
	Treatment	4.805	3	76	.004	.159
	UC * Block	6.188	3	74	.001	.201
	UC * Treatment	1.506	9	180.247	.149	.057
	Block * Treatment	6.932	3	76	<.001	.251
	UC * Block * Treatment	1.449	9	180.247	.171	.055
Error Rate	UC	3.120	3	74	.031	.112
	Block	15.224	1	76	<.001	.176
	Treatment	2.500	3	76	.066	.090
	UC * Block	5.615	3	74	.002	.185
	UC * Treatment	1.416	9	180.247	.184	.054
	Block * Treatment	2.155	3	76	.100	.078
	UC * Block * Treatment	0.601	9	180.247	.975	.024

11.3.3 Satisfaction

Two participants missed one single SUS item each. Missing values were estimated using an Expectation-Maximization Algorithm (Lüdtke et al., 2007; Howell, 2007). Descriptively, participants in the ML+TL condition reported the highest satisfaction with the HMI ($M=78.95$, $SD=11.86$) closely followed by the BL condition ($M=77.25$, $SD=9.49$). The ratings decreased in the ML condition ($M=71.59$, $SD=14.90$) and were lowest in the TL condition ($M=65.63$, $SD=20.39$). Results of a one-factorial between-subjects ANOVA showed that there is a difference between the four experimental conditions re-

garding central tendency ($F(3,76)=3.355$, $p=.023$, $\eta_p^2=.117$). Post-hoc Scheffé multiple comparisons revealed that this effect is driven by lower SUS values in the tutorial condition as compared to the other conditions. Thus, the highest amount of education (i.e., ML+TL) and the lowest amount (i.e., BL) did not differ in terms of mean user satisfaction (CI limits from $-15.02 - 11.63$, $p=.988$). The only post-hoc comparison closely reaching statistical significance was observed for BL vs. TL (CI limits from $-26.64 - 0.00$, $p=.05$).

11.3.4 Preference-Performance Relationship

Figure 11.4 and table 11.3 show the results for the preference-performance relationship by fitting linear regressions to the scatterplot data. There were no significant regression equations for the experimenter rating. The relationship for the ML condition showed a slight negative trend where higher SUS scores were associated with better performance. Time on task revealed two significant equations and correlations for both stand-alone procedures. Here, with increasing performance, the SUS score also increased. The baseline and two-step procedure did not show a significant relationship. A significant linear regression for the error rate was only observed in the BL condition. This also marked the strongest slope of all regressions.

Figure 11.4. Scatterplots of preference-performance relationships for experimenter rating, time on task and error rate (from left to right) by the four educational procedures.

Table 11.3

Linear regression coefficients (i.e., R^2 , p), equations with criterion (C) and respective predictor (p) and correlation coefficients (i.e., r , p) for experimenter rating, reaction times and error rate by four educational procedures.

Variable	Education	Linear Model Equation	R^2	p	r	p
Exp.- Rating	Baseline	$C = -0.921 + 0.213 * p$	.032	.448	.180	.224
	Manual	$C = -0.078 - 0.103 * p$	.019	.558	-.139	.279
	Tutorial	$C = 0.538 + 0.202 * p$	.089	.202	.298	.101
	Manual+Tutorial	$C = 0.401 + 0.267 * p$	.040	.396	.201	.198
RT	Baseline	$C = -0.780 + 0.150 * p$	.006	.754	.075	.377
	Manual	$C = -0.012 + 0.557 * p$	.302	.012	.550	.006
	Tutorial	$C = 0.434 + 0.208 * p$	.161	.079	.401	.040
	Manual+Tutorial	$C = 0.452 + 0.099 * p$	.025	.507	.157	.254
Error rate	Baseline	$C = -0.764 + 0.721 * p$	.158	.083	.398	.041
	Manual	$C = 0.094 + 0.074 * p$	.010	.681	.098	.340
	Tutorial	$C = 0.325 + 0.164 * p$	.079	.231	.280	.116
	Manual+Tutorial	$C = 0.196 + 0.155 * p$	.011	.657	.106	.329

11.4 Discussion

We conducted a driving simulator study to investigate the effects of different user education approaches on understanding, interaction performance and satisfaction with driving automation systems. In a mixed within-between-subjects design, $N=80$ participants received either a two-step education procedure consisting of reading owner's manual information and a subsequent interactive tutorial, either of the two education procedures as stand-alone programs or only baseline information about the system function according to SAE (2018).

The results indicate that all three education procedures (i.e., ML+TL, TL, ML) contribute to a more accurate formation of mental models for L3 automation as compared to the baseline. For L2 automation, however, the most accurate mental model was obtained in the two step procedure and decreased for the ML and TL procedures. Still, the stand-alone approaches showed higher accuracy than the baseline. Subsequent interaction performance showed particularly strong effects of user education in transitions from manual to L2 or L3, respectively, as compared to baseline information. Transitions between the two driving automation systems (i.e., L2 to L3 and vice versa) seemed to

be influenced by preceding interactions and did not show comparable effects of user education. Strongest performance increases for repeated UC were observed for the baseline group. The three user education groups' performance changed only slightly at best. Prior treatments did not affect satisfaction with the interface. However, the stand-alone procedures in tendency produced lower satisfaction as compared to the baseline or the two-step procedure. The following paragraphs discuss the present findings with regards to study limitations, the effect of conceptual design and point towards future research opportunities for automated driving education.

11.4.1 Mental Models

The mental model was separately assessed for L2 and L3 since the ODD restrictions were only present for L3. Results revealed that independent from the treatment, all education groups showed high understanding of the ODD restrictions (SAE, 2018). In comparison, the BL information led to ratings on the center of the scale indicating that participants could not for certain decide whether an ODD restriction was present or not (see figure 11.2). Even for the availability display (item 3 in figure 11.2) that was expected to a high degree by BL participants (see chapter 8), all three educational approaches could add to a higher accuracy of the mental model. As the manual and tutorial approaches by themselves already supported the evolution of the mental model to a large degree, there was no room for further improvement for the two-step procedure. Thus, we conclude that the education of drivers when it comes to understanding of ODD restrictions can already be accomplished through stand-alone procedures comparably well as through a combined procedure. User education for L2 automation produced a different picture. Here, one has to consider that no ODD restrictions existed and this fact is therefore not as explicitly mentioned in the user education approaches. Hence, it turned out that most accurate mental models were present in the ML+TL condition. Participants in the two stand-alone procedure conditions (i.e., ML and TL) did not achieve a comparable accuracy of mental models but still outperformed participants in the BL condition. Here, participants' answers accumulated on the center of the scale indicating an indecisiveness as in the L3 mental model. For L2 automation, BL participants more strongly expected an availability display (see chapter 8) when compared to educated participants. In general, the present results support the hypothesis that user education impacts mental models for automated vehicle HMIs. If ODD restrictions are present, this study suggests that approaches are similarly helpful. If this is not the case, it seemed that users were more eager to indicate that a restriction did not exist if they received no information

about such a restriction in a combined education program (ML+TL) as compared to only one program by itself (either ML or TL). The results suggest that mental models are prone to change depending on prior information which is accordance with prior research (Beggiato & Krems, 2013; Blömacher et al., 2018). Compared to these two studies, the present approach supported users only with correct information but changed (1) the extent of education (two-step vs. stand-alone) and (2) the conceptualization of educating users (manual vs. tutorial) varying the degree of immersion among others (Sportillo et al., 2018). Since mental models bear predictive validity for interaction behavior (Boer & Hoedemaeker, 1998), these results imply that performance differences between the experimental conditions can be directly traced back to observed variations in the mental model. From these results we conclude that user education can help to promote accurate evolution of mental models and no long-lasting and inefficient trial-and-error learning is necessary to arrive at correct conclusions about automation and HMI functioning (Abraham et al., 2018; Beggiato et al., 2015; Forster et al., 2019a). Rather, by means of presenting information before first interaction, one can support users to correctly understand system functioning. This also translates into more efficient and effective interaction behavior being outlined in the following paragraph.

11.4.2 Interaction Performance

Concerning the three interaction performance measures, results of the present study indicate a UC specific pattern, which is reflected in significant main and two way interactions of the UC factor (see table 11.2). As outlined in the introduction section, investigating automated driving and control transitions, research suffers the drawback that it is not possible to permute the sequential order completely. Thus, the increased understanding gained through user education approaches beforehand might be overridden by actual system experience from initial contacts (so called “*first-order*” UCs) on subsequent UCs that are never first encounters with driving automation such as transitions from L2 to L3 and vice versa (so called “*second-order*” UCs). Additionally, as users learn from first interactions and have completed these successfully, a higher level of competence in form of basic understanding of the interior layout and the automated vehicle’s HMI can be assumed for the second-order UCs.

Between-Group Differences in First Encounters

Results of initial interaction performance differences in UC1 and UC2 between the treatment groups support hypothesis 2a. Here, comparisons with the baseline (see table 11.1) showed that superior interaction was present for the experimenter rating, speed and accuracy. The result that there was no difference between the stand-alone and the two-step procedure on the one hand but significant differences between these approaches and the BL on the other hand (UC1 in table 11.1) can be explained having regard to mental model results. Here, knowledge on ODD restrictions was on a similar level for all three groups as compared to the BL. This pattern of data seems to have directly translated to all three performance measures in the first block of UC1. In a similar manner, the mental model observations for UC2 influenced the experimenter rating, time on task and error rate. The gradual decrease in mental model accuracy from the two-step via the stand-alone procedures to the BL was also apparent for interaction performance measures. Best performance for all three measures was recorded for the two-step procedure (see figure 11.3 UC2) followed by the stand-alone approaches and eventually the BL. This gradual performance decrease is also reflected in the magnitude of F -values and effect sizes for between-group contrasts, which are larger for two-step vs. BL as compared to stand-alone vs. BL (see table 11.1). Taken together, the observations of mental models and transitions from manual to automated mode support theoretical considerations by Rudin-Brown (2010) that mental models influence user behavior on both tactical and operational level. Moreover, these results support Boer and Hoedemaeker (1998) since mental models thus showed predictive validity for interaction performance measures. Transferring conceptual considerations from prior research on training users with automated driving were thus successful since the observed increased understanding also translated into increased performance measures (Hergeth et al., 2017; Payre et al., 2017; Sportillo et al., 2018). In addition, the two-step procedure led to the best results which supports Payre et al. (2017) stating that more elaborated prior treatments lead to improved performance. In the present study, the aim of user education was to provide knowledge of system understanding through prior treatments before the operator could engage in extensive trial-and-error learning (Abraham et al., 2018). However, one has to consider that performance-enhancing effects were not apparent for transitions from L2 to L3 and vice versa. The pattern of interaction performance was similar for all treatment conditions. This is likely due to interference of learning from experience of preceding successful control transitions in first-order UCs with the initial understanding. This translates into improved performance especially for the BL group. Here, experiential

learning through experience seemed to have already influenced the users' behavior with the driving automation system. The observation of significant between-group contrasts for experimenter ratings in UC 3 (two-step vs. BL) and UC4 (two-step vs. BL; stand-alone vs. BL) contradicts this reasoning (see table 11.1). Since this pattern was not present for speed and accuracy measures and due to the inconsistency for these UCs, no valid conclusion regarding user education influence on second-order UCs can be drawn at this point.

Performance Measure Increases

The hypothesis 2b stating that there are stronger learning effects and increases in performance with less available user education is partly confirmed. Without prior education, increases from the first to the second block appeared especially in the transitions from manual to both automated driving modes (i.e., UC1, UC2) for all three dependent measures (see table 11.1 and figure 11.3). For the transition to L2 specifically, the stand-alone procedures also increased across all measures. In contrast this result was not obtained for the transition to L3 where speed and accuracy did not change in neither approach. This indicates that in first-order UCs, a higher amount of available information leads to a more stable performance early on. It is thus possible to investigate skilled user behavior already in the first interaction trial. Consequently, a high number of errors, long time on task and low experimenter ratings related to subsequent steep learning curves of uneducated users (See chapter 7) could be eliminated by appropriate prior education. The results only partly support hypothesis 2b. UC specificity was also observed here as indicated by significant two-way interactions between block and UC (see table 11.2). None of the three performance parameters revealed improvements from the first to the second block for UC3 independent from user education. This indicates either that experiential learning effects are at place or that this UC simply put too high demands on the operator to be solved without struggling in the first two trials. Further performance development might still be possible but could not be observed in the two repeated trials here. In contrast to that, the observed increases for experimenter rating and time on task in UC4 (see table 11.1) across all conditions could be explained by the fact that the combination of driver-support systems (i.e., L2 and lower) and separation from the ADS (i.e., L3) leads to confusion for the human operator. Overall, the obtained results for the development of the three performance measures revealed that supporting the user with information fostering mental model formation can already be sufficient for reaching stable performance in initial encounters. This is especially important for critical tran-

sitions from manual to automated mode. Such treatments, however, have only limited effectiveness for subsequent interactions because the mental model is updated by the experience itself (Beggiato & Krems, 2013). This in turn influences subsequent performance (Rudin-Brown, 2010) more strongly than initial mental models derived from education.

Consolidation: Interaction Performance Measures

The present paper supports the introduction of user education approaches for facilitating performance. It shall once more be emphasized here, that this does not imply that HMI design receives a free ticket for adding complexity to the interface. The introduction section already pointed out that the reduction of complexity through user-centered design must always come first to support safe and efficient human-automation interaction. Still, we have to assume that users of driving automation will not be experts left alone having received any sophisticated education on driving automation (C. A. Hart, 2019) besides shallow media coverage. Another issue might be the contingency between educational treatment and actual system use (Casner & Hutchins, 2019). While in the present study, there were not more than ten minutes between the education procedure and the control transitions, we cannot assume that in the real world similar proximity of time will be given. Rather, this time might be considerably longer. Thus, we also have to consider memory decay of the learned content. It remains to be seen how persistent the observed change in mental models is and whether this still translates into improved operator performance with more timely distance between learning and applying information. Furthermore, less stringent operator qualifications for driving automation will prevail as compared to flight automation where extensive user training programs are mandatory (Casner & Hutchins, 2019; C. A. Hart, 2017). Even beneficial procedures such as an owner’s manual are unlikely to be checked prior to using such a system on the road (Mehlenbacher et al., 2002). Instead, a trial-and-error approach might be preferred by a large number of users (Abraham et al., 2018) pointing towards the importance of intuitive HMI design for driving automation. Introducing mandatory user education such as the quiz-based tutorial in the present study could lead to positive results in terms of understanding and interaction performance. On the other hand, enforcing users to undergo an educational procedure might also restrict their freedom to act. Such a deliberate enforcement could in turn lead to reactance and constitute an impediment for public acceptance.

11.4.3 Satisfaction

Satisfaction did not show an effect of user education. Here, the two stand-alone procedures led to descriptive differences between the groups. This difference was mainly driven by low satisfaction with the interface in the TL condition. A possible explanation for the poor scores might be that participants were aware of system limitations and complexity but had to follow a trial-and-error learning approach in the tutorial itself. Through this, they necessarily struggled more in giving correct answers to all seven questions of the tutorial as compared to the ML+TL group where accurate understanding could well be assumed before they had even started the tutorial. Possibly, difficulties in completing the education procedure was remembered and added to actual interaction with the automated vehicle's HMI and lower satisfaction was reported. These observations point towards the importance of appropriate conceptualization of user education when it comes not only to facilitating behavioral interactions but also attitudes towards the interface itself. Even though an approach might evoke beneficial behavioral changes, this does not necessarily mean that there will be no negative impact on satisfaction with the interface. Consequently, development of user education approaches need to carefully consider design and avoid potential detrimental influences of poor conceptualization on interface satisfaction.

11.4.4 Performance-Preference Relationship

Referring to the findings from chapter 7, the expectation for the preference performance relationship was that there is also a close relationship at the first block in the BL condition, since this would replicate the previous results. Furthermore, there should be a weaker relationship for more experienced or trained users, as there is less dispersion in behavior. This expectation applies to the obtained results only in the case of the error rate. No significant regression equations could be observed for the experimenter rating and the time on task even revealed a pattern that contradicts the expectation. Here, there was no significant relationship in the BL condition, while the stand-alone procedures produced significant correlations between preference and performance. The decrease in dispersion with rising experience, as reasoned in chapter 7.2.2 was also apparent in the present data (see figure 11.3). However, it might have been the smaller number of participants per cell, that led to strong and biasing influences on the multivariate analysis in this case. While $N=57$ participants were observed at each block, the present between-subjects design only permitted to sample $n=20$ participants per

cell that is not even half the size. Consequently, outliers exert a strong influence on the data set. For example, there are some observations with very poor performance getting assigned a z-score of around -3 (see figure 11.4). Concerning their SUS score, they still align only at a medium level. The observations here might also be due to the respective preference measures. If a participant was educated beforehand and is thus familiar with the HMI from the beginning (see table 11.2, it is more likely that he/she reports lower satisfaction. When in the BL condition, one has to derive satisfaction based solely on the observation of one's own behavior without being able to add it into a context of potential errors in interaction. In comparison, users with superior knowledge can relate their behavior into this larger context of possible erroneous interactions. A slightly more negative evaluation as described above leads thus to more dispersion in the preference rating. However, this was only true for the stand-alone procedures, but not for the two-step procedure. Since the stand-alone procedures each come with special advantages and drawbacks (see table 10.1), their involvement in the multivariate development of preference and performance cannot be consistently estimated. Comparing only the Baseline with the two-step procedure, a slightly more consistent picture emerges since there was one strong relationship for errors in the BL condition but none in the two-step procedure. This shall not cover up the fact that a contradictory data situation was present here and more research especially in terms of sample size might be necessary to make robust inferences for the multivariate relationship.

11.4.5 Limitations and Future Research

The present study investigated only driver-initiated transitions of control. However, research on user education and training also needs to consider the bigger picture of human-automation interaction. Merely focusing on correct operational inputs and necessary conditions is only a first step towards enabling the consumer population to effectively operate these systems. This does not yet support appropriate behavior during active system functioning or system-initiated transfer of control (Casner & Hutchins, 2019). The conceptual gap between educating users about frequent interactions as in the present study and less frequent unplanned take-over requests issued by the system (Hergeth et al., 2017; Payre et al., 2017) still needs to be closed. The mental model was assessed through four items focusing only on ODD restrictions for transitions between automated driving levels. Thus, the mental model about the driving automation system is still incomplete not covering the full range of human-automation interaction. As the focus of the present study lay specifically on user-initiated transitions, the reported re-

sults hold true. To extend the obtained insights there is still future research necessary. Another limitation is the statistical procedure that was undertaken here when performing contrast analyses. The combination of the manual and tutorial conditions into one group was necessary since there were no hypotheses about superiority of one over the other. This prohibits a direct comparison of these two approaches by means of planned contrasts. The results, however, showed that in some cases (e.g., experimenter rating UC1) the two stand-alone procedures produced considerable different results in terms of performance in the first block and improvements towards the second block. Therefore it remains to be seen how these stand-alone procedures exactly differ from each other and whether these are applicable by themselves or not. At the present, no valid conclusion can be drawn which approach might be the better one for increasing system understanding and facilitating performance. We are therefore left with the dodo bird verdict (Rosenzweig, 1936), a suggestion that is most prominent in psychotherapy. It states that all treatments are equal and as long as there is any kind of therapeutic approach this is still better than none at all. A similar suggestion might hold true for stand-alone user education on HMIs for automated driving presuming that only correct information and the same amount of information (Beggiato & Krems, 2013; Blömacher et al., 2018) is reported to users. Another limitation is that the user education approaches had only significant impact on the very first encounters with automated driving. However, it seemed like there was no longer-lasting impact over two blocks. Focusing on human-computer interaction from a usability perspective, it is still unclear how these procedures affect other important constructs in automated driving such as trust and acceptance. With ease of use being a precursor of intention to use (Davis, 1989), it is likely that facilitation of first time automation usage can be beneficial for acceptance of the driving automation systems. The representativeness of the present sample might be regarded as another limitation. First, there was considerable experience with ADAS by many participants. It is not likely that about one half of the users (as in the present study) will be experienced with such features. However, the present results indicate that prior experience with such ADAS has only limited influence on a priori knowledge and learning how to use these functions. The mental model results for BL participants were considerably more inaccurate compared to educated users and interaction behavior also differed in the expected manner. Second, the sample includes participants from various backgrounds within BMW's employees. Even though such a sample is most likely more representative than a college student sample (see e.g., Henrich et al., 2010), generalizability also suffers from the western, educated, industrialized, rich and democratic background of the

sample. This study followed a two-step procedure to educate users with driving automation. In the first step, there was information presented to the users so they can freely inform themselves about the automation (i.e., manual). In a second step, there was an interactive desktop-PC approach that tested appropriate understanding through a quiz procedure. The two components were also used as stand-alone procedures. Presented in such a way, however, comes with specific drawbacks for each approach. Regarding the owner's manual there is small to no experimental control since one cannot ensure that the information had been processed and understood correctly. Additionally, generalizability of results to an applied context is limited since there is evidence that most users do not read the owner's manual at all (Mehlenbacher et al., 2002) rather following a trial-and-error approach as more than 50% of respondents indicated in a survey by Abraham et al. (2018). A stand-alone tutorial approach requires trial-and-error learning since no prior knowledge is available. While reasoning by Wickens et al. (2015) supports such an active learning approach, it might also evoke reactance of learners due to the complexity of automated vehicle HMIs. This could lead to a necessarily large amount of distracting information in such a tutorial.

11.4.6 Conclusions

The study at hand holds conceptual, methodological and theoretical implications. Having shown that the present user education procedures lead to more accurate mental models and increased performance of human-automation interaction, the present study implies that legal authorities as well as suppliers of automated driving technology might consider working towards the development of both concepts and standards for user education. Only through sophisticated procedures it is possible to arrive at safer and more efficient usage of driving automation as already stated by NHTSA (2016). The present approaches provide first directions on how user education might be designed and applied before actual use of driving automation supporting understanding, effectiveness and efficiency of use. The study also showed that the design and conceptualization of user education requires careful consideration since there could be negative effects on user satisfaction with the interface itself. Research and development in the driving automation domain needs to bring forth various approaches to educate and train users in interaction with automation technology. From a cognitive psychological perspective, this work supports and extends findings of lower automation levels (Beggiato & Krems, 2013) and theoretical considerations (Rudin-Brown, 2010). . Initial mental models are translated into interaction behavior thus emphasizing the importance of users' initial

knowledge of automated driving systems and HMIs. This implies that developers of driving automation need to regard that (1) initial mental models are frequently incorrect, which (2) results in inefficient operator performance (see chapter 7) and (3) is changed through trial-and-error learning during the interaction (Abraham et al., 2018). Supporting user education prior to first interactions, however, can have beneficial effects in a way that (1) initial mental models are formed more correctly resulting in (2) improved operator performance and (3) mitigating the detrimental effects of trial-and-error learning. From a methodological perspective, this study proposed three different approaches that could possibly applied in research and development of automated driving when setting up experimental user studies focusing on experienced users instead of pure novices. By applying such education prior to an experimental session, it is possible to investigate the perception and evaluation of a more skilled user population on an HMI. Additionally, these approaches ensure a common understanding of the sample which benefits method standardization.

This chapter outlined the last hypothesized variation for the preference-performance relationship regarding study design. The following chapter now turns towards a possibility of how the dissociation can appear post hoc by means of the analysis strategy. An exemplary procedure in form of a quartile split on the basis of user performance is outlined and investigated in the next chapter.

12 Unskilled and unaware: Subpar Users of Automated Driving Systems make spurious Decisions

11

Abstract: This work investigated differences between preference and performance in Human Computer Interactions and their dependency to the respective user skill level. A driving simulator study with $N=57$ participants was conducted to evaluate a Human-Machine Interface for a Level 3 Automated Driving System. Two experimenters rated interaction performance (e.g., input errors, mode confusions, etc.). Additionally, participants reported their preference by means of perceived usability and acceptance. The sample was split into four groups based on the quartiles of performance. Results revealed that the four groups differed significantly in their performance. However, preference ratings did not show this effect. Thus, the present research could find evidence that the dissociation of performance and preference depends on participants' skills. Finally, future research directions are outlined.

12.1 Introduction

With the maturation and feasibility of L3 ADS (SAE, 2018), research on and development of HMIs need to ensure users' safe and efficient adoption of this technology. Referring to the considerations on the preference-performance relationship in chapter 3, there are drivers who show bad performance (e.g., slow task completion times, large number of errors) but positively evaluate an HMI. On the other hand, there are users,

¹¹This chapter is based on a previous publication: Forster, Y., Hergeth, S., Naujoks F., Krems, J. F. & Keinath, A. (2018). Unskilled and unaware: Subpar Users of Automated Driving Systems make spurious Decisions. *Adjunct Proceedings of the 10th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* Toronto, ON, CN. doi.org/10.1145/3239092.3265960

who perform very well with an interface without this being reflected in self-report measures. Kruger and Dunning (1999) trace dissociations between people’s ability (i.e., performance) and self-assessments (i.e., preference) back to the respective skill level. According to the authors, unskilled individuals spuriously overestimate their personal ability.

The present work reports first findings from a driving simulator study on the relationship between preference and performance measures. This analysis focuses on the comparison of self-report measures (i.e., usability and acceptance) concerning the observed interaction success. The aim of this approach is to find whether the pattern found in Kruger and Dunning (1999) is also apparent in automated vehicle HMI evaluation.

12.2 Method

The present method includes the driving simulator, HMI, driving automation system and use cases as described in chapter 5.2. This section separately describes the specifics concerning study design and procedure, dependent variables, statistical procedure and the analyzed sample.

12.2.1 Participants

$N=57$ (9 female, 48 male) participants took part in the driving simulation experiment. Mean age was 40.56 years ($SD=9.32$, $MAX=60$, $MIN=25$).

12.2.2 Study Design and Procedure

The original study employed a single-factor within subject design with two different HMIs. Participants were randomly assigned to one of the two HMIs in the first drive. The present work reports results from evaluations of one interface condition (see chapter 5.2.4).

Upon arrival, participants were welcomed and gave informed consent. The experimenter explained the study purpose of evaluating two different HMIs by means of different questionnaires. After a familiarization trial and a brief description of the system capabilities, the first experimental drive started, where drivers interacted with the system through the HMI. After each drive, the HMI was evaluated through a set of questionnaires. Use-cases (Naujoks, Hergeth, et al., 2018) in each drive are shown in table 5.2.

12.2.3 Dependent Variables

This chapter reports the results of preference for the SUS (Brooke, 1996) and van-der-Laen scale (VDL, van der Laan et al., 1997). Performance was assessed by means of an experimenter rating of activation behavior. Two experimenters rated the interaction behavior in activation use-cases on an 11-point Cooper-Harper scale from 0 (not at all) to 10 (perfect) (Cooper & Harper Jr, 1969; Neukum et al., 2008; Naujoks, Wiedemann, et al., 2018). Table 12.1 shows the experimenter rating with the rating domain, observable behavior and according rating category.

Table 12.1

Experimenter rating with domain, observed behavior and category.

Observable behavior	Category
use-case not solved	not at all [0]
serious problems, assistance of experimenter	poor [1-3]
problems, failed attempts, hesitation	average [4-6]
correct/targeted action, no failed attempts	good [7-9]
perfect interaction	perfect [10]

12.2.4 Statistical Procedure and Data Analysis

SUS scores were calculated as described in Brooke (1996) resulting in a score from 1 to 100. Means for the usefulness (Use) and satisfaction (Sat) subscales of the VDL scale were calculated which range from -2 to +2. To ensure inter-rater reliability, the two raters were compared by means of ICCs. Subsequently, the sample was split into four groups according to the quartiles of the performance measure.

12.3 Results

ICC estimates for both experimental conditions were calculated based on a single-rating, consistency, 2-way random-effects model. Results revealed a high inter-rater reliability with a correlation of $r=.818$ ($F(56,56)=10.013$, $p<.001$). The mean of the two raters was applied in further analysis. Table 12.4 shows descriptive results (i.e., N , M , SD , range) for the experimenter rating by quartiles.

Results of the SUS and Van-der-Laen Scale showed high perceived usability ($M=82.45$, $SD=14.01$), high usefulness ($M=1.24$, $SD=0.52$) and high satisfaction ($M=1.25$,

Table 12.2

Descriptive statistics (i.e., N, M, SD, range) for performance parameter

Quartile	N	M	SD	range
Bottom	12	5.33	1.20	3.0 - 6.5
2nd	14	7.57	0.42	7.0 - 8.0
3rd	18	8.50	0.00	8.5 - 8.5
Top	13	9.00	0.00	9.0 - 9.0

Table 12.3

Descriptive Statistics (i.e., M, SD) for preference parameters (i.e., SUS, VDL usefulness, VDL satisfaction)

Quartile	SUS		VDL Usefulness		VDL Satisfaction	
	M	SD	M	SD	M	SD
Bottom	78.96	22.14	1.25	0.57	1.21	0.80
2nd	82.14	9.30	1.21	0.35	1.25	0.26
3rd	81.94	11.41	1.17	0.63	1.14	0.69
Top	86.37	9.48	1.35	0.40	1.40	0.41

$SD=0.59$). Table 12.3 shows means and standard deviations for the three preference measures by performance quartiles.

Figure 12.1 shows z-scored performance and preference results for all three preference measures. Univariate ANOVAs for behavior and self-report data showed a significant effect of quartile for behavior but not for self-report measures (see table 12.3). This indicates that the difference of interaction behavior is not reflected in measures of user preference.

Figure 12.1. Means and standard errors for preference-performance comparisons of SUS, VDL usefulness and VDL satisfaction (from left to right).

Table 12.4

Inferential statistics (i.e., F , $df1$, $df2$, p , η_p^2 value) for performance and preference comparison by quartiles.

Measure	Statistic
Behavior	$F(3,53)=90.982$, $p<.001$, $\eta_p^2=.837$
SUS	$F(3,53)=.651$, $p=.586$, $\eta_p^2=.036$
Usefulness	$F(3,53)=.322$, $p=.809$, $\eta_p^2=.018$
Satisfaction	$F(3,53)=.502$, $p=.682$, $\eta_p^2=.028$

12.4 Discussion

This chapter investigated whether differences between preference and performance in human-automation interaction depend in the respective skill level of participants (Kruger & Dunning, 1999). In a driving simulator study with $N=57$ participants, interaction in activation use-cases was rated by two experimenters. Additionally, participants reported their preference by means of perceived usability (i.e., SUS) and acceptance (i.e., van-der-Laan scale). Results revealed that the difference of performance between four groups (from best to worst) was not reflected in self-report measures. Overall, self-reports showed high user preference for both SUS and VDL. Thus, the present research could find evidence of the Kruger-Dunning Effect in HMI evaluation studies on automated driving. These first results show that participants with low performance are more positive than might be expected from their performance while participants with high performance are less positive than expected from their performance. These results showed that self-reported appreciation is partly independent from observational measures. The post-hoc procedure of splitting data according to performance showed that study analysis can also lead to the appearance of a dissociation. Therefore, it is not only measure operationalization or study design as outlined in the previous chapters. This example of analysis and marks an additional possible root for the occurrence of the preference-performance dissociation.

This finding emphasizes the importance of a multi-method approach when evaluating HMIs for L3 ADS. Self-report data must be interpreted cautiously always regarding interaction behavior and if possible skill level. The results at hand hold implications for the development of HMI evaluation methods. Researchers and practitioners must not rely on self-report data but also consider user behavior.

The present study comes with several shortcomings. This approach used post-study

questionnaires and did not evaluate self-report data directly after the interaction. With self-reports assessed immediately after an interaction, specific interaction performance might still be more accessible to participants thus leading to a smaller dissociation between performance and preference. To raise accessibility, a promising approach might be to report interaction performance to users in form of experimenter ratings. Furthermore, there was only one interaction scenario (i.e., activation from manual to L3 ADS) not taking into account deactivations of the automated driving function. Future research will also need to investigate not only L3 ADS but also include lower levels of automated driving as there is a wide range of transitions between the levels of automation (Naujoks, Hergeth, et al., 2018).

With this chapter, the empirical part of this thesis ends. To conclude, the following final chapter provides a general discussion of all the findings herein. It derives theoretical and practical implications in a chapter-overarching manner.

13 General Discussion and Conclusions

This thesis pursued a two-fold aim, namely (1) operationalizing and measuring users' preference and performance when interacting with automated vehicle HMIs and (2) identifying factors that influence both sources of data. The central issue here is a dissociation between what users report after interaction with a certain technology (i.e., preference) and the observation of their interaction behavior with the technology (i.e., performance). Chapter 3 outlined that this phenomenon poses a challenge for automated vehicle HMI development and testing from both a theoretical and practical perspective. When developing interfaces and testing these, proper study design and accurate retrospective interpretation of results is of high importance due to high efforts in research and development on automated vehicle HMIs. Within the context of usability research on automated vehicle HMIs (see chapter 2), several issues for human-automation interaction arise. These concern the appropriate constructs to evaluate preference, the development of interaction and understanding with such technology over time (assuming no prior knowledge) and the education of users prior to first interaction with driving automation technology. The present results show that (1) some questionnaires adhere to diagnostic quality criteria to a higher degree than others, (2) that repeated interaction changes behavioral parameters, diagnostic self-reports and understanding and (3) that user education supports initial mental model formation and human-automation interaction.

To lay a foundation for the theoretical and practical applications, a brief summary of the main findings is presented below. Eventually, methodological considerations about the studies conducted are outlined and future research directions are pointed out. A detailed discussion of the findings of each respective chapter can be found therein. This general discussion does therefore not repeat any of the parts above but rather focuses in the interrelations between the chapters and studies.

13.1 Overall Findings

Concerning the operationalization goal, this work outlines suitable measures for evaluating preference (see chapter 5) and performance (see chapter 7). As not only summative but also diagnostic measures are applied in studies evaluating automated vehicle HMIs, chapter 9 describes the findings on repeated interaction and use case specificity influence of these. Performance was assumed to be influenced by users' understanding of system and HMI functionality. Hence, the development of the mental model as assessed through questionnaires and additional learning was examined in chapter 8. These measures are all relevant for evaluating automated vehicle HMIs and thus make inferences about subsequent product adoption and use. This operationalization part advances research through its in-depth evaluation of relevant measures in human-automation interaction. Moreover, the relationship between preference and performance was investigated as they frequently do not align. There are factors that were initially hypothesized to influence this relationship (see chapter 3). Appropriate operationalization of each measure (Ajzen & Fishbein, 1977) had marked the first aim. The second aim were factors that lie in study design. Chapter 7 showed that a repetition of use cases led to the disappearance of the correlation between preference and performance. Thus, only first encounters permit a valid inference from preference to performance and vice versa. Feedback on interaction performance marked another factor since it bears the potential to influence diagnostic self-report measures but not performance measures (see chapter 9). This finding is just the opposite of what was found for the influence of use case repetition in chapters 7 and 8. In addition, the respective skill level of the users potentially influences the relationship in line with the Kruger-Dunning Effect (see chapter 12). Finally, the thesis covered the imminent issue of how to educate users with driving automation. First, a comprehensive description of the conceptual development and findings of a pilot study (see chapter 10) is described. The subsequent main study (see chapter 11) showed the impact of different educational treatments (i.e., manual, tutorial, manual+tutorial) on mental models, interaction performance and satisfaction. It revealed that user education is a potential tool to support accurate user understanding of the HMI's functionality which consequently translated into superior user performance. In contrast, within a driving simulator study, satisfaction remained largely unaffected by prior user education. The present thesis targeted the preference-performance relationship from a perspective that performance determines preference but not vice versa (such as expectancy-value models would assume; see chapter 3.2.2 and 3.3). As a consequence, factors that in-

fluence performance (see chapters 7, 8 and 11) were considered with higher priority in comparison to attitude influencing factors (see chapters 5 and 9).

13.2 Theoretical Implications

The main theoretical contribution is the examination and application of models that predict attitude, behavior and their relationship from a cognitive-psychological perspective. Moreover, the thesis supports the application of these theoretical models to the specific human-automation interaction context.

First, it sheds light into how both sources of data (i.e., attitude and behavior) are formed and how and whether they exert reciprocal influence. The present work's contribution lies in the transfer of the knowledge about relationships between understanding, behavior and attitudes to the automated driving and human-automation interaction context. The preceding chapters hypothesized attitude-behavior relations, outlined research on these and showed that hypothesized influences from technology research in general and ADAS in specific held true.

Second, as outlined in chapter 3.3, there are many instances where existing study results did not reveal a coherent picture and the respective authors eventually pointed towards this issue recommending further investigation. With the insights of the present work, potential factors leading to such results can be detected in advance and (if desired) be avoided. This section comprehensively outlines these two theoretical implications.

13.2.1 Attitude-Behavior Formation and Development in Automated Driving

Similar to prior work (Rudin-Brown, 2010; Stevens, Brusque, & Krems, 2012), the present results support the direct link between system understanding as a cognitive factor (Wege et al., 2014) in form of mental models and resulting interaction performance with the HMI. While chapter 8 evaluated the development of learning, mental models and gaze behavior over repeated interactions, chapters 10 and 11 focused on the influence of user education on prior mental models and initial performance. These chapters showed that both experience and prior information affect the accurate evolution of mental models which in turn leads to improved performance (see chapter 7). However, mental models take a considerable number of repeated interaction to evolve accurately (see figure 8.4). In contrast, prior information showed a strong influence on accurate

mental model formation (see figure 11.2). From these observations, it becomes apparent that small changes in mental models already lead to strong effects on behavior despite the fact that additional successful interactions are necessary for the uninformed user to become confident about the HMI's functioning. From that, the issue arises, how predictive behavioral observations of interaction (i.e., efficiency, effectiveness) are for system understanding. A combined contemplation of findings on behavior development (chapter 7) and mental model evolution (chapter 8) suggests that even under stable performance a further development of understanding is at place in case there has not been any prior information that already led to accurate mental models as in chapter 11. In turn, this strongly emphasizes the role of user education. It not only leads to direct adaptation of users' interaction performance (see figure 11.3 and table 11.1) but also to an accurate understanding of functioning that does not require additional successful interaction trials.

One direct influential factor for attitude as hypothesized in the present thesis was behavior (e.g., Bem, 1967). However, this is tied to specific circumstances. The present results support a link between attitude and behavior only in first contact encounters (see chapter 7.2.2) but not under repeated interaction and stable performance. The evidence concerning user education, however, is not completely consistent (see figure 11.4 and table 11.3). In regard to the observations from repeated interaction, where prior information resembled the baseline education condition in chapters 10 and 11, the best premise for agreeableness between preference and performance thus seems to lie in uneducated users. Furthermore, suitable measures for both attitude and behavior are necessary (Ajzen & Fishbein, 1977). After having found out about operationalization of preference in chapter 5, the present work did not additionally test whether weaker preference-performance relationships had emerged with application of the AttrakDiff (Hassenzahl, 2003) for instance.

Chapter 9 additionally investigated a factor, namely feedback, that was expected to influence attitude formation. As uncertainty and inaccurate mental models about the system's and HMI's functioning might lead self-reports astray, support for users' reported attitude could help calibrate diagnostic self-reports. This result is in accordance with research on calibration effects in the area of automation trust (Helldin et al., 2013; Seong & Bisantz, 2008). The chapter showed that users' attitudes are not exclusively based on the observation of their own interaction performance but succumbs to additional factors that moderate the path from behavior to attitude formation. Of course, feedback is only a single factor and as mentioned before, the present work does not and

cannot examine a comprehensive list of individual, organizational and environmental factors (see J. D. Lee & See, 2004). Nevertheless, the present empirical evidence of self-reports revealed that prior study design and retrospective interpretation of obtained results must consider the presence or absence of these factors as these might lead to different attitude outcomes.

Sometimes, research design demands certain aspects such as extensive familiarization by means of use case repetition (AAM, 2006) or user education prior to interaction. This work suggests that in these cases it is more likely for a dissociation to occur. The following section describes the very same case.

13.2.2 Potential to explain Preference-Performance Dissociations

In many instances a dissociation between preference and performance appeared and was observed in the empirical work of this thesis.

In addition, prior treatments for educating users of driving automation by means of tutorials or manuals changed understanding and performance but left satisfaction largely unaffected. This is especially highlighted by the fact that non-educated and users with sophisticated education reported the same degree of satisfaction with the HMI (see chapter 11). Even though investigation of the correlation between preference and performance did not reveal a consistent picture (see figure 11.4 and table 11.3), the increased understanding and performance as opposed to constant satisfaction between the experimental groups marks one example of a preference-performance dissociation. Thus, the present work supports the assumption that elaborated treatments prior to interacting with driving automation increase the likelihood of an emerging dissociation. Why is that so? One possible explanation is that learning about the HMI's functioning in regard to ODD limitations happens during the treatment phase prior to interaction. As reasoned above, this understanding is then transferred directly into interaction and results in superior performance (as compared to no education). When interviewing users, however, they still have to answer SUS items such as *"I found the system unnecessarily complex"* (Item 2) or *"I needed to learn a lot of things before I could get going with this system"* (Item 10). It becomes obvious that self-reported satisfaction in this case also covers the learning about the HMI that happened prior to actual interaction and these in turn enter into evaluative judgments. Preference thus not only incorporates the observation of one's experience during interaction with the interface but if applicable

also information obtained prior to interaction. Consequently, if all this falls together in first encounters (such as the baseline condition in chapter 11 and the first contact in chapter 7), agreeableness between preference and performance might be high. If they are separated by prior treatments or repeated interaction for example, agreeableness is lowered. Also, as mentioned before, repeated conduction of use cases and inquiries (see figure 7.2 and table 7.6) have the same effect. While preference remains constant, performance increases up to a stable level (see figure 7.1). This finding can explain, why repeated measures designs (e.g., Naujoks, Forster, et al., 2017b) might be prone to lead to performance-preference dissociations. Moreover, it also supports the observations by Nielsen and Levy (1994), who report higher agreeableness of preference and performance for experts as compared to novices. Assuming that the degree of education and number of repetitive interactions with driving automation resembles an expert-novice paradigm, the agreeableness between the two sources of data decreases as the degree of expertise increases (i.e., understanding and interaction performance).

Another instance of the preference-performance dissociation are different user skill levels on the base of a quartile split (see chapter 12). In line with observations by Kruger and Dunning (1999), an additional analysis of data from the first study revealed that users who performed poorly (i.e., bottom quartile) did not report different satisfaction and acceptance as compared to more skilled users (i.e., top quartile). This shows that self-reported satisfaction is to some degree independent from different skill levels within a study sample. All four sub-groups based on performance quartiles can thus be expected to report similar preference.

Taken together, it is more likely to observe a dissociation between preference and performance, if (1) interaction is repeatedly evaluated, (2) users are elaborately educated, (3) only sub-samples such as the poorest performers are regarded or (4) if unsuitable measures are applied by the researcher. Studies where such dissociations have occurred in human-computer interaction (e.g., Sprinks et al., 2017), automotive HMI in general (e.g., Mehler et al., 2017; Navarro et al., 2010) or driving automation in specific (e.g., Naujoks, Forster, et al., 2017b) could retrospectively take the findings of this work into regard to understand the factors that are responsible for users reporting preference for a concept that might not be best for them (Andre & Wickens, 1995).

13.3 Practical Application

The studies reported herein originated within the context of method development for evaluating automated vehicle HMIs. For an overview of the framework see Naujoks, Hergeth, et al. (2019). The three pillars of this methodological framework are (1) the definition of use cases (Naujoks, Hergeth, et al., 2018), (2) heuristic expert assessments (Naujoks, Wiedemann, et al., 2019) and (3) a test protocol for simulator and on-road studies in which the present experiments were located. In this context, one central issue was the operationalization of preference and performance in future automated vehicle HMI studies. To provide a sophisticated recommendation, the diagnostic quality criteria (Nunnally, 1978) of reliability and validity have been applied for determining measure suitability. The second issue concerned the design for user studies. Here, the question was how to design studies when it comes to the number of UC-repetition, provision of feedback, supporting education and retrospectively analyzing data with regard to user skill levels. The results obtained in the series of studies give comprising insights into these two issues. This section discusses these in a chapter-spanning manner. Apart from HMI testing and method development, the results hold practical implications for future real-world deployment and usage of driving automation. Eventually, this section outlines to what degree the insights generalize to other domains than driving automation. A brief outline of implications for aviation, robotics and health-care technology completes the practical applications.

13.3.1 Operationalization of Preference

For the operationalization of preference the usability-related component might be the best fit for assessing HMI satisfaction. Here, in particular the SUS (Brooke, 1996) showed the most positive results. Other questionnaires for an HMI's "look & feel" (i.e., hedonic quality) and usage intentions should also be included to derive a holistic image. Researchers should also check a questionnaire's results for reliability as in some instances (see table 5.5) this prerequisite for further statistical analysis is not met. The questionnaire that covered most preference-facets, showed high reliability and whose items were best understood by participants was the meCUE (Minge et al., 2016). The conclusion that the SUS turned out to be the most suitable measure for the specific aspect of interface satisfaction was consequently followed in the subsequent studies. Concerning time of measurement, results of the second study (see chapter 7) suggest that (within a driving simulator study) it does not really matter when participants complete the ques-

tionnaire. Results tended to remain constant over this time course. Single application of such a measure for interface satisfaction is sufficient and this researchers can save a considerable amount of time. The result that SUS scores were even independent from the user education condition in chapter 11 indicates that even if trained users provide their satisfaction, one can infer completely naive users' satisfaction and vice versa. In contrast to that, diagnostic measures are more prone to the influence of repeated measure application (see chapter 9) and depend on the respective UC. Consequently, data on perceived ease of use representing an effort estimate should be assessed separately for each UC and at least twice. Data of such single-item measures are very efficient to collect and benefit the more global summative satisfaction measures.

13.3.2 Operationalization of Mental Models

The mental model of HMI functionality and ODD-related system restrictions represents a substantive precursor for interaction performance and was therefore introduced in the second study that primarily concerned suitability of behavioral measures (see chapters 7 and 8). A questionnaire approach turned out to be promising when assessing understanding of HMI and system restrictions. The observation that mental model questionnaires are instruction sensitive (see figure 11.2) further supports findings by Beggiato and Krems (2013) and Blömacher et al. (2018). Hence, these questionnaires are an applicable method to capture understanding. Since two items in specific (see items 3 and 5 in figure 8.4) showed sensitivity to the information in the second study, the benefit regarding insights into ODD-restrictions between automation levels is questionable and these were not analyzed in the subsequent chapters 10 and 11. As reasoned in chapter 13.2, mental model questionnaires are a suitable tool for assessing higher-level cognitive processes and give important additional insights into HMI evaluation apart from self-reports on interface satisfaction alone. Thus, studies can greatly benefit from additional application of mental model questionnaires.

For users of driving automation technology this implies that it will take a considerable time and certain number of (successful) transitions until they are certain about the system's and HMI's functionality. If a participant completely failed in a use case (i.e., experimenter rating category 5), they were instructed how to complete the respective transition. If they succeeded, they could also be sure to have performed the correct input due to the subsequent inquiry. In realistic settings, however, there will be no clues about interaction success or failure by a human factors expert but users will have to infer this from the HMIs status indications alone. As a consequence, accurate understanding

might take even longer to evolve. Without proper education a last degree of uncertainty will most likely remain.

13.3.3 Operationalization of Performance

Concerning behavioral measures, this work investigated the "*big three*" measures of error rate, time on task and attentional demand (Wickens et al., 2015) plus additional experimenter ratings (e.g., Kenntner-Mabiala et al., 2016) to capture performance on a more tactical level. The reliability of these measures was evaluated by means of fitting a power-law function (Newell & Rosenbloom, 1981) to the data (see figures 7.1 and 8.1). Especially the big three measures showed the expected pattern of a strong initial performance increase and subsequent stabilization. The power-law fits to the experimenter rating did not reveal comparably good fit indices and even after repeated interaction considerable outliers (e.g., block 4 in figure 7.1) were present. From that, first contact evaluation of all four measures provides a conservative estimate of initial interaction performance and should be considered in future studies. In contrast, a robust estimate for more skilled users' performance (i.e., repeated interaction performance) can rather be gained by error rates and time on task than by experimenter ratings. Criterion validity for the three measures in chapter 7 (i.e., error rate, time on task, experimenter rating) was given by predicting SUS-scores in the first block (see table 7.6) but not in subsequent ones. Consequently, error rate and time on task represent suitable measures for human-automation interaction performance and should be an integral aspect of user studies of HMIs. The more conservative experimenter rating can support additional insights especially in issues on tactical level regarding repeated interaction. Gaze behavior as an indicator of higher-level cognitive functions (Just & Carpenter, 1984) resembled self-reported subjective learning more closely than the actual accuracy of the mental model. Gaze behavior operationalized as the number of switches between AOIs and the monitoring frequency especially benefit research for determining use-case specific characteristics as indicated by different model fits (see table 8.1) and patterns of attention towards AOIs (see figure 8.3). Due to the high efforts that are required both in data collection and preprocessing, gaze behavior might be disregarded in quick iterative conceptual developments for the sake of more economical measures. However, for very early developmental stages in which fundamental decisions (e.g., display location or complexity) are made as well as in final conceptual evaluations it can serve as an important indicator for understanding (Underwood, 2007) and attentional demand (Wickens et al., 2015). Eventually, researchers need to trade off additional insights of gaze behavior

against the efforts of data collection and analysis.

For real-world application it remains to be seen whether such strong learning patterns will also emerge. As reasoned in the previous subsection, the experimental setup might have influenced these observations. Without information by a third party (i.e., the experimenter), users will most likely struggle initially with only scarce information and this might be crucial for the success of using driving automation. As a consequence it emphasizes the importance of intuitive HMI design for first usage of driving automation. Moreover, flaws on tactical level will still be present which is also supported by mental model results that still take longer to evolve accurately. To approve the accuracy of their mental models, users need to explore other possibilities (e.g., activation without current availability) leading to decreases in tactical performance but do not affect operational performance (i.e., time on task remains the same but minor errors were observed).

13.3.4 Varying Factors in Study Design

Use Case Repetition

The first issue for study design concerns the necessary number of use case repetitions. Results of the second study (see chapter 7) showed that summative self-reports only require initial interactions to produce a reliable estimate for user satisfaction within a driving simulator study. On the other hand, diagnostic measures require repeated interaction since these ratings change from the first to the second contact (see figure 9.2). Behavioral measures provide a conservative estimate in the first contact, but already closely align to long-term performance at the second contact. In some instances, however, it might be necessary to repeat UCs more than only once since further change was observed (e.g., UC 3 in figure 8.2). Especially when a study focuses on users' understanding, multiple repetitions of interacting with the HMI should be considered in study design. Even after stabilization of interaction performance (see figure 7.1) and users' self-reported effort (see figure 9.2), accuracy gains for mental models were still observed. Thus, depending on the respective study aim and focus, a different number of repetitions is necessary.

For real-world application of driving automation this means that users will quickly adapt to HMIs for driving automation. However, as reasoned above, more conservative results as compared to the experimental setting and its accompanying restrictions might be expected. Unlike other behavioral adaptation processes such as reliance calibration (e.g.,

Hergeth, 2016) that take a considerably long time, efficient and effective performance is supported after a small number of interactions.

Feedback

The second issue for study design is the provision of feedback about interaction success or failure (see chapter 9). As indications for calibrating effects were present and slightly more conservative ratings were given in specific UCs, the hypothesis was partly confirmed. However, the procedure for rating interaction performance on-site requires a highly skilled experimenter. Furthermore, it is not possible to let two independent raters evaluate performance in a double-blind manner. Due to these concerns, the provision of feedback about interaction performance is debatable in an applied setting. Still, chapter 9 shall remind researchers to keep in mind that results of diagnostic measures might be influenced by calibration processes. The provision of feedback merely served as a methodological possibility to find out about calibration processes for attitudes. For pragmatic reasons, an application in real-world settings is also highly unlikely.

User Education

Third, user education approaches were investigated. The provision of such prior treatments is a double edged sword for research methodology. If a researcher decides not to provide any information, he/she will obtain the most conservative estimate of performance and understanding. This, in turn makes repetitions of use cases necessary to find out about the maximum degree of understanding and performance that the specific HMI can support. However, this is not necessarily a bad thing since additional insights about the very gains of a specific HMI conceptualization are obtained. On the other hand, if proper education is provided beforehand, more liberal results can be expected making repetitive interaction and inquiries obsolete. While this represents an economic approach to evaluate stable performance with accurate mental models, it neglects the fact that initial interactions tend to be more ineffective and inefficient. This poses the risk of a too favorable HMI evaluation and could affect decisions for further development. Additionally, performance and understanding gains that are inherent to specific HMI conceptualizations cannot be observed and evaluated with educated users. Consequently, regarding user education, HMI testing must carefully weigh the pros and cons of providing prior information (or not).

Concerning user education, the most frequent scenario will match the Baseline conditions in most cases (Abraham et al., 2018; Mehlenbacher et al., 2002) thus resembling the

power-law functions of performance development (see chapter 7) and understanding (see chapter 8). Concluding, the benefits of education for the performance and understanding points towards the stellar role of development of such approaches for automated driving technology but has until now been largely neglected due to seemingly more urgent issues.

13.3.5 Transfer to related Domains

The present series of studies was conducted within the specific automation context of supporting or temporarily replacing the human from driving. Herein, ODD restrictions were identified and applied as a major factor contributing to differences between the levels of automation. These results, however, are not at all limited to this context but can also be transferred to other domains where automation technology was or is currently introduced. The following paragraph outlines possible implications for (1) aviation, (2) robotics and (3) health care technology.

Aviation

As reasoned before, the introduction of automation into aviation is a precursor for driving automation. Therefore, the concepts for levels of automation from complete manual to full automation control (e.g., Parasuraman & Riley, 1997) are very similar. Also, the workplaces are similar since there is a human in an operator seat who uses certain control elements to navigate a vehicle or aircraft, respectively. Differences between automotive and aviation lie in the time-criticality which is much higher in driving due to shorter distances between and total number of objects in the close surroundings. Furthermore, the context concerning users of the automation is fundamentally different. While only highly skilled individuals use aviation automation (i.e., pilots), even novice drivers might have access to driving automation. Thus, aviation might test encounters with completely novice users in simulation for training purposes only, but these will certainly not appear in real-world setting. The role of education (see chapters 10 and 11) is even more critical in aviation compared to driving automation. Therefore, even the two-step procedure as tested in chapter 11 does certainly not represent a suitable solution. Instead, extensive simulator trainings have been developed to educate pilots in both understanding and handling aviation automation (see e.g., Trösterer et al., 2017). With the development and testing of novel HMI concepts for pilots (e.g., J. Liu, Gardi, Ramasamy, Lim, & Sabatini, 2016), even this highly skilled population of pilots can be considered as novice users of specific HMI concepts. Therefore, similar behavioral trends as in the present

work with initial poor performance and subsequent steep learning might be observed. Concerning the more generic understanding of automation technology, however, it is more likely that pilots already hold accurate mental models about flight automation that develop less over time. Theoretical implications of attitude-behavior relationship as outlined in chapter 13.2 and practical implications for study design (e.g., repetition of use cases, education) are thus expected to hold true for the testing of such interfaces in aviation.

Robotics

In the robotics domain, the context is very different since it does not support operator seat positions as in driving. However, transitions from manual to different automated modes as well as transitions between these are imaginable. Among others, Schmidtler, Bengler, Dimeas, and Campeau-Lecours (2017) describe the usability evaluation of a production robot that supports the human in a horizontal manipulation task. Other examples are service robots (Harmo, Taipalus, Knuuttila, Vallet, & Halme, 2005) and shopping robots (Tomizawa, Ohya, et al., 2006). In the latter, users are also familiar with and skilled in the task itself (i.e., shopping groceries) and robot support marks a novel technology in this context which must be understood first to be used appropriately. Therefore, one can expect that first encounters might also be characterized by some erroneous trials and users are most likely not entirely sure about the robot's capabilities and limitations. However, educating users about these should enhance understanding and performance just as observed in the driving automation domain described herein.

Health Care

One example of automation technology in health-care are insulin pumps. While conventional therapy for type-1 diabetes patients required multiple injections with insulin pens per day, insulin-pumps release basal-rate insulin automatically. The human is only responsible for additional bolus insulin releases. For an overview of treatments see for example DeWitt and Hirsch (2003). The glucose level, however has still to be monitored by the human without closed-loop technology, where glucose monitoring systems (CGM) communicate with the pumps and according insulin-level adjustments are made independently. Insulin-pump and closed-loop systems are characterized by a rising degree of automation technology and showed beneficial effects in user studies (see e.g., Weinzier et al., 2008). A combination of pumps and CGM systems corroborate L1 or L2 automated systems (SAE, 2018), where the human is still responsible at all times but

does not execute the respective task anymore. With recent advancements in closed-loop technology, today there are first systems on the market that turn off insulin release in case the CGM senses a hypoglycemic trend. This function works independently from human operation and even if the patient is asleep. Therefore could be considered a L3 or even L4 automation according to the SAE (2018) taxonomy. HMI elements are an integral part of pumps and CGM systems to communicate their status (e.g., current insulin amount, last release, glucose level etc.). Consequently, when starting such a therapy, user education is of utmost importance (DeWitt & Hirsch, 2003). Otherwise, poor performance and erroneous trials in initial interactions would cause detrimental health consequences (i.e., hypo- or hyperglycemia). The implications of user education and repeated interaction that were observed in the present work on driving automation also apply to interaction with insulin-pump and CGM technology since users do not hold accurate mental models and cannot operate this technology accordingly without extensive education and training. Here, the first impression (i.e., preference) of a device that provides new opportunities for therapy certainly depends on the success of initial interactions. If it is difficult to use and one does not succeed in operating insulin releases, temporary basal rates and so forth, unstable glucose level result that might eventually lead to resistance of further using this system despite its huge benefits. Therefore, testing procedures for this technology and HMIs in particular might also benefit from the present methodological work on preference, interaction performance and understanding.

13.4 Methodological Considerations

For the interpretation of the series of studies conducted in this thesis there are some methodological peculiarities that need to be considered. Each chapter by itself discussed methodological concerns, but a more generic discussion shall be provided in this section. When examining the preference-performance relationship it is not only about correlations and scatterplots. This approach was the initial starting point as shown in Nielsen and Levy (1994) and adapted in figure 3.1. However, there are also other ways to approach this phenomenon. Especially empirical studies such as Roberts et al. (2017) or Navarro et al. (2010) rather found that certain variations in interface design affected one measure but not the other. These studies did not investigate the preference-performance issue based on correlations but rather on the observation about congruence of change in both measures. Hence, considering factors that influence one measure, but not the other are another way of looking at it. For instance, use case repetition influenced performance

but not preference (see chapter 7); feedback influenced preference but not performance (see chapter 9) and user education influenced mental models and performance but not preference (see chapter 11). This difference in analyzing the relationship became especially obvious in chapter 11. Here, the correlations and scatterplot (see figure 11.4) analysis using linear regressions (see table 11.3) revealed inconclusive results. However, considering the preference-performance dissociation as a change in one measure and parallel stability in the other measure, user education also led to the observation of a dissociation: It changes understanding and performance, but does not affect satisfaction. Concluding, the preference-performance dissociation might appear in different forms that are either a correlational form or a sensitivity form to research design and HMI variations.

The mental model mainly or rather exclusively covered ODD-related limitations for transitions between levels of automation but did not go beyond these. In interaction with driving automation and HMIs, there are more things to comprehend for the users. One example is mode awareness (Sarter & Woods, 1995) and the issue of communicating driving task responsibility. Here, possible mental model questions would focus on certain mode indicators during active system functioning and the respective role of the driver that might be active driver, supervisor of fallback performer (SAE, 2018). Such mode awareness issues are especially important regarding safety-critical events (e.g., emergency take-over situations). Mental models play a crucial role as an incorrect understanding of the respective role can have severe consequences for safe transfers back to manual driving (Feldhütter et al., 2017). Especially since silent failures during L2 are possible (Louw et al., 2019), but L3 ADS are by definition characterized through mandatory TORs in such instances, the understanding of roles and responsibilities during L2 automation must be taken into account given the combination of the automation functions.

Another methodological consideration concerns the relative importance of the tested use cases. In the present research, all use cases were considered as equally important which is reflected especially in the aggregation procedure in chapter 6.4.8. After having found that user-initiated transitions to manual only provide limited information, these UCs (i.e., L3 to manual, L2 to manual) were not considered in the aggregation procedure in the third study as described in chapter 11.2.5. Again, all other UCs entered the procedure with equal weights reflected in the calculation of the mean of each of the four values per participant. However, chapter 11.4.2 extensively discussed influences of first-order UCs (i.e., transitions from manual to automated mode) to second-order UCs

(i.e., transitions between levels of automation). Therefore, it remains an open question whether (1) interpretation of results should place higher emphasis on such first-order UCs and whether (2) the aggregation procedure in chapter 7 and 11 assigning equal weights for each UC is acceptable.

The power-law fits for behavioral parameters (see figure 7.1) and gaze behavior (see figure 8.2) can also be criticized. The fits imply that there is a metric scale in between contiguous blocks, while, in fact, this is not the case. The power-law equations, thus only allow integers to enter and the visual depiction as a continuous line is - strictly speaking - not permitted.

13.5 Future Research

Despite the insights into method development and human-automation interaction in driving simulator studies delivered in the present work, there still remain open research directions. One question is what the behavioral adaptations and increases in understanding look like for different HMI conceptualizations. Comparing recent HMIs in research on L3 ADS in chapter 1.4.2 showed that they all share some common features. Still, this is a very important issue since in the near future several OEMs are expected to launch their L3 ADS to the market - with most certainly different HMI concepts. It remains an open question whether or to what degree generic knowledge about ODDs and functionality as derived from interaction with one HMI can be transferred or might even be hindering understanding and interaction with another OEM's HMI. To support transfer, deployers and regulatory entities will have to work towards the common goal of standardizing HMI design for automated vehicles just as had been done before for symbols of controls, indicators and tell tales among others (ISO, 2010). Moreover, one and the same HMI implementation might be evaluated differently depending on the cultural background. Research on attitudes towards driving automation in different cultures have been investigated for automation trust by Chien, Hergeth, Semnani-Azad, and Sycara (2015) among others. Self-reported satisfaction and learning processes for automated driving remain yet to be investigated.

Future research must also take a look at long-term effects of usage with driving automation technology. Results in chapter 7 showed that within a driving simulator study, satisfaction remains constant and performance changes according to power-law functions. However, to date there is no evidence what pattern would emerge if users repeatedly used an automated driving system in, say, three consecutive drives that are

one week apart each. Conducting such field operational tests marks a next step in automated driving research and development. At present, L3 functionality development and legislation are not yet ready for large-scale on-road testing. On-road testing offers additional realistic conditions for vehicle dynamics that are required in many UCs including transitions from or to manual driving. Additionally, it poses a challenge to visual HMI components due to light incidence and auditory components due to vehicle and surrounding noise.

The present work focused on the relationship between pragmatic self-reports and interaction performance by comparing SUS scores and times on task among others. Chapter 5 has shown that there is another aspect of self-reports, namely non-pragmatic or hedonic quality (e.g., Hassenzahl et al., 2003). A behavioral correlate for this aspect, however, has not yet been discovered. As proposed by expectancy-value models (Davis, 1989; Venkatesh et al., 2003), real use results from prior attitude formation processes and interactions between these. Without commercial availability of L3 ADS, at the present there is no possibility to make statements about the predictive validity of attitudes towards future usage and buy-rates of ADS. Consequently, the only behavioral measures for human-automation interaction are the ones that were covered in this thesis. In automated vehicle HMI development, future efforts are necessary to examine acceptance-related and hedonic metrics to derive a more holistic image of these HMIs.

Concluding the present thesis, it shed some light into automated vehicle HMI testing, the relationship and change of attitudes and behavior in interaction with these systems emphasizing influential factors for performance (i.e., repetition, user education). These insights shall enter methodological study design for HMI testing and hopefully encourage industry and academia for a common ground in evaluating this novel technology.

Bibliography

- AAM. (2006). Statement of principles, criteria and verification procedures on driver interactions with advanced in-vehicle information and communication systems. *Washington, DC: Alliance of Automobile Manufactures.*
- Abraham, H., Reimer, B., & Mehler, B. (2017). Advanced Driver Assistance Systems (ADAS): A Consideration of Driver Perceptions on Training Usage & Implementation. In *Proceedings of the Human Factors and Ergonomics Society Annual Meeting*. Austin, TX, USA.
- Abraham, H., Reimer, B., & Mehler, B. (2018). Learning to Use In-Vehicle Technologies: Consumer Preferences and Effects on Understanding. In *Proceedings of the Human Factors and Ergonomics Society Annual Meeting* (Vol. 62, pp. 1589–1593).
- AdaptIVe Consortium. (2017). Final human factors recommendations (d3.3).
- Adell, E. (2010). Acceptance of driver support systems. In *Proceedings of the european conference on human centered design for intelligent transport systems* (p. 475-486). Berlin, Germany.
- Adell, E., Nilsson, L., & Varhelyi, A. (2014). How is acceptance measured? Overview of measurement issues, methods and tools. *Driver Acceptance of New Technology. Theory, Measurement and Optimisation*, 73–89.
- Ajzen, I. (1985). From intentions to actions: A theory of planned behavior. In *Action control* (pp. 11–39). Springer, Berlin, Heidelberg.
- Ajzen, I. (1991). The theory of planned behavior. *Organizational behavior and human decision processes*, 50(2), 179–211.
- Ajzen, I., & Fishbein, M. (1977). Attitude-behavior relations: A theoretical analysis and review of empirical research. *Psychological Bulletin*, 84(5), 888.
- Alvarez, I., Martin, A., Dunbar, J., Taiber, J., Wilson, D.-M., & Gilbert, J. E. (2011). Designing driver-centric natural voice user interfaces. , 11, 42–49.
- Amelang, M., & Schmidt-Atzert, L. (2006). *Psychologische Diagnostik und Intervention*. Springer, Berlin, Heidelberg.

- Anderson, J. R., Bothell, D., Byrne, M. D., Douglass, S., Lebiere, C., & Qin, Y. (2004). An integrated theory of the mind. *Psychological review*, 111(4), 1036.
- Anderson, J. R., & Lebiere, C. J. (2014). *The atomic components of thought*. Mahwah, NJ: Erlbaum.
- Andre, A. D., & Wickens, C. D. (1995). When users want what's not best for them. *Ergonomics in design*, 3(4), 10–14.
- Anthoine, E., Moret, L., Regnault, A., Sébille, V., & Hardouin, J.-B. (2014). Sample size used to validate a scale: a review of publications on newly-developed patient reported outcomes measures. *Health and quality of life outcomes*, 12, 176. doi: 10.1186/s12955-014-0176-2
- Auricht, M., Stark, R., & Blume, C. (2014). Integrating User Experience Validation into a New Engineering Development Process for Advanced Driver Assistance Systems. In L. N. Boyle (Ed.), *The 6th International Conference of Automotive User Interfaces and Interactive Vehicular Applications*. Seattle, WA, USA.
- Bainbridge, L. (1983). Ironies of automation. *Automatica*, 19(6), 775–779. doi: 10.1016/0005-1098(83)90046-8
- Balters, S., Sibi, S., Johns, M., Steinert, M., & Ju, W. (2017). Learning-by-Doing: Using Near Infrared Spectroscopy to Detect Habituation and Adaptation in Automated Driving. In S. Boll, B. Pfleging, & B. Donmez (Eds.), *Proceedings of the 9th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 134–143). New York, NY: ACM. doi: 10.1145/3122986.3123006
- Bangor, A., Kortum, P., & Miller, J. (2009). Determining what individual SUS scores mean: Adding an adjective rating scale. *Journal of usability studies*, 4(3), 114–123.
- Bazilinsky, P., Eriksson, A., Petermeijer, B., & de Winter, J. (2017). Usefulness and satisfaction of take-over requests for highly automated driving. In *Road Safety & Simulation International Conference (RSS 2017)*. the Hague, Netherlands.
- Beattie, D., Baillie, L., & Halvey, M. (2015). A comparison of artificial driving sounds for automated vehicles. In *Proceedings of the 2015 ACM International Joint Conference on Pervasive and Ubiquitous Computing* (pp. 451–462).
- Beggiato, M. (2013). Effect of ADAS use on drivers' information processing and situation awareness. In A. Stevens, C. Brusque, & J. Krems (Eds.), *Driver adaptation to information and assistance systems* (pp. 57–80). London: The Institution of Engineering and Technology.
- Beggiato, M., & Krems, J. F. (2013). The evolution of mental model, trust and accep-

- tance of adaptive cruise control in relation to initial information. *Transportation Research Part F: Traffic Psychology and Behaviour*, 18, 47–57.
- Beggiato, M., Pereira, M., Petzoldt, T., & Krems, J. F. (2015). Learning and development of trust, acceptance and the mental model of ACC. A longitudinal on-road study. *Transportation Research Part F: Traffic Psychology and Behaviour*, 35, 75–84. doi: 10.1016/j.trf.2015.10.005
- Beller, J., Heesen, M., & Vollrath, M. (2013). Improving the driver–automation interaction: An approach using automation uncertainty. *Human factors*, 55(6), 1130–1141.
- Bem, D. J. (1967). Self perception: an alternative interpretation of cognitive dissonance phenomena. *Psychological Review*, 74(3), 183–200.
- Bem, D. J. (1972). Self-perception theory. In *Advances in experimental social psychology* (Vol. 6, pp. 1–62). Elsevier.
- Billings, C. E. (2018). *Aviation automation: The search for a human-centered approach*. Erlbaum, Mahwah, NJ.
- Bissell, C. (2009). A history of automatic control. In *Springer handbook of automation* (pp. 53–69). Springer.
- Blömacher, K., Nöcker, G., & Huff, M. (2018). The role of system description for conditionally automated vehicles. *Transportation Research Part F: Traffic Psychology and Behaviour*, 54, 159–170. doi: 10.1016/j.trf.2018.01.010
- Boer, E. R., & Hoedemaeker, M. (1998). Modeling driver behavior with different degrees of automation: A hierarchical decision framework of interacting mental models. In *Proceedings of the 17th European annual conference on human decision making and manual control*. Valenciennes, France.
- Bol, L., & Hacker, D. J. (2012). Calibration research: Where do we go from here? *Frontiers in psychology*, 3, 229. doi: 10.3389/fpsyg.2012.00229
- Brooke, J. (1996). SUS - A quick and dirty usability scale. *Usability evaluation in industry*, 194(189).
- Bubb, H., Bengler, K., Grünen, R. E., & Vollrath, M. (2015). *Automobilergonomie*. Springer, Berlin, Heidelberg.
- Bühner, M. (2011). *Einführung in die Test-und Fragebogenkonstruktion*. Pearson Deutschland GmbH, München.
- Campbell, D. T., & Fiske, D. W. (1959). Convergent and discriminant validation by the multitrait-multimethod matrix. *Psychological Bulletin*, 56(2), 81.
- Carsten, O., Kircher, K., & Jamson, S. (2013). Vehicle-based studies of driving in the

- real world: The hard truth? *Accident Analysis & Prevention*(58), 162–174.
- Carsten, O., & Martens, M. H. (2018). How can humans understand their automated cars? HMI principles, problems and solutions. *Cognition, Technology & Work*, 29(6), 415. doi: 10.1007/s10111-018-0484-0
- Casner, S. M., & Hutchins, E. L. (2019). What Do We Tell the Drivers? Toward Minimum Driver Training Standards for Partially Automated Cars. *Journal of Cognitive Engineering and Decision Making*, 5. doi: 10.1177/1555343419830901
- Chang, C.-M., Toda, K., Sakamoto, D., & Igarashi, T. (2017). Eyes on a Car: An Interface Design for Communication between an Autonomous Car and a Pedestrian. In S. Boll, B. Pfleging, & B. Donmez (Eds.), *Proceedings of the 9th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 65–73). New York, NY: ACM. doi: 10.1145/3122986.3122989
- Chien, S.-Y., Hergeth, S., Semnani-Azad, Z., & Sycara, K. (2015). *Cross-country validation of a cultural scale in measuring trust in automation*.
- Chien, S.-Y., Semnani-Azad, Z., Lewis, M., & Sycara, K. (2014). Towards the development of an inter-cultural scale to measure trust in automation..
- Cooper, G. E., & Harper Jr, R. P. (1969). The use of pilot rating in the evaluation of aircraft handling qualities.
- Cramer, S., & Klohr, J. (2019). Announcing automated lane changes: Active vehicle roll motions as feedback for the driver. *International Journal of Human–Computer Interaction*, 63, 1–16. Retrieved 15.01.2019, from <https://www.tandfonline.com/doi/pdf/10.1080/10447318.2018.1561790?needAccess=true> doi: 10.1080/10447318.2018.1561790
- Cronbach, L. J. (1951). Coefficient alpha and the internal structure of tests. *Psychometrika*, 16(3), 297–334. doi: 10.1007/BF02310555
- Cronbach, L. J., & Meehl, P. E. (1955). Construct validity in psychological tests. *Psychological Bulletin*, 52(4), 281–302. doi: 10.1037/h0040957
- Crundall, D., Andrews, B., van Loon, E., & Chapman, P. (2010). Commentary training improves responsiveness to hazards in a driving simulator. *Accident Analysis and Prevention*, 42(6), 2117–2124. doi: 10.1016/j.aap.2010.07.001
- Cumming, G. (2013). *Understanding the new statistics: Effect sizes, confidence intervals, and meta-analysis*. Routledge, New York, NY, USA.
- Cumming, G., & Finch, S. (2005). Inference by eye: Confidence intervals and how to read pictures of data. *American Psychologist*, 60(2), 170.
- Curran, R., Park, S. Y., Domingo, L., Garcia-Mancilla, J., Santana-Mancilla, P. C.,

- Gonzalez, V. M., & Ju, W. (2018). ¡Vamos!: Observations of Pedestrian Interactions with Driverless Cars in Mexico. In *Proceedings of the 10th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 210–220). Toronto, ON, CN.
- Davis, F. D. (1989). Perceived usefulness, perceived ease of use, and user acceptance of information technology. *MIS quarterly*, 13(3), 319. doi: 10.2307/249008
- de Waard, D. (1996). *The measurement of drivers' mental workload: Doctoral Dissertation Univ. Groningen*.
- DeWitt, D. E., & Hirsch, I. B. (2003). Outpatient insulin therapy in type 1 and type 2 diabetes mellitus: scientific review. *Jama*, 289(17), 2254–2264.
- Dikmen, M., & Burns, C. M. (2016). Autonomous Driving in the Real World: Experiences with Tesla Autopilot and Summon. In P. Green, S. Boll, G. Burnett, J. Gabbard, & S. Osswald (Eds.), *Proceedings of the 8th International Conference on Automotive User Interfaces and Vehicular Applications*. Ann Arbor, MI, USA.
- DIN-EN ISO. (2011). *Ergonomie der Mensch-System-Interaktion – Teil 210: Prozess zur Gestaltung gebrauchstauglicher interaktiver Systeme* (No. 9241-210).
- Dingus, T. A., Klauer, S. G., Neale, V. L., Petersen, A., Lee, S. E., Sudweeks, J., ... others (2006). *The 100-car naturalistic driving study. phase 2: Results of the 100-car field experiment* (Tech. Rep.). United States. Department of Transportation. National Highway Traffic Safety Administration (NHTSA).
- Dmitrenko, D., Vi, C. T., & Obrist, M. (2016). A comparison of scent-delivery devices and their meaningful use for in-car olfactory interaction. In *Proceedings of the 8th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 23–26). Ann Arbor, MI, USA.
- Donmez, B., Boyle, L. N., Lee, J. D., & McGehee, D. V. (2006). Drivers' attitudes toward imperfect distraction mitigation strategies. *Transportation research part F: traffic psychology and behaviour*, 9(6), 387–398.
- Du, N., Haspiel, J., Zhang, Q., Tilbury, D., Pradhan, A. K., Yang, X. J., & Robert Jr, L. P. (2019). Look who's talking now: Implications of av's explanations on driver's trust, av preference, anxiety and mental workload. *Transportation Research Part C: Emerging Technologies*, 104, 428–442.
- Duchowski, A. T. (2007). *Eye tracking methodology: Theory and practice* (2nd ed.). London: Springer.
- Durso, F. T., & Gronlund, S. D. (1999). Situation awareness. *Handbook of Applied Cognition*, 283–314.

- Eichinger, A. (2011). Untersuchungskonzepte für die Evaluation von Systemen zur Erkennung des Fahrerzustands: BASt-Forschungsbericht: FE 82.369/2009. *Berichte der Bundesanstalt für Straßenwesen*, 45–94.
- Endsley, M. R. (2017). Autonomous driving systems: A preliminary naturalistic study of the Tesla Model S. *Journal of Cognitive Engineering and Decision Making*, 11(3), 225–238.
- Endsley, M. R. (2019). The divergence of objective and subjective situation awareness: A meta-analysis. *Journal of Cognitive Engineering and Decision Making*.
- Eriksson, A., & Stanton, N. A. (2017). Takeover time in highly automated vehicles: Noncritical transitions to and from manual control. *Human factors*, 59(4), 689–705.
- European Commission. (2017). High Level Group on the Competitiveness and Sustainable Growth of the Automotive Industry in the European Union - Final Report.
- Feldhütter, A., Segler, C., & Bengler, K. (2017). Does Shifting Between Conditionally and Partially Automated Driving Lead to a Loss of Mode Awareness? In *International Conference on Applied Human Factors and Ergonomics*. Los Angeles, CA, USA.
- Forster, Y., Hergeth, S., Naujoks, F., Beggiato, M., Krems, J. F., & Keinath, A. (2019a). Learning and Development of Mental Models in Interaction with Driving Automation: A Simulator Study. In *The 10th International Driving Symposium on Human Factors in Driver Assessment, Training, and Vehicle Design* (pp. 398–404). Santa Fe, NM, USA.
- Forster, Y., Hergeth, S., Naujoks, F., Beggiato, M., Krems, J. F., & Keinath, A. (2019b). Learning to Use Automation: Behavioral Changes in Interaction with Automated Driving Systems. *Transportation Research Part F: Traffic Psychology and Behaviour*(62), 599–614.
- Forster, Y., Hergeth, S., Naujoks, F., & Krems, J. F. (2018a). How Usability can Save the Day: Methodological Considerations for Making Automated Driving a Success Story. In B. Donmez, B. N. Walker, & K. Fröhlich (Eds.), *Proceedings of the 10th International Conference on Automotive User Interfaces and Interactive Vehicular Applications*. Toronto, ON, CN.
- Forster, Y., Hergeth, S., Naujoks, F., & Krems, J. F. (2018b). Unskilled and Unaware: Subpar Users of Automated Driving Systems Make Spurious Decisions. In *Adjunct Proceedings of the 10th International Conference on Automotive User Interfaces and Interactive Vehicular Applications*. Toronto, ON, CA.

- Forster, Y., Kraus, J., Feinauer, S., & Baumann, M. (2018). Calibration of Trust Expectancies in Conditionally Automated Driving by Brand, Reliability Information and Introductory Videos: An online study. In B. Donmez, B. N. Walker, & K. Fröhlich (Eds.), *Proceedings of the 10th International Conference on Automotive User Interfaces and Interactive Vehicular Applications*. Toronto, ON, CN.
- Forster, Y., Naujoks, F., & Neukum, A. (2016). Your Turn or My Turn? Design of a Human-Machine Interface for Conditional Automation. In *Proceedings of the 8th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 253–260). Ann Arbor, MI, USA. doi: 10.1145/3003715.3005463
- Forster, Y., Naujoks, F., & Neukum, A. (2017). Increasing anthropomorphism and trust in automated driving functions by adding speech output. In *Intelligent Vehicles Symposium (IV), 2017 IEEE*. Redondo Beach, California, USA.
- Forster, Y., Naujoks, F., Neukum, A., & Huestegge, L. (2017). Driver compliance to take-over requests with different auditory outputs in conditional automation. *Accident Analysis and Prevention*, 109, 18–28. doi: 10.1016/j.aap.2017.09.019
- François, M., Osiurak, F., Fort, A., Crave, P., & Navarro, J. (2016). Automotive HMI design and participatory user involvement: review and perspectives. *Ergonomics*, 60(4), 541–552.
- Frison, A.-K., Wintersberger, P., Riener, A., & Schartmüller, C. (2017). Driving Hotzenplotz: A Hybrid Interface for Vehicle Control Aiming to Maximize Pleasure in Highway Driving. In *Proceedings of the 9th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 236–244). Oldenburg, Germany.
- Frison, A.-K., Wintersberger, P., Riener, A., Schartmüller, C., Boyle, L. N., Miller, E., & Weigl, K. (2019). In UX We Trust: Investigation of Aesthetics and Usability of Driver-Vehicle Interfaces and Their Impact on the Perception of Automated Driving. In *Proceedings of the 2019 CHI Conference on Human Factors in Computing Systems* (p. 144). Glasgow, UK.
- Gagne, R. (1984). Learning outcomes and their effects: Useful categories of human performance. *American Psychologist*, 39(4), 377–385.
- Gasser, T. M., Arzt, C., Ayoubi, M., Bartels, A., Bürkle, L., Eier, J., ... Huber, W. (2012). Rechtsfolgen zunehmender fahrzeugautomatisierung. *Berichte der Bundesanstalt für Straßenwesen. Unterreihe Fahrzeugtechnik*(83).
- Gawron, V. (2019). Lessons Lost: What We Learned About Automation in Aviation Can Be Applied to Autonomous Vehicles. *Ergonomics in Design*. doi: 10.1177/

- Ghazizadeh, M., Lee, J. D., & Boyle, L. N. (2012). Extending the technology acceptance model to assess automation. *Cognition, Technology & Work*, 14(1), 39–49.
- Glasman, L. R., & Albarracin, D. (2006). Forming attitudes that predict future behavior: A meta-analysis of the attitude-behavior relation. *Psychological bulletin*, 132(5), 778.
- Gold, C., Damböck, D., Lorenz, L., & Bengler, K. (2013). “Take over!” How long does it take to get the driver back into the loop? In *Proceedings of the Human Factors and Ergonomics Society Annual Meeting*. SAGE Publications Sage CA: Los Angeles, CA.
- Gold, C., Körber, M., Hohenberger, C., Lechner, D., & Bengler, K. (2015). Trust in automation—Before and after the experience of take-over scenarios in a highly automated vehicle. *Procedia Manufacturing*, 3, 3025–3032.
- Gold, C., Naujoks, F., Radlmayr, J., Bellem, H., & Jarosch, O. (2017). Testing Scenarios for Human Factors Research in Level 3 Automated Vehicles. In *International Conference on Applied Human Factors and Ergonomics*. Los Angeles, CA, USA: Springer, Berlin, Heidelberg.
- Green, P., Levison, w., Paelke, G., & Serafin, C. (1994). *Suggested Human Factors Design Guidelines for Driver Information Systems* (Tech. Rep.). University of Michigan Transportation Research Institute (UMTRI).
- Gugenheimer, J., Schaub, F., Neiswander, G. M., Guneratne, E., & Weber, M. (2014). User Authentication for Rotary Knob Controlled In-car Applications. In L. N. Boyle (Ed.), *In Proceedings of the 6th International Conference on Automotive User Interfaces and Vehicular Applications* (pp. 1–8). Seattle, WA, USA. doi: 10.1145/2667317.2667338
- Guo, C., Sentouh, C., Popieul, J.-C., & Haué, J.-B. (2019). Predictive shared steering control for driver override in automated driving: A simulator study. *Transportation Research Part F: Traffic Psychology and Behaviour*, 61, 326–336. doi: 10.1016/j.trf.2017.12.005
- Guttman, L. (1945). A basis for analyzing test-retest reliability. *Psychometrika*, 10, 255–282.
- Haeuslschmid, R., Pfleging, B., & Alt, F. (2016). A Design Space to Support the Development of Windshield Applications for the Car. In J. Kaye, A. Druin, C. Lampe, D. Morris, & J. P. Hourcade (Eds.), *the 2016 CHI Conference* (pp. 5076–5091). San Jose, CA, USA. doi: 10.1145/2858036.2858336

- Hancock, P. A., & Matthews, G. (2018). Workload and performance: Associations, insensitivities, and dissociations. *Human factors*. doi: 10.1177/0018720818809590
- Harmo, P., Taipalus, T., Knuuttila, J., Vallet, J., & Halme, A. (2005). Needs and solutions-home automation and service robots for the elderly and disabled. In *2005 IEEE/RSJ international conference on intelligent robots and systems* (pp. 3201–3206).
- Hart, C. A. (2017). *Challenges of increasing automation*. Retrieved from <https://commons.erau.edu/ntas/2017/tuesday-august-15/8>
- Hart, C. A. (2019). *Self driving safety steps into the unknown: [web blog post]*. Retrieved from <http://www.thedrive.com/tech/26896/self-driving-safety-steps-into-the-unknown>
- Hart, S., & Staveland, L. (1988). Development of NASA-TLX (Task Load Index): Results of empirical and theoretical research. In *Advances in psychology* (Vol. 52, pp. 139–183). Elsevier.
- Hassenzahl, M. (2001). The effect of perceived hedonic quality on product appealingness. *International Journal of Human-Computer Interaction*, 13(4), 481–499. doi: 10.1207/S15327590IJHC1304_07
- Hassenzahl, M. (2003). The thing and i: understanding the relationship between user and product. In *Funology* (pp. 31–42). Springer Netherlands.
- Hassenzahl, M., Burmester, M., & Koller, F. (2003). AttrakDiff: Ein Fragebogen zur Messung wahrgenommener hedonischer und pragmatischer Qualität. In *Mensch & Computer 2003* (pp. 187–196). Springer.
- HAVEit Consortium. (2011). The future of driving. Deliverable D61.1 Final Report.
- Hayhoe, M. M., & Ballard, D. (2005). Eye movements in natural behavior. *Trends in Cognitive Sciences*, 9(4), 188–194. doi: 10.1016/j.tics.2005.02.009
- Hayhoe, M. M., Shrivastava, A., Mruczek, R., & Pelz, J. B. (2003). Visual memory and motor planning in a natural task. *Journal of vision*, 3(1), 49–63. doi: 10.1167/3.1.6
- Helldin, T., Falkman, G., Riveiro, M., & Davidsson, S. (2013). Presenting system uncertainty in automotive UIs for supporting trust calibration in autonomous driving. In J. Terken (Ed.), *Proceedings of the 5th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 210–217). Eindhoven, The Netherlands: ACM. doi: 10.1145/2516540.2516554
- Henrich, J., Heine, S. J., & Norenzayan, A. (2010). The weirdest people in the world? *The Behavioral and brain sciences*, 33(2-3), 61–135. doi: 10.1017/

- Hergeth, S. (2016). *Automation Trust in Conditional Automated Driving Systems: Approaches to Operationalization and Design: PhD Thesis*. Technische Universität Chemnitz.
- Hergeth, S., Lorenz, L., & Krems, J. F. (2017). Prior familiarization with takeover requests affects drivers' takeover performance and automation trust. *Human factors*, 59(3), 457–470.
- Hergeth, S., Lorenz, L., Vilimek, R., & Krems, J. F. (2016). Keep your scanners peeled: Gaze behavior as a measure of automation trust during highly automated driving. *Human factors*, 58(3), 509–519.
- Hock, P., Kraus, J., Babel, F., Walch, M., Rukzio, E., & Baumann, M. (2018). How to design valid simulator studies for investigating user experience in automated driving. In B. Donmez, B. N. Walker, & K. Fröhlich (Eds.), *Proceedings of the 10th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 105–117). Toronto, ON, CN. doi: 10.1145/3239060.3239066
- Hock, P., Kraus, J., Walch, M., Lang, N., & Baumann, M. (2016). Elaborating feedback strategies for maintaining automation in highly automated driving. In P. Green & S. Boll (Eds.), *Proceedings of the 8th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 105–112). Ann Arbor, MI, USA. doi: 10.1145/3003715.3005414
- Hoff, K. A., & Bashir, M. (2015). Trust in automation: Integrating empirical evidence on factors that influence trust. *Human Factors*, 57(3), 407–434.
- Homans, H., Radlmayr, J., & Bengler, K. (2019). Levels of Driving Automation from a User's Perspective: How Are the Levels Represented in the User's Mental Model? In *International Conference on Human Interaction and Emerging Technologies* (pp. 21–27).
- Hornbæk, K. (2006). Current practice in measuring usability: Challenges to usability studies and research. *International Journal of Human-Computer Studies*, 64(2), 79–102. doi: 10.1016/j.ijhcs.2005.06.002
- Hornbæk, K., & Law, E. L.-C. (2007). Meta-analysis of correlations among usability measures. In *Proceedings of the sigchi conference on human factors in computing systems* (pp. 617–626). San Jose, California, USA: ACM. doi: 10.1145/1240624.1240722
- Howell, D. C. (2007). The treatment of missing data. *The Sage handbook of social science methodology*, 208–224.

- Huys, R., Daffertshofer, A., & Beek, P. J. (2004). Multiple time scales and multiform dynamics in learning to juggle. *Motor Control*, 8(2), 188–212. doi: 10.1123/mcj.8.2.188
- Inners, M., & Kun, A. L. (2017). Beyond liability: Legal issues of human-machine interaction for automated vehicles. In *Proceedings of the 9th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 245–253). Oldenburg, Germany.
- Irwin, D. E. (1992). Visual memory within and across fixations. In *Eye movements and visual cognition* (pp. 146–165). Springer, Cham.
- ISO. (2010). *Road vehicles – Symbols for controls, indicators and tell-tales* (No. ISO 2575:2010).
- ISO. (2012). *Road vehicles—Ergonomic aspects of transport information and control systems—Calibration tasks for methods which assess driver demand due to the use of in-vehicle systems* (No. 14198). Geneva, Switzerland.
- Jacob, R. J., & Karn, K. S. (2003). Eye tracking in human-computer interaction and usability research: Ready to deliver the promises. *Mind*, 2(3), 4.
- Jahn, G., Krems, J. F., & Gelau, C. (2009). Skill acquisition while operating in-vehicle information systems: Interface design determines the level of safety-relevant distractions. *Human factors*, 51(2), 136–151. doi: 10.1177/0018720809336542
- Jarosch, O., Bellem, H., & Bengler, K. (2019). Effects of Task-Induced Fatigue in Prolonged Conditional Automated Driving. *Human factors*.
- Jarosch, O., & Bengler, K. (2018). Rating of Take-Over Performance in Conditionally Automated Driving Using an Expert-Rating System. In *International Conference on Applied Human Factors and Ergonomics*. Los Angeles, CA, USA: Springer.
- Jarosch, O., Kuhnt, M., Paradies, S., & Bengler, K. (2017). It's Out of Our Hands Now! Effects of Non-Driving Related Tasks During Highly Automated Driving on Drivers' Fatigue. In *The 9th International Driving Symposium on Human Factors in Driver Assessment, Training, and Vehicle Design*. Manchester Village, Vermont, USA.
- Jian, J.-Y., Bisantz, A. M., & Drury, C. G. (2000). Foundations for an empirically determined scale of trust in automated systems. *International Journal of Cognitive Ergonomics*, 4(1), 53–71.
- Jones, P. S., Lee, J. W., Phillips, L. R., Zhang, X. E., & Jaceldo, K. B. (2001). An adaptation of brislin's translation model for cross-cultural research. *Nursing research*, 50(5), 300–304.

- Just, M. A., & Carpenter, P. A. (1976). The role of eye-fixation research in cognitive psychology. *Behavior Research Methods & Instrumentation*, 8(2), 139–143.
- Just, M. A., & Carpenter, P. A. (1984). Using eye fixations to study reading comprehension. *New methods in reading comprehension research*, 151–182.
- Karahanna, E., & Straub, D. W. (1999). The psychological origins of perceived usefulness and ease-of-use. *Information & Management*, 35(4), 237–250. doi: 10.1016/S0378-7206(98)00096-2
- Kauffmann, N., Winkler, F., & Vollrath, M. (2018). What Makes an Automated Vehicle a Good Driver? In *Proceedings of the 2018 CHI Conference on Human Factors in Computing Systems*. Montreal, QC, CN.
- Kaye, S.-A., Lewis, I., & Freeman, J. (2018). Comparison of self-report and objective measures of driving behavior and road safety: A systematic review. *Journal of safety research*, 65, 141–151. doi: 10.1016/j.jsr.2018.02.012
- Kemeny, A., & Panerai, F. (2003). Evaluating perception in driving simulation experiments. *Trends in Cognitive Sciences*, 7(1), 31–37. doi: 10.1016/S1364-6613(02)00011-6
- Kenntner-Mabiala, R., Kaussner, Y., Hoffmann, S., & Volk, M. (2016). Driving performance of elderly drivers in comparison to middle-aged drivers during a representative, standardized driving test. *Zeitschrift für Verkehrssicherheit*, 3, 73.
- Keselman, H. J., Wilcox, R. R., Othman, A. R., & Fradette, K. (2002). Trimming, transforming statistics, and bootstrapping: Circumventing the biasing effects of heteroscedasticity and nonnormality. *Journal of Modern Applied Statistical Methods*, 1(2), 288–309.
- Kline, T. J. B. (1999). The team player inventory: Reliability and validity of a measure of predisposition toward organizational team-working environments. *Journal for specialists in Group Work*, 24(1), 102–112.
- Knappe, G., Keinath, A., & Meinecke, C. (2006). Empfehlungen für die Bestimmung der Spurhaltequalität im Kontext der Fahrsimulation. *MMI-interaktiv*, 11, 3–13.
- König, M., & Neumayr, L. (2017). Users' resistance towards radical innovations: The case of the self-driving car. *Transportation Research Part F: Traffic Psychology and Behaviour*, 44, 42–52.
- Konradt, U., & Christophersen, T. (2013). Measuring psychological constructs using single-item scales: Answers to experts' comments and additional questions. *Interacting with Computers*, 25(4), 331–333.
- Koo, J., Kwac, J., Ju, W., Steinert, M., Leifer, L., & Nass, C. (2015). Why did

- my car just do that? explaining semi-autonomous driving actions to improve driver understanding, trust, and performance. *International Journal on Interactive Design and Manufacturing (IJIDeM)*, 9(4), 269–275.
- Körber, M., Baseler, E., & Bengler, K. (2018). Introduction matters: Manipulating trust in automation and reliance in automated driving. *Applied ergonomics*, 66, 18–31. doi: 10.1016/j.apergo.2017.07.006
- Kruger, J., & Dunning, D. (1999). 6Unskilled and unaware of it: How difficulties in recognizing one’s own incompetence lead to inflated self-assessments. *Journal of Personality and Social Psychology*, 77(6), 1121.
- Kun, A. L. (2017). Human-machine interaction for vehicles: Review and outlook. *Foundations and Trends in Human-Computer Interaction*, 11(4), 201–293. doi: 10.1561/11000000069
- Kunze, A., Summerskill, S., Marshall, R., & Filtness, A. (2018). Augmented reality displays for communicating uncertainty information in automated driving. In B. Donmez & P. Fröhlich (Eds.), *Proceedings of the 10th international conference on automotive user interfaces and interactive vehicular applications - automotiveui ’18* (pp. 164–175). New York, New York, USA: ACM Press.
- Kyriakidis, M., Happee, R., & de Winter, J. C. F. (2015). Public opinion on automated driving: Results of an international questionnaire among 5000 respondents. *Transportation Research Part F: Traffic Psychology and Behaviour*, 32, 127–140.
- Large, D., Burnett, G., Crundall, E., Lawson, G., & Skrypchuk, L. (2016). Twist It, Touch It, Push It, Swipe It: Evaluating Secondary Input Devices for Use with an Automotive Touchscreen HMI. In P. Green, S. Boll, G. Burnett, J. Gabbard, & S. Osswald (Eds.), *The 8th International Conference on Automotive User Interfaces and Vehicular Applications*. Ann Arbor, MI, USA: ACM.
- Large, D., Pampel, S., Burnett, G., Matthias, R., Thompson, S., & Skrypchuk, L. (2018). Exploring Drivers’ Visual Behavior During Take-Over Requests. In *6th International Conference on Driver Distraction and Inattention*. Gothenburg, Sweden.
- Large, D. R., Banks, V., Burnett, G., & Margaritis, N. (2017). Putting the joy in driving: Investigating the use of a joystick as an alternative to traditional controls within future autonomous vehicles. In *Proceedings of the 9th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 31–39). Oldenburg, Germany.
- Laugwitz, B., Held, T., & Schrepp, M. (2008). Construction and evaluation of a user experience questionnaire. In *Symposium of the Austrian HCI and Usability Engi-*

- neering Group* (pp. 63–76).
- Lee, J., Kim, N., Imm, C., Kim, B., Yi, K., & Kim, J. (2016). A question of trust: An ethnographic study of automated cars on real roads. In *Proceedings of the 8th international conference on automotive user interfaces and interactive vehicular applications* (pp. 201–208). Ann Arbor, MI, USA.
- Lee, J. D., & See, K. A. (2004). Trust in automation: Designing for appropriate reliance. *Human factors*, 46(1), 50–80.
- Lee, S. C., Hwangbo, H., & Ji, Y. G. (2016). Perceived visual complexity of in-vehicle information display and its effects on glance behavior and preferences. *International Journal of Human-Computer Interaction*, 32(8), 654–664. doi: 10.1080/10447318.2016.1184546
- Lee, S. C., & Ji, Y. G. (2018). Complexity of in-vehicle controllers and their effect on task performance. *International Journal of Human-Computer Interaction*, 1–10. doi: 10.1080/10447318.2018.1428263
- Lewis, J. R. (2002). Psychometric Evaluation of the PSSUQ Using Data from Five Years of Usability Studies. *International Journal of Human-Computer Interaction*, 14(3–4), 463–488. doi: 10.1515/9783110887242.3
- Lewis, J. R., & Sauro, J. (2009). The factor structure of the system usability scale. In *International conference on human centered design* (pp. 94–103).
- Liu, J., Gardi, A., Ramasamy, S., Lim, Y., & Sabatini, R. (2016). Cognitive pilot-aircraft interface for single-pilot operations. *Knowledge-based systems*, 112, 37–53.
- Liu, R., Kwak, D., Devarakonda, S., Bekris, K., & Iftode, L. (2017). Investigating remote driving over the LTE network. In *Proceedings of the 9th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 264–269). Oldenburg, Germany.
- Löcken, A., Heuten, W., & Boll, S. (2016). Enlightening Drivers: A Survey on In-Vehicle Light Displays. In *Proceedings of the 8th international conference on automotive user interfaces and interactive vehicular applications* (pp. 97–104). Ann Arbor, MI, USA.
- Lord, F. M. (1953). On the statistical treatment of football numbers. *American Psychologist*, 8, 750–751.
- Louw, T. (2017). *The Human Factors of Transitions in Highly Automated Driving: Doctoral Dissertation*. University of Leeds Institute for Transport Studies.
- Louw, T., Kuo, J., Romano, R., Radhakrishnan, V., Lenné, M. G., & Merat, N. (2019). Engaging in NDRTs affects drivers’ responses and glance patterns after silent au-

- tomation failures. *Transportation Research Part F: Traffic Psychology and Behaviour*, 62, 870–882.
- Louw, T., Madigan, R., Carsten, O., & Merat, N. (2016). Were they in the loop during automated driving? Links between visual attention and crash potential. *Injury Prevention*, 23(4), 281–286.
- Louw, T., & Merat, N. (2017). Are you in the loop? Using gaze dispersion to understand driver visual attention during vehicle automation. *Transportation Research Part C: Emerging Technologies*, 76, 35–50. doi: 10.1016/j.trc.2017.01.001
- Lüdtke, O., Robitzsch, A., Trautwein, U., & Köller, O. (2007). Umgang mit fehlenden Werten in der psychologischen Forschung. *Psychologische Rundschau*, 58(2), 103–117. doi: 10.1026/0033-3042.58.2.103
- Manca, L., de Winter, J. C. F., & Happee, R. (2015). Visual Displays for Automated Driving: A Survey. In *Adjunct Proceedings of the 7th International Conference on Automotive User Interfaces and Interactive Vehicular Applications*. Nottingham, UK.
- Manser, M., Creaser, J., & Boyle, L. (2013). Methodological and measurement issues in behavioural adaptation. In M. Rudin-Brown & S. Jamson (Eds.), *Behavioural adaptation and road safety: Theory, evidence, and action* (pp. 339–358). CRC Press: London.
- McCall, R., McGee, F., Meschtscherjakov, A., Louveton, N., & Engel, T. (2016). Towards a taxonomy of autonomous vehicle handover situations. In *Proceedings of the 8th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 193–200). Ann Arbor, MI, USA.
- McIlwraith, A. (2016). *Information security and employee behaviour: how to reduce risk through employee education, training and awareness*. Routledge, New York, NY, USA.
- Mehlenbacher, B., Wogalter, M. S., & Laughery, K. R. (2002). On the Reading of Product Owner’s Manuals: Perceptions and Product Complexity. In *Proceedings of the Human Factors and Ergonomics Society Annual Meeting* (Vol. 46, pp. 730–734). doi: 10.1177/154193120204600610
- Mehler, B., Reimer, B., Lee, C., Kidd, D., & Reagan, I. (2017). Considering self-report in the interpretation of objective performance data in the comparison of HMI systems. In *Proceedings of the 9th International Driving Symposium on Human Factors in Driver Assessment, Training, and Vehicle Design*. Manchester Village, Vermont, USA.

- Merat, N., Jamson, A. H., Lai, F. C., Daly, M., & Carsten, O. M. (2014). Transition to manual: Driver behaviour when resuming control from a highly automated vehicle. *Transportation Research Part F: Traffic Psychology and Behaviour*, 27, 274–282. doi: 10.1016/j.trf.2014.09.005
- Merat, N., Seppelt, B., Louw, T., Engström, J., Lee, J. D., Johansson, E., ... Keinath, A. (2019). The “out-of-the-loop” concept in automated driving: Proposed definition, measures and implications. *Cognition, Technology & Work*, 21(1), 87–98.
- Merenda, C., Kim, H., Gabbard, J. L., Leong, S., Large, D. R., & Burnett, G. (2017). Did you see me?: Assessing perceptual vs. real driving gains across multi-modal pedestrian alert systems. In *Proceedings of the 9th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 40–49). Oldenburg, Germany.
- Michon, J. A. (1985). A critical view of driver behavior models: what do we know, what should we do? In *Human behavior and traffic safety* (pp. 485–524). Springer US: Boston, MA. doi: 10.1007/978-1-4613-2173-6_19
- Millonig, A., & Fröhlich, P. (2018). Where Autonomous Buses Might and Might Not Bridge the Gaps in the 4 A’s of Public Transport Passenger Needs: a Review. In *Proceedings of the 10th international conference on automotive user interfaces and interactive vehicular applications* (pp. 291–297). Toronto, ON, CN.
- Minge, M., Thüring, M., Wagner, I., & Kuhr, C. V. (2016). The mecue questionnaire: A modular tool for measuring user experience. *Advances in Ergonomics Modeling*, 115–128.
- Mirrig, A., Wintersberger, P., Sutter, C., & Ziegler, J. (2016). A framework for analyzing and calibrating trust in automated vehicles. In *In Proceedings of the 8th International Conference on Automotive User Interfaces and Interactive Vehicular Applications*. Ann Arbor, MI, USA.
- Moore, G. E., et al. (1965). *Cramming more components onto integrated circuits*. McGraw-Hill New York, NY, USA:.
- Naujoks, F., Befelein, D., Wiedemann, K., & Neukum, A. (2017). A review of non-driving-related tasks used in studies on automated driving. In *International Conference on Applied Human Factors and Ergonomics* (pp. 525–537). Los Angeles, CA, USA: Springer.
- Naujoks, F., Forster, Y., Wiedemann, K., & Neukum, A. (2017a). A human-machine interface for cooperative highly automated driving. In *Advances in Human Aspects of Transportation* (pp. 585–595). Springer.

- Naujoks, F., Forster, Y., Wiedemann, K., & Neukum, A. (2017b). Improving Usefulness of Automated Driving by Lowering Primary Task Interference through HMI Design. *Journal of Advanced Transportation*, 2017.
- Naujoks, F., Hergeth, S., Wiedemann, K., Schömig, N., Forster, Y., & Keinath, A. (2019). Test procedure for evaluating the human-machine-interface of vehicles with automated driving. *Traffic Injury Prevention*, 20, 146–151. doi: 10.1080/15389588.2019.1603374
- Naujoks, F., Hergeth, S., Wiedemann, K., Schömig, N., & Keinath, A. (2018). Use cases for assessing, testing, and validating the human machine interface of automated driving systems. In *Proceedings of the human factors and ergonomics society annual meeting* (pp. 1873–1877). Los Angeles, CA: Sage publications.
- Naujoks, F., Kiesel, A., & Neukum, A. (2016). Cooperative warning systems: The impact of false and unnecessary alarms on drivers' compliance. *Accident Analysis and Prevention*, 97, 162–175.
- Naujoks, F., Mai, C., & Neukum, A. (2014). The effect of urgency take-over requests during highly automated driving under distraction conditions. *Advances in Human Aspects of Transportation*, 7(Part I), 431.
- Naujoks, F., Purucker, C., & Neukum, A. (2015). Determining maximum velocity for automated driving functions. In *Mensch und Computer: Workshop Automotive HMI*. Stuttgart, Germany.
- Naujoks, F., Purucker, C., Neukum, A., Wolter, S., & Steiger, R. (2015). Controllability of partially automated driving functions—does it matter whether drivers are allowed to take their hands off the steering wheel? *Transportation Research Part F: Traffic Psychology and Behaviour*, 35, 185–198.
- Naujoks, F., Purucker, C., Wiedemann, K., & Marberger, C. (2019). Noncritical state transitions during conditionally automated driving on german freeways: Effects of non-driving related tasks on takeover time and takeover quality. *Human factors*, 1–18.
- Naujoks, F., & Totzke, I. (2014). Behavioral adaptation caused by predictive warning systems – The case of congestion tail warnings. *Transportation Research Part F: Traffic Psychology and Behaviour*, 26, 49–61.
- Naujoks, F., Wiedemann, K., Schömig, N., Hergeth, S., & Keinath, A. (2019). Towards guidelines and verification methods for automated vehicle HMIs. *Transportation Research Part F: Traffic Psychology and Behaviour*, 60, 121–136.
- Naujoks, F., Wiedemann, K., Schömig, N., Jarosch, O., & Gold, C. (2018). Expert-

- based controllability assessment of control transitions from automated to manual driving. *MethodsX*, 5, 579–592. doi: 10.1016/j.mex.2018.05.007
- Navarro, J., Mars, F., Forzy, J.-F., El-Jaafari, M., & Hoc, J.-M. (2010). Objective and subjective evaluation of motor priming and warning systems applied to lateral control assistance. *Accident Analysis and Prevention*, 42(3), 904–912. doi: 10.1016/j.aap.2009.07.008
- Neale, V. L., & Dingus, T. A. (1998). Commentaries in: Human Factors issues for automated highway systems (AHS). *Intelligent Transportation Systems Journal: Technology, Planning, and Operations*, 4, 111–119.
- Nees, M. (2016). *Acceptance of self-driving cars: An examination of idealized versus realistic portrayals with a self-driving cars acceptance scale*. Washington, D.C..
- Neukum, A., Lübbecke, T., Krüger, H.-P., Mayser, C., & Steinle, J. (2008). ACC-Stop&Go: Fahrerverhalten an funktionalen Systemgrenzen. In 5. Workshop Fahrerassistenzsysteme-FAS. FMRT Karlsruhe.
- Neves, D. M., & Anderson, J. R. (1981). Knowledge compilation: Mechanisms for the automatization of cognitive skills. *Cognitive skills and their acquisition*, 57–84.
- Nevitt, J., & Hancock, G. R. (2001). Performance of bootstrapping approaches to model test statistics and parameter standard error estimation in structural equation modeling. *Structural Equation Modelling*, 8(3), 353–377.
- Newell, A., & Rosenbloom, P. S. (1981). Mechanisms of skill acquisition and the law of practice. *Cognitive skills and their acquisition*, 1(1981), 1–55.
- NHTSA. (2012). Visual-manual NHTSA driver distraction guidelines for in-vehicle electronic devices. *Washington, DC: National Highway Traffic Safety Administration (NHTSA), Department of Transportation (DOT)*.
- NHTSA. (2013). *Preliminary statement of policy concerning automated vehicles*. NHTSA (14-13). Washington D.C.: US DOT.
- NHTSA. (2016). Federal Automated Vehicles Policy. Accelerating the Next Revolution in Roadway Safety. *Washington, DC: National Highway Traffic Safety Administration (NHTSA), Department of Transportation (DOT)*.
- Nielsen, J., & Levy, J. (1994). Measuring Usability: Preference vs. Performance. *Communications of the ACM*, 37(4), 66–75.
- Noble, A. M., Klauer, S. G., Doerzaph, Z. R., & Manser, M. P. (2019). Driver Training for Automated Vehicle Technology—Knowledge, Behaviors, and Perceived Familiarity. In *Proceedings of the Human Factors and Ergonomics Society Annual Meeting* (Vol. 63, pp. 2110–2114). SAGE Publications Sage CA: Los Angeles, CA.

- Nordhoff, S., de Winter, J., Madigan, R., Merat, N., van Arem, B., & Happee, R. (2018). User acceptance of automated shuttles in Berlin-Schöneberg: A questionnaire study. *Transportation Research Part F: Traffic Psychology and Behaviour*, 58, 843–854. doi: 10.1016/j.trf.2018.06.024
- Nordhoff, S., van Arem, B., & Happee, R. (2016). Conceptual Model to Explain, Predict, and Improve User Acceptance of Driverless Podlike Vehicles. *Transportation Research Record: Journal of the Transportation Research Board*, 2602, 60–67. doi: 10.3141/2602-08
- Norman, D., Miller, J., & Henderson, A. (1995). What you see, some of what’s in the future, and how we go about doing it: HI at Apple Computer. Denver, CO, USA.
- Norman, D. A. (1990). The ‘problem’ with automation: Inappropriate feedback and interaction, not ‘over-automation’. *Philosophical Transactions of the Royal Society of London. Series B, Biological Sciences*, 585–593.
- Norman, D. A. (2005). Human-centered design considered harmful. *Interactions*, 12(4), 14–19.
- Norman, G. (2010). Likert scales, levels of measurement and the laws of statistics. *Advances in health sciences education*, 15(5), 625–632.
- Nunes, A., Reimer, B., & Coughlin, J. F. (2018). People must retain control of autonomous vehicles. *Nature*, 556(7700), 169–171. doi: 10.1038/d41586-018-04158-5
- Nunnally, J. C. (1978). Psychometric theory. *New York: McGraw-Hill*.
- O’connor, B. P. (2000). SPSS and SAS programs for determining the number of components using parallel analysis and Velicer’s MAP test. *Behavior Research Methods, Instruments, & Computers*, 32(3), 396–402. doi: 10.3758/BF03200807
- Omozik, K., Yang, Y., Kuntermann, I., Hergeth, S., & Bengler, K. (2019). How long does it take to relax? Observation of driver behaviors during real-world conditionally automated driving. In *The 10th International Driving Symposium on Human Factors in Driver Assessment, Training, and Vehicle Design*. Santa Fe, NM, USA.
- Osswald, S., Wurhofer, D., Trösterer, S., Beck, E., & Tscheligi, M. (2012). Predicting information technology usage in the car: Towards a car technology acceptance model. In A. L. Kun, L. N. Boyle, B. Reimer, & A. Riener (Eds.), *Proceedings of the 4th International Conference on Automotive User Interfaces and Interactive Vehicular Applications*. Portsmouth NH, USA.
- Ostrom, T. M. (1969). The relationship between the affective, behavioral, and cognitive components of attitude. *Journal of Experimental Social Psychology*, 5(1), 12–30.

- Palmer, C., & Meyer, R. K. (2000). Conceptual and motor learning in music performance. *Psychological science*, 11(1), 63–68. doi: 10.1111/1467-9280.00216
- Parasuraman, R., & Byrne, E. A. (2003). Automation and human performance in aviation. *Principles and practice of aviation psychology*, 311–356.
- Parasuraman, R., & Riley, V. (1997). Humans and automation: Use, misuse, disuse, abuse. *Human factors*, 39(2), 230–253.
- Parasuraman, R., Sheridan, T. B., & Wickens, C. D. (2000). A model for types and levels of human interaction with automation. *IEEE Transactions on systems, man, and cybernetics-Part A: Systems and Humans*, 30(3), 286–297.
- Patterson, R. D. (1990). Auditory warning sounds in the work environment. *Philosophical Transactions of the Royal Society of London. B, Biological Sciences*, 327(1241), 485–492.
- Payre, W., Cestac, J., Dang, N.-T., Vienne, F., & Delhomme, P. (2017). Impact of training and in-vehicle task performance on manual control recovery in an automated car. *Transportation Research Part F: Traffic Psychology and Behaviour*, 46, 216–227. doi: 10.1016/j.trf.2017.02.001
- Payre, W., Cestac, J., & Delhomme, P. (2014). Intention to use a fully automated car: Attitudes and a priori acceptability. *Transportation Research Part F: Traffic Psychology and Behaviour*, 27, 252–263. doi: 10.1016/j.trf.2014.04.009
- Payre, W., Cestac, J., & Delhomme, P. (2016). Fully automated driving: impact of trust and practice on manual control recovery. *Human factors*, 58(2), 229–241.
- Petermeijer, S. M., De Winter, J. C., & Bengler, K. J. (2015). Vibrotactile displays: A survey with a view on highly automated driving. *IEEE Transactions on Intelligent Transportation Systems*, 17(4), 897–907.
- Pettersson, I., Frison, A.-K., Lachner, F., Riener, A., & Nohage, J. (2018). Triangulation in UX Studies: Learning from Experience. In O. Mival, M. Smyth, & P. Dalsgaard (Eds.), *The 2016 ACM Conference Companion Publication* (pp. 341–344). doi: 10.1145/3064857.3064858
- Pettersson, I., Lachner, F., Frison, A.-K., Riener, A., & Butz, A. (2018). A Bermuda Triangle? A Review of Method Application and Triangulation in User Experience Evaluation. In R. Mandryk, M. Hancock, M. Perry, & A. Cox (Eds.), *The 2018 CHI Conference* (pp. 1–16). doi: 10.1145/3173574.3174035
- Petty, R. E., & Cacioppo, J. T. (1986). The elaboration likelihood model of persuasion. In L. Berkowitz (Ed.), *Advances in experimental social psychology* (Vol. 19, pp. 123–205). Orlando (FL): Academic Press. doi: 10.1016/S0065-2601(08)60214-2

- Plan, E. L. (2014). Modeling and simulation of count data. *CPT Pharmacotherapeutics & Systems Pharmacology*, 3(8), 1–12.
- Politis, I., Brewster, S., & Pollick, F. (2015). Language-based multimodal displays for the handover of control in autonomous cars. In *Proceedings of the 7th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 3–10). Nottingham, UK.
- Pradhan, A. K., Fisher, D. L., & Pollatsek, A. (2005). The effect of PC-based training on novice driver' risk awareness in a driving simulator. In *Proceedings of the 3rd international driving symposium on human factors in driver assessment, training and vehicle design*. Rockport, ME, USA.
- Pradhan, A. K., Pollatsek, A., Knodler, M., & Fisher, D. L. (2009). Can younger drivers be trained to scan for information that will reduce their risk in roadway traffic scenarios that are hard to identify as hazardous? *Ergonomics*, 52(6), 657–673. doi: 10.1080/00140130802550232
- Pradhan, A. K., Sullivan, J., Schwarz, C., Feng, F., & Bao, S. (2019). Training and education: Human factors considerations for automated driving systems. In G. Meyer & S. Beiker (Eds.), *Road vehicle automation 5* (Vol. 40, pp. 77–84). Cham, Switzerland: Springer. doi: 10.1007/978-3-319-94896-6_7
- Price, M., Lee, J. D., Dinparastdjadid, A., Toyoda, H., & Domeyer, J. (2019). Effect of automation instructions and vehicle control algorithms on eye behavior in highly automated vehicles. *International Journal of Automotive Engineering*, 10(1), 73–79.
- Purucker, C., Naujoks, F., Prill, A., & Neukum, A. (2016). Evaluating distraction of in-vehicle information systems while driving by predicting total eyes-off-road times with keystroke level modeling. *Applied Ergonomics*, 58, 543–554.
- Radlmayr, J., Gold, C., Lorenz, L., Farid, M., & Bengler, K. (2014). How traffic situations and non-driving related tasks affect the take-over quality in highly automated driving. *Proceedings of the Human Factors and Ergonomics Society Annual Meeting*, 58(1), 2063–2067. doi: 10.1177/1541931214581434
- Rahman, M. M., Lesch, M. F., Horrey, W. J., & Strawderman, L. (2017). Assessing the utility of TAM, TPB, and UTAUT for advanced driver assistance systems. *Accident Analysis & Prevention*, 108, 361–373. doi: 10.1016/j.aap.2017.09.011
- RESPONSE Consortium. (2006). Code of practice for the design and evaluation of ADAS: RESPONSE 3: A PReVENT Project.
- Revelle, W., & Zinbarg, R. E. (2009). Coefficients alpha, beta, omega, and the glb:

- Comments on Sijtsma. *Psychometrika*, 74(1), 145.
- Richardson, N. T., Sprung, A., & Michel, B. (2019). Entwicklung und Validierung eines Fragebogens zur Erfassung des mentalen Modells für das hochautomatisierte Fahren. *Zeitschrift fuer Arbeitswissenschaft*.
- Roberts, M. J., Gray, H., & Lesnik, J. (2017). Preference versus performance: Investigating the dissociation between objective measures and subjective ratings of usability for schematic metro maps and intuitive theories of design. *International Journal of Human-Computer Studies*, 98, 109–128. doi: 10.1016/j.ijhcs.2016.06.003
- Rödel, C., Stadler, S., Meschtscherjakov, A., & Tscheligi, M. (2014). Towards autonomous cars. In L. N. Boyle (Ed.), *Proceedings of the 6th international conference on automotive user interfaces and interactive vehicular applications* (pp. 1–8). Seattle, WA, USA. doi: 10.1145/2667317.2667330
- Roider, F., Rümelin, S., Pfleging, B., & Gross, T. (2017). The effects of situational demands on gaze, speech and gesture input in the vehicle. In (pp. 94–102). Oldenburg, Germany.
- Rosenzweig, S. (1936). Some implicit common factors in diverse methods of psychotherapy. *American Journal of Orthopsychiatry*, 6(3), 412.
- Ross, L., Lepper, M. R., & Hubbard, M. (1975). Perseverance in self-perception and social perception: Biased attributional processes in the debriefing paradigm. *Journal of Personality and Social Psychology*, 32(5), 880.
- Rudin-Brown, C. M. (2010). ‘intelligent’in-vehicle intelligent transport systems: Limiting behavioural adaptation through adaptive design. *IET Intelligent Transport Systems*, 4(4), 252–261.
- SAE. (2018). *Taxonomy and definitions for terms related to on-road motor vehicle automated driving systems* (No. J3016R).
- SAE International. (2018). SAE brings autonomy to the public in new demonstration program. *www.sae.org*. Retrieved from <https://www.sae.org/news/2018/05/sae-demo-days-in-florida>
- Sarter, N. B., Mumaw, R. J., & Wickens, C. D. (2007). Pilots’ monitoring strategies and performance on automated flight decks: An empirical study combining behavioral and eye-tracking data. *Human factors*, 49(3), 347–357. doi: 10.1518/001872007X196685
- Sarter, N. B., & Woods, D. D. (1995). How in the world did we ever get into that mode? mode error and awareness in supervisory control. *Human factors*, 37(1), 5–19.
- Sauer, C. (1993). *Why information systems fail: A case study approach*. Alfred Waller

Ltd., Publishers Oxfordshire, UK, UK.

- Schäfer, T. (2018). Die New Statistics in der Psychologie. *Zeitschrift für Entwicklungspsychologie und Pädagogische Psychologie*, 50(1), 3–18. doi: 10.1026/0049-8637/a000184
- Schmidtler, J., Bengler, K., Dimeas, F., & Campeau-Lecours, A. (2017). A questionnaire for the evaluation of physical assistive devices (quead): Testing usability and acceptance in physical human-robot interaction. In *2017 IEEE International Conference on Systems, Man, and Cybernetics (SMC)* (pp. 876–881).
- Seong, Y., & Bisantz, A. M. (2008). The impact of cognitive feedback on judgment performance and trust with decision aids. *International Journal of Industrial Ergonomics*, 38(7-8), 608–625. doi: 10.1016/j.ergon.2008.01.007
- Seppelt, B. D., & Lee, J. D. (2019). Keeping the driver in the loop: Dynamic feedback to support appropriate use of imperfect vehicle control automation. *International Journal of Human-Computer Studies*, 125, 66–80. doi: 10.1016/j.ijhcs.2018.12.009
- Seppelt, B. D., Lees, M. N., & Lee, J. D. (2005). Driver distraction and reliance: Adaptive cruise control in the context of sensor reliability and algorithm limits. In *The 3rd International Driving Symposium on Human Factors in Driver Assessment, Training, and Vehicle Design* (pp. 255–261). Rockport, Maine, USA.
- Sheldon, K. M., Elliot, A. J., Kim, Y., & Kasser, T. (2001). What is satisfying about satisfying events? Testing 10 candidate psychological needs. *Journal of Personality and Social Psychology*, 80(2), 325.
- Sheridan, T. B., & Verplank, W. L. (1978). *Human and computer control of undersea teleoperators* (Tech. Rep.). Massachusetts Inst of Tech Cambridge Man-Machine Systems Lab.
- Sijtsma, K. (2009). On the use, the misuse, and the very limited usefulness of cronbach's alpha. *Psychometrika*, 74(1), 107–120. doi: 10.1007/s11336-008-9101-0
- Sikkenk, M., & Terken, J. (2015). Rules of conduct for autonomous vehicles. In G. Burnett, J. Gabbard, P. Green, & S. Osswald (Eds.), *Proceedings of the 7th international conference on automotive user interfaces and interactive vehicular applications* (pp. 19–22). Nottingham, UK: ACM.
- Slater, M. (2003). A note on presence terminology. *Presence connect*, 3(3), 1–5.
- Smith, E., Mackie, D., & Claypool, H. (2015). *Social psychology*. NY: Psychology Press.
- Spain, R. D., Bustamante, E. A., & Bliss, J. P. (2008). Towards an empirically developed scale for system trust: Take two. *Proceedings of the Human Fac-*

- tors and Ergonomics Society Annual Meeting, 52(19), 1335–1339. doi: 10.1177/154193120805201907
- Sportillo, D., Paljic, A., & Ojeda, L. (2018). Get ready for automated driving using virtual reality. *Accident Analysis and Prevention*, 118, 102–113. doi: 10.1016/j.aap.2018.06.003
- Sprinks, J., Wardlaw, J., Houghton, R., Bamford, S., & Morley, J. (2017). Task workflow design and its impact on performance and volunteers' subjective preference in virtual citizen science. *International Journal of Human-Computer Studies*, 104, 50–63. doi: 10.1016/j.ijhcs.2017.03.003
- State of California. (2017). *Disengagement report*.
- Stevens, A., Brusque, C., & Krems, J. (2012). *Driver adaptation to information and assistance systems*. London: The Institution of Engineering and Technology.
- Stevens, A., Quimby, A., Board, A., Kersloot, T., & Burns, P. (2002). Design guidelines for safety in-vehicle information systems. *TRL Limited*.
- Sullivan, G. M., & Feinn, R. (2012). Using effect size - or why the p value is not enough. *Journal of graduate medical education*, 4(3), 279–282. doi: 10.4300/JGME-D-12-00156.1
- Sweeney, M., Maguire, M., & Shackel, B. (1993). Evaluating user-computer interaction: A framework. *International Journal of Man-Machine Studies*, 38(4), 689–711.
- Tabachnick, B. G., & Fidell, L. S. (2007). *Using multivariate statistics*. Allyn & Bacon/Pearson Education: Boston, MA.
- Telpaz, A., Rhindress, B., Zelman, I., & Tsimhoni, O. (2015). Haptic seat for automated driving: Preparing the driver to take control effectively. In *Proceedings of the 7th international conference on automotive user interfaces and interactive vehicular applications* (pp. 23–30). Nottingham, UK.
- Tomizawa, T., Ohya, A., et al. (2006). Remote shopping robot system,-development of a hand mechanism for grasping fresh foods in a supermarket. In *2006 IEEE/RSJ International Conference on Intelligent Robots and Systems* (pp. 4953–4958).
- Totzke, I. (2012). *Einfluss des Lernprozesses auf den Umgang mit menügesteuerten Fahrerinformationssystemen: Doctoral Dissertation, University of Wuerzburg*.
- Trösterer, S., Meschtscherjakov, A., Mirnig, A. G., Lupp, A., Gärtner, M., McGee, F., ... Engel, T. (2017). What We Can Learn from Pilots for Handovers and (De)Skilling in Semi-Autonomous Driving. In S. Boll, B. Pfleging, & B. Donmez (Eds.), *Proceedings of the 9th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 173–182). New York, NY: ACM.

doi: 10.1145/3122986.3123020

- Tversky, A., & Kahneman, D. (1974). Judgment under uncertainty: Heuristics and biases. *Science*, 185(4157), 1124–1131.
- Underwood, G. (2007). Visual attention and the transition from novice to advanced driver. *Ergonomics*, 50(8), 1235–1249.
- van der Laan, J. D., Heino, A., & de Waard, D. (1997). A simple procedure for the assessment of acceptance of advanced transport telematics. *Transportation Research Part C: Emerging Technologies*, 5(1), 1–10.
- van der Meulen, H., Kun, A. L., & Janssen, C. P. (2016). Switching Back to Manual Driving: How Does it Compare to Simply Driving Away After Parking? In P. Green, S. Boll, G. Burnett, J. Gabbard, & S. Osswald (Eds.), *the 8th International Conference on Automotive User Interfaces and Vehicular Applications* (pp. 229–236). New York: ACM.
- van Loggem, B. (2013). User documentation: The cinderella of information systems. In Á. Rocha, A. M. Correia, T. Wilson, & K. A. Stroetmann (Eds.), *Advances in information systems and technologies* (Vol. 206, pp. 167–177). Berlin and Heidelberg: Springer. doi: 10.1007/978-3-642-36981-0_16
- van Veen, T., Karjanto, J., & Terken, J. (2016). Situation awareness in automated vehicles through proximal peripheral light signals. In P. Green, S. Boll, G. Burnett, J. Gabbard, & S. Osswald (Eds.), *the 8th International Conference on Automotive User Interfaces and Vehicular Applications* (pp. 287–292). New York: ACM.
- Vandekerckhove, J., Matzke, D., & Wagenmakers, E.-J. (2015). Model comparison and the principle of parsimony. *The Oxford handbook of computational and mathematical psychology*, 300.
- Vanderhaegen, F., & Carsten, O. (2017). Can dissonance engineering improve risk analysis of human-machine systems? *Cognition, Technology & Work*, 19(1), 1.
- Velicer, W. F. (1976). Determining the number of components from the matrix of partial correlations. *Psychometrika*, 41(3), 321–327. doi: 10.1007/BF02293557
- Venkatesh, V., Morris, M. G., Davis, G. B., & Davis, F. D. (2003). User acceptance of information technology: Toward a unified view. *MIS quarterly*, 425–478.
- Verberne, F. M. F., Ham, J., & Midden, C. J. H. (2012). Trust in smart systems: Sharing driving goals and giving information to increase trustworthiness and acceptability of smart systems in cars. *Human factors*, 54(5), 799–810.
- Walch, M., Baumann, M., Jaschke, L., Weber, M., & Hock, P. (2017). Touch Screen Maneuver Approval Mechanisms for Highly Automated Vehicles: A First Evaluation.

- In *Adjunct Proceedings of the 9th International ACM Conference on Automotive User Interfaces and Interactive Vehicular Applications*. Oldenburg, Germany.
- Wandtner, B. (2018). *Non-driving related tasks in highly automated driving - Effects of task characteristics and drivers' self-regulation on take-over performance*. Doctoral Dissertation. University of Wuerzburg.
- Waytz, A., Heafner, J., & Epley, N. (2014). The mind in the machine: Anthropomorphism increases trust in an autonomous vehicle. *Journal of Experimental Social Psychology*, 52, 113–117. doi: 10.1016/j.jesp.2014.01.005
- Wege, C., Pereira, M., Victor, T., & Krems, J. (2014). Behavioural adaptation in response to driving assistance technologies: A literature review. In A. Stevens, C. Brusque, & J. Krems (Eds.), (pp. 13–34). London: The Institution of Engineering and Technology.
- Weinzimer, S. A., Steil, G. M., Swan, K. L., Dziura, J., Kurtz, N., & Tamborlane, W. V. (2008). Fully automated closed-loop insulin delivery versus semiautomated hybrid control in pediatric patients with type 1 diabetes using an artificial pancreas. *Diabetes care*, 31(5), 934–939.
- Wickens, C. D. (2002). Multiple resources and performance prediction. *Theoretical Issues in Ergonomics Science*, 3(2), 159–177.
- Wickens, C. D., Hollands, J. G., Banbury, S., & Parasuraman, R. (2015). *Engineering psychology & human performance*. Psychology Press.
- Wiedemann, K., Schömig, N., Mai, C., Naujoks, F., & Neukum, A. (2015). Drivers' monitoring behaviour and interaction with non-driving related tasks during driving with different automation levels. In *6th International Conference on Applied Human Factors and Ergonomics (AHFE)*. Las Vegas, NV, USA: Springer.
- Will, S. (2017). *Development of a presence model for driving simulators based on speed perception in a motorcycle riding simulator*. Doctoral Dissertation. University of Wuerzburg.
- Winkler, S., Kazazi, J., & Vollrath, M. (2018). Practice makes better—learning effects of driving with a multi-stage collision warning. *Accident Analysis & Prevention*, 117, 398–409.
- Wintersberger, P., Frison, A.-K., Riener, A., & von Sawitzky, T. (2019). Fostering User Acceptance and Trust in Fully Automated Vehicles: Evaluating the Potential of Augmented Reality. *Presence*, 27(1), 1–17.
- Wintersberger, P., Riener, A., & Frison, A.-K. (2016). Automated Driving System, Male, or Female Driver: Who'd You Prefer? Comparative Analysis of Passengers'

- Mental Conditions, Emotional States & Qualitative Feedback. In *Proceedings of the 8th International Conference on Automotive User Interfaces and Interactive Vehicular Applications*. Ann Arbor, MI, USA.
- Wintersberger, P., Riener, A., Schartmüller, C., Frison, A.-K., & Weigl, K. (2018). Let Me Finish before I Take Over: Towards Attention Aware Device Integration in Highly Automated Vehicles. In B. Donmez & P. Fröhlich (Eds.), *Proceedings of the 10th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 53–65). Toronto, ON, CA: ACM Press. doi: 10.1145/3239060.3239085
- Woerle, J., Metz, B., Thiele, C., & Weller, G. (2019). Detecting sleep in drivers during highly automated driving: The potential of physiological parameters. *IET Intelligent Transport Systems*.
- Wogalter, M. S. (2006). *Handbook of warnings*. CRC Press: London.
- Yamani, Y., Samuel, S., Knodler, M. A., & Fisher, D. L. (2006). Evaluation of the effectiveness of a multi-skill program for training younger drivers on higher cognitive skills. *Applied ergonomics*, 52, 135–141.
- Young, K. L., Koppel, S., & Charlton, J. L. (2017). Toward best practice in human machine interface design for older drivers: A review of current design guidelines. *Accident Analysis and Prevention*, 106, 460–467. doi: 10.1016/j.aap.2016.06.010
- Yusof, N. M., Karjanto, J., Terken, J., Delbressine, F., Hassan, M. Z., & Rauterberg, M. (2016). The Exploration of Autonomous Vehicle Driving Styles. In P. Green, B. Pfleging, G. Burnett, J. Gabbard, & S. Oswald (Eds.), *Proceedings of the 8th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 245–252). Ann Arbor, MI, USA: ACM: New York. doi: 10.1145/3003715.3005455
- Zimmerman, B. J. (2000). Attaining self-regulation: A social cognitive perspective. In B. J. Zimmerman (Ed.), *Handbook of self-regulation* (pp. 13–39). Academic Press: Cambridge, MA, USA.
- Zoellick, J. C., Kuhlmei, A., Schenk, L., Schindel, D., & Blüher, S. (2019). Assessing acceptance of electric automated vehicles after exposure in a realistic traffic environment. *PLOS ONE*, 14(5).

CV Yannick Forster

Born March 23rd 1992

CURRENT ADDRESS

Sulzweg 23

81827 Munich

Germany

Phone: 0157 87002593

Email: forster.yannick@web.de

EDUCATION

July 2017 - June 2020	Chemnitz University of Technology PhD Psychology	Chemnitz
April 2015-Sept. 2016	Julius-Maximilians-University Wuerzburg M.Sc. Psychology final grade:1.4	Wuerzburg
Sept. 2011-March 2015	Julius-Maximilians-University Wuerzburg B.Sc. Psychology final grade: 1.4	Wuerzburg
Aug. 2013-May 2014	The University of Texas at Austin Undergraduate exchange student	Austin, TX, USA
Aug. 2002-May 2011	Margarete-Steiff-Gymnasium Higher education qualification final grade: 1.3	Giengen a.d. Brenz

PROFESSIONAL EXPERIENCE

Dec. 2019 - present	BMW Group Technical Product Manager: Product Strategy Automated Driving	Munich
July 2017-Nov. 2019	BMW Group PhD Candidate: Development and validation of methods for evaluating Human-Machine Interfaces in automated driving	Munich
March 2016-June 2017	WIVW (Wuerzburg Institute for Traffic Sciences) Research Associate: Planning, conducting and analyzing simulator and real-road user studies	Wuerzburg
Feb. 2012-Feb. 2016	WIVW (Wuerzburg Institute for Traffic Sciences) Student Research Assistant Conducting simulator and real-road user studies	Wuerzburg

Yannick Forster

June 2014-Oct. 2014	BMW Research and Development GmbH	Munich
	Student Internship: Evaluation of stereoscopic 3D driving simulation	
Jan. 2014-May 2014	Center for Perceptual Systems, UT Austin	Austin, TX, USA
	Student Research Assistant: Conducting eye-tracking experiments	
Oct. 2012-July 2016	Chair for Social Psychology, University Wuerzburg	Wuerzburg
	Teaching Assistant Social Psychology: Lecturing and preparation of exams	

ACTIVITIES

Sept. 2017-present	Secretary SV Altenberg Football Department
April 2012-Sept. 2016	Psychology Students' Council
Nov. 1996-present	Member of SV Altenberg
Aug. 2013-present	NASCO - North American Students of Cooperation
Feb. 2015-Feb. 2017	DAV - German Alpine Association
June 2017	GSERM Summer School (HSG St. Gallen): Introduction to Machine Learning with R.

LANGUAGES

German (native), English (fluent), Spanish (good),
Latin (advanced proficiency)

TECHNICAL SKILLS

SPSS, Matlab, SILAB, R (Machine Learning), Microsoft Office,
LaTeX, Java, SQL

INTERESTS

Football, American Football, Crossfit, , Snowboarding, Reading

SCIENTIFIC REVIEWING

- 2017: Automotive UI
Transportation Research Part F
International Journal of Mobile HCI
- 2018: Automotive UI
Cognition, Technology & Work
- 2019: Automotive UI
Transportation Research Part F
Accident Analysis and Prevention
Journal of Advanced Transportation
Multimodal Technologies and Interaction
- 2020: Automotive UI
Transportation Research Part F
Accident Analysis and Prevention
Journal of Advanced Transportation
Multimodal Technologies and Interaction

June 13th, 2020

SCIENTIFIC PUBLICATIONS (in chronological order)

- Forster, Y., Paradies, S., Bee, N. (2015). The third dimension: Stereoscopic displaying in a fully immersive driving simulator. In *Proceedings of DSC 2015 Europe Driving Simulation Conference & Exhibition* (pp. 25-32).
- Forster, Y., Naujoks, F., & Neukum, A. (2016). Your Turn or My Turn? Design of a Human-Machine Interface for Conditional Automation. In *Proceedings of the 8th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 253-260). ACM.
- Naujoks, F., Forster, Y., Wiedemann, K., & Neukum, A. (2016). Speech improves human-automation cooperation in automated driving. *Mensch und Computer 2016–Workshopband*.
- Muehlbacher, D., Rademacher, J., Forster, Y., & Engelhardt, S. (2016). New solutions for complex traffic situations: Requirements analysis and driving simulation of the Finkenwerder Ring in the Port of Hamburg. *Practice*, 2214, 241.
- Naujoks, F., Forster, Y., Wiedemann, K., & Neukum, A. (2017). A human-machine interface for cooperative highly automated driving. In *Advances in Human Aspects of Transportation* (pp. 585-595). Springer, Cham.
- Forster, Y., Naujoks, F., & Neukum, A. (2017). Increasing anthropomorphism and trust in automated driving functions by adding speech output. In *2017 IEEE intelligent vehicles symposium (IV)* (pp. 365-372). IEEE. Los Angeles, CA, USA.
- Naujoks, F., Forster, Y., Wiedemann, K., & Neukum, A. (2017). Improving usefulness of automated driving by lowering primary task interference through HMI design. *Journal of Advanced Transportation*.
- Forster, Y., Naujoks, F., Neukum, A., & Huestegge, L. (2017). Driver compliance to take-over requests with different auditory outputs in conditional automation. *Accident Analysis & Prevention*, 109, 18-28.
- Muehlbacher, D., Engelhardt, S., Forster, Y., & Rademacher, J. (2018) New ways for roadway design—Using driving simulation to restructure the Finkenwerder Ring in the Port of Hamburg aiming at enhanced traffic safety and reliability. *Transportation Research Arena (TRA)*. Vienna, Austria.
- Forster, Y., Hergeth, S., Kugler, T.-A., Krichbaum, E., & Keinath, A. (2018). Identification and Evaluation of Influences on the Occurrence of Simulator Sickness. In *Proceedings of DSC 2018 Europe Driving Simulation Conference & Exhibition*. Antibes, France.
- Forster, Y., Hergeth, S., Naujoks, F., & Krems, J. F. (2018). Unskilled and Unaware. Subpar Users of Automated Driving Systems make Spurious Decisions. In *Adjunct proceedings of the 10th International ACM Conference on Automotive User Interfaces and Interactive Vehicular Applications*: September 23-25, 2018, Toronto, Canada. (pp. 159–163). New York, New York: ACM. <https://doi.org/10.1145/3239092.3265960>
- Forster, Y., Hergeth, S., Naujoks, F., & Krems, J. F. (2018). How Usability Can Save the Day - Methodological Considerations for Making Automated Driving a Success Story. In *Proceedings, 10th International ACM Conference on Automotive User Interfaces and Interactive Vehicular Applications*: September 23-25, 2018, Toronto, Canada. (pp. 278–290). New York, New York: ACM. <https://doi.org/10.1145/3239060.3239076>
- Forster, Y., Kraus, J., Feinauer, S., & Baumann, M. (2018). Calibration of Trust Expectancies in Conditionally Automated Driving by Brand, Reliability Information and Introductory Videos: An Online Study. In *Proceedings of the 10th International Conference on Automotive User Interfaces and Interactive Vehicular Applications* (pp. 118-128). ACM.
- Semnani-Azad, Z., Chien, S. Y. J., Forster, Y., Schuckers, S., & Gan, H. (2019). Development of Trust Measure in Biometric Technology. In *Proceedings of the 52nd Hawaii International Conference on System Sciences*. Hawaii, US.
- Forster, Y., Hergeth, S., Naujoks, F., Beggiato, M., Krems, J. F., & Keinath, A. (2019). Learning to use automation: Behavioral changes in interaction with automated driving systems. *Transportation Research Part F: Traffic Psychology and Behaviour*, 62, 599–614. doi:10.1016/j.trf.2019.02.013
- Forster, Y., Hergeth, S., Naujoks, F., Krems, J. F., & Keinath, A. (2019a). Tell Them How They Did: Feedback on Operator Performance Helps Calibrate Perceived Ease of Use in Automated Driving. *Multimodal Technologies and Interaction*, 3(2), 29. <https://doi.org/10.3390/mti3020029>
- Forster, Y., Hergeth, S., Naujoks, F., Krems, J. F., & Keinath, A. (2019b). User Education in Automated Driving: Owner's Manual and Interactive Tutorial Support Mental Model Formation and Human-Automation Interaction. *Information (Switzerland)*, 10(4), 143. <https://doi.org/10.3390/info10040143>
- Forster, Y., Hergeth, S., Naujoks, F., Beggiato, M., Krems, J. F., & Keinath, A. (2019). Learning and Development of Mental Models during Interactions with Driving Automation: A simulator Study. *The 10th International*

Driving Symposium on Human Factors in Driver Assessment, Training, and Vehicle Design. Santa Fe, NM, USA.

- Kraus, J. M., Forster, Y., Hergeth, S., & Baumann, M. (2019). Two Routes to Trust Calibration: Effects of Reliability and Brand Information on Trust in Automation. *International Journal of Mobile Human Computer Interaction (IJMHCI)*, 11(3), 1-17.
- Naujoks, F., Hergeth, S., Wiedemann, K., Schoemig, N., Forster Y., & Keinath, A. (2019) Test Procedure for Evaluating the Human-Machine-Interface of Vehicles with Automated Driving Systems. *Traffic Injury Prevention*. 20(sup1), p.146-151.
- Forster, Y., Hergeth, S., Naujoks, F., Krems, J. F., & Keinath, A. (2019, July). Empirical Validation of a Checklist for Heuristic Evaluation of Automated Vehicle HMIs. In *International Conference on Applied Human Factors and Ergonomics* (pp. 3-14). Springer, Cham.
- Parduzi, A., Venrooj, J., Peller, M., Forster, Y., & Marker, S. (2019) Evaluation of a 3-DOF Mid-Size Simulator Concept: A Behavioural Validation Study. In *Proceedings of the 2019 Driving Simulation Conference Europe*. Straßbourg, France.
- Forster, Y., Frison, A.-K., Wintersberger, P., Geisel, V., Hergeth, S., & Riener, A. (2019) Where We Come From and Where We Are Going: A Review of Automated Driving Studies. In *Adjunct proceedings of the 11th International ACM Conference on Automotive User Interfaces and Interactive Vehicular Applications*: Utrecht, The Netherlands.
- Forster, Y., Hergeth, S., Naujoks, F., Krems, J. F., & Keinath, A. (2019). Self-report measures for the assessment of human-machine interfaces in automated driving. *Cognition, Technology & Work*, 1-18.
- Forster, Y., Hergeth, S., Naujoks, F., Krems, J. F., & Keinath, A. (2020). What and how to tell beforehand: the effect of user education on understanding, interaction and satisfaction with driving automation. *Transportation research part F: traffic psychology and behaviour*, 68, 316-335.
- Forster, Y., Geisel, V., Hergeth, S., Naujoks, F., & Keinath, A. (2020). Engagement in Non-Driving Related Tasks as a Non-Intrusive Measure for Mode Awareness: A Simulator Study. *Information*, 11(5), 239.
- Schömig, N., Wiedemann, K., Hergeth, S., Forster, Y., Muttart, J., Eriksson, A., ... & Neukum, A. (2020). Checklist for Expert Evaluation of HMIs of Automated Vehicles—Discussions on Its Value and Adaptions of the Method within an Expert Workshop. *Information*, 11(4), 233.

Eidesstattliche Erklärung

Hiermit erkläre ich, dass ich die vorliegende Arbeit selbstständig verfasst, nicht anderweitig zu Prüfungszwecken vorgelegt und keine anderen als die angegebenen Hilfsmittel verwendet habe. Sämtliche wissentlich verwendeten Textausschnitte, Zitate oder Inhalte anderer Verfasser wurden ausdrücklich als solchen gekennzeichnet.

München, den 28.06.2020

Yannick Forster